



Data Lineage Records

! INFO

Tenant Admins, Tenant Managers, Source Agency Users, and Platform Admins can download the data lineage records of a dataset.

In compliance with [IM8 Data Security Clause 1.14](#), tenant admins, tenant managers, and source agency users (SSOTs) can download data lineage records on DataHive, for purposes of identifying any unauthorised access, usage or modification of data.

To access the Data Lineage Record, navigate to "Manage datasets" under the "Datasets" tab and click on the ellipsis icon associated with the dataset, then click "Download lineage record".



Municipal Feedback	TCS	test@tech.gov.sg, admin@tech.gov.sg	12 Mar 2024	Published	⋮
Water Consumption	TCS	test@tech.gov.sg, admin@tech.gov.sg	01 Jan 1970	Published	⋮
Town Gas Sales	TCG	test@tech.gov.sg, admin@tech.gov.sg, koh_jun_wei@tech.gov.sg	01 Jan 1970		Manage tenant admins Download lineage record

Record Fields

The Data Lineage Record file contains the following sheets.

Dataset Metadata Records

Field	Description
modified_datetime	The datetime that the metadata was updated. If no changes were made after dataset was published, this date will be the date of publication.

Field	Description
modified_by	The email of the officer who updated the metadata. If the dataset was published before data lineage records were kept, this is set to admin@datahive.gov.sg.
dataset_id	The dataset ID displayed on the portal.
name	The dataset name displayed on the portal.
domain	Domain of the dataset selected by the tenant.
category	Category of the dataset selected by the tenant.
sub_category	Subcategory of the dataset selected by the tenant.
rcst_id	RCST of the dataset when identifiable. Either of the following: Official (Open), Official (Closed), Restricted, Confidential (Cloud Eligible)
isf_id	ISF of the dataset when identifiable. Either of the following: Non-Sensitive, Sensitive (Normal), Sensitive (High)
rcst_deident	RCST of the dataset when de-identified. Either of the following: Official (Open), Official (Closed), Restricted, Confidential (Cloud Eligible)
isf_deident	ISF of the dataset when de-identified. Either of the following: Non-Sensitive, Sensitive (Normal), Sensitive (High)
description	The description of the dataset.
source_agency	A list of SSOT agencies. Separated by commas.
ssot_assignees	A list of SSOT emails. This will allow us to route the request of NFT fields to them.
sensitive_data_fields	A list of data fields in dataset with ISF classification (Identifiable) classified Sensitive High and above.

Data Consumers

Field	Description
request_id	The data request ID of a data request that includes this dataset.
request_by_name	Name of DR requestor.
request_by_email	Email of DR requestor.
owner_email	Email of DR owner.
team_emails	Emails of DR team members.
agency	Agency of DR owner.
purpose	Purpose of DR.
fulfilled_on	Datetime that DR was fulfilled.
status	Status of DR. DRs pending approval are not included.
expiry_date	Date that DR expired.
access_to_databricks	Either of the following: Yes / No.
nge_name	Name of NGE. If blank, data is not onward shared to NGEs.
nge_email	Email of contact at NGE. If blank, data is not onward shared to NGEs.
data_fields	A list of data fields in the dataset requested by the DR requestor for that dataset.
from_date	Start of the datetime range of data requested.
to_date	End of the datetime range of data requested.
spn_connections	A list of systems identified by their Service Principal Names (SPNs) that can access the dataset in fulfilled data requests. An SPN is a system identity that enables programmatic access to datasets.

Field	Description
	- To learn what SPNs can do, see the System Connection Selection Guide. - To create an SPN, see SPN Account Creation. - To set up a data request connection, see SPN Connection Setup.

Data Access - Download

Field	Description
request_id	The data request ID of a data request that includes this dataset.
curation_id	The download job ID.
curation_reference_id	This should be the same as the dataset ID.
curation_created_by_name	DR team member or service principal account that triggered the download.
curation_created_by_email	Email of the team member who triggered the download.
curation_created_on	Datetime that the team member triggered the download.
curation_state	State of the download job.
curation_start_date	Start of the datetime range of data downloaded
curation_end_date	End of the datetime range of data downloaded

Data Access - Queries

Field	Description
user_id	For interactive users on the DataHive portal, this will be the email of the data request team member. For SPN, this will be the ID of the SPN which has a data request connection with a data request that includes this dataset.
user_name	For interactive users on the DataHive portal, this will be the name of the data request team member. For SPN, this will be the name of the system identified by the SPN.
user_type	The type of user that triggered the queries. Portal: interactive users on the DataHive portal. SPN: a system identified by the Service Principal Name that has a connection to the data request.
request_id	The data request ID of a data request that includes this dataset.
agency	For interactive users, the agency of the user. For SPN, the agency of the system identified by the SPN.
cdo_team	The CDO team with oversight of the system identified by the SPN.
query_volume	Number of queries made by the user in the reference period (month).
reference_period ¹	The reference month in MM-YYYY format.

¹ Query records are only available from September 2025 onwards. The `reference_period` field will therefore only contain values starting from 09-2025.