



Share Dataset via Snowflake Private Listing

! INFO

You must be assigned the **Tenant Admin** role to share datasets via Snowflake Private Listing. Please note that Snowflake Private Listing is **only available to tenants configured to have data shared via Snowflake Private Listing** with DataHive. If your tenant is not configured to have data shared via Snowflake Private Listing, refer to [Uploading Dataset Files](#) for manual file upload instructions.

For more information on setting up a Snowflake Private Listing connection with DataHive, contact us at support@datahive.gov.sg.

Accessing the Dataset Details Form

To access the dataset details form, click on "Manage Datasets" > "Edit" after you click on the ellipsis associated with the dataset.

The screenshot shows the 'A Singapore Government Agency Website' interface. On the left sidebar, the 'Datasets' menu is expanded, and 'Manage datasets' is highlighted with a red box. The main content area displays a table of datasets. The table has columns for 'Dataset', 'Tenant', 'Dataset Admin(s)', 'Published Date', and 'Status'. A single dataset is listed: 'Dataset for test upload 1' under 'Mock Tenant 1', with 'gt-dlinwz@gcc.gov.sg, marc_chern_from.tp@tech.gov.sg, pang_biao_vig@tech.gov.sg' as the admin(s). The status is 'Unpublished'. To the right of the dataset row, there is a vertical ellipsis menu, and the 'Edit' option is highlighted with a red box.

Dataset	Tenant	Dataset Admin(s)	Published Date	Status
Dataset for test upload 1	Mock Tenant 1	gt-dlinwz@gcc.gov.sg, marc_chern_from.tp@tech.gov.sg, pang_biao_vig@tech.gov.sg	-	Unpublished

After clicking on the edit button, you will be redirected to the dataset details form.

! INFO

DataHive supports datasets up to the following classifications:

- RCST: Confidential (Cloud Eligible)
- ISF: Sensitive (Normal)

Filling in the Table Details

Fill in the table details in the section depicted by the image above. These details will appear in the DataHive portal and help consumers understand how to access and interpret the data.

WARNING

Ensure that the table name matches the actual table name you've shared via Snowflake. This is used by DataHive to expose the dataset to users.

Filling in the Dataset Metadata

After filling in the table details, fill in the necessary information as detailed in [editing and publishing dataset](#) and publish your dataset.

Do note that the datafields will have to be filled in manually for sharing via Snowflake Private Listing.

WARNING

Tenant Admins should ensure that the ordering, naming and metadata of the datafields entered on the DataHive portal matches the schema in their Snowflake tables.

DataHive does not perform any additional mapping behind the scenes.

Upon publishing, the DataHive system will reference the shared tables made available through your Snowflake Private Listing. These tables will be exposed to users for subscription directly from the DataHive portal.

Once the publishing task has completed, Tenant Admins will receive an email notification stating whether the task succeeded or failed.

Providing Key & IV for Identifiable Fields

! INFO

These fields are required only if **one or more datafields are marked as identifiable**. Once the dataset is published, the Key and IV cannot be modified.

If your dataset contains any identifiable fields (e.g. personal identifiers), you are required to supply a Key and Initialisation Vector (IV) to support secure de-tokenisation for authorised users.

These values are used by DataHive to de-tokenise values that were previously tokenised in your shared Snowflake tables. Re-identification will only be performed for users who have a fulfilled data request to access the original (de-tokenised) data.

Fields Explained

- **Key:** The key used to reverse the tokenisation of field values.
 - Must be a 64-character hexadecimal string (representing a 256-bit SHA-256 key).
- **IV (Initialisation Vector):** Used alongside the key to support secure de-tokenisation.
 - Must be a 32-character hexadecimal string (representing 16 bytes).

The screenshot displays the 'Onboard Dataset' workflow in the DataHive portal. The left sidebar contains navigation links: Home, Marketplace, Resources, Approval, Visualisation, and Datasets. The main content area shows a progress bar with three steps: 1. Dataset level, 2. Datafield level, and 3. Key/IV configuration (the current step). The 'Key/IV configuration' section is titled 'Tokenisation via Encryption: Key/IV Configuration' and includes the instruction: 'Provide your Key/IV pair to share data via Snowflake. This is required as one or more data fields are identifiers.' Below this, there are two input fields: 'Key' with a placeholder 'Input key' and 'IV' with a placeholder 'Input IV'.

These values are securely stored and are not exposed to dataset consumers. De-tokenisation is handled internally by DataHive and is only available to authorised users under strict access controls.

Updating Published Dataset

The following conditions currently apply after a dataset has been published:

1. Datafields cannot be removed or reordered.
2. The Key and Initialisation Vector (IV) cannot be modified.

If you need to apply any of the above mentioned changes to a dataset after it has been published, please refer to the guide on [Un-publishing Dataset](#).