



VISTA Qlik Sense

What is VISTA Qlik Sense?

VISTA Qlik Sense enables WoG officers to create, share and explore interactive dashboards and visualisations securely across WOG. Officers can use Qlik Sense to analyse data, build self-service visualisations, and publish dashboards for authorised users.

For more information, visit <https://vista.gov.sg/SitePages/VisualAnalytics.aspx>.

How does VISTA Qlik Sense work with DataHive?

DataHive enables WoG users to discover, request and access government-owned datasets. Once a data request has been approved, officers may use VISTA Qlik Sense to connect to the approved dataset(s) and build dashboards or visualisations.

In a typical use case, the officer will:

1. Submit and obtain approval for a data request (DR) in DataHive.
2. Create a data connection in VISTA Qlik Sense to the approved DataHive data request.
3. Build a Qlik Sense app using the approved dataset.
4. Publish or share the dashboard with authorised users, where applicable.

WARNING

VISTA Qlik Sense is supported for data up to **Confidential / Sensitive (High)**.

Users are responsible for ensuring that their use of data, dashboards and sharing arrangements comply with the applicable data classification, security and governance requirements.

How can I configure VISTA Qlik Sense to connect to DataHive?

PRE-REQUISITES

To access your approved DataHive data request via VISTA Qlik Sense, you will need:

- A valid VISTA account with the Content Manager key role.
 - i. Apply for a VISTA account at <https://vista.gov.sg>.
 - ii. Apply for the Content Manager key role at <https://vista.gov.sg/SitePages/KeyRole.aspx>.
- An approved DataHive data request. Refer to the [DataHive Data Request guide](#).
- A service principal account to connect to your requested DataHive dataset(s). Refer to the [DataHive Service Principal Account guide](#).
 - i. IP address for firewall whitelisting: `10.59.229.212`.
 - ii. Upload the public key file. Refer to the [public key setup guide](#).

Steps to connect VISTA Qlik Sense to DataHive

Reference video tutorial:

0:00 / 2:56

1. Log in to [VISTA Qlik Sense](#) using your WoG account. From the Qlik Sense hub, create a new app.

2. Open **Data Manager**. Select **Add data** and choose the **Snowflake** connector.
3. Enter the connection details for your approved DataHive data request.
4. Select **Key-Pair** as the authentication mechanism. Upload the private key file and enter the private key password.
5. Test the connection before saving.

Connection settings

The following settings are used to configure the Snowflake connector in VISTA Qlik Sense.

! INFO

For fields marked as **Example only**, replace the sample value with the actual value from your approved DataHive data request or service principal connection details.

You can obtain the user-specific connection details from your DataHive service principal account. Refer to the [DataHive Service Principal Account guide](#).

General connection settings

Setting	Value to enter	Remarks
Server	govtech-datahive.privatelink.snowflakecomputing.com	Fixed production value. The DataHive Production Snow server address.
Server IP	10.192.185.164	Fixed production value. The DataHive Production server address.
Port	443	Fixed production value. The Snowflake connection port.
Database	DATA_REQUESTS	Fixed production value. The database containing approved DataHive data requests.
Schema	<your_data_request_schema>	Example only. Replace with approved Data Request ID.

Setting	Value to enter	Remarks
		Example: <code>SINGSTAT_2026</code> .
Warehouse	<code><your_assigned_warehouse></code>	Example only. Replace with Snowflake warehouse assigned to your service principal. Example: <code>X_LARGE</code> .
Role	<code><your_assigned_role></code>	Example only. Replace with Snowflake role assigned for approved DataHive access. Example: <code>DHUSER_SINGSTAT_VISTA</code>

Authentication settings

For **Credentials**, select the following authentication mechanism:

Key-Pair

Setting	Value to enter	Remarks
User	<code><your_service_principal_user_id></code>	Example only. Replace with the User ID from your DataHive service principal connection details. Example: <code>b377a3ff-6d4a-4750-acd9-250fac3235de</code> .
Private Key File Path	<code><your_private_key_file></code>	Upload the private key file downloaded during service principal account setup. Example: <code>rsa_key.p8</code> .
Private Key File Password	<code><your_private_key_password></code>	Enter the password that was used when creating the RSA private key.

Setting	Value to enter	Remarks
		Do not share or reuse the example value.



DANGER

Do not share your private key file, private key password or service principal credentials with other users.

Advanced settings

Setting	Value to enter	Remarks
Proxy	<code>10.59.29.212:3128</code>	Required for Qlik Sense to connect to DataHive through the approved gateway. Enter this value exactly as shown. Fixed production value. This is the Qlik Sense forward proxy server.