

RxJava and Retrolambda

Making Android development more FUNctional

Async Programming

Standard Async Classes


Android	AsyncTaskLoader	IntentService
	AsyncTask	
	HandlerThread / Looper / Handler	
Java	Executor	
	Thread	

Standard Async Classes

Android	AsyncTaskLoader	IntentService
	AsyncTask	
	HandlerThread / Looper / Handler	
Java	Executor	
	Thread	


AsyncTask

Looks easy




AsyncTask

No exception handling




AsyncTask

Chaining tasks




AsyncTask

Serialized thread processing




AsyncTask

Serialized thread processing




Loader

Caching




Loader

Caching



Loader

Exceptions



Alternative:

RxJava

Functional Reactive Programming



Reactive Extensions

- Created by Erik Meijer at Microsoft
- Ported to Java by Netflix
- It's everywhere
 - .NET, Java, Groovy, Scala, JS, Cocoa, etc.

Rx Concepts

- **Observer Pattern**

- Reactive

- **Iterator Pattern**

- Collections

- **Functional Programming**

- Transformations



Reactive Programming

Not Reactive

Imperative

```
x = 2;  
y = 3;  
sum = x + y;  
// sum == 5
```

Not Reactive

Imperative

```
x = 2;  
y = 3;  
sum = x + y;  
// sum == 5
```

```
x = 4;  
// sum == ?
```

Not Reactive


Imperative

```
x = 2;  
y = 3;  
sum = x + y;  
// sum == 5
```

```
x = 4;  
// sum == still 5 of course
```


Reactive

Similar to a spreadsheet




Reactive

Similar to a spreadsheet




Reactive

Similar to a spreadsheet




Iterable

Pulls from producer
Blocks consumer thread




Iterable

Pulls from producer
Blocks consumer thread




Iterable

Pulls from producer
Blocks consumer thread




Iterable

Pulls from producer
Blocks consumer thread




Observable

Reacts to producer
Does **not** block consumer




Observable

Reacts to producer
Does **not** block consumer



Observable

Reacts to producer
Does **not** block consumer



Functional Programming

Not Functional

Imperative

```
integers = [0, 1, 2, 3, 4, 5, 6, 7, 9];  
  
doubled = new int[integers.length];  
for(int i = 0; i < integers.length; i++) {  
    doubled[i] = integers[i] * 2;  
}
```

Not Functional

Imperative

```
integers = [0, 1, 2, 3, 4, 5, 6, 7, 9];
```

```
doubled = new int[integers.length];  
for(int i = 0; i < integers.length; i++) {  
    doubled[i] = integers[i] * 2;  
}
```

```
filtered = new ArrayList<>();  
for(int d : doubled) {  
    if (d < 10) {  
        filtered.add(d);  
    }  
}
```


Not Functional

Imperative

```
integers = [0, 1, 2, 3, 4, 5, 6, 7, 9];
```

```
doubled = new int[integers.length];  
for(int i = 0; i < integers.length; i++) {  
    doubled[i] = integers[i] * 2;  
}
```

```
filtered = new ArrayList<>();  
for(int d : doubled) {  
    if (d < 10) {  
        filtered.add(d);  
    }  
}
```

Functional

Apply to collections

```
integers = [0, 1, 2, 3, 4, 5, 6, 7, 9];
```

```
doubled = integers.map(i -> i * 2);
```

```
filtered = doubled.filter(i -> i < 10);
```

Functional

Apply to collections

```
integers = [0, 1, 2, 3, 4, 5, 6, 7, 9];
```

```
doubled = integers.map(i -> i * 2);
```

```
filtered = doubled.filter(i -> i < 10);
```

Functional

Apply to collections

```
integers = [0, 1, 2, 3, 4, 5, 6, 7, 9];
```

```
doubled = integers.map(i -> i * 2);
```

```
filtered = doubled.filter(i -> i < 10);
```

```
sum = filtered.sum();
```

```
sorted = filtered.sort(Integer::compare);
```

Functional

Composing

```
integers = [0, 1, 2, 3, 4, 5, 6, 7, 9];
```

```
doubledAndFilteredSum = integers.map(i -> i * 2)  
                                .filter(i -> i < 10)  
                                .sum();
```

Functional

Composing

```
integers = [0, 1, 2, 3, 4, 5, 6, 7, 9];  
  
doubledAndFilteredSum = integers.map(i -> i * 2)  
                                .filter(i -> i < 10)  
                                .sum();
```

More expressive. Less error prone.


Functions

Inputs, output, no side-effects

```
public static float fahrenheitFromKelvin(float kelvin) {  
    return (kelvin - 273.15) * 1.80 + 32.00;  
}
```

```
public static Customer customerFromJson(JSONObject customerJson) {  
    Customer customer = new Customer();  
    customer.setFirstName(customerJson.getString("firstName"));  
    customer.setFirstName(customerJson.getString("lastName"));  
    return customer;  
}
```

Parallelism



Lambdas

Basically a one method class

```
button.setOnClickListener(new OnClickListener() {  
    @Override  
    public void onClick(View button) {  
        doSomething();  
    }  
});
```

Lambdas


Basically a one method class

```
button.setOnClickListener(new OnClickListener() {  
    @Override  
    public void onClick(View button) {  
        doSomething();  
    }  
});
```

Lambdas

Basically a one method class

```
button.setOnClickListener(new OnClickListener() {  
    @Override  
    public void onClick(View button) {  
        doSomething();  
    }  
});
```



```
button.setOnClickListener(button -> doSomething());
```

Method References

```
.map(json -> new Customer(json))
```

```
.map(Customer::new)
```

Method References

```
.map(json -> new Customer(json))
```



```
.map(Customer::new)
```

Retrolambda

- Lambda syntax in Android projects
- Gradle plugin
- Converts Java 8 bytecode to Java 7
- **Risk:** Jack and Jill compiler

Functional + Reactive Programming

The Code

Declaration

```
Observable<List<Customer>> localCustomerList =  
    webService.getCustomers()  
        .flatMap(r -> Observable.from(r.customerList))  
        .map(json -> new Customer(json))  
        .filter(c -> c.isLocal())  
        .toList();
```


The Code

Declaration

```
Observable<List<Customer>> localCustomerList =  
    webService.getCustomers()  
        .flatMap(r -> Observable.from(r.customerList))  
        .map(json -> new Customer(json))  
        .filter(c -> c.isLocal())  
        .toList();
```

Web Service Example

```
{
  customers: [
    {
      firstName: "Paul",
      lastName: "Cicero",
      isLocal: true
    },
    {
      firstName: "Tommy",
      lastName: "DeVito",
      isLocal: false
    },
    {
      firstName: "Billy",
      lastName: "Batts",
      isLocal: true
    }
  ]
}
```


The Code

Declaration

```
Observable<List<Customer>> localCustomerList =  
    webService.getCustomers()  
        .flatMap(r -> Observable.from(r.customerList))  
        .map(json -> new Customer(json))  
        .filter(c -> c.isLocal())  
        .toList();
```

FlatMap

Convert each item to Observable




The Code

Declaration

```
Observable<List<Customer>> localCustomerList =  
    webService.getCustomers()  
        .flatMap(r -> Observable.from(r.customerList))  
        .map(json -> new Customer(json))  
        .filter(c -> c.isLocal())  
        .toList();
```

Map

Transform each item to another item




The Code

Declaration

```
Observable<List<Customer>> localCustomerList =  
    webService.getCustomers()  
        .flatMap(r -> Observable.from(r.customerList))  
        .map(json -> new Customer(json))  
        .filter(c -> c.isLocal())  
        .toList();
```

Filter

Select items that match criteria




The Code

Declaration

```
Observable<List<Customer>> localCustomerList =  
    webService.getCustomers()  
        .flatMap(r -> Observable.from(r.customerList))  
        .map(json -> new Customer(json))  
        .filter(c -> c.isLocal())  
        .toList();
```

Aggregate Operators




The Code

Declaration

```
Observable<Customer> allCustomers =  
    webService.getCustomers()  
        .flatMap(r -> Observable.from(r.customerList))  
        .map(json -> new Customer(json));
```

```
Observable<List<Customer>> localCustomerList =  
    allCustomers.filter(c -> c.isLocal())  
        .toList();
```

Functional Pipelines



Subscribing

Declaration

```
Observable<List<Customer>> localCustomerList =  
    webService.getCustomers()  
        .flatMap(r -> Observable.from(r.customerList))  
        .map(json -> new Customer(json))  
        .filter(c -> c.isLocal())  
        .toList();
```

Consume

```
localCustomerList.subscribe(  
    list -> display(list),  
    e -> handleError(e) <— error handling!  
);
```

Subscribing

Declaration

```
Observable<List<Customer>> localCustomerList =  
    webService.getCustomers()  
        .flatMap(r -> Observable.from(r.customerList))  
        .map(json -> new Customer(json))  
        .filter(c -> c.isLocal())  
        .toList();
```

Consume

```
localCustomerList.subscribe(  
    list -> display(list),  
    e -> handleError(e)  
);
```

or

```
localCustomerList.subscribe(  
    this::display,  
    this::handleError  
);
```

RxAndroid

RxAndroid

- **AndroidSchedulers**
 - Observe on UI thread
- **AppObservable**
 - Protects against destroyed Fragment / Activity
- **LifecycleObservable**
 - Prevents leaking Fragment / Activity

Threading

```
localCustomerList.subscribe(  
    this::display,  
    this::handleError  
);
```

Threading

Work in background thread pool

```
localCustomerList
    .observeOn(Schedulers.io())
    .observeOn(AndroidSchedulers.mainThread())
    .subscribe(
        this::display,
        this::handleError
    );
```

Threading

Handle on UI thread

```
localCustomerList
    .subscribeOn(Schedulers.io())
    .observeOn(AndroidSchedulers.mainThread())
    .subscribe(
        this::display,
        this::handleError
    );
```

Threads

```
localCustomerList
    .observeOn(Schedulers.io())
    .observeOn(AndroidSchedulers.mainThread())
    .subscribe(
        this::display,
        this::handleError
    );
```

AppObservable

```
AppObservable.bindFragment(this, localCustomerList)
    .subscribeOn(Schedulers.io())
——.observeOn(AndroidSchedulers.mainThread())
    .subscribe(
        this::display,
        this::handleError
    );
```

AppObservable

```
AppObservable.bindFragment(this, localCustomerList)
    .subscribeOn(Schedulers.io())
    .subscribe(
        this::display,
        this::handleError
    );
```

AppObservable

```
Observable<List> localCustomerList =  
    webService.getCustomers() <— move inside here  
        .flatMap(r -> Observable.from(r.customerList))  
        .map(json -> new Customer(json))  
        .filter(c -> c.isLocal())  
        .toList();
```

```
AppObservable.bindFragment(this, localCustomerList)  
——.subscribeOn(Schedulers.io())  
    .subscribe(  
        this::display,  
        this::handleError  
    );
```

AppObservable

```
Observable<List> localCustomerList =  
    webService.getCustomers()  
        .flatMap(r -> Observable.from(r.customerList))  
        .map(json -> new Customer(json))  
        .filter(c -> c.isLocal())  
        .toList();
```


```
AppObservable.bindFragment(this, localCustomerList)  
    .subscribe(  
        this::display,  
        this::handleError  
    );
```


AppObservable


```
Observable<List> localCustomerList =  
    webService.getCustomers()  
        .flatMap(r -> Observable.from(r.customerList))  
        .map(json -> new Customer(json))  
        .filter(c -> c.isLocal())  
        .toList();  
  
bindFragment(this, localCustomerList)  
    .subscribe(  
        this::display,  
        this::handleError  
    );
```

AppObservable

Safeguards



LifecycleObservable



More Power

Complex threading

```
public Observable<List<CityWeather>> getWeatherForLargeUsCapitals() {  
    return cityDirectory.getUsCapitals()  
        .flatMap(cityList -> Observable.from(cityList))  
        .filter(city -> city.getPopulation() > 500,000)  
        .flatMap(city -> weatherService.getCurrentWeather(city))  
        .toSortedList((cw1,cw2) -> cw1.getName().compare(cw2.getName()));  
}
```

Complex threading

```
public Observable<List<CityWeather>> getWeatherForLargeUsCapitals() {  
    return cityDirectory.getUsCapitals()  
        .flatMap(cityList -> Observable.from(cityList))  
        .filter(city -> city.getPopulation() > 500,000)  
        .flatMap(city -> weatherService.getCurrentWeather(city))  
        .toSortedList((cw1,cw2) -> cw1.getName().compare(cw2.getName()));  
}
```

Complex threading

```
public Observable<List<CityWeather>> getWeatherForLargeUsCapitals() {  
    return cityDirectory.getUsCapitals()  
        .flatMap(cityList -> Observable.from(cityList))  
        .filter(city -> city.getPopulation() > 500,000)  
        .flatMap(city -> weatherService.getCurrentWeather(city))  
        .toSortedList((cw1,cw2) -> cw1.getName().compare(cw2.getName()));  
}
```

Complex threading

```
public Observable<List<CityWeather>> getWeatherForLargeUsCapitals() {  
    return cityDirectory.getUsCapitals()  
        .flatMap(cityList -> Observable.from(cityList))  
        .filter(city -> city.getPopulation() > 500,000)  
        .flatMap(city -> weatherService.getCurrentWeather(city))  
        .toSortedList((cw1,cw2) -> cw1.getName().compare(cw2.getName()));  
}
```


Complex threading

```
public Observable<List<CityWeather>> getWeatherForLargeUsCapitals() {  
    return cityDirectory.getUsCapitals()  
        .flatMap(cityList -> Observable.from(cityList))  
        .filter(city -> city.getPopulation() > 500,000)  
        .flatMap(city -> weatherService.getCurrentWeather(city))  
        .toSortedList((cw1,cw2) -> cw1.getName().compare(cw2.getName()));  
}
```

Complex threading

```
public Observable<List<CityWeather>> getWeatherForLargeUsCapitals() {  
    return cityDirectory.getUsCapitals()  
        .flatMap(cityList -> Observable.from(cityList))  
        .filter(city -> city.getPopulation() > 500,000)  
        .flatMap(city -> weatherService.getCurrentWeather(city))  
        .toSortedList((cw1,cw2) -> cw1.getName().compare(cw2.getName()));  
}
```

Complex threading

```
public Observable<List<CityWeather>> getWeatherForLargeUsCapitals() {  
    return cityDirectory.getUsCapitals()  
        .flatMap(cityList -> Observable.from(cityList))  
        .filter(city -> city.getPopulation() > 500,000)  
        .flatMap(city -> weatherService.getCurrentWeather(city))  
        .toSortedList((cw1,cw2) -> cw1.getName().compare(cw2.getName()));  
}
```

Complex threading

```
public Observable<List<CityWeather>> getWeatherForLargeUsCapitals() {  
    return cityDirectory.getUsCapitals()  
        .flatMap(cityList -> Observable.from(cityList))  
        .filter(city -> city.getPopulation() > 500,000)  
        .flatMap(city -> weatherService.getCurrentWeather(city))  
        .toSortedList((cw1,cw2) -> cw1.getName().compare(cw2.getName()));  
}
```

Debouncing

```
temperatureChanges  
  .debounce(2, SECONDS)  
  .subscribe(WebService::save);
```

Debouncing

```
temperatureChanges  
  .debounce(2, SECONDS)  
  .subscribe(WebService::save);
```

```
WidgetObservable.text(searchBox)  
  .debounce(500, MILLISECONDS)  
  .flatMap(webService::search)  
  .subscribe(this::displayResults);
```

Cache on rotation

```
public void onCreate(Bundle savedInstanceState) {  
    super.onCreate(savedInstanceState);  
  
    setRetainInstance(true);  
    weatherObservable = weatherManager.getWeather().cache();  
}  
  
public void onCreateView(...) {  
    super.onCreateView(...)  
    weatherObservable.subscribe(this);  
}
```

Why RxJava / RxAndroid?

- **More robust interface than AsyncTask**
- **Easy to do complex threading**
- **Functional nature is more expressive**

Why Retrolambda?

- **Lambdas for Android**
- **Cleaner, simpler, more expressive**
- **Actually feels more functional**