

PRODUCT CATLOGUE



RUSHAB METAL INDUSTRIES

Ravindra Yadav

GST NO.: 27ACLPY2579H1ZU



All Type of Industrial Valve, Pipe, Pipe Fittings,
Pneumatics, Motorized Valve & Valve Automation

3 Pc Ball Valve with Pneumatic Rotary Actuator



Actuator	: Single / Double Acting
Size Range	: 1/2" to 12"
Ball Valve	: 3 Piece Design
MOC	: CF8 / CF8M / WCB C.S / PP
Ends	: Screwed / Flanged Socket Weld

3 Way - 4 Way Ball Valve with Pneumatic Rotary Actuator



Actuator	: Single / Double Acting
Size Range	: 1/2" to 6"
Ways	: 3 Way / 4 Way
MOC	: CF8 / CF8M / WCB C.S / PP
Ends	: Screwed / Flanged Socket Weld

Butterfly Valve with Pneumatic Rotary Actuator



Actuator	: Single / Double Acting
Size Range	: 1.1/2" to 20"
Valve Body	: Cast Iron / Brass
Disc	: SG Iron / CF8 / CF8M
Seals	: Nitrile / EPDM / Viton
Pressure Rating	: PN 16 (Max.)
Oper.Temp.Range	: 80°C / 120°C

Off. Set Disc Butterfly Valve with Pneumatic Rotary Actuator



Actuator	: Single / Double Acting
Size Range	: 1.1/2" to 12"
Valve Body	: CF8 / CF8M / WCB
Disc	: CF8 / CF8M
Seal	: PTFE Replacable / GFT
Mounting	: Universal
Press.Rating	: ANSI 150#
Opr.Temp.	: 180°C / 220°C

Aluminium Butterfly Valve with Pneumatic Rotary Actuator



Actuator	: Single / Double Acting
Size Range	: 2" to 6"
Valve Body	: Aluminium
Disc	: CF8 / CF8M
Seals	: EPDM Replaceable
Pressure	: 10 Bar
Temperature	: 100°C / 120°C

FEP Lined Butterfly Valve with Pneumatic Rotary Actuator



Actuator	: Single / Double Acting
Size Range	: 1.1/2" to 14"
Valve Body	: SG Iron / CF8 / CF8M
Disc	: CF8 / CF8M
Seals	: FEP
Pressure Rating	: 7 kg/cm ²
Temperature	: FEP Upto 180°C

2/2 Way Pneumatic Angle Type ON/OFF Control Valve



Type	: Normally Close / Open
Size Range	: 1/2" to 3"
Body	: CF8 / CF8M
Pneu. Press.	: 3.5 to 7 Bar
Working Press.	: Upto 16 Bar
Working Temp.	: 180 °C
Ends	: Screwed / Flanged
Media	: Air, Water, Oil, Gas Steam & Chemicals

3/2 Way Pneumatic 42 Kg Control Valve



Type	: Normally Close / Open
Size Range	: 1/2" to 2"
Body	: CF8 / CF8M
Pneu. Press.	: 3.5 to 7 Bar
Working Press.	: Upto 42 Bar
Working Temp.	: 180 °C
Ends	: Screwed / Flanged
Media	: Air, Water, Oil, Gas Steam & Chemicals

2/2 & 3/2 Way High Thermic Fluid Control Valve



Operation Type	: Diaphragm Type / Cylinder Diaphragm Type Thermic Fluid Control Valve
Size Range	: 1" to 8"
Body & End Piece	: WCB / S.S.
Diaphragm	: Nitrile Canvas Moulded
Diaphragm Cover	: Sheet, Metal, Pressing
Working Press.	: 150#
Working Temp.	: Upto 450 °C
Seating	: Metal to Metal
Media	: Thermic Fluid

Lug Type Knife Edge Gate Valve



Operation	: Pneumatic / Manual
Size Range	: 2" to 20"
Valve Body	: CI / CS / CF8 / CF8M
Seals	: AISI SS 304 / 316
Gland Packing	: Metal to Metal / NRV
Leakage Class	: Cotton Graphite Rope
Ends	: IV to V

Diaphragm Type Solenoid Valve



Actuator	: Diaphragm type internal pilot operated
Type	: Normally Close / Open
Size Range	: 1/2" to 2"
Body	: CF8
Diaphragm	: Nitrile
Pressure	: 0.5 to 10 Bar
Temperature	: Upto 85 °C
Ends	: Screwed / Flanged
Media	: Air, Water, Oil, Gas, Vacuum
Available Volt.	: All std. voltage available

Low Pressure Diaphragm Type Solenoid Valve



Type	: Normally Close / Open
Size Range	: 1/2" to 2"
Body	: CF8
Seals	: Nitrile
Pressure	: 0 to 5 Bar
Temperature	: Upto 85 °C
Ends	: Screwed / Flanged
Media	: Hot Water, Air, Water, Oil, Gas, Vacuum
Available Volt.	: All std. voltage available

2/2 Way Brass Solenoid Valve



Body	: Forged Brass
Pressure	: 0.5 to 10 Bar
Temperature	: -10 to 90 °C
Diaphragm	: Nitrile, Viton, EPDM
Media	: Air, Water, Oil, Gas
Opet. Voltage	: All std. voltage available
End Connection	: Screwed

Pilot Operated Solenoid Valve for Steam



Type	: Normally Close / Open
Size Range	: 1/2" to 2 1/2"
Body	: CF8
Seals	: Teflon
Pressure	: 1 to 12 Bar
Temperature	: Upto 170 °C
Ends	: Screwed / Flanged
Media	: Steam
Available Volt.	: All std. voltage available

Pulse Jet Solenoid Valve (Dust Collector Valve)



Size Range	: 1" to 1 1/2"
Body	: Aluminium Die Cast
Diaphragm	: Canvas / Nitrile / PU
Press.	: 0.6 to 10 Bar
Temp.	: 80 °C / 125 °C / (Upto 125 °C on request)
Available Volt.	: All std. voltage available

Pressure Reducing Valve (PRV)



Size	: 1/2" to 2"
Ends	: Screwed / Flanged
Body	: S.S. 304 / S.S. 316
Press. Adjusting Range	: 1 ~ 6 Kg/cm ² 4 ~ 10 Kg/cm ² 20 ~ 35 Kg/cm ²
Max. Inlet Press.	: 18 Kg/cm ² , 40 Kg/cm ²
Media	: Water, Air, Gas, Oil & Steam
Temperature	: -15 °C ~ 85 °C, 220 °C

Non Return Valve (NRV)



Body	: CF8 / CF8M
Size	: 1/2" to 2"
Pressure	: Upto 3000psi
Temp.	: 125 °C
Media	: Air, Gas, Water, Oil
Seat	: Nitrile / Viton

Disc Check Valve Non Slam



Size Range	: 1/2" to 8"
Body	: CF8 / CF8M
Disc	: S.S. 304 / S.S. 316
Disc Seat	: Metal to Metal / PTFE
Spring	: Standard
Max. Oper. Press.	: PN - 40
Max. Oper. Temp.	: Upto 300 °C

Aluminum Pneumatic Cylinder Single / Double Acting



Bore Size	: 32mm to 250mm
Stroke	: Upto 1000mm
End Cover	: Aluminum
Barrel	: Aluminum
Seals	: Buna - N
Piston	: Aluminum
Piston Rod	: EN 8
Pressure	: Upto 10 Bar
Temp.	: 60°C Max.
Media	: Air & Gas

Heavy Duty Pneumatic Cylinder Single / Double Acting



Bore Size	: 40mm to 450mm
Stroke	: Upto 3000mm
End Cover	: C.I.
Barrel	: S.Steel
Seals	: Buna - N
Piston	: C.I. / M.S.
Piston Rod	: EN 8 / 25 micron
Pressure	: Upto 12 Bar
Temp.	: 85 °C Max.
Media	: Air & Gas

Compact & Round Body Pneumatic Cylinder



End Cover	: Aluminum
Piston	: LM-2 / ALSI-132 Aluminum
Piston Rod	: BS-970-90, EN-8
V-Seal	: PU / Nitrile Buna-N Gr. 80

Filtration



Size	: 1/4" / 1/2"
Body	: Aluminum Press, Die Cast
Bowl	: Polycarbonate with Metal Guard
Element	: 25 Micron
Oper. Press	: Upto 10 Kg/cm ²

Roto Seal Coupling (Right / Left Handed Thread)



Size	: 1/4" to 2" BSP
Body	: S.Steel / WCB
Shaft	: S.Steel
Pressure	: 10 Kg/cm ²
Media	: Air, Water, Oil & Gas

Auto Drain Valve



Valve Body	: IC SS 304
Off Time	: 0.5 to 45 Minutes
On Time	: 0.5 to 10 Second
Voltage	: 230 V AC

5/2 - 3/2 Way Single - Double Coil Solenoid Valve



Design	: Spool Type, Internal Pilot Operated
Pressure	: 1 to 10 Kg/cm ²
Temperature	: 5 to 55°C
Leakage	: Bubble Tight
Coil Voltage	: 12V, 230V, 24V 110V

Moisture Separator



Body	: M S
Cartridge	: S.S. 316
Working Press.	: Upto 16 Bar
Testing Press.	: 24 Bar
Ends	: Screwed / Flanged
Installation	: Advisable at end use before FRL

Low / High Pressure Needle Valve



Size	: 1/4" to 1/2"
MOC	: S.S. 304 / 316
Seals	: Metal to Metal
Pressure	: 200 Kg/Cm ² to 700 Kg/Cm ²
Temperature	: 100° C to 350° C
Media	: Air, Water, Oil, & Gas
Ends	: Screwed End (F)

Electrical Actuator



Power Supply	: 230 Volts A/C
Rotation	: 0 - 90°
Optional	: Modulating 4 - 20 MA Input Signal & Output Signal
Limit Switch	: 1 No + 1 NC
Position Indicator	: Provided
Maximum Temp.	: -20°C + 70°C
Operating Time	: 20 To 30 Sec

3 Pc. Ball Valve with Electrical Actuator



Actuator	: Electrical
Size Range	: 1/2" to 6"
Ball Valve	: 3 Piece Design
MOC	: CF8 / CF8M / WCB C.S / PP
Ends	: Screwed / Flanged Socket Weld

3 Way - 4 Way Ball Valve with Electrical Actuator



Actuator	: Electrical
Size Range	: 1/2" to 4"
Ways	: 3 Way / 4 Way
MOC	: CF8 / CF8M / WCB C.S / PP
Ends	: Screwed / Flanged Socket Weld

Butterfly Valve with Electrical Actuator



Actuator	: Electrical
Size Range	: 1.1/2" to 20"
Valve Body	: Cast Iron
Disc	: SG Iron / CF8 / CF8M
Seals	: Nitrile
Pressure Rating	: PN 16 (Max.)
Oper.Temp.Range	: 80°C

Off. Set Disc Butterfly Valve with Electrical Actuator



Actuator	: Electrical
Size Range	: 1.1/2" to 12"
Valve Body	: CF8 / CF8M / WCB
Disc	: CF8 / CF8M
Seat	: PTFE Replacable / GFT
Mounting	: Universal
Press.Rating	: ANSI 150#
Opr.Temp.	: 180°C / 220°C

Double Flange Butterfly Valve with Electrical Actuator



Actuator	: Electrical
Size Range	: 3" to 24"
Valve Body	: Cast Iron
Disc	: CF8 / CF8M
Seals	: Nitrile / EPDM / Viton
Pressure	: PN 16 (Max.)
Temp.	: 80°C

PTFE (FEP-PFA) Lined Ball Valve with Electrical Actuator



Actuator	: Electrical
Size Range	: 1/2" to 8"
Valve Body	: CF8 / CF8M / WCB
Line	: FEP / PFA
Seals	: PTFE / GFT
Pressure	: 150#
Temp.	: FEP 180°C PFA 230°C

2/2 & 3/2 Way High Thermic Fluid Control Valve



Operation Type	: Electrical Diaphragm Type Thermic Fluid Control Valve
Size Range	: 1" to 8"
Body & End Piece	: WCB / S.S.
Diaphragm	: Nitrile Canvas Moulded
Diaphragm Cover	: Sheet, Metal, Pressing
Working Press.	: 150#
Working Temp.	: Upto 450 °C
Seating	: Metal to Metal
Media	: Thermic Fluid

Lug Type Knife Edge Gate Valve



Operation	: Electrical
Size Range	: 2" to 20"
Valve Body	: CI / CS / CF8 / CF8M
Seals	: AISI SS 304 / 316
Gland Packing	: Metal to Metal / NRV
Leakage Class	: Cotton Graphite Rope
Ends	: IV to V

Ball valve



MOC	: CF8 / CF8M / WCB C.S / PP
Ball	: CF8 / CF8M / CF3M
Mfg. Std.	: BS 5351
Size Range	: 1/2" to 12"
Ball Valve	: 2 & 3 Piece Design
Class	: 150#, 300#, 600#
Ends	: Screwed / Flanged Socket Weld

Forged Steel Ball valve



MOC	: CF8 / CF8M / ASTM 105, F304 / F316
Ball	: CF8 / CF8M / CF3M
Mfg. Std.	: BS 5351
Size Range	: 1/2" to 2"
Ball Valve	: 3 Piece Design
Class	: 800#
Ends	: Screwed / Flanged Socket Weld

Gate Valve



Range	Size	Class
Bolted Bonnet GTV	15NB to 900NB	150# to 600#
Forged Steel GTV	6NB to 50NB	800# to 2500#
Pressure Seal GTV	50NB to 600NB	900# to 2500#

Globe valve



Range	Size	Class
Bolted Bonnet GLV	15NB to 400NB	150# to 600#
Forged Steel GLV	6NB to 50NB	800# to 2500#
Pressure Seal GLV	50NB to 200NB	900# to 2500#

Non Return valve



Range	Size	Class
Bolted Bonnet SCV	15NB to 900NB	150# to 600#
Forged Steel SCV	6NB to 50NB	800# to 2500#
Pressure Seal SCV	50NB to 600NB	900# to 2500#

Wafer Check valve



Range	Size	Class
Bolted Bonnet CV	40NB to 1000NB	150# to 600#
Forged Steel CV	15NB to 300NB	800# to 2500#
Pressure Seal CV	50NB to 600NB	900# to 2500#

Plug valve Flanged End



Body	: WCB / CF8 / CF8M
Plug	: WCB / CF8 / CF8M
Class	: 150#
Body Press.	: 30 Kg/cm ²
Seat Press.	: 22 Kg/cm ²
Pneu. Press.	: 7 Kg/cm ²

Strainer



Range	Size	Class
"Y" Type	15NB to 600NB	150# to 2500#
Basket Type	50NB to 1000NB	150#

Investment Casting Steam Trap



Ends	: Screwed / Socketweld
Size	: 15mm To 25mm
Max. Inlet Press.	: 32kg / Cm ² at 425°C
Min. Press	: 0.25 Kg / Cm ²

Vertical Steam Trap



Make	: REX
Size	: 15mm to 50mm
Moc	: CI, CS
End Connection	: Screwed / Flanged / Socket Weld
Temperature	: Up to 450 °C
Media	: Steam
Type	: Vertical Type / Horizontal Type

Ball Float Steam Trap



Make	: REX
Size	: 15mm to 50mm
Moc	: CI, CS
End Connection	: Screwed / Flanged / Socket Weld
Temperature	: Up to 200 °C
Media	: Steam
Type	: Vertical Type / Horizontal Type

All Model Steam Rotary Joints



Make	: REX
Size	: 15mm to 125mm
Moc	: CI, CS, GM
End Connection	: Screwed / Flanged /
Temperature	: Up to 350 °C
Media	: Steam, Water, Air, Hot Oil

Triple Off. Set Design Butterfly valve



Body	: CI / CS / SG Iron / CF8 / CF8M
Bottom Cover	: CI / CS / SG Iron / CF8 / CF8M
Disc	: PTFE / Nitrile / EPDM / Viton
Seat Ring	: SS 304 / SS 316
Class	: PN 10 / PN 16
Body Press.	: 15 Kg/cm ² / 22 Kg/cm ²
Seat Press.	: 10 Kg/cm ² / 16 Kg/cm ²

Safety valve



Body	: WCB / CF8 / CF8M / CI
Bonnet	: WCB / CF8 / CF8M / CI
Cap	: WCB / CF8 / CF8M / CI
Body Press.	: 1 Kg/cm ² to 21 Kg/cm ²
Seat Press.	: Hydrostatic Test Twice the Seat pressure
Temperature	: 425 °C

Tube Glass



CARBON STEEL	
Moc	: EN 8 (150#)
Size	: 15mm to 100mm
STAINLESS STEEL	
Moc	: SS 304 / 316 (150#)
Size	: 15mm to 150mm
INVESTMENT CASTING	
Moc	: Cf8 / Cf8M (150#)
Size	: 25mm to 150mm

Gun Metal Valve



- Gate Valve as per IS 778 CL-I
- Globe Valve as per IS 778 CL-I
- Horizontal Non Return Valve as per IS 778 CL-I
- Steam Stop Valve

Strainer



Material Of Construction :	
CI DI CS SS	
Seat : Nitrile Neoprene PTFE Viton Hypalon Silicon	
End Connections :	
Wafer Type Double Flanged Lug End	
Pressure Rating :	
ASA 125# 150# PN 1.0 PN 1.6 PN 2.0 PN 2.5	
Size Range :	
40mm to 2000mm	

Sluice Valve / Reflux Valve / Air Valve



Pressure Gauge



PU Pipe



Pneumatic PU Fittings



High Pressure Ball valve



Pharma Industry valves



Hydraulic Hoses & Fittings



Flanges & Fittings



S.S. Fittings



Brass Fittings

