




 Secrets


 ABAP


 Apex


 C


 C++


 CloudFormation


 COBOL


 C#


 CSS


 Flex


 Go


 HTML


 Java


 JavaScript


 Kotlin


 Objective C


 PHP


 PL/I


 PL/SQL


 Python


 RPG


 Ruby


 Scala


 Swift


 **Terraform**


 Text


 TypeScript

 T-SQL

 VB.NET

 VB6


 XML





Terraform static code analysis


Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your TERRAFORM code


All rules 50

 Vulnerability 5


 Security Hotspot 43

 Code Smell 2


Tags 

Search by name... 


to all resources of an account is security-sensitive

 Security Hotspot


Having policies that grant all privileges is security-sensitive

 Security Hotspot


Policies authorizing public access to resources are security-sensitive

 Security Hotspot


Granting access to S3 buckets to all or authenticated users is security-sensitive

 Security Hotspot


AWS IAM policies should not allow privilege escalation

 Vulnerability


Weak SSL/TLS protocols should not be used

 Vulnerability


Allowing public ACLs or policies on a S3 bucket is security-sensitive

 Security Hotspot


Authorizing HTTP communications with S3 buckets is security-sensitive

 Security Hotspot


Using clear-text protocols is security-sensitive

 Security Hotspot


Google Cloud load balancers SSL policies should not offer weak cipher suites



 Vulnerability


Azure custom roles should not grant subscription Owner capabilities

 Vulnerability

Allowing public network access to cloud resources is security-sensitive

 Security Hotspot

 Blocker 

 cwe owasp aws azure gcp

Enabling public network access to cloud resources can affect an organization's ability to protect its data or internal operations from data theft or disruption.

Depending on the component, inbound access from the Internet can be enabled via:

- a boolean value that explicitly allows access to the public network.
- the assignment of a public IP address.
- database firewall rules that allow public IP ranges.

Deciding to allow public access may happen for various reasons such as for quick maintenance, time saving, or by accident.

This decision increases the likelihood of attacks on the organization, such as:

- data breaches.
- intrusions into the infrastructure to permanently steal from it.
- and various malicious traffic, such as DDoS attacks.

Ask Yourself Whether

This cloud resource:

- should be publicly accessible to any Internet user.
- requires inbound traffic from the Internet to function properly.

There is a risk if you answered no to any of those questions.

Recommended Secure Coding Practices

Avoid publishing cloud services on the Internet unless they are intended to be publicly accessible, such as customer portals or e-commerce sites.

Use private networks (and associated private IP addresses) and VPC peering or other secure communication tunnels to communicate with other cloud components.

The goal is to prevent the component from intercepting traffic coming in via the public IP address. If the cloud resource does not support the absence of a public IP address, assign a public IP address to it, but do not create listeners for the public IP address.





Sensitive Code Example

For AWS:

```
resource "aws_instance" "example" {
  associate_public_ip_address = true # Sensitive
}
```

https://rules.sonarsource.com/terraform/RSPEC-6329

1/3

<div>Excluding users or groups activities from audit logs is security-sensitive</div> <div> Security Hotspot</div>
<div>Defining a short log retention duration is security-sensitive</div> <div> Security Hotspot</div>
<div>Enabling Attribute-Based Access Control for Kubernetes is security-sensitive</div> <div> Security Hotspot</div>
<div>Creating custom roles allowing privilege escalation is security-sensitive</div> <div> Security Hotspot</div>

```
resource "aws_dms_replication_instance" "example" {
  publicly_accessible = true # Sensitive
}
```

For Azure:

```
resource "azurerm_postgresql_server" "example" {
  public_network_access_enabled = true # Sensitive
}
```

```
resource "azurerm_postgresql_server" "example" {
  public_network_access_enabled = true # Sensitive
}
```

```
resource "azurerm_kubernetes_cluster" "production" {
  api_server_authorized_ip_ranges = ["176.0.0/4"] # Sensitive
  default_node_pool {
    enable_node_public_ip = true # Sensitive
  }
}
```

For GCP:

```
resource "google_compute_instance" "example" {
  network_interface {
    network = "default"

    access_config { # Sensitive
      # Ephemeral public IP
    }
  }
}
```

Compliant Solution

For AWS:

```
resource "aws_instance" "example" {
  associate_public_ip_address = false
}
```

```
resource "aws_dms_replication_instance" "example" {
  publicly_accessible = false
}
```

For Azure:

```
resource "azurerm_postgresql_server" "example" {
  public_network_access_enabled = false
}
```

```
resource "azurerm_kubernetes_cluster" "production" {
  api_server_authorized_ip_ranges = ["192.168.0.0/16"]
  default_node_pool {
    enable_node_public_ip = false
  }
}
```

For GCP:

```
resource "google_compute_instance" "example" {
  network_interface {
    network = "default"
  }
}
```

See

- [OWASP Top 10 2021 Category A1](#) - Broken Access Control
- [AWS Documentation](#) - Amazon EC2 instance IP addressing
- [AWS Documentation](#) - Public and private replication instances
- [AWS Documentation](#) - VPC Peering
- [MITRE, CWE-284](#) - Improper Access Control
- [MITRE, CWE-668](#) - Exposure of Resource to Wrong Sphere
- [OWASP Top 10 2017 Category A5](#) - Broken Access Control

Available In:



© 2008-2022 SonarSource S.A., Switzerland. All content is copyright protected.
SONAR, SONARSOURCE, SONARLINT, SONARQUBE and SONARCLOUD are
trademarks of SonarSource S.A. All other trademarks and copyrights are the
property of their respective owners. All rights are expressly reserved.
[Privacy Policy](#)