

---

# AWS Identity and Access Management

## API Reference

### API Version 2010-05-08



## AWS Identity and Access Management: API Reference

Copyright © 2022 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

## Table of Contents

Welcome .....	1
Programmatic access to IAM .....	1
Signing requests .....	1
Additional resources .....	1
Actions .....	2
AddClientIDToOpenIDConnectProvider .....	6
Request Parameters .....	6
Errors .....	6
Examples .....	7
See Also .....	7
AddRoleToInstanceProfile .....	8
Request Parameters .....	8
Errors .....	8
Examples .....	9
See Also .....	9
AddUserToGroup .....	11
Request Parameters .....	11
Errors .....	11
Examples .....	12
See Also .....	12
AttachGroupPolicy .....	13
Request Parameters .....	13
Errors .....	13
Examples .....	14
See Also .....	14
AttachRolePolicy .....	16
Request Parameters .....	16
Errors .....	16
Examples .....	17
See Also .....	18
AttachUserPolicy .....	19
Request Parameters .....	19
Errors .....	19
Examples .....	20
See Also .....	20
ChangePassword .....	22
Request Parameters .....	22
Errors .....	22
Examples .....	23
See Also .....	23
CreateAccessKey .....	25
Request Parameters .....	25
Response Elements .....	25
Errors .....	25
Examples .....	26
See Also .....	26
CreateAccountAlias .....	28
Request Parameters .....	28
Errors .....	28
Examples .....	28
See Also .....	29
CreateGroup .....	30
Request Parameters .....	30
Response Elements .....	30

Errors .....	31
Examples .....	31
See Also .....	32
CreateInstanceProfile .....	33
Request Parameters .....	33
Response Elements .....	34
Errors .....	34
Examples .....	34
See Also .....	35
CreateLoginProfile .....	36
Request Parameters .....	36
Response Elements .....	37
Errors .....	37
Examples .....	37
See Also .....	38
CreateOpenIDConnectProvider .....	39
Request Parameters .....	39
Response Elements .....	40
Errors .....	41
Examples .....	41
See Also .....	42
CreatePolicy .....	43
Request Parameters .....	43
Response Elements .....	44
Errors .....	45
Examples .....	45
See Also .....	46
CreatePolicyVersion .....	47
Request Parameters .....	47
Response Elements .....	48
Errors .....	48
Examples .....	49
See Also .....	49
CreateRole .....	50
Request Parameters .....	50
Response Elements .....	52
Errors .....	52
Examples .....	53
See Also .....	53
CreateSAMLProvider .....	54
Request Parameters .....	54
Response Elements .....	55
Errors .....	55
Examples .....	56
See Also .....	56
CreateServiceLinkedRole .....	57
Request Parameters .....	57
Response Elements .....	58
Errors .....	58
See Also .....	58
CreateServiceSpecificCredential .....	60
Request Parameters .....	60
Response Elements .....	60
Errors .....	61
Examples .....	61
See Also .....	62
CreateUser .....	63

Request Parameters .....	63
Response Elements .....	64
Errors .....	64
Examples .....	65
See Also .....	65
CreateVirtualMFADevice .....	66
Request Parameters .....	66
Response Elements .....	67
Errors .....	67
Examples .....	68
See Also .....	68
DeactivateMFADevice .....	69
Request Parameters .....	69
Errors .....	69
Examples .....	70
See Also .....	70
DeleteAccessKey .....	72
Request Parameters .....	72
Errors .....	72
Examples .....	73
See Also .....	73
DeleteAccountAlias .....	74
Request Parameters .....	74
Errors .....	74
Examples .....	74
See Also .....	75
DeleteAccountPasswordPolicy .....	76
Errors .....	76
Examples .....	76
See Also .....	76
DeleteGroup .....	78
Request Parameters .....	78
Errors .....	78
Examples .....	79
See Also .....	79
DeleteGroupPolicy .....	80
Request Parameters .....	80
Errors .....	80
Examples .....	81
See Also .....	81
DeleteInstanceProfile .....	82
Request Parameters .....	82
Errors .....	82
Examples .....	83
See Also .....	83
DeleteLoginProfile .....	84
Request Parameters .....	84
Errors .....	84
Examples .....	85
See Also .....	85
DeleteOpenIDConnectProvider .....	86
Request Parameters .....	86
Errors .....	86
Examples .....	86
See Also .....	87
DeletePolicy .....	88
Request Parameters .....	88

Errors .....	88
Examples .....	89
See Also .....	89
DeletePolicyVersion .....	90
Request Parameters .....	90
Errors .....	90
Examples .....	91
See Also .....	91
DeleteRole .....	93
Request Parameters .....	93
Errors .....	93
Examples .....	94
See Also .....	94
DeleteRolePermissionsBoundary .....	95
Request Parameters .....	95
Errors .....	95
See Also .....	95
DeleteRolePolicy .....	97
Request Parameters .....	97
Errors .....	97
Examples .....	98
See Also .....	98
DeleteSAMLProvider .....	99
Request Parameters .....	99
Errors .....	99
Examples .....	100
See Also .....	100
DeleteServerCertificate .....	101
Request Parameters .....	101
Errors .....	101
Examples .....	102
See Also .....	102
DeleteServiceLinkedRole .....	103
Request Parameters .....	103
Response Elements .....	103
Errors .....	103
Examples .....	104
See Also .....	104
DeleteServiceSpecificCredential .....	106
Request Parameters .....	106
Errors .....	106
Examples .....	107
See Also .....	107
DeleteSigningCertificate .....	108
Request Parameters .....	108
Errors .....	108
Examples .....	109
See Also .....	109
DeleteSSHPublicKey .....	110
Request Parameters .....	110
Errors .....	110
Examples .....	111
See Also .....	111
DeleteUser .....	112
Request Parameters .....	112
Errors .....	112
Examples .....	113

See Also .....	113
DeleteUserPermissionsBoundary .....	115
Request Parameters .....	115
Errors .....	115
See Also .....	115
DeleteUserPolicy .....	117
Request Parameters .....	117
Errors .....	117
Examples .....	118
See Also .....	118
DeleteVirtualMFADevice .....	119
Request Parameters .....	119
Errors .....	119
Examples .....	120
See Also .....	120
DetachGroupPolicy .....	121
Request Parameters .....	121
Errors .....	121
Examples .....	122
See Also .....	122
DetachRolePolicy .....	123
Request Parameters .....	123
Errors .....	123
Examples .....	124
See Also .....	124
DetachUserPolicy .....	126
Request Parameters .....	126
Errors .....	126
Examples .....	127
See Also .....	127
EnableMFADevice .....	128
Request Parameters .....	128
Errors .....	129
Examples .....	130
See Also .....	130
GenerateCredentialReport .....	131
Response Elements .....	131
Errors .....	131
Examples .....	131
See Also .....	132
GenerateOrganizationsAccessReport .....	133
Request Parameters .....	134
Response Elements .....	135
Errors .....	135
Examples .....	135
See Also .....	136
GenerateServiceLastAccessedDetails .....	137
Request Parameters .....	137
Response Elements .....	138
Errors .....	138
Examples .....	138
See Also .....	139
GetAccessKeyLastUsed .....	140
Request Parameters .....	140
Response Elements .....	140
Errors .....	140
Examples .....	141

See Also .....	141
GetAccountAuthorizationDetails .....	142
Request Parameters .....	142
Response Elements .....	143
Errors .....	143
Examples .....	144
See Also .....	148
GetAccountPasswordPolicy .....	149
Response Elements .....	149
Errors .....	149
Examples .....	149
See Also .....	150
GetAccountSummary .....	151
Response Elements .....	151
Errors .....	151
Examples .....	151
See Also .....	154
GetContextKeysForCustomPolicy .....	155
Request Parameters .....	155
Response Elements .....	155
Errors .....	155
Examples .....	156
See Also .....	156
GetContextKeysForPrincipalPolicy .....	158
Request Parameters .....	158
Response Elements .....	159
Errors .....	159
Examples .....	159
See Also .....	160
GetCredentialReport .....	161
Response Elements .....	161
Errors .....	161
Examples .....	162
See Also .....	162
GetGroup .....	163
Request Parameters .....	163
Response Elements .....	163
Errors .....	164
Examples .....	164
See Also .....	165
GetGroupPolicy .....	166
Request Parameters .....	166
Response Elements .....	166
Errors .....	167
Examples .....	167
See Also .....	168
GetInstanceProfile .....	169
Request Parameters .....	169
Response Elements .....	169
Errors .....	169
Examples .....	170
See Also .....	170
GetLoginProfile .....	172
Request Parameters .....	172
Response Elements .....	172
Errors .....	172
Examples .....	173

See Also .....	173
GetOpenIDConnectProvider .....	174
Request Parameters .....	174
Response Elements .....	174
Errors .....	175
Examples .....	175
See Also .....	176
GetOrganizationsAccessReport .....	177
Request Parameters .....	177
Response Elements .....	178
Errors .....	179
Examples .....	179
See Also .....	180
GetPolicy .....	181
Request Parameters .....	181
Response Elements .....	181
Errors .....	181
Examples .....	182
See Also .....	182
GetPolicyVersion .....	184
Request Parameters .....	184
Response Elements .....	184
Errors .....	185
Examples .....	185
See Also .....	186
GetRole .....	187
Request Parameters .....	187
Response Elements .....	187
Errors .....	187
Examples .....	188
See Also .....	188
GetRolePolicy .....	189
Request Parameters .....	189
Response Elements .....	189
Errors .....	190
Examples .....	190
See Also .....	191
GetSAMLProvider .....	192
Request Parameters .....	192
Response Elements .....	192
Errors .....	193
Examples .....	193
See Also .....	193
GetServerCertificate .....	195
Request Parameters .....	195
Response Elements .....	195
Errors .....	195
Examples .....	196
See Also .....	196
GetServiceLastAccessedDetails .....	198
Request Parameters .....	198
Response Elements .....	199
Errors .....	200
Examples .....	200
See Also .....	201
GetServiceLastAccessedDetailsWithEntities .....	203
Request Parameters .....	203

Response Elements .....	204
Errors .....	205
Examples .....	205
See Also .....	206
GetServiceLinkedRoleDeletionStatus .....	207
Request Parameters .....	207
Response Elements .....	207
Errors .....	207
Examples .....	208
See Also .....	209
GetSSHPublicKey .....	210
Request Parameters .....	210
Response Elements .....	210
Errors .....	211
Examples .....	211
See Also .....	212
GetUser .....	213
Request Parameters .....	213
Response Elements .....	213
Errors .....	213
Examples .....	214
See Also .....	214
GetUserPolicy .....	216
Request Parameters .....	216
Response Elements .....	216
Errors .....	217
Examples .....	217
See Also .....	218
ListAccessKeys .....	219
Request Parameters .....	219
Response Elements .....	220
Errors .....	220
Examples .....	220
See Also .....	221
ListAccountAliases .....	222
Request Parameters .....	222
Response Elements .....	222
Errors .....	223
Examples .....	223
See Also .....	223
ListAttachedGroupPolicies .....	225
Request Parameters .....	225
Response Elements .....	226
Errors .....	226
Examples .....	227
See Also .....	227
ListAttachedRolePolicies .....	229
Request Parameters .....	229
Response Elements .....	230
Errors .....	230
Examples .....	231
See Also .....	231
ListAttachedUserPolicies .....	233
Request Parameters .....	233
Response Elements .....	234
Errors .....	234
Examples .....	235

See Also .....	235
ListEntitiesForPolicy .....	237
Request Parameters .....	237
Response Elements .....	238
Errors .....	239
Examples .....	239
See Also .....	240
ListGroupPolicies .....	241
Request Parameters .....	241
Response Elements .....	242
Errors .....	242
Examples .....	242
See Also .....	243
ListGroups .....	244
Request Parameters .....	244
Response Elements .....	245
Errors .....	245
Examples .....	245
See Also .....	246
ListGroupsForUser .....	247
Request Parameters .....	247
Response Elements .....	247
Errors .....	248
Examples .....	248
See Also .....	249
ListInstanceProfiles .....	250
Request Parameters .....	250
Response Elements .....	251
Errors .....	251
Examples .....	251
See Also .....	252
ListInstanceProfilesForRole .....	253
Request Parameters .....	253
Response Elements .....	254
Errors .....	254
Examples .....	254
See Also .....	255
ListInstanceProfileTags .....	256
Request Parameters .....	256
Response Elements .....	256
Errors .....	257
Examples .....	257
See Also .....	258
ListMFADevices .....	259
Request Parameters .....	259
Response Elements .....	260
Errors .....	260
Examples .....	260
See Also .....	261
ListMFADeviceTags .....	262
Request Parameters .....	262
Response Elements .....	263
Errors .....	263
Examples .....	263
See Also .....	264
ListOpenIDConnectProviders .....	265
Response Elements .....	265

Errors .....	265
Examples .....	265
See Also .....	266
ListOpenIDConnectProviderTags .....	267
Request Parameters .....	267
Response Elements .....	267
Errors .....	268
Examples .....	268
See Also .....	269
ListPolicies .....	270
Request Parameters .....	270
Response Elements .....	271
Errors .....	272
Examples .....	272
See Also .....	273
ListPoliciesGrantingServiceAccess .....	274
Request Parameters .....	274
Response Elements .....	275
Errors .....	275
Examples .....	276
See Also .....	276
ListPolicyTags .....	278
Request Parameters .....	278
Response Elements .....	278
Errors .....	279
Examples .....	279
See Also .....	280
ListPolicyVersions .....	281
Request Parameters .....	281
Response Elements .....	281
Errors .....	282
Examples .....	282
See Also .....	283
ListRolePolicies .....	284
Request Parameters .....	284
Response Elements .....	285
Errors .....	285
Examples .....	285
See Also .....	286
ListRoles .....	287
Request Parameters .....	287
Response Elements .....	288
Errors .....	288
Examples .....	288
See Also .....	289
ListRoleTags .....	290
Request Parameters .....	290
Response Elements .....	290
Errors .....	291
Examples .....	291
See Also .....	292
ListSAMLProviders .....	293
Response Elements .....	293
Errors .....	293
Examples .....	293
See Also .....	294
ListSAMLProviderTags .....	295

Request Parameters .....	295
Response Elements .....	296
Errors .....	296
Examples .....	296
See Also .....	297
<b>ListServerCertificates .....</b>	<b>299</b>
Request Parameters .....	299
Response Elements .....	300
Errors .....	300
Examples .....	300
See Also .....	301
<b>ListServerCertificateTags .....</b>	<b>302</b>
Request Parameters .....	302
Response Elements .....	303
Errors .....	303
Examples .....	303
See Also .....	304
<b>ListServiceSpecificCredentials .....</b>	<b>305</b>
Request Parameters .....	305
Response Elements .....	305
Errors .....	305
Examples .....	306
See Also .....	306
<b>ListSigningCertificates .....</b>	<b>308</b>
Request Parameters .....	308
Response Elements .....	309
Errors .....	309
Examples .....	309
See Also .....	310
<b>ListSSHPublicKeys .....</b>	<b>311</b>
Request Parameters .....	311
Response Elements .....	312
Errors .....	312
Examples .....	312
See Also .....	313
<b>ListUserPolicies .....</b>	<b>314</b>
Request Parameters .....	314
Response Elements .....	315
Errors .....	315
Examples .....	315
See Also .....	316
<b>ListUsers .....</b>	<b>317</b>
Request Parameters .....	317
Response Elements .....	318
Errors .....	318
Examples .....	318
See Also .....	319
<b>ListUserTags .....</b>	<b>320</b>
Request Parameters .....	320
Response Elements .....	320
Errors .....	321
Examples .....	321
See Also .....	322
<b>ListVirtualMFADevices .....</b>	<b>323</b>
Request Parameters .....	323
Response Elements .....	324
Errors .....	324

Examples .....	324
See Also .....	325
PutGroupPolicy .....	326
Request Parameters .....	326
Errors .....	327
Examples .....	327
See Also .....	328
PutRolePermissionsBoundary .....	329
Request Parameters .....	329
Errors .....	329
See Also .....	330
PutRolePolicy .....	331
Request Parameters .....	331
Errors .....	332
Examples .....	333
See Also .....	333
PutUserPermissionsBoundary .....	334
Request Parameters .....	334
Errors .....	334
See Also .....	335
PutUserPolicy .....	336
Request Parameters .....	336
Errors .....	337
Examples .....	337
See Also .....	338
RemoveClientIDFromOpenIDConnectProvider .....	339
Request Parameters .....	339
Errors .....	339
Examples .....	340
See Also .....	340
RemoveRoleFromInstanceProfile .....	341
Request Parameters .....	341
Errors .....	341
Examples .....	342
See Also .....	342
RemoveUserFromGroup .....	344
Request Parameters .....	344
Errors .....	344
Examples .....	345
See Also .....	345
ResetServiceSpecificCredential .....	346
Request Parameters .....	346
Response Elements .....	346
Errors .....	347
Examples .....	347
See Also .....	347
ResyncMFADevice .....	349
Request Parameters .....	349
Errors .....	350
Examples .....	350
See Also .....	351
SetDefaultPolicyVersion .....	352
Request Parameters .....	352
Errors .....	352
Examples .....	353
See Also .....	353
SetSecurityTokenServicePreferences .....	354

Request Parameters .....	354
Errors .....	354
Examples .....	354
See Also .....	355
SimulateCustomPolicy .....	356
Request Parameters .....	356
Response Elements .....	360
Errors .....	360
Examples .....	361
See Also .....	363
SimulatePrincipalPolicy .....	365
Request Parameters .....	365
Response Elements .....	369
Errors .....	370
Examples .....	370
See Also .....	375
TagInstanceProfile .....	376
Request Parameters .....	376
Errors .....	377
Examples .....	377
See Also .....	378
TagMFADevice .....	379
Request Parameters .....	379
Errors .....	380
Examples .....	380
See Also .....	381
TagOpenIDConnectProvider .....	382
Request Parameters .....	382
Errors .....	383
Examples .....	383
See Also .....	384
TagPolicy .....	385
Request Parameters .....	385
Errors .....	386
Examples .....	386
See Also .....	387
TagRole .....	388
Request Parameters .....	388
Errors .....	389
Examples .....	389
See Also .....	390
TagSAMLProvider .....	391
Request Parameters .....	391
Errors .....	392
Examples .....	392
See Also .....	393
TagServerCertificate .....	394
Request Parameters .....	394
Errors .....	395
Examples .....	395
See Also .....	396
TagUser .....	397
Request Parameters .....	397
Errors .....	398
Examples .....	398
See Also .....	399
UntagInstanceProfile .....	400

Request Parameters .....	400
Errors .....	400
Examples .....	401
See Also .....	401
UntagMFADevice .....	403
Request Parameters .....	403
Errors .....	403
Examples .....	404
See Also .....	404
UntagOpenIDConnectProvider .....	406
Request Parameters .....	406
Errors .....	406
Examples .....	407
See Also .....	407
UntagPolicy .....	409
Request Parameters .....	409
Errors .....	409
Examples .....	410
See Also .....	410
UntagRole .....	412
Request Parameters .....	412
Errors .....	412
Examples .....	413
See Also .....	413
UntagSAMLProvider .....	415
Request Parameters .....	415
Errors .....	415
Examples .....	416
See Also .....	416
UntagServerCertificate .....	418
Request Parameters .....	418
Errors .....	418
Examples .....	419
See Also .....	420
UntagUser .....	421
Request Parameters .....	421
Errors .....	421
Examples .....	422
See Also .....	422
UpdateAccessKey .....	424
Request Parameters .....	424
Errors .....	425
Examples .....	425
See Also .....	425
UpdateAccountPasswordPolicy .....	427
Request Parameters .....	427
Errors .....	429
Examples .....	429
See Also .....	430
UpdateAssumeRolePolicy .....	431
Request Parameters .....	431
Errors .....	431
Examples .....	432
See Also .....	432
UpdateGroup .....	434
Request Parameters .....	434
Errors .....	435

Examples .....	435
See Also .....	436
UpdateLoginProfile .....	437
Request Parameters .....	437
Errors .....	438
Examples .....	438
See Also .....	439
UpdateOpenIDConnectProviderThumbprint .....	440
Request Parameters .....	440
Errors .....	440
Examples .....	441
See Also .....	441
UpdateRole .....	443
Request Parameters .....	443
Errors .....	443
See Also .....	444
UpdateRoleDescription .....	445
Request Parameters .....	445
Response Elements .....	445
Errors .....	445
See Also .....	446
UpdateSAMLProvider .....	447
Request Parameters .....	447
Response Elements .....	447
Errors .....	447
Examples .....	448
See Also .....	448
UpdateServerCertificate .....	450
Request Parameters .....	450
Errors .....	451
Examples .....	451
See Also .....	452
UpdateServiceSpecificCredential .....	453
Request Parameters .....	453
Errors .....	453
Examples .....	454
See Also .....	454
UpdateSigningCertificate .....	455
Request Parameters .....	455
Errors .....	455
Examples .....	456
See Also .....	456
UpdateSSHPublicKey .....	458
Request Parameters .....	458
Errors .....	458
Examples .....	459
See Also .....	459
UpdateUser .....	460
Request Parameters .....	460
Errors .....	461
Examples .....	461
See Also .....	462
UploadServerCertificate .....	463
Request Parameters .....	463
Response Elements .....	465
Errors .....	465
Examples .....	466

See Also .....	467
UploadSigningCertificate .....	468
Request Parameters .....	468
Response Elements .....	469
Errors .....	469
Examples .....	470
See Also .....	471
UploadSSHPublicKey .....	472
Request Parameters .....	472
Response Elements .....	472
Errors .....	473
Examples .....	473
See Also .....	474
Data Types .....	475
AccessDetail .....	477
Contents .....	477
See Also .....	478
AccessKey .....	479
Contents .....	479
See Also .....	480
AccessKeyLastUsed .....	481
Contents .....	481
See Also .....	481
AccessKeyMetadata .....	483
Contents .....	483
See Also .....	483
AttachedPermissionsBoundary .....	485
Contents .....	485
See Also .....	485
AttachedPolicy .....	486
Contents .....	486
See Also .....	486
ContextEntry .....	487
Contents .....	487
See Also .....	487
DeletionTaskFailureReasonType .....	488
Contents .....	488
See Also .....	488
EntityDetails .....	489
Contents .....	489
See Also .....	489
EntityInfo .....	490
Contents .....	490
See Also .....	491
ErrorDetails .....	492
Contents .....	492
See Also .....	492
EvaluationResult .....	493
Contents .....	493
See Also .....	494
Group .....	496
Contents .....	496
See Also .....	497
GroupDetail .....	498
Contents .....	498
See Also .....	499
InstanceProfile .....	500

Contents .....	500
See Also .....	501
ListPoliciesGrantingServiceAccessEntry .....	502
Contents .....	502
See Also .....	502
LoginProfile .....	503
Contents .....	503
See Also .....	503
ManagedPolicyDetail .....	504
Contents .....	504
See Also .....	506
MFADevice .....	507
Contents .....	507
See Also .....	507
OpenIDConnectProviderListEntry .....	508
Contents .....	508
See Also .....	508
OrganizationsDecisionDetail .....	509
Contents .....	509
See Also .....	509
PasswordPolicy .....	510
Contents .....	510
See Also .....	511
PermissionsBoundaryDecisionDetail .....	512
Contents .....	512
See Also .....	512
Policy .....	513
Contents .....	513
See Also .....	515
PolicyDetail .....	516
Contents .....	516
See Also .....	516
PolicyGrantingServiceAccess .....	517
Contents .....	517
See Also .....	518
PolicyGroup .....	519
Contents .....	519
See Also .....	519
PolicyRole .....	520
Contents .....	520
See Also .....	520
PolicyUser .....	521
Contents .....	521
See Also .....	521
PolicyVersion .....	522
Contents .....	522
See Also .....	523
Position .....	524
Contents .....	524
See Also .....	524
ResourceSpecificResult .....	525
Contents .....	525
See Also .....	526
Role .....	527
Contents .....	527
See Also .....	529
RoleDetail .....	530

Contents .....	530
See Also .....	532
RoleLastUsed .....	533
Contents .....	533
See Also .....	533
RoleUsageType .....	534
Contents .....	534
See Also .....	534
SAMLProviderListEntry .....	535
Contents .....	535
See Also .....	535
ServerCertificate .....	536
Contents .....	536
See Also .....	536
ServerCertificateMetadata .....	538
Contents .....	538
See Also .....	539
ServiceLastAccessed .....	540
Contents .....	540
See Also .....	541
ServiceSpecificCredential .....	542
Contents .....	542
See Also .....	543
ServiceSpecificCredentialMetadata .....	544
Contents .....	544
See Also .....	545
SigningCertificate .....	546
Contents .....	546
See Also .....	547
SSHPublicKey .....	548
Contents .....	548
See Also .....	549
SSHPublicKeyMetadata .....	550
Contents .....	550
See Also .....	550
Statement .....	552
Contents .....	552
See Also .....	552
Tag .....	553
Contents .....	553
See Also .....	553
TrackedActionLastAccessed .....	554
Contents .....	554
See Also .....	554
User .....	556
Contents .....	556
See Also .....	557
UserDetail .....	558
Contents .....	558
See Also .....	559
VirtualMFADevice .....	561
Contents .....	561
See Also .....	562
Common Parameters .....	563
Common Errors .....	565

# Welcome to the IAM API Reference

AWS Identity and Access Management (IAM) is a web service for securely controlling access to AWS services. With IAM, you can centrally manage users, security credentials such as access keys, and permissions that control which AWS resources users and applications can access. For more information about IAM, see [AWS Identity and Access Management \(IAM\)](#) and the [AWS Identity and Access Management User Guide](#).

## Programmatic access to IAM

We recommend that you use the AWS SDKs to make programmatic API calls to IAM. The AWS SDKs consist of libraries and sample code for various programming languages and platforms (for example, Java, Ruby, .NET, iOS, and Android). The SDKs provide a convenient way to create programmatic access to IAM and AWS. For example, the SDKs take care of tasks such as cryptographically signing requests, managing errors, and retrying requests automatically. For more information, see [Tools to build on AWS](#).

Alternatively, you can also use the IAM Query API to make direct calls to the IAM service. For more information about calling the IAM Query API, see [Making query requests](#) in the *AWS Identity and Access Management User Guide*. IAM supports GET and POST requests for all actions. That is, the API does not require you to use GET for some actions and POST for others. However, GET requests are subject to the limitation size of a URL. Therefore, for operations that require larger sizes, use a POST request.

## Signing requests

Requests must be signed using an access key ID and a secret access key. We strongly recommend that you do not use your AWS account access key ID and secret access key for everyday work with IAM. You can use the access key ID and secret access key for an IAM user or you can use the AWS Security Token Service to generate temporary security credentials and use those to sign requests.

To sign requests, we recommend that you use [Signature Version 4](#). If you have an existing application that uses Signature Version 2, you do not have to update it to use Signature Version 4. However, some operations now require Signature Version 4. The documentation for operations that require version 4 indicate this requirement.

## Additional resources

- [AWS security credentials](#). This topic provides general information about the types of credentials used for accessing AWS.
- [IAM best practices](#). This topic presents a list of suggestions for using the IAM service to help secure your AWS resources.
- [Signing AWS API requests](#). This set of topics walk you through the process of signing a request using an access key ID and secret access key.

# Actions

The following actions are supported:

- [AddClientIDToOpenIDConnectProvider \(p. 6\)](#)
- [AddRoleToInstanceProfile \(p. 8\)](#)
- [AddUserToGroup \(p. 11\)](#)
- [AttachGroupPolicy \(p. 13\)](#)
- [AttachRolePolicy \(p. 16\)](#)
- [AttachUserPolicy \(p. 19\)](#)
- [ChangePassword \(p. 22\)](#)
- [CreateAccessKey \(p. 25\)](#)
- [CreateAccountAlias \(p. 28\)](#)
- [CreateGroup \(p. 30\)](#)
- [CreateInstanceProfile \(p. 33\)](#)
- [CreateLoginProfile \(p. 36\)](#)
- [CreateOpenIDConnectProvider \(p. 39\)](#)
- [CreatePolicy \(p. 43\)](#)
- [CreatePolicyVersion \(p. 47\)](#)
- [CreateRole \(p. 50\)](#)
- [CreateSAMLProvider \(p. 54\)](#)
- [CreateServiceLinkedRole \(p. 57\)](#)
- [CreateServiceSpecificCredential \(p. 60\)](#)
- [CreateUser \(p. 63\)](#)
- [CreateVirtualMFADevice \(p. 66\)](#)
- [DeactivateMFADevice \(p. 69\)](#)
- [DeleteAccessKey \(p. 72\)](#)
- [DeleteAccountAlias \(p. 74\)](#)
- [DeleteAccountPasswordPolicy \(p. 76\)](#)
- [DeleteGroup \(p. 78\)](#)
- [DeleteGroupPolicy \(p. 80\)](#)
- [DeleteInstanceProfile \(p. 82\)](#)
- [DeleteLoginProfile \(p. 84\)](#)
- [DeleteOpenIDConnectProvider \(p. 86\)](#)
- [DeletePolicy \(p. 88\)](#)
- [DeletePolicyVersion \(p. 90\)](#)
- [DeleteRole \(p. 93\)](#)
- [DeleteRolePermissionsBoundary \(p. 95\)](#)
- [DeleteRolePolicy \(p. 97\)](#)
- [DeleteSAMLProvider \(p. 99\)](#)
- [DeleteServerCertificate \(p. 101\)](#)
- [DeleteServiceLinkedRole \(p. 103\)](#)
- [DeleteServiceSpecificCredential \(p. 106\)](#)
- [DeleteSigningCertificate \(p. 108\)](#)

- [DeleteSSHPublicKey \(p. 110\)](#)
- [DeleteUser \(p. 112\)](#)
- [DeleteUserPermissionsBoundary \(p. 115\)](#)
- [DeleteUserPolicy \(p. 117\)](#)
- [DeleteVirtualMFADevice \(p. 119\)](#)
- [DetachGroupPolicy \(p. 121\)](#)
- [DetachRolePolicy \(p. 123\)](#)
- [DetachUserPolicy \(p. 126\)](#)
- [EnableMFADevice \(p. 128\)](#)
- [GenerateCredentialReport \(p. 131\)](#)
- [GenerateOrganizationsAccessReport \(p. 133\)](#)
- [GenerateServiceLastAccessedDetails \(p. 137\)](#)
- [GetAccessKeyLastUsed \(p. 140\)](#)
- [GetAccountAuthorizationDetails \(p. 142\)](#)
- [GetAccountPasswordPolicy \(p. 149\)](#)
- [GetAccountSummary \(p. 151\)](#)
- [GetContextKeysForCustomPolicy \(p. 155\)](#)
- [GetContextKeysForPrincipalPolicy \(p. 158\)](#)
- [GetCredentialReport \(p. 161\)](#)
- [GetGroup \(p. 163\)](#)
- [GetGroupPolicy \(p. 166\)](#)
- [GetInstanceProfile \(p. 169\)](#)
- [GetLoginProfile \(p. 172\)](#)
- [GetOpenIDConnectProvider \(p. 174\)](#)
- [GetOrganizationsAccessReport \(p. 177\)](#)
- [GetPolicy \(p. 181\)](#)
- [GetPolicyVersion \(p. 184\)](#)
- [GetRole \(p. 187\)](#)
- [GetRolePolicy \(p. 189\)](#)
- [GetSAMLProvider \(p. 192\)](#)
- [GetServerCertificate \(p. 195\)](#)
- [GetServiceLastAccessedDetails \(p. 198\)](#)
- [GetServiceLastAccessedDetailsWithEntities \(p. 203\)](#)
- [GetServiceLinkedRoleDeletionStatus \(p. 207\)](#)
- [GetSSHPublicKey \(p. 210\)](#)
- [GetUser \(p. 213\)](#)
- [GetUserPolicy \(p. 216\)](#)
- [ListAccessKeys \(p. 219\)](#)
- [ListAccountAliases \(p. 222\)](#)
- [ListAttachedGroupPolicies \(p. 225\)](#)
- [ListAttachedRolePolicies \(p. 229\)](#)
- [ListAttachedUserPolicies \(p. 233\)](#)
- [ListEntitiesForPolicy \(p. 237\)](#)
- [ListGroupPolicies \(p. 241\)](#)
- [ListGroups \(p. 244\)](#)
- [ListGroupsForUser \(p. 247\)](#)

- [ListInstanceProfiles \(p. 250\)](#)
- [ListInstanceProfilesForRole \(p. 253\)](#)
- [ListInstanceProfileTags \(p. 256\)](#)
- [ListMFADevices \(p. 259\)](#)
- [ListMFADeviceTags \(p. 262\)](#)
- [ListOpenIDConnectProviders \(p. 265\)](#)
- [ListOpenIDConnectProviderTags \(p. 267\)](#)
- [ListPolicies \(p. 270\)](#)
- [ListPoliciesGrantingServiceAccess \(p. 274\)](#)
- [ListPolicyTags \(p. 278\)](#)
- [ListPolicyVersions \(p. 281\)](#)
- [ListRolePolicies \(p. 284\)](#)
- [ListRoles \(p. 287\)](#)
- [ListRoleTags \(p. 290\)](#)
- [ListSAMLProviders \(p. 293\)](#)
- [ListSAMLProviderTags \(p. 295\)](#)
- [ListServerCertificates \(p. 299\)](#)
- [ListServerCertificateTags \(p. 302\)](#)
- [ListServiceSpecificCredentials \(p. 305\)](#)
- [ListSigningCertificates \(p. 308\)](#)
- [ListSSHPublicKeys \(p. 311\)](#)
- [ListUserPolicies \(p. 314\)](#)
- [ListUsers \(p. 317\)](#)
- [ListUserTags \(p. 320\)](#)
- [ListVirtualMFADevices \(p. 323\)](#)
- [PutGroupPolicy \(p. 326\)](#)
- [PutRolePermissionsBoundary \(p. 329\)](#)
- [PutRolePolicy \(p. 331\)](#)
- [PutUserPermissionsBoundary \(p. 334\)](#)
- [PutUserPolicy \(p. 336\)](#)
- [RemoveClientIDFromOpenIDConnectProvider \(p. 339\)](#)
- [RemoveRoleFromInstanceProfile \(p. 341\)](#)
- [RemoveUserFromGroup \(p. 344\)](#)
- [ResetServiceSpecificCredential \(p. 346\)](#)
- [ResyncMFADevice \(p. 349\)](#)
- [SetDefaultPolicyVersion \(p. 352\)](#)
- [SetSecurityTokenServicePreferences \(p. 354\)](#)
- [SimulateCustomPolicy \(p. 356\)](#)
- [SimulatePrincipalPolicy \(p. 365\)](#)
- [TagInstanceProfile \(p. 376\)](#)
- [TagMFADevice \(p. 379\)](#)
- [TagOpenIDConnectProvider \(p. 382\)](#)
- [TagPolicy \(p. 385\)](#)
- [TagRole \(p. 388\)](#)
- [TagSAMLProvider \(p. 391\)](#)
- [TagServerCertificate \(p. 394\)](#)

- [TagUser \(p. 397\)](#)
- [UntagInstanceProfile \(p. 400\)](#)
- [UntagMFADevice \(p. 403\)](#)
- [UntagOpenIDConnectProvider \(p. 406\)](#)
- [UntagPolicy \(p. 409\)](#)
- [UntagRole \(p. 412\)](#)
- [UntagSAMLProvider \(p. 415\)](#)
- [UntagServerCertificate \(p. 418\)](#)
- [UntagUser \(p. 421\)](#)
- [UpdateAccessKey \(p. 424\)](#)
- [UpdateAccountPasswordPolicy \(p. 427\)](#)
- [UpdateAssumeRolePolicy \(p. 431\)](#)
- [UpdateGroup \(p. 434\)](#)
- [UpdateLoginProfile \(p. 437\)](#)
- [UpdateOpenIDConnectProviderThumbprint \(p. 440\)](#)
- [UpdateRole \(p. 443\)](#)
- [UpdateRoleDescription \(p. 445\)](#)
- [UpdateSAMLProvider \(p. 447\)](#)
- [UpdateServerCertificate \(p. 450\)](#)
- [UpdateServiceSpecificCredential \(p. 453\)](#)
- [UpdateSigningCertificate \(p. 455\)](#)
- [UpdateSSHPublicKey \(p. 458\)](#)
- [UpdateUser \(p. 460\)](#)
- [UploadServerCertificate \(p. 463\)](#)
- [UploadSigningCertificate \(p. 468\)](#)
- [UploadSSHPublicKey \(p. 472\)](#)

# AddClientIDToOpenIDConnectProvider

Adds a new client ID (also known as audience) to the list of client IDs already registered for the specified IAM OpenID Connect (OIDC) provider resource.

This operation is idempotent; it does not fail or return an error if you add an existing client ID to the provider.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### **ClientID**

The client ID (also known as audience) to add to the IAM OpenID Connect provider resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

### **OpenIDConnectProviderArn**

The Amazon Resource Name (ARN) of the IAM OpenID Connect (OIDC) provider resource to add the client ID to. You can get a list of OIDC provider ARNs by using the [ListOpenIDConnectProviders \(p. 265\)](#) operation.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **InvalidInput**

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### **LimitExceeded**

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of AddClientIDToOpenIDConnectProvider.

#### Sample Request

```
https://iam.amazonaws.com/?Action=AddClientIDToOpenIDConnectProvider
&ClientID=my-application-ID
&OpenIDConnectProviderArn=arn:aws:iam::123456789012:oidc-provider/server.example.com
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<AddClientIDToOpenIDConnectProviderResponse xmlns="https://iam.amazonaws.com/
doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>e4bdcdae-4f66-11e4-aefa-bfd6aEXAMPLE</RequestId>
  </ResponseMetadata>
</AddClientIDToOpenIDConnectProviderResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# AddRoleToInstanceProfile

Adds the specified IAM role to the specified instance profile. An instance profile can contain only one role, and this quota cannot be increased. You can remove the existing role and then add a different role to an instance profile. You must then wait for the change to appear across all of AWS because of [eventual consistency](#). To force the change, you must [disassociate the instance profile](#) and then [associate the instance profile](#), or you can stop your instance and then restart it.

## **Note**

The caller of this operation must be granted the `PassRole` permission on the IAM role by a permissions policy.

For more information about roles, see [Working with roles](#). For more information about instance profiles, see [About instance profiles](#).

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### **InstanceProfileName**

The name of the instance profile to update.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: Yes

### **RoleName**

The name of the role to add.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w+=,.@-]+`

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **EntityAlreadyExists**

The request was rejected because it attempted to create a resource that already exists.

HTTP Status Code: 409

#### **LimitExceeded**

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

#### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

#### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

#### **UnmodifiableEntity**

The request was rejected because only the service that depends on the service-linked role can modify or delete the role on your behalf. The error message includes the name of the service that depends on this service-linked role. You must request the change through that service.

HTTP Status Code: 400

## Examples

### Example

This example illustrates one usage of AddRoleToInstanceProfile.

#### Sample Request

```
https://iam.amazonaws.com/?Action=AddRoleToInstanceProfile
&InstanceProfileName=Webserver
&RoleName=S3Access
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<AddRoleToInstanceProfileResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>12657608-99f2-11e1-a4c3-27EXAMPLE804</RequestId>
  </ResponseMetadata>
</AddRoleToInstanceProfileResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# AddUserToGroup

Adds the specified user to the specified group.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### GroupName

The name of the group to update.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: Yes

### UserName

The name of the user to add.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### LimitExceeded

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of AddUserToGroup.

#### Sample Request

```
https://iam.amazonaws.com/?Action=AddUserToGroup
&GroupName=Managers
&UserName=Bob
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<AddUserToGroupResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
  </ResponseMetadata>
</AddUserToGroupResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# AttachGroupPolicy

Attaches the specified managed policy to the specified IAM group.

You use this operation to attach a managed policy to a group. To embed an inline policy in a group, use [PutGroupPolicy \(p. 326\)](#).

As a best practice, you can validate your IAM policies. To learn more, see [Validating IAM policies](#) in the *IAM User Guide*.

For more information about policies, see [Managed policies and inline policies](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### GroupName

The name (friendly name, not ARN) of the group to attach the policy to.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: Yes

### PolicyArn

The Amazon Resource Name (ARN) of the IAM policy you want to attach.

For more information about ARNs, see [Amazon Resource Names \(ARNs\)](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### InvalidInput

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### **LimitExceeded**

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### **PolicyNotAttachable**

The request failed because AWS service role policies can only be attached to the service-linked role for that service.

HTTP Status Code: 400

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of `AttachGroupPolicy`.

#### Sample Request

```
https://iam.amazonaws.com/?Action=AttachGroupPolicy
&GroupName=Finance
&PolicyArn=arn:aws:iam::aws:policy/ReadOnlyAccess
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<AttachGroupPolicyResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>f8a7b7b9-3d01-11e4-bfad-8d1c6EXAMPLE</RequestId>
  </ResponseMetadata>
</AttachGroupPolicyResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# AttachRolePolicy

Attaches the specified managed policy to the specified IAM role. When you attach a managed policy to a role, the managed policy becomes part of the role's permission (access) policy.

## Note

You cannot use a managed policy as the role's trust policy. The role's trust policy is created at the same time as the role, using [CreateRole \(p. 50\)](#). You can update a role's trust policy using [UpdateAssumeRolePolicy \(p. 431\)](#).

Use this operation to attach a *managed* policy to a role. To embed an inline policy in a role, use [PutRolePolicy \(p. 331\)](#). For more information about policies, see [Managed policies and inline policies](#) in the *IAM User Guide*.

As a best practice, you can validate your IAM policies. To learn more, see [Validating IAM policies](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### PolicyArn

The Amazon Resource Name (ARN) of the IAM policy you want to attach.

For more information about ARNs, see [Amazon Resource Names \(ARNs\)](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

### RoleName

The name (friendly name, not ARN) of the role to attach the policy to.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w+=,.@-]+`

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### InvalidInput

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

#### **LimitExceeded**

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

#### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

#### **PolicyNotAttachable**

The request failed because AWS service role policies can only be attached to the service-linked role for that service.

HTTP Status Code: 400

#### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

#### **UnmodifiableEntity**

The request was rejected because only the service that depends on the service-linked role can modify or delete the role on your behalf. The error message includes the name of the service that depends on this service-linked role. You must request the change through that service.

HTTP Status Code: 400

## Examples

### Example

This example illustrates one usage of AttachRolePolicy.

#### Sample Request

```
https://iam.amazonaws.com/?Action=AttachRolePolicy
&PolicyArn=arn:aws:iam::aws:policy/ReadOnlyAccess
&RoleName=ReadOnlyRole
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<AttachRolePolicyResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>37a87673-3d07-11e4-bfad-8d1c6EXAMPLE</RequestId>
  </ResponseMetadata>
</AttachRolePolicyResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# AttachUserPolicy

Attaches the specified managed policy to the specified user.

You use this operation to attach a *managed* policy to a user. To embed an inline policy in a user, use [PutUserPolicy \(p. 336\)](#).

As a best practice, you can validate your IAM policies. To learn more, see [Validating IAM policies](#) in the *IAM User Guide*.

For more information about policies, see [Managed policies and inline policies](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### PolicyArn

The Amazon Resource Name (ARN) of the IAM policy you want to attach.

For more information about ARNs, see [Amazon Resource Names \(ARNs\)](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

### UserName

The name (friendly name, not ARN) of the IAM user to attach the policy to.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w+=,.@-]+`

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### InvalidInput

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### **LimitExceeded**

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### **PolicyNotAttachable**

The request failed because AWS service role policies can only be attached to the service-linked role for that service.

HTTP Status Code: 400

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of `AttachUserPolicy`.

#### Sample Request

```
https://iam.amazonaws.com/?Action=AttachUserPolicy
&PolicyArn=arn:aws:iam::aws:policy/AdministratorAccess
&UserName=Alice
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<AttachUserPolicyResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>ed7e72d3-3d07-11e4-bfad-8d1c6EXAMPLE</RequestId>
  </ResponseMetadata>
</AttachUserPolicyResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ChangePassword

Changes the password of the IAM user who is calling this operation. This operation can be performed using the AWS CLI, the AWS API, or the **My Security Credentials** page in the AWS Management Console. The AWS account root user password is not affected by this operation.

Use [UpdateLoginProfile \(p. 437\)](#) to use the AWS CLI, the AWS API, or the **Users** page in the IAM console to change the password for any IAM user. For more information about modifying passwords, see [Managing passwords](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### NewPassword

The new password. The new password must conform to the AWS account's password policy, if one exists.

The [regex pattern](#) that is used to validate this parameter is a string of characters. That string can include almost any printable ASCII character from the space (\u0020) through the end of the ASCII character range (\u00FF). You can also include the tab (\u0009), line feed (\u000A), and carriage return (\u000D) characters. Any of these characters are valid in a password. However, many tools, such as the AWS Management Console, might restrict the ability to type certain characters because they have special meaning within that tool.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [\u0009\u000A\u000D\u0020-\u00FF]+

Required: Yes

### OldPassword

The IAM user's current password.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [\u0009\u000A\u000D\u0020-\u00FF]+

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### EntityTemporarilyUnmodifiable

The request was rejected because it referenced an entity that is temporarily unmodifiable, such as a user name that was deleted and then recreated. The error indicates that the request is likely to succeed if you try again after waiting several minutes. The error message describes the entity.

HTTP Status Code: 409

### **InvalidUserType**

The request was rejected because the type of user for the transaction was incorrect.

HTTP Status Code: 400

### **LimitExceeded**

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### **PasswordPolicyViolation**

The request was rejected because the provided password did not meet the requirements imposed by the account password policy.

HTTP Status Code: 400

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of ChangePassword.

#### Sample Request

```
https://iam.amazonaws.com/?Action=ChangePassword
&OldPassword=U79]kgds4?
&NewPassword=Lb0*1(9xpN
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<ChangePasswordResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
  </ResponseMetadata>
</ChangePasswordResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## CreateAccessKey

Creates a new AWS secret access key and corresponding AWS access key ID for the specified user. The default status for new keys is Active.

If you do not specify a user name, IAM determines the user name implicitly based on the AWS access key ID signing the request. This operation works for access keys under the AWS account. Consequently, you can use this operation to manage AWS account root user credentials. This is true even if the AWS account has no associated users.

For information about quotas on the number of keys you can create, see [IAM and AWS STS quotas](#) in the *IAM User Guide*.

### Important

To ensure the security of your AWS account, the secret access key is accessible only during key and user creation. You must save the key (for example, in a text file) if you want to be able to access it again. If a secret key is lost, you can delete the access keys for the associated user and then create new keys.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### UserName

The name of the IAM user that the new key will belong to.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: No

## Response Elements

The following element is returned by the service.

### AccessKey

A structure with details about the access key.

Type: [AccessKey \(p. 479\)](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **LimitExceeded**

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of CreateAccessKey.

#### Sample Request

```
https://iam.amazonaws.com/?Action/CreateAccessKey
&UserName=Bob
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<CreateAccessKeyResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <CreateAccessKeyResult>
    <AccessKey>
      <UserName>Bob</UserName>
      <AccessKeyId>AKIAIOSFODNN7EXAMPLE</AccessKeyId>
      <Status>Active</Status>
      <SecretAccessKey>wJalrXutnFEMI/K7MDENG/bPxRfiCYzEXAMPLEKEY
      </SecretAccessKey>
    </AccessKey>
  </CreateAccessKeyResult>
  <ResponseMetadata>
    <RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
  </ResponseMetadata>
</CreateAccessKeyResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateAccountAlias

Creates an alias for your AWS account. For information about using an AWS account alias, see [Using an alias for your AWS account ID](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### AccountAlias

The account alias to create.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of lowercase letters, digits, and dashes. You cannot start or finish with a dash, nor can you have two dashes in a row.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: ^[a-z0-9](([a-z0-9]|-(?!-))\*[a-z0-9])? \$

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### EntityAlreadyExists

The request was rejected because it attempted to create a resource that already exists.

HTTP Status Code: 409

### LimitExceeded

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of CreateAccountAlias.

## Sample Request

```
https://iam.amazonaws.com/?Action=CreateAccountAlias
&AccountAlias=example-corporation
&Version=2010-05-08
&AUTHPARAMS
```

## Sample Response

```
<CreateAccountAliasResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>36b5db08-f1b0-11df-8fbe-45274EXAMPLE</RequestId>
  </ResponseMetadata>
</CreateAccountAliasResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateGroup

Creates a new group.

For information about the number of groups you can create, see [IAM and AWS STS quotas](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### GroupName

The name of the group to create. Do not include the path in this value.

IAM user, group, role, and policy names must be unique within the account. Names are not distinguished by case. For example, you cannot create resources named both "MyResource" and "myresource".

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=, .@-]+`

Required: Yes

### Path

The path to the group. For more information about paths, see [IAM identifiers](#) in the *IAM User Guide*.

This parameter is optional. If it is not included, it defaults to a slash (/).

This parameter allows (through its [regex pattern](#)) a string of characters consisting of either a forward slash (/) by itself or a string that must begin and end with forward slashes. In addition, it can contain any ASCII character from the ! (\u0021) through the DEL character (\u007F), including most punctuation characters, digits, and upper and lowercased letters.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `(\u002F)|(\\u002F[\u0021-\u007F]+\u002F)`

Required: No

## Response Elements

The following element is returned by the service.

### Group

A structure containing details about the new group.

Type: [Group \(p. 496\)](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **EntityAlreadyExists**

The request was rejected because it attempted to create a resource that already exists.

HTTP Status Code: 409

### **LimitExceeded**

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of CreateGroup.

#### Sample Request

```
https://iam.amazonaws.com/?Action=CreateGroup
&GroupName=Admins
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<CreateGroupResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <CreateGroupResult>
    <Group>
      <Path>/</Path>
      <GroupName>Admins</GroupName>
      <GroupId>AGPACKCEVSQ6C2EXAMPLE</GroupId>
      <Arn>arn:aws:iam::123456789012:group/Admins</Arn>
    </Group>
  </CreateGroupResult>
  <ResponseMetadata>
    <RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
  </ResponseMetadata>
</CreateGroupResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateInstanceProfile

Creates a new instance profile. For information about instance profiles, see [Using roles for applications on Amazon EC2](#) in the *IAM User Guide*, and [Instance profiles](#) in the *Amazon EC2 User Guide*.

For information about the number of instance profiles you can create, see [IAM object quotas](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### InstanceProfileName

The name of the instance profile to create.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: Yes

### Path

The path to the instance profile. For more information about paths, see [IAM Identifiers](#) in the *IAM User Guide*.

This parameter is optional. If it is not included, it defaults to a slash (/).

This parameter allows (through its [regex pattern](#)) a string of characters consisting of either a forward slash (/) by itself or a string that must begin and end with forward slashes. In addition, it can contain any ASCII character from the ! (\u0021) through the DEL character (\u007F), including most punctuation characters, digits, and upper and lowercased letters.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `(\u002F)|(\\u002F[\u0021-\u007F]+\u002F)`

Required: No

### Tags.member.N

A list of tags that you want to attach to the newly created IAM instance profile. Each tag consists of a key name and an associated value. For more information about tagging, see [Tagging IAM resources](#) in the *IAM User Guide*.

#### Note

If any one of the tags is invalid or if you exceed the allowed maximum number of tags, then the entire request fails and the resource is not created.

Type: Array of [Tag \(p. 553\)](#) objects

Array Members: Maximum number of 50 items.

Required: No

## Response Elements

The following element is returned by the service.

### **InstanceProfile**

A structure containing details about the new instance profile.

Type: [InstanceProfile \(p. 500\)](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **ConcurrentModification**

The request was rejected because multiple requests to change this object were submitted simultaneously. Wait a few minutes and submit your request again.

HTTP Status Code: 409

### **EntityAlreadyExists**

The request was rejected because it attempted to create a resource that already exists.

HTTP Status Code: 409

### **InvalidInput**

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### **LimitExceeded**

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of `CreateInstanceProfile`.

#### Sample Request

```
https://iam.amazonaws.com/?Action=CreateInstanceProfile
```

```
&InstanceProfileName=Webserver
&Path=/application_abc/component_xyz/
&Version=2010-05-08
&AUTHPARAMS
```

## Sample Response

```
<CreateInstanceProfileResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <CreateInstanceProfileResult>
    <InstanceProfile>
      <InstanceProfileId>AIPAD5AR02C5EXAMPLE3G</InstanceProfileId>
      <Roles/>
      <InstanceProfileName>Webserver</InstanceProfileName>
      <Path>/application_abc/component_xyz/</Path>
      <Arn>arn:aws:iam::123456789012:instance-profile/application_abc/component_xyz/
      Webserver</Arn>
      <CreateDate>2012-05-09T16:11:10.222Z</CreateDate>
    </InstanceProfile>
  </CreateInstanceProfileResult>
  <ResponseMetadata>
    <RequestId>974142ee-99f1-11e1-a4c3-27EXAMPLE804</RequestId>
  </ResponseMetadata>
</CreateInstanceProfileResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateLoginProfile

Creates a password for the specified IAM user. A password allows an IAM user to access AWS services through the AWS Management Console.

You can use the AWS CLI, the AWS API, or the **Users** page in the IAM console to create a password for any IAM user. Use [ChangePassword \(p. 22\)](#) to update your own existing password in the **My Security Credentials** page in the AWS Management Console.

For more information about managing passwords, see [Managing passwords](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### Password

The new password for the user.

The [regex pattern](#) that is used to validate this parameter is a string of characters. That string can include almost any printable ASCII character from the space (\u0020) through the end of the ASCII character range (\u00FF). You can also include the tab (\u0009), line feed (\u000A), and carriage return (\u000D) characters. Any of these characters are valid in a password. However, many tools, such as the AWS Management Console, might restrict the ability to type certain characters because they have special meaning within that tool.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [\u0009\u000A\u000D\u0020-\u00FF]+

Required: Yes

### PasswordResetRequired

Specifies whether the user is required to set a new password on next sign-in.

Type: Boolean

Required: No

### UserName

The name of the IAM user to create a password for. The user must already exist.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: \_+=,.@-

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [\w+=,.@-]+

Required: Yes

## Response Elements

The following element is returned by the service.

### **LoginProfile**

A structure containing the user name and password create date.

Type: [LoginProfile \(p. 503\)](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **EntityAlreadyExists**

The request was rejected because it attempted to create a resource that already exists.

HTTP Status Code: 409

### **LimitExceeded**

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### **PasswordPolicyViolation**

The request was rejected because the provided password did not meet the requirements imposed by the account password policy.

HTTP Status Code: 400

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of CreateLoginProfile.

#### Sample Request

```
https://iam.amazonaws.com/?Action/CreateLoginProfile
&UserName=Bob
&Password=h]6EszR}vJ*m
&Version=2010-05-08
```

&AUTHPARAMS

## Sample Response

```
<CreateLoginProfileResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <CreateLoginProfileResult>
    <LoginProfile>
      <PasswordResetRequired>false</PasswordResetRequired>
      <UserName>Bob</UserName>
      <CreateDate>2015-03-25T20:48:52.558Z</CreateDate>
    </LoginProfile>
  </CreateLoginProfileResult>
  <ResponseMetadata>
    <RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
  </ResponseMetadata>
</CreateLoginProfileResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateOpenIDConnectProvider

Creates an IAM entity to describe an identity provider (IdP) that supports [OpenID Connect \(OIDC\)](#).

The OIDC provider that you create with this operation can be used as a principal in a role's trust policy. Such a policy establishes a trust relationship between AWS and the OIDC provider.

If you are using an OIDC identity provider from Google, Facebook, or Amazon Cognito, you don't need to create a separate IAM identity provider. These OIDC identity providers are already built-in to AWS and are available for your use. Instead, you can move directly to creating new roles using your identity provider. To learn more, see [Creating a role for web identity or OpenID connect federation](#) in the *IAM User Guide*.

When you create the IAM OIDC provider, you specify the following:

- The URL of the OIDC identity provider (IdP) to trust
- A list of client IDs (also known as audiences) that identify the application or applications allowed to authenticate using the OIDC provider
- A list of thumbprints of one or more server certificates that the IdP uses

You get all of this information from the OIDC IdP you want to use to access AWS.

**Note**

AWS secures communication with some OIDC identity providers (IdPs) through our library of trusted certificate authorities (CAs) instead of using a certificate thumbprint to verify your IdP server certificate. These OIDC IdPs include Google, and those that use an Amazon S3 bucket to host a JSON Web Key Set (JWKS) endpoint. In these cases, your legacy thumbprint remains in your configuration, but is no longer used for validation.

**Note**

The trust for the OIDC provider is derived from the IAM provider that this operation creates. Therefore, it is best to limit access to the [CreateOpenIDConnectProvider \(p. 39\)](#) operation to highly privileged users.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

**ClientIDList.member.N**

Provides a list of client IDs, also known as audiences. When a mobile or web app registers with an OpenID Connect provider, they establish a value that identifies the application. This is the value that's sent as the `client_id` parameter on OAuth requests.

You can register multiple client IDs with the same provider. For example, you might have multiple applications that use the same OIDC provider. You cannot register more than 100 client IDs with a single IAM OIDC provider.

There is no defined format for a client ID. The `CreateOpenIDConnectProviderRequest` operation accepts client IDs up to 255 characters long.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

### Tags.member.N

A list of tags that you want to attach to the new IAM OpenID Connect (OIDC) provider. Each tag consists of a key name and an associated value. For more information about tagging, see [Tagging IAM resources](#) in the *IAM User Guide*.

#### Note

If any one of the tags is invalid or if you exceed the allowed maximum number of tags, then the entire request fails and the resource is not created.

Type: Array of [Tag \(p. 553\)](#) objects

Array Members: Maximum number of 50 items.

Required: No

### ThumbprintList.member.N

A list of server certificate thumbprints for the OpenID Connect (OIDC) identity provider's server certificates. Typically this list includes only one entry. However, IAM lets you have up to five thumbprints for an OIDC provider. This lets you maintain multiple thumbprints if the identity provider is rotating certificates.

The server certificate thumbprint is the hex-encoded SHA-1 hash value of the X.509 certificate used by the domain where the OpenID Connect provider makes its keys available. It is always a 40-character string.

You must provide at least one thumbprint when creating an IAM OIDC provider. For example, assume that the OIDC provider is `server.example.com` and the provider stores its keys at `https://keys.server.example.com/openid-connect`. In that case, the thumbprint string would be the hex-encoded SHA-1 hash value of the certificate used by `https://keys.server.example.com`.

For more information about obtaining the OIDC provider thumbprint, see [Obtaining the thumbprint for an OpenID Connect provider](#) in the *IAM User Guide*.

Type: Array of strings

Length Constraints: Fixed length of 40.

Required: Yes

### Url

The URL of the identity provider. The URL must begin with `https://` and should correspond to the `iss` claim in the provider's OpenID Connect ID tokens. Per the OIDC standard, path components are allowed but query parameters are not. Typically the URL consists of only a hostname, like `https://server.example.org` or `https://example.com`. The URL should not contain a port number.

You cannot register the same provider multiple times in a single AWS account. If you try to submit a URL that has already been used for an OpenID Connect provider in the AWS account, you will get an error.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

## Response Elements

The following elements are returned by the service.

## OpenIDConnectProviderArn

The Amazon Resource Name (ARN) of the new IAM OpenID Connect provider that is created. For more information, see [OpenIDConnectProviderListEntry \(p. 508\)](#).

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

## Tags.member.N

A list of tags that are attached to the new IAM OIDC provider. The returned list of tags is sorted by tag key. For more information about tagging, see [Tagging IAM resources](#) in the *IAM User Guide*.

Type: Array of [Tag \(p. 553\)](#) objects

Array Members: Maximum number of 50 items.

# Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

## ConcurrentModification

The request was rejected because multiple requests to change this object were submitted simultaneously. Wait a few minutes and submit your request again.

HTTP Status Code: 409

## EntityAlreadyExists

The request was rejected because it attempted to create a resource that already exists.

HTTP Status Code: 409

## InvalidInput

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

## LimitExceeded

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

## ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

# Examples

## Example

This example illustrates one usage of `CreateOpenIDConnectProvider`.

## Sample Request

```
https://iam.amazonaws.com/?Action=CreateOpenIDConnectProvider
&ThumbprintList.list.1=c3768084dfb3d2b68b7897bf5f565da8eEXAMPLE
&ClientIDList.list.1=my-application-ID
&Url=https://server.example.com
&Version=2010-05-08
&AUTHPARAMS
```

## Sample Response

```
<CreateOpenIDConnectProviderResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <CreateOpenIDConnectProviderResult>
    <OpenIDConnectProviderArn>
      arn:aws:iam::123456789012:oidc-provider/server.example.com
    </OpenIDConnectProviderArn>
  </CreateOpenIDConnectProviderResult>
  <ResponseMetadata>
    <RequestId>f248366a-4f64-11e4-aefa-bfd6aEXAMPLE</RequestId>
  </ResponseMetadata>
</CreateOpenIDConnectProviderResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreatePolicy

Creates a new managed policy for your AWS account.

This operation creates a policy version with a version identifier of v1 and sets v1 as the policy's default version. For more information about policy versions, see [Versioning for managed policies](#) in the *IAM User Guide*.

As a best practice, you can validate your IAM policies. To learn more, see [Validating IAM policies](#) in the *IAM User Guide*.

For more information about managed policies in general, see [Managed policies and inline policies](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### Description

A friendly description of the policy.

Typically used to store information about the permissions defined in the policy. For example, "Grants access to production DynamoDB tables."

The policy description is immutable. After a value is assigned, it cannot be changed.

Type: String

Length Constraints: Maximum length of 1000.

Required: No

### Path

The path for the policy.

For more information about paths, see [IAM identifiers](#) in the *IAM User Guide*.

This parameter is optional. If it is not included, it defaults to a slash (/).

This parameter allows (through its [regex pattern](#)) a string of characters consisting of either a forward slash (/) by itself or a string that must begin and end with forward slashes. In addition, it can contain any ASCII character from the ! (\u0021) through the DEL character (\u007F), including most punctuation characters, digits, and upper and lowercased letters.

#### Note

You cannot use an asterisk (\*) in the path name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: ((/[A-Za-z0-9\.\,\+\@\=\-\\_]+)\*)/

Required: No

### PolicyDocument

The JSON policy document that you want to use as the content for the new policy.

You must provide policies in JSON format in IAM. However, for AWS CloudFormation templates formatted in YAML, you can provide the policy in JSON or YAML format. AWS CloudFormation always converts a YAML policy to JSON format before submitting it to IAM.

The maximum length of the policy document that you can pass in this operation, including whitespace, is listed below. To view the maximum character counts of a managed policy with no whitespaces, see [IAM and AWS STS character quotas](#).

To learn more about JSON policy grammar, see [Grammar of the IAM JSON policy language](#) in the *IAM User Guide*.

The [regex pattern](#) used to validate this parameter is a string of characters consisting of the following:

- Any printable ASCII character ranging from the space character (\u0020) through the end of the ASCII character range
- The printable characters in the Basic Latin and Latin-1 Supplement character set (through \u00FF)
- The special characters tab (\u0009), line feed (\u000A), and carriage return (\u000D)

Type: String

Length Constraints: Minimum length of 1. Maximum length of 131072.

Pattern: [\u0009\u000A\u000D\u0020-\u00FF]+

Required: Yes

#### PolicyName

The friendly name of the policy.

IAM user, group, role, and policy names must be unique within the account. Names are not distinguished by case. For example, you cannot create resources named both "MyResource" and "myresource".

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [\w+=,.@-]+

Required: Yes

#### Tags.member.N

A list of tags that you want to attach to the new IAM customer managed policy. Each tag consists of a key name and an associated value. For more information about tagging, see [Tagging IAM resources](#) in the *IAM User Guide*.

##### Note

If any one of the tags is invalid or if you exceed the allowed maximum number of tags, then the entire request fails and the resource is not created.

Type: Array of [Tag \(p. 553\)](#) objects

Array Members: Maximum number of 50 items.

Required: No

## Response Elements

The following element is returned by the service.

## Policy

A structure containing details about the new policy.

Type: [Policy \(p. 513\)](#) object

# Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### ConcurrentModification

The request was rejected because multiple requests to change this object were submitted simultaneously. Wait a few minutes and submit your request again.

HTTP Status Code: 409

### EntityAlreadyExists

The request was rejected because it attempted to create a resource that already exists.

HTTP Status Code: 409

### InvalidInput

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### LimitExceeded

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### MalformedPolicyDocument

The request was rejected because the policy document was malformed. The error message describes the specific error.

HTTP Status Code: 400

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

# Examples

## Example

This example illustrates one usage of CreatePolicy.

### Sample Request

```
https://iam.amazonaws.com/?Action=CreatePolicy
```

```
&PolicyDocument={"Version":"2012-10-17", "Statement":  
[{"Effect":"Allow", "Action":"s3>ListAllMyBuckets",  
"Resource":"arn:aws:s3:::*"}, {"Effect":"Allow", "Action":["s3:Get*", "s3>List*"], "Resource":  
["arn:aws:s3:::EXAMPLE-BUCKET", "arn:aws:s3:::EXAMPLE-BUCKET/*"]}]}  
&PolicyName=S3-read-only-example-bucket  
&Version=2010-05-08  
&AUTHPARAMS
```

## Sample Response

```
<CreatePolicyResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">  
  <CreatePolicyResult>  
    <Policy>  
      <PolicyName>S3-read-only-example-bucket</PolicyName>  
      <DefaultVersionId>v1</DefaultVersionId>  
      <PolicyId>AGPACKCEVSQ6C2EXAMPLE</PolicyId>  
      <Path>/</Path>  
      <Arn>arn:aws:iam::123456789012:policy/S3-read-only-example-bucket</Arn>  
      <AttachmentCount>0</AttachmentCount>  
      <CreateDate>2014-09-15T17:36:14.673Z</CreateDate>  
      <UpdateDate>2014-09-15T17:36:14.673Z</UpdateDate>  
    </Policy>  
  </CreatePolicyResult>  
  <ResponseMetadata>  
    <RequestId>ca64c9e1-3cfe-11e4-bfad-8d1c6EXAMPLE</RequestId>  
  </ResponseMetadata>  
</CreatePolicyResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreatePolicyVersion

Creates a new version of the specified managed policy. To update a managed policy, you create a new policy version. A managed policy can have up to five versions. If the policy has five versions, you must delete an existing version using [DeletePolicyVersion \(p. 90\)](#) before you create a new version.

Optionally, you can set the new version as the policy's default version. The default version is the version that is in effect for the IAM users, groups, and roles to which the policy is attached.

For more information about managed policy versions, see [Versioning for managed policies](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### PolicyArn

The Amazon Resource Name (ARN) of the IAM policy to which you want to add a new version.

For more information about ARNs, see [Amazon Resource Names \(ARNs\)](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

### PolicyDocument

The JSON policy document that you want to use as the content for this new version of the policy.

You must provide policies in JSON format in IAM. However, for AWS CloudFormation templates formatted in YAML, you can provide the policy in JSON or YAML format. AWS CloudFormation always converts a YAML policy to JSON format before submitting it to IAM.

The maximum length of the policy document that you can pass in this operation, including whitespace, is listed below. To view the maximum character counts of a managed policy with no whitespaces, see [IAM and AWS STS character quotas](#).

The [regex pattern](#) used to validate this parameter is a string of characters consisting of the following:

- Any printable ASCII character ranging from the space character (\u0020) through the end of the ASCII character range
- The printable characters in the Basic Latin and Latin-1 Supplement character set (through \u00FF)
- The special characters tab (\u0009), line feed (\u000A), and carriage return (\u000D)

Type: String

Length Constraints: Minimum length of 1. Maximum length of 131072.

Pattern: [\u0009\u000A\u000D\u0020-\u00FF]+

Required: Yes

### **SetAsDefault**

Specifies whether to set this version as the policy's default version.

When this parameter is `true`, the new policy version becomes the operative version. That is, it becomes the version that is in effect for the IAM users, groups, and roles that the policy is attached to.

For more information about managed policy versions, see [Versioning for managed policies](#) in the *IAM User Guide*.

Type: Boolean

Required: No

## Response Elements

The following element is returned by the service.

### **PolicyVersion**

A structure containing details about the new policy version.

Type: [PolicyVersion \(p. 522\)](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **InvalidInput**

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### **LimitExceeded**

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### **MalformedPolicyDocument**

The request was rejected because the policy document was malformed. The error message describes the specific error.

HTTP Status Code: 400

### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of CreatePolicyVersion.

#### Sample Request

```
https://iam.amazonaws.com/?Action=CreatePolicyVersion
&PolicyArn=arn:aws:iam::123456789012:policy/S3-read-only-example-bucket
&PolicyDocument={"Version":"2012-10-17","Statement":
[{"Effect":"Allow","Action":"s3>ListAllMyBuckets",
"Resource":"arn:aws:s3:::*"}, {"Effect":"Allow","Action":["s3:Get*","s3>List*"],"Resource":
["arn:aws:s3:::EXAMPLE-BUCKET","arn:aws:s3:::EXAMPLE-BUCKET/*"]},
 {"Effect":"Deny","Action":"s3:*",
"Resource":["arn:aws:s3:::EXAMPLE-BUCKET","arn:aws:s3:::EXAMPLE-BUCKET/*"],"Condition":
{"StringLike":
{"s3:prefix":["SENSITIVE-FILES*"]}}]}
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<CreatePolicyVersionResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
<CreatePolicyVersionResult>
  <PolicyVersion>
    <IsDefaultVersion>false</IsDefaultVersion>
    <VersionId>v2</VersionId>
    <CreateDate>2014-09-15T19:58:59.430Z</CreateDate>
  </PolicyVersion>
</CreatePolicyVersionResult>
<ResponseMetadata>
  <RequestId>bb551b92-3d12-11e4-bfad-8d1c6EXAMPLE</RequestId>
</ResponseMetadata>
</CreatePolicyVersionResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateRole

Creates a new role for your AWS account. For more information about roles, see [IAM roles](#). For information about quotas for role names and the number of roles you can create, see [IAM and AWS STS quotas](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### AssumeRolePolicyDocument

The trust relationship policy document that grants an entity permission to assume the role.

In IAM, you must provide a JSON policy that has been converted to a string. However, for AWS CloudFormation templates formatted in YAML, you can provide the policy in JSON or YAML format. AWS CloudFormation always converts a YAML policy to JSON format before submitting it to IAM.

The [regex pattern](#) used to validate this parameter is a string of characters consisting of the following:

- Any printable ASCII character ranging from the space character (\u0020) through the end of the ASCII character range
- The printable characters in the Basic Latin and Latin-1 Supplement character set (through \u00FF)
- The special characters tab (\u0009), line feed (\u000A), and carriage return (\u000D)

Upon success, the response includes the same trust policy in JSON format.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 131072.

Pattern: [\u0009\u000A\u000D\u0020-\u00FF]+

Required: Yes

### Description

A description of the role.

Type: String

Length Constraints: Maximum length of 1000.

Pattern: [\p{L}\p{M}\p{Z}\p{S}\p{N}\p{P}]\*

Required: No

### MaxSessionDuration

The maximum session duration (in seconds) that you want to set for the specified role. If you do not specify a value for this setting, the default value of one hour is applied. This setting can have a value from 1 hour to 12 hours.

Anyone who assumes the role from the AWS CLI or API can use the DurationSeconds API parameter or the duration-seconds AWS CLI parameter to request a longer session. The MaxSessionDuration setting determines the maximum duration that can be requested using

the DurationSeconds parameter. If users don't specify a value for the DurationSeconds parameter, their security credentials are valid for one hour by default. This applies when you use the AssumeRole\* API operations or the assume-role\* AWS CLI operations but does not apply when you use those operations to create a console URL. For more information, see [Using IAM roles](#) in the *IAM User Guide*.

Type: Integer

Valid Range: Minimum value of 3600. Maximum value of 43200.

Required: No

#### Path

The path to the role. For more information about paths, see [IAM Identifiers](#) in the *IAM User Guide*.

This parameter is optional. If it is not included, it defaults to a slash (/).

This parameter allows (through its [regex pattern](#)) a string of characters consisting of either a forward slash (/) by itself or a string that must begin and end with forward slashes. In addition, it can contain any ASCII character from the ! (\u0021) through the DEL character (\u007F), including most punctuation characters, digits, and upper and lowercased letters.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: (\u002F)|(\\u002F[\u0021-\u007F]+\u002F)

Required: No

#### PermissionsBoundary

The ARN of the policy that is used to set the permissions boundary for the role.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: No

#### RoleName

The name of the role to create.

IAM user, group, role, and policy names must be unique within the account. Names are not distinguished by case. For example, you cannot create resources named both "MyResource" and "myresource".

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [\w+=, .@-]+

Required: Yes

#### Tags.member.N

A list of tags that you want to attach to the new role. Each tag consists of a key name and an associated value. For more information about tagging, see [Tagging IAM resources](#) in the *IAM User Guide*.

**Note**

If any one of the tags is invalid or if you exceed the allowed maximum number of tags, then the entire request fails and the resource is not created.

Type: Array of [Tag \(p. 553\)](#) objects

Array Members: Maximum number of 50 items.

Required: No

## Response Elements

The following element is returned by the service.

**Role**

A structure containing details about the new role.

Type: [Role \(p. 527\)](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

**ConcurrentModification**

The request was rejected because multiple requests to change this object were submitted simultaneously. Wait a few minutes and submit your request again.

HTTP Status Code: 409

**EntityAlreadyExists**

The request was rejected because it attempted to create a resource that already exists.

HTTP Status Code: 409

**InvalidInput**

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

**LimitExceeded**

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

**MalformedPolicyDocument**

The request was rejected because the policy document was malformed. The error message describes the specific error.

HTTP Status Code: 400

**ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of CreateRole.

#### Sample Request

```
https://iam.amazonaws.com/?Action=CreateRole
&RoleName=S3Access
&Path=/application_abc/component_xyz/
&AssumeRolePolicyDocument={"Version":"2012-10-17","Statement":
[{"Effect":"Allow","Principal":{"Service":["ec2.amazonaws.com"]},"Action":
["sts:AssumeRole"]}]}
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<CreateRoleResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <CreateRoleResult>
    <Role>
      <Path>/application_abc/component_xyz/</Path>
      <Arn>arn:aws:iam::123456789012:role/application_abc/component_xyz/S3Access</Arn>
      <RoleName>S3Access</RoleName>
      <AssumeRolePolicyDocument>
        {"Version":"2012-10-17","Statement":[{"Effect":"Allow",
          "Principal":{"Service":["ec2.amazonaws.com"]},"Action":["sts:AssumeRole"]}]}
      </AssumeRolePolicyDocument>
      <CreateDate>2012-05-08T23:34:01.495Z</CreateDate>
      <RoleId>AROADBQP57FF2AEXAMPLE</RoleId>
    </Role>
  </CreateRoleResult>
  <ResponseMetadata>
    <RequestId>4a93ceee-9966-11e1-b624-b1aEXAMPLE7c</RequestId>
  </ResponseMetadata>
</CreateRoleResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateSAMLProvider

Creates an IAM resource that describes an identity provider (IdP) that supports SAML 2.0.

The SAML provider resource that you create with this operation can be used as a principal in an IAM role's trust policy. Such a policy can enable federated users who sign in using the SAML IdP to assume the role. You can create an IAM role that supports Web-based single sign-on (SSO) to the AWS Management Console or one that supports API access to AWS.

When you create the SAML provider resource, you upload a SAML metadata document that you get from your IdP. That document includes the issuer's name, expiration information, and keys that can be used to validate the SAML authentication response (assertions) that the IdP sends. You must generate the metadata document using the identity management software that is used as your organization's IdP.

**Note**

This operation requires [Signature Version 4](#).

For more information, see [Enabling SAML 2.0 federated users to access the AWS Management Console](#) and [About SAML 2.0-based federation](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

**Name**

The name of the provider to create.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w._-]+`

Required: Yes

**SAMLMetadataDocument**

An XML document generated by an identity provider (IdP) that supports SAML 2.0. The document includes the issuer's name, expiration information, and keys that can be used to validate the SAML authentication response (assertions) that are received from the IdP. You must generate the metadata document using the identity management software that is used as your organization's IdP.

For more information, see [About SAML 2.0-based federation](#) in the *IAM User Guide*

Type: String

Length Constraints: Minimum length of 1000. Maximum length of 10000000.

Required: Yes

**Tags.member.N**

A list of tags that you want to attach to the new IAM SAML provider. Each tag consists of a key name and an associated value. For more information about tagging, see [Tagging IAM resources](#) in the *IAM User Guide*.

**Note**

If any one of the tags is invalid or if you exceed the allowed maximum number of tags, then the entire request fails and the resource is not created.

Type: Array of [Tag \(p. 553\)](#) objects

Array Members: Maximum number of 50 items.

Required: No

## Response Elements

The following elements are returned by the service.

**SAMLProviderArn**

The Amazon Resource Name (ARN) of the new SAML provider resource in IAM.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

**Tags.member.N**

A list of tags that are attached to the new IAM SAML provider. The returned list of tags is sorted by tag key. For more information about tagging, see [Tagging IAM resources](#) in the *IAM User Guide*.

Type: Array of [Tag \(p. 553\)](#) objects

Array Members: Maximum number of 50 items.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

**ConcurrentModification**

The request was rejected because multiple requests to change this object were submitted simultaneously. Wait a few minutes and submit your request again.

HTTP Status Code: 409

**EntityAlreadyExists**

The request was rejected because it attempted to create a resource that already exists.

HTTP Status Code: 409

**InvalidInput**

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

**LimitExceeded**

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of CreateSAMLProvider.

#### Sample Request

```
https://iam.amazonaws.com/?Action=CreateSAMLProvider
&Name=MyUniversity
&SAMLProviderDocument=VGhpcyBpcyB3aGVyZSB5b3UgcHV0IHRoZSBTQU1MIHByb3ZpZGVyIG1ldGFkYXRhIGRvY3VtZW50
LCBCYXNlNjQtZW5jb2RlZCBpbnRvIGEgYmlnIHN0cmLuZy4=
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<CreateSAMLProviderResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <CreateSAMLProviderResult>
    <SAMLProviderArn>arn:aws:iam::123456789012:saml-provider/MyUniversity</SAMLProviderArn>
  </CreateSAMLProviderResult>
  <ResponseMetadata>
    <RequestId>29f47818-99f5-11e1-a4c3-27EXAMPLE804</RequestId>
  </ResponseMetadata>
</CreateSAMLProviderResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateServiceLinkedRole

Creates an IAM role that is linked to a specific AWS service. The service controls the attached policies and when the role can be deleted. This helps ensure that the service is not broken by an unexpectedly changed or deleted role, which could put your AWS resources into an unknown state. Allowing the service to control the role helps improve service stability and proper cleanup when a service and its role are no longer needed. For more information, see [Using service-linked roles](#) in the *IAM User Guide*.

To attach a policy to this service-linked role, you must make the request using the AWS service that depends on this role.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### **AWSServiceName**

The service principal for the AWS service to which this role is attached. You use a string similar to a URL but without the `http://` in front. For example: `elasticbeanstalk.amazonaws.com`.

Service principals are unique and case-sensitive. To find the exact service principal for your service-linked role, see [AWS services that work with IAM](#) in the *IAM User Guide*. Look for the services that have **Yes** in the **Service-Linked Role** column. Choose the **Yes** link to view the service-linked role documentation for that service.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=, .@-]+`

Required: Yes

### **CustomSuffix**

A string that you provide, which is combined with the service-provided prefix to form the complete role name. If you make multiple requests for the same service, then you must supply a different **CustomSuffix** for each request. Otherwise the request fails with a duplicate role name error. For example, you could add `-1` or `-debug` to the suffix.

Some services do not support the **CustomSuffix** parameter. If you provide an optional suffix and the operation fails, try the operation again without the suffix.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w+=, .@-]+`

Required: No

### **Description**

The description of the role.

Type: String

Length Constraints: Maximum length of 1000.

Pattern: [\p{L}\p{M}\p{Z}\p{S}\p{N}\p{P}]\*

Required: No

## Response Elements

The following element is returned by the service.

### Role

A [Role \(p. 527\)](#) object that contains details about the newly created role.

Type: [Role \(p. 527\)](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### InvalidInput

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### LimitExceeded

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateServiceSpecificCredential

Generates a set of credentials consisting of a user name and password that can be used to access the service specified in the request. These credentials are generated by IAM, and can be used only for the specified service.

You can have a maximum of two sets of service-specific credentials for each supported service per user.

You can create service-specific credentials for CodeCommit and Amazon Keyspaces (for Apache Cassandra).

You can reset the password to a new service-generated value by calling [ResetServiceSpecificCredential \(p. 346\)](#).

For more information about service-specific credentials, see [Using IAM with CodeCommit: Git credentials, SSH keys, and AWS access keys](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### ServiceName

The name of the AWS service that is to be associated with the credentials. The service you specify here is the only service that can be accessed using these credentials.

Type: String

Required: Yes

### UserName

The name of the IAM user that is to be associated with the credentials. The new service-specific credentials have the same permissions as the associated user except that they can be used only to access the specified service.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w+=,.@-]+`

Required: Yes

## Response Elements

The following element is returned by the service.

### ServiceSpecificCredential

A structure that contains information about the newly created service-specific credential.

**Important**

This is the only time that the password for this credential set is available. It cannot be recovered later. Instead, you must reset the password with [ResetServiceSpecificCredential \(p. 346\)](#).

Type: [ServiceSpecificCredential \(p. 542\)](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

**LimitExceeded**

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

**NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

**NotSupportedService**

The specified service does not support service-specific credentials.

HTTP Status Code: 404

## Examples

### Example

In the following example, the caller creates service-specific credentials for the IAM user named Anika in account 123456789012. The credentials can be used only with the AWS service associated with the service endpoint at `codecommit.amazonaws.com` .

#### Sample Request

```
https://iam.amazonaws.com/?Action/CreateServiceSpecificCredential
&UserName=Anika
&ServiceName=codecommit.amazonaws.com
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<CreateServiceSpecificCredentialResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
<CreateServiceSpecificCredentialResult>
  <ServiceSpecificCredential>
    <ServicePassword>xTBar/czp+D3EXAMPLE471rJ6/43r2zqGwR3EXAMPLE=</ServicePassword>
    <ServiceName>codecommit.amazonaws.com</ServiceName>
    <UserName>anika</UserName>
    <ServiceUserName>anika+1-at-123456789012</ServiceUserName>
    <ServiceSpecificCredentialId>ACCA12345ABCDEEXAMPLE</ServiceSpecificCredentialId>
```

```
<Status>Active</Status>
<CreateDate>2016-11-01T17:47:22.382Z</CreateDate>
</ServiceSpecificCredential>
</CreateServiceSpecificCredentialResult>
<ResponseMetadata>
<RequestId>EXAMPLE8-90ab-cdef-fecd-ba987EXAMPLE</RequestId>
</ResponseMetadata>
</CreateServiceSpecificCredentialResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateUser

Creates a new IAM user for your AWS account.

For information about quotas for the number of IAM users you can create, see [IAM and AWS STS quotas](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### Path

The path for the user name. For more information about paths, see [IAM identifiers](#) in the *IAM User Guide*.

This parameter is optional. If it is not included, it defaults to a slash (/).

This parameter allows (through its [regex pattern](#)) a string of characters consisting of either a forward slash (/) by itself or a string that must begin and end with forward slashes. In addition, it can contain any ASCII character from the ! (\u0021) through the DEL character (\u007F), including most punctuation characters, digits, and upper and lowercased letters.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: (\u002F)|(\\u002F[\u0021-\u007F]+\u002F)

Required: No

### PermissionsBoundary

The ARN of the policy that is used to set the permissions boundary for the user.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: No

### Tags.member.N

A list of tags that you want to attach to the new user. Each tag consists of a key name and an associated value. For more information about tagging, see [Tagging IAM resources](#) in the *IAM User Guide*.

#### Note

If any one of the tags is invalid or if you exceed the allowed maximum number of tags, then the entire request fails and the resource is not created.

Type: Array of [Tag \(p. 553\)](#) objects

Array Members: Maximum number of 50 items.

Required: No

### UserName

The name of the user to create.

IAM user, group, role, and policy names must be unique within the account. Names are not distinguished by case. For example, you cannot create resources named both "MyResource" and "myresource".

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [\w+=, .@-]+

Required: Yes

## Response Elements

The following element is returned by the service.

### User

A structure with details about the new IAM user.

Type: [User \(p. 556\)](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### ConcurrentModification

The request was rejected because multiple requests to change this object were submitted simultaneously. Wait a few minutes and submit your request again.

HTTP Status Code: 409

### EntityAlreadyExists

The request was rejected because it attempted to create a resource that already exists.

HTTP Status Code: 409

### InvalidInput

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### LimitExceeded

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of CreateUser.

#### Sample Request

```
https://iam.amazonaws.com/?Action=CreateUser
&Path=/division_abc/subdivision_xyz/
&UserName=Bob
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<CreateUserResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <CreateUserResult>
    <User>
      <Path>/division_abc/subdivision_xyz/</Path>
      <UserName>Bob</UserName>
      <UserId>AIDACKCEVSQ6C2EXAMPLE</UserId>
      <Arn>arn:aws:iam::123456789012:user/division_abc/subdivision_xyz/Bob</Arn>
    </User>
  </CreateUserResult>
  <ResponseMetadata>
    <RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
  </ResponseMetadata>
</CreateUserResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateVirtualMFADevice

Creates a new virtual MFA device for the AWS account. After creating the virtual MFA, use [EnableMFADevice \(p. 128\)](#) to attach the MFA device to an IAM user. For more information about creating and working with virtual MFA devices, see [Using a virtual MFA device](#) in the *IAM User Guide*.

For information about the maximum number of MFA devices you can create, see [IAM and AWS STS quotas](#) in the *IAM User Guide*.

## Important

The seed information contained in the QR code and the Base32 string should be treated like any other secret access information. In other words, protect the seed information as you would your AWS access keys or your passwords. After you provision your virtual device, you should ensure that the information is destroyed following secure procedures.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### Path

The path for the virtual MFA device. For more information about paths, see [IAM identifiers](#) in the *IAM User Guide*.

This parameter is optional. If it is not included, it defaults to a slash (/).

This parameter allows (through its [regex pattern](#)) a string of characters consisting of either a forward slash (/) by itself or a string that must begin and end with forward slashes. In addition, it can contain any ASCII character from the ! (\u0021) through the DEL character (\u007F), including most punctuation characters, digits, and upper and lowercased letters.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: (\u002F)|(\\u002F[\u0021-\u007F]+\u002F)

Required: No

### Tags.member.N

A list of tags that you want to attach to the new IAM virtual MFA device. Each tag consists of a key name and an associated value. For more information about tagging, see [Tagging IAM resources](#) in the *IAM User Guide*.

#### Note

If any one of the tags is invalid or if you exceed the allowed maximum number of tags, then the entire request fails and the resource is not created.

Type: Array of [Tag \(p. 553\)](#) objects

Array Members: Maximum number of 50 items.

Required: No

### VirtualMFADeviceName

The name of the virtual MFA device. Use with path to uniquely identify a virtual MFA device.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1.

Pattern: `[\w+=,.@-]+`

Required: Yes

## Response Elements

The following element is returned by the service.

### **VirtualMFADevice**

A structure containing details about the new virtual MFA device.

Type: [VirtualMFADevice \(p. 561\)](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **ConcurrentModification**

The request was rejected because multiple requests to change this object were submitted simultaneously. Wait a few minutes and submit your request again.

HTTP Status Code: 409

### **EntityAlreadyExists**

The request was rejected because it attempted to create a resource that already exists.

HTTP Status Code: 409

### **InvalidInput**

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### **LimitExceeded**

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of CreateVirtualMFADevice.

#### Sample Request

```
https://iam.amazonaws.com/?Action=CreateVirtualMFADevice
&VirtualMFADeviceName=ExampleName
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<CreateVirtualMFADeviceResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <CreateVirtualMFADeviceResult>
    <VirtualMFADevice>
      <SerialNumber>arn:aws:iam::123456789012:mfa/ExampleName</SerialNumber>
      <Base32StringSeed>
        2K5K5XTLA7GGE75TQLYEXAMPLEEXAMPLEEXAMPLECHDFW4KJYZ6UFQ75LL7C0CYKM
      </Base32StringSeed>
      <QRCodePNG>
        89504E470D0A1A0AASDFAHSDFKJKLJFKALSDFJASDF <!-- byte array of png file -->
      </QRCodePNG>
    </VirtualMFADevice>
  </CreateVirtualMFADeviceResult>
  <ResponseMetadata>
    <RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
  </ResponseMetadata>
</CreateVirtualMFADeviceResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeactivateMFADevice

Deactivates the specified MFA device and removes it from association with the user name for which it was originally enabled.

For more information about creating and working with virtual MFA devices, see [Enabling a virtual multi-factor authentication \(MFA\) device](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### **SerialNumber**

The serial number that uniquely identifies the MFA device. For virtual MFA devices, the serial number is the device ARN.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: =, .@:/-

Type: String

Length Constraints: Minimum length of 9. Maximum length of 256.

Pattern: [\w+=/:, .@-]+

Required: Yes

### **UserName**

The name of the user whose MFA device you want to deactivate.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: \_+=, .@-

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [\w+=, .@-]+

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **EntityTemporarilyUnmodifiable**

The request was rejected because it referenced an entity that is temporarily unmodifiable, such as a user name that was deleted and then recreated. The error indicates that the request is likely to succeed if you try again after waiting several minutes. The error message describes the entity.

HTTP Status Code: 409

### **LimitExceeded**

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of `DeactivateMFADevice`.

#### Sample Request

```
https://iam.amazonaws.com/?Action=DeactivateMFADevice
&UserName=Bob
&SerialNumber=R1234
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<DeactivateMFADeviceResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
  </ResponseMetadata>
</DeactivateMFADeviceResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# DeleteAccessKey

Deletes the access key pair associated with the specified IAM user.

If you do not specify a user name, IAM determines the user name implicitly based on the AWS access key ID signing the request. This operation works for access keys under the AWS account. Consequently, you can use this operation to manage AWS account root user credentials even if the AWS account has no associated users.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### AccessKeyId

The access key ID for the access key ID and secret access key you want to delete.

This parameter allows (through its [regex pattern](#)) a string of characters that can consist of any upper or lowercased letter or digit.

Type: String

Length Constraints: Minimum length of 16. Maximum length of 128.

Pattern: `[\w]+`

Required: Yes

### UserName

The name of the user whose access key pair you want to delete.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: No

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### LimitExceeded

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

#### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of DeleteAccessKey.

#### Sample Request

```
https://iam.amazonaws.com/?Action=DeleteAccessKey
&UserName=Bob
&AccessKeyId=AKIAIOSFODNN7EXAMPLE
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<DeleteAccessKeyResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
  </ResponseMetadata>
</DeleteAccessKeyResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteAccountAlias

Deletes the specified AWS account alias. For information about using an AWS account alias, see [Using an alias for your AWS account ID](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### AccountAlias

The name of the account alias to delete.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of lowercase letters, digits, and dashes. You cannot start or finish with a dash, nor can you have two dashes in a row.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: `^[a-z0-9](([a-z0-9]|-(!-))*[a-z0-9])?$`

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### LimitExceeded

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of DeleteAccountAlias.

## Sample Request

```
https://iam.amazonaws.com/?Action=DeleteAccountAlias
&AccountAlias=ExampleCorp
&Version=2010-05-08
&AUTHPARAMS
```

## Sample Response

```
<DeleteAccountAliasResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
  </ResponseMetadata>
</DeleteAccountAliasResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteAccountPasswordPolicy

Deletes the password policy for the AWS account. There are no parameters.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **LimitExceeded**

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of DeleteAccountPasswordPolicy.

#### Sample Request

```
https://iam.amazonaws.com/?Action=DeleteAccountPasswordPolicy
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<DeleteAccountPasswordPolicyResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
  </ResponseMetadata>
</DeleteAccountPasswordPolicyResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteGroup

Deletes the specified IAM group. The group must not contain any users or have any attached policies.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### GroupName

The name of the IAM group to delete.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### DeleteConflict

The request was rejected because it attempted to delete a resource that has attached subordinate entities. The error message describes these entities.

HTTP Status Code: 409

### LimitExceeded

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of DeleteGroup.

#### Sample Request

```
https://iam.amazonaws.com/?Action=DeleteGroup
&GroupName=Test
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<DeleteGroupResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
  </ResponseMetadata>
</DeleteGroupResponse>
```

### See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteGroupPolicy

Deletes the specified inline policy that is embedded in the specified IAM group.

A group can also have managed policies attached to it. To detach a managed policy from a group, use [DetachGroupPolicy \(p. 121\)](#). For more information about policies, refer to [Managed policies and inline policies](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### GroupName

The name (friendly name, not ARN) identifying the group that the policy is embedded in.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: Yes

### PolicyName

The name identifying the policy document to delete.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### LimitExceeded

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

#### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of DeleteGroupPolicy.

#### Sample Request

```
https://iam.amazonaws.com/?Action=DeleteGroupPolicy
&GroupName=Admins
&PolicyName=AdminFullAccess
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<DeleteGroupPolicyResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
  </ResponseMetadata>
</DeleteGroupPolicyResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteInstanceProfile

Deletes the specified instance profile. The instance profile must not have an associated role.

## Important

Make sure that you do not have any Amazon EC2 instances running with the instance profile you are about to delete. Deleting a role or instance profile that is associated with a running instance will break any applications running on the instance.

For more information about instance profiles, see [About instance profiles](#).

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### InstanceProfileName

The name of the instance profile to delete.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### DeleteConflict

The request was rejected because it attempted to delete a resource that has attached subordinate entities. The error message describes these entities.

HTTP Status Code: 409

### LimitExceeded

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of `DeleteInstanceProfile`.

#### Sample Request

```
https://iam.amazonaws.com/?Action=DeleteInstanceProfile
&InstanceProfileName=Webserver
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<DeleteInstanceProfileResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
<ResponseMetadata>
  <RequestId>90c18667-99f3-11e1-a4c3-27EXAMPLE804</RequestId>
</ResponseMetadata>
</DeleteInstanceProfileResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteLoginProfile

Deletes the password for the specified IAM user. For more information, see [Managing passwords for IAM users](#).

You can use the AWS CLI, the AWS API, or the **Users** page in the IAM console to delete a password for any IAM user. You can use [ChangePassword \(p. 22\)](#) to update, but not delete, your own password in the **My Security Credentials** page in the AWS Management Console.

## Important

Deleting a user's password does not prevent a user from accessing AWS through the command line interface or the API. To prevent all user access, you must also either make any access keys inactive or delete them. For more information about making keys inactive or deleting them, see [UpdateAccessKey \(p. 424\)](#) and [DeleteAccessKey \(p. 72\)](#).

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### UserName

The name of the user whose password you want to delete.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w+=,.@-]+`

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### EntityTemporarilyUnmodifiable

The request was rejected because it referenced an entity that is temporarily unmodifiable, such as a user name that was deleted and then recreated. The error indicates that the request is likely to succeed if you try again after waiting several minutes. The error message describes the entity.

HTTP Status Code: 409

### LimitExceeded

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

#### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of DeleteLoginProfile.

#### Sample Request

```
https://iam.amazonaws.com/?Action=DeleteLoginProfile
&UserName=Bob
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<DeleteLoginProfileResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
  </ResponseMetadata>
</DeleteLoginProfileResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteOpenIDConnectProvider

Deletes an OpenID Connect identity provider (IdP) resource object in IAM.

Deleting an IAM OIDC provider resource does not update any roles that reference the provider as a principal in their trust policies. Any attempt to assume a role that references a deleted provider fails.

This operation is idempotent; it does not fail or return an error if you call the operation for a provider that does not exist.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### OpenIDConnectProviderArn

The Amazon Resource Name (ARN) of the IAM OpenID Connect provider resource object to delete. You can get a list of OpenID Connect provider resource ARNs by using the [ListOpenIDConnectProviders \(p. 265\)](#) operation.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### InvalidInput

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of DeleteOpenIDConnectProvider.

## Sample Request

```
https://iam.amazonaws.com/?Action=DeleteOpenIDConnectProvider
&OpenIDConnectProviderArn=arn:aws:iam::123456789012:oidc-provider/server.example.com
&Version=2010-05-08
&AUTHPARAMS
```

## Sample Response

```
<DeleteOpenIDConnectProviderResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
<ResponseMetadata>
    <RequestId>b5e49e29-4f64-11e4-afca-bfd6aEXAMPLE</RequestId>
</ResponseMetadata>
</DeleteOpenIDConnectProviderResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeletePolicy

Deletes the specified managed policy.

Before you can delete a managed policy, you must first detach the policy from all users, groups, and roles that it is attached to. In addition, you must delete all the policy's versions. The following steps describe the process for deleting a managed policy:

- Detach the policy from all users, groups, and roles that the policy is attached to, using [DetachUserPolicy \(p. 126\)](#), [DetachGroupPolicy \(p. 121\)](#), or [DetachRolePolicy \(p. 123\)](#). To list all the users, groups, and roles that a policy is attached to, use [ListEntitiesForPolicy \(p. 237\)](#).
- Delete all versions of the policy using [DeletePolicyVersion \(p. 90\)](#). To list the policy's versions, use [ListPolicyVersions \(p. 281\)](#). You cannot use [DeletePolicyVersion \(p. 90\)](#) to delete the version that is marked as the default version. You delete the policy's default version in the next step of the process.
- Delete the policy (this automatically deletes the policy's default version) using this operation.

For information about managed policies, see [Managed policies and inline policies](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### PolicyArn

The Amazon Resource Name (ARN) of the IAM policy you want to delete.

For more information about ARNs, see [Amazon Resource Names \(ARNs\)](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### DeleteConflict

The request was rejected because it attempted to delete a resource that has attached subordinate entities. The error message describes these entities.

HTTP Status Code: 409

### InvalidInput

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### LimitExceeded

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

#### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

#### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of DeletePolicy.

#### Sample Request

```
https://iam.amazonaws.com/?Action=DeletePolicy
&PolicyArn=arn:aws:iam::123456789012:policy/S3-read-only-example-bucket
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<DeletePolicyResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>4706281b-3d19-11e4-a4a0-cffb9EXAMPLE</RequestId>
  </ResponseMetadata>
</DeletePolicyResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeletePolicyVersion

Deletes the specified version from the specified managed policy.

You cannot delete the default version from a policy using this operation. To delete the default version from a policy, use [DeletePolicy \(p. 88\)](#). To find out which version of a policy is marked as the default version, use [ListPolicyVersions \(p. 281\)](#).

For information about versions for managed policies, see [Versioning for managed policies](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### PolicyArn

The Amazon Resource Name (ARN) of the IAM policy from which you want to delete a version.

For more information about ARNs, see [Amazon Resource Names \(ARNs\)](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

### VersionId

The policy version to delete.

This parameter allows (through its [regex pattern](#)) a string of characters that consists of the lowercase letter 'v' followed by one or two digits, and optionally followed by a period '.' and a string of letters and digits.

For more information about managed policy versions, see [Versioning for managed policies](#) in the *IAM User Guide*.

Type: String

Pattern: v[1-9][0-9]\*(\.[A-Za-z0-9-]\*)?

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### DeleteConflict

The request was rejected because it attempted to delete a resource that has attached subordinate entities. The error message describes these entities.

HTTP Status Code: 409

### InvalidInput

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### LimitExceeded

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of DeletePolicyVersion.

#### Sample Request

```
https://iam.amazonaws.com/?Action=DeletePolicyVersion
&PolicyArn=arn:aws:iam::123456789012:policy/S3-read-only-example-bucket
&VersionId=v2
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<DeletePolicyVersionResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>268e1556-3d19-11e4-a4a0-cffb9EXAMPLE</RequestId>
  </ResponseMetadata>
</DeletePolicyVersionResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteRole

Deletes the specified role. The role must not have any policies attached. For more information about roles, see [Working with roles](#).

## Important

Make sure that you do not have any Amazon EC2 instances running with the role you are about to delete. Deleting a role or instance profile that is associated with a running instance will break any applications running on the instance.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### RoleName

The name of the role to delete.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w+=,.@-]+`

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### ConcurrentModification

The request was rejected because multiple requests to change this object were submitted simultaneously. Wait a few minutes and submit your request again.

HTTP Status Code: 409

### DeleteConflict

The request was rejected because it attempted to delete a resource that has attached subordinate entities. The error message describes these entities.

HTTP Status Code: 409

### LimitExceeded

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

#### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

#### UnmodifiableEntity

The request was rejected because only the service that depends on the service-linked role can modify or delete the role on your behalf. The error message includes the name of the service that depends on this service-linked role. You must request the change through that service.

HTTP Status Code: 400

## Examples

### Example

This example illustrates one usage of DeleteRole.

#### Sample Request

```
https://iam.amazonaws.com/?Action=DeleteRole
&RoleName=S3Access
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<DeleteRoleResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>913e3f37-99ed-11e1-a4c3-270EXAMPLE04</RequestId>
  </ResponseMetadata>
</DeleteRoleResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteRolePermissionsBoundary

Deletes the permissions boundary for the specified IAM role.

## Important

Deleting the permissions boundary for a role might increase its permissions. For example, it might allow anyone who assumes the role to perform all the actions granted in its permissions policies.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### RoleName

The name (friendly name, not ARN) of the IAM role from which you want to remove the permissions boundary.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [\w+=, .@-]+

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

### UnmodifiableEntity

The request was rejected because only the service that depends on the service-linked role can modify or delete the role on your behalf. The error message includes the name of the service that depends on this service-linked role. You must request the change through that service.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteRolePolicy

Deletes the specified inline policy that is embedded in the specified IAM role.

A role can also have managed policies attached to it. To detach a managed policy from a role, use [DetachRolePolicy \(p. 123\)](#). For more information about policies, refer to [Managed policies and inline policies](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### PolicyName

The name of the inline policy to delete from the specified IAM role.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: Yes

### RoleName

The name (friendly name, not ARN) identifying the role that the policy is embedded in.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w+=,.@-]+`

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### LimitExceeded

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

#### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

#### UnmodifiableEntity

The request was rejected because only the service that depends on the service-linked role can modify or delete the role on your behalf. The error message includes the name of the service that depends on this service-linked role. You must request the change through that service.

HTTP Status Code: 400

## Examples

### Example

This example illustrates one usage of DeleteRolePolicy.

#### Sample Request

```
https://iam.amazonaws.com/?Action=DeleteRolePolicy
&PolicyName=S3AccessPolicy
&RoleName=S3Access
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<DeleteRolePolicyResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>c749ee7f-99ef-11e1-a4c3-27EXAMPLE804</RequestId>
  </ResponseMetadata>
</DeleteRolePolicyResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteSAMLProvider

Deletes a SAML provider resource in IAM.

Deleting the provider resource from IAM does not update any roles that reference the SAML provider resource's ARN as a principal in their trust policies. Any attempt to assume a role that references a non-existent provider resource ARN fails.

**Note**

This operation requires [Signature Version 4](#).

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

**SAMLProviderArn**

The Amazon Resource Name (ARN) of the SAML provider to delete.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

**InvalidInput**

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

**LimitExceeded**

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

**NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

**ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of DeleteSAMLProvider.

#### Sample Request

```
https://iam.amazonaws.com/?Action=DeleteSAMLProvider
&SAMLProviderArn=arn:aws:iam::123456789012:saml-provider/MyUniversity
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<DeleteSAMLProviderResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>c749ee7f-99ef-11e1-a4c3-27EXAMPLE804</RequestId>
  </ResponseMetadata>
</DeleteSAMLProviderResponse>
```

### See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteServerCertificate

Deletes the specified server certificate.

For more information about working with server certificates, see [Working with server certificates](#) in the *IAM User Guide*. This topic also includes a list of AWS services that can use the server certificates that you manage with IAM.

## Important

If you are using a server certificate with Elastic Load Balancing, deleting the certificate could have implications for your application. If Elastic Load Balancing doesn't detect the deletion of bound certificates, it may continue to use the certificates. This could cause Elastic Load Balancing to stop accepting traffic. We recommend that you remove the reference to the certificate from Elastic Load Balancing before using this command to delete the certificate. For more information, see [DeleteLoadBalancerListeners](#) in the *Elastic Load Balancing API Reference*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### ServerCertificateName

The name of the server certificate you want to delete.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### DeleteConflict

The request was rejected because it attempted to delete a resource that has attached subordinate entities. The error message describes these entities.

HTTP Status Code: 409

### LimitExceeded

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

#### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of DeleteServerCertificate.

#### Sample Request

```
https://iam.amazonaws.com/?Action=DeleteServerCertificate
&ServerCertificateName=ProdServerCert
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<DeleteServerCertificateResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
  </ResponseMetadata>
</DeleteServerCertificateResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteServiceLinkedRole

Submits a service-linked role deletion request and returns a `DeletionTaskId`, which you can use to check the status of the deletion. Before you call this operation, confirm that the role has no active sessions and that any resources used by the role in the linked service are deleted. If you call this operation more than once for the same service-linked role and an earlier deletion task is not complete, then the `DeletionTaskId` of the earlier request is returned.

If you submit a deletion request for a service-linked role whose linked service is still accessing a resource, then the deletion task fails. If it fails, the [GetServiceLinkedRoleDeletionStatus \(p. 207\)](#) operation returns the reason for the failure, usually including the resources that must be deleted. To delete the service-linked role, you must first remove those resources from the linked service and then submit the deletion request again. Resources are specific to the service that is linked to the role. For more information about removing resources from a service, see the [AWS documentation](#) for your service.

For more information about service-linked roles, see [Roles terms and concepts: AWS service-linked role](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### **RoleName**

The name of the service-linked role to be deleted.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w+=, .@-]+`

Required: Yes

## Response Elements

The following element is returned by the service.

### **DeletionTaskId**

The deletion task identifier that you can use to check the status of the deletion. This identifier is returned in the format `task/aws-service-role/<service-principal-name>/<role-name>/<task-uuid>`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **LimitExceeded**

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

#### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

#### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

The following example shows how to submit the role named AWSServiceRoleForLexBots for deletion.

#### Sample Request

```
https://iam.amazonaws.com/?Action=DeleteServiceLinkedRole  
&RoleName=AWSServiceRoleForLexBots  
&Version=2010-05-08
```

### Example

This example illustrates one usage of DeleteServiceLinkedRole.

#### Sample Response

```
<DeleteServiceLinkedRoleResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">  
  <DeleteServiceLinkedRoleResult>  
    <DeletionTaskId>task/aws-service-role/lex.amazonaws.com/AWSServiceRoleForLexBots/  
    ec720f7a-c0ba-4838-be33-f72e1873dd52</DeletionTaskId>  
  </DeleteServiceLinkedRoleResult>  
  <ResponseMetadata>  
    <RequestId>4aff7ebf-8297-11e7-898c-4904717fb079</RequestId>  
  </ResponseMetadata>  
</DeleteServiceLinkedRoleResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteServiceSpecificCredential

Deletes the specified service-specific credential.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### ServiceSpecificCredentialId

The unique identifier of the service-specific credential. You can get this value by calling [ListServiceSpecificCredentials \(p. 305\)](#).

This parameter allows (through its [regex pattern](#)) a string of characters that can consist of any upper or lowercased letter or digit.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 128.

Pattern: `[\w]+`

Required: Yes

### UserName

The name of the IAM user associated with the service-specific credential. If this value is not specified, then the operation assumes the user whose credentials are used to call the operation.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w+=,.@-]+`

Required: No

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

## Examples

### Example

The following example shows how to delete a service-specific credential associated with the user named Juan. If Juan's IAM access keys are used to make the call, then he does not need to include the `UserName` parameter.

#### Sample Request

```
https://iam.amazonaws.com/?Action=DeleteServiceSpecificCredential
&ServiceSpecificCredentialId=ACCA12345ABCDEEXAMPLE
&UserName=Juan
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<DeleteServiceSpecificCredentialResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE</RequestId>
  </ResponseMetadata>
</DeleteServiceSpecificCredentialResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteSigningCertificate

Deletes a signing certificate associated with the specified IAM user.

If you do not specify a user name, IAM determines the user name implicitly based on the AWS access key ID signing the request. This operation works for access keys under the AWS account. Consequently, you can use this operation to manage AWS account root user credentials even if the AWS account has no associated IAM users.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### **CertificateId**

The ID of the signing certificate to delete.

The format of this parameter, as described by its [regex pattern](#), is a string of characters that can be upper- or lower-cased letters or digits.

Type: String

Length Constraints: Minimum length of 24. Maximum length of 128.

Pattern: `[\w]+`

Required: Yes

### **UserName**

The name of the user the signing certificate belongs to.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: No

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **LimitExceeded**

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

#### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of DeleteSigningCertificate.

#### Sample Request

```
https://iam.amazonaws.com/?Action=DeleteSigningCertificate
&UserName=Bob
&CertificateId=TA7SMP42TDNZ260BPJE7EXAMPLE
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<DeleteSigningCertificateResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
  </ResponseMetadata>
</DeleteSigningCertificateResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteSSHPublicKey

Deletes the specified SSH public key.

The SSH public key deleted by this operation is used only for authenticating the associated IAM user to an CodeCommit repository. For more information about using SSH keys to authenticate to an CodeCommit repository, see [Set up CodeCommit for SSH connections](#) in the *CodeCommit User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### SSHPublicKeyId

The unique identifier for the SSH public key.

This parameter allows (through its [regex pattern](#)) a string of characters that can consist of any upper or lowercased letter or digit.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 128.

Pattern: [\w]+

Required: Yes

### UserName

The name of the IAM user associated with the SSH public key.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: \_+=,.@-

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [\w+=,.@-]+

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

## Examples

### Example

This example illustrates one usage of DeleteSSHPublicKey.

#### Sample Request

```
https://iam.amazonaws.com/?Action=DeleteSSHPublicKey
&SSHPublicKeyId=APKAEIVFHP46CEEXAMPLE
&UserName=Jane
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<DeleteSSHPublicKeyResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>1a21282e-f36e-11e4-a53b-6b544EXAMPLE</RequestId>
  </ResponseMetadata>
</DeleteSSHPublicKeyResponse>
```

### See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## DeleteUser

Deletes the specified IAM user. Unlike the AWS Management Console, when you delete a user programmatically, you must delete the items attached to the user manually, or the deletion fails. For more information, see [Deleting an IAM user](#). Before attempting to delete a user, remove the following items:

- Password ([DeleteLoginProfile \(p. 84\)](#))
- Access keys ([DeleteAccessKey \(p. 72\)](#))
- Signing certificate ([DeleteSigningCertificate \(p. 108\)](#))
- SSH public key ([DeleteSSHPublicKey \(p. 110\)](#))
- Git credentials ([DeleteServiceSpecificCredential \(p. 106\)](#))
- Multi-factor authentication (MFA) device ([DeactivateMFADevice \(p. 69\)](#), [DeleteVirtualMFADevice \(p. 119\)](#))
- Inline policies ([DeleteUserPolicy \(p. 117\)](#))
- Attached managed policies ([DetachUserPolicy \(p. 126\)](#))
- Group memberships ([RemoveUserFromGroup \(p. 344\)](#))

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### UserName

The name of the user to delete.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### ConcurrentModification

The request was rejected because multiple requests to change this object were submitted simultaneously. Wait a few minutes and submit your request again.

HTTP Status Code: 409

### DeleteConflict

The request was rejected because it attempted to delete a resource that has attached subordinate entities. The error message describes these entities.

HTTP Status Code: 409

#### **LimitExceeded**

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

#### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

#### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of DeleteUser.

#### Sample Request

```
https://iam.amazonaws.com/?Action=DeleteUser
&UserName=Bob
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<DeleteUserResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
  </ResponseMetadata>
</DeleteUserResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

# DeleteUserPermissionsBoundary

Deletes the permissions boundary for the specified IAM user.

**Important**

Deleting the permissions boundary for a user might increase its permissions by allowing the user to perform all the actions granted in its permissions policies.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

**UserName**

The name (friendly name, not ARN) of the IAM user from which you want to remove the permissions boundary.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [\\w+=, .@-]+

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

**NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

**ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteUserPolicy

Deletes the specified inline policy that is embedded in the specified IAM user.

A user can also have managed policies attached to it. To detach a managed policy from a user, use [DetachUserPolicy \(p. 126\)](#). For more information about policies, refer to [Managed policies and inline policies](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### PolicyName

The name identifying the policy document to delete.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: Yes

### UserName

The name (friendly name, not ARN) identifying the user that the policy is embedded in.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### LimitExceeded

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

#### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of DeleteUserPolicy.

#### Sample Request

```
https://iam.amazonaws.com/?Action=DeleteUserPolicy
&UserName=Bob
&PolicyName=AllAccessPolicy
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<DeleteUserPolicyResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
  </ResponseMetadata>
</DeleteUserPolicyResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteVirtualMFADevice

Deletes a virtual MFA device.

## **Note**

You must deactivate a user's virtual MFA device before you can delete it. For information about deactivating MFA devices, see [DeactivateMFADevice \(p. 69\)](#).

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### **SerialNumber**

The serial number that uniquely identifies the MFA device. For virtual MFA devices, the serial number is the same as the ARN.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: =,.@:/-

Type: String

Length Constraints: Minimum length of 9. Maximum length of 256.

Pattern: [\w+=/:, .@-]+

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **DeleteConflict**

The request was rejected because it attempted to delete a resource that has attached subordinate entities. The error message describes these entities.

HTTP Status Code: 409

### **LimitExceeded**

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of DeleteVirtualMFADevice.

#### Sample Request

```
https://iam.amazonaws.com/?Action=DeleteVirtualMFADevice
&SerialNumber=arn:aws:iam::123456789012:mfa/ExampleName
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<DeleteVirtualMFADeviceResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
  </ResponseMetadata>
</DeleteVirtualMFADeviceResponse>
```

### See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DetachGroupPolicy

Removes the specified managed policy from the specified IAM group.

A group can also have inline policies embedded with it. To delete an inline policy, use [DeleteGroupPolicy \(p. 80\)](#). For information about policies, see [Managed policies and inline policies](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### **GroupName**

The name (friendly name, not ARN) of the IAM group to detach the policy from.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: Yes

### **PolicyArn**

The Amazon Resource Name (ARN) of the IAM policy you want to detach.

For more information about ARNs, see [Amazon Resource Names \(ARNs\)](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **InvalidInput**

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### **LimitExceeded**

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of DetachGroupPolicy.

#### Sample Request

```
https://iam.amazonaws.com/?Action=DetachGroupPolicy
&GroupName=Finance
&PolicyArn=arn:aws:iam::aws:policy/ReadOnlyAccess
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<DetachGroupPolicyResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>d4faa7aa-3d1d-11e4-a4a0-cffb9EXAMPLE</RequestId>
  </ResponseMetadata>
</DetachGroupPolicyResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DetachRolePolicy

Removes the specified managed policy from the specified role.

A role can also have inline policies embedded with it. To delete an inline policy, use [DeleteRolePolicy \(p. 97\)](#). For information about policies, see [Managed policies and inline policies](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### PolicyArn

The Amazon Resource Name (ARN) of the IAM policy you want to detach.

For more information about ARNs, see [Amazon Resource Names \(ARNs\)](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

### RoleName

The name (friendly name, not ARN) of the IAM role to detach the policy from.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w+=,.@-]+`

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### InvalidInput

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### LimitExceeded

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

### UnmodifiableEntity

The request was rejected because only the service that depends on the service-linked role can modify or delete the role on your behalf. The error message includes the name of the service that depends on this service-linked role. You must request the change through that service.

HTTP Status Code: 400

## Examples

### Example

This example illustrates one usage of DetachRolePolicy.

#### Sample Request

```
https://iam.amazonaws.com/?Action=DetachRolePolicy
&PolicyArn=arn:aws:iam::aws:policy/ReadOnlyAccess
&RoleName=ReadOnlyRole
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<DetachRolePolicyResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>4c80ccf4-3d1e-11e4-a4a0-cffb9EXAMPLE</RequestId>
  </ResponseMetadata>
</DetachRolePolicyResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

# DetachUserPolicy

Removes the specified managed policy from the specified user.

A user can also have inline policies embedded with it. To delete an inline policy, use [DeleteUserPolicy \(p. 117\)](#). For information about policies, see [Managed policies and inline policies](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### PolicyArn

The Amazon Resource Name (ARN) of the IAM policy you want to detach.

For more information about ARNs, see [Amazon Resource Names \(ARNs\)](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

### UserName

The name (friendly name, not ARN) of the IAM user to detach the policy from.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w+=,.@-]+`

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### InvalidInput

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### LimitExceeded

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of DetachUserPolicy.

#### Sample Request

```
https://iam.amazonaws.com/?Action=DetachUserPolicy
&PolicyArn=arn:aws:iam::aws:policy/AdministratorAccess
&UserName=Alice
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<DetachUserPolicyResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>85ba31fa-3d1f-11e4-a4a0-cffb9EXAMPLE</RequestId>
  </ResponseMetadata>
</DetachUserPolicyResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# EnableMFADevice

Enables the specified MFA device and associates it with the specified IAM user. When enabled, the MFA device is required for every subsequent login by the IAM user associated with the device.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### AuthenticationCode1

An authentication code emitted by the device.

The format for this parameter is a string of six digits.

**Important**

Submit your request immediately after generating the authentication codes. If you generate the codes and then wait too long to submit the request, the MFA device successfully associates with the user but the MFA device becomes out of sync. This happens because time-based one-time passwords (TOTP) expire after a short period of time. If this happens, you can [resync the device](#).

Type: String

Length Constraints: Fixed length of 6.

Pattern: `[\d]+`

Required: Yes

### AuthenticationCode2

A subsequent authentication code emitted by the device.

The format for this parameter is a string of six digits.

**Important**

Submit your request immediately after generating the authentication codes. If you generate the codes and then wait too long to submit the request, the MFA device successfully associates with the user but the MFA device becomes out of sync. This happens because time-based one-time passwords (TOTP) expire after a short period of time. If this happens, you can [resync the device](#).

Type: String

Length Constraints: Fixed length of 6.

Pattern: `[\d]+`

Required: Yes

### SerialNumber

The serial number that uniquely identifies the MFA device. For virtual MFA devices, the serial number is the device ARN.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `=, @, :, -`

Type: String

Length Constraints: Minimum length of 9. Maximum length of 256.

Pattern: [\w+=/:,.@-]+

Required: Yes

#### **UserName**

The name of the IAM user for whom you want to enable the MFA device.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: \_+=,.@-

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [\w+=,.@-]+

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

#### **EntityAlreadyExists**

The request was rejected because it attempted to create a resource that already exists.

HTTP Status Code: 409

#### **EntityTemporarilyUnmodifiable**

The request was rejected because it referenced an entity that is temporarily unmodifiable, such as a user name that was deleted and then recreated. The error indicates that the request is likely to succeed if you try again after waiting several minutes. The error message describes the entity.

HTTP Status Code: 409

#### **InvalidAuthenticationCode**

The request was rejected because the authentication code was not recognized. The error message describes the specific error.

HTTP Status Code: 403

#### **LimitExceeded**

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

#### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of `EnableMFADevice`.

#### Sample Request

```
https://iam.amazonaws.com/?Action=EnableMFADevice
&UserName=Bob
&SerialNumber=R1234
&AuthenticationCode1=234567
&AuthenticationCode2=987654
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<EnableMFADeviceResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
  </ResponseMetadata>
</EnableMFADeviceResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GenerateCredentialReport

Generates a credential report for the AWS account. For more information about the credential report, see [Getting credential reports](#) in the *IAM User Guide*.

## Response Elements

The following elements are returned by the service.

### Description

Information about the credential report.

Type: String

### State

Information about the state of the credential report.

Type: String

Valid Values: STARTED | INPROGRESS | COMPLETE

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### LimitExceeded

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of GenerateCredentialReport.

#### Sample Request

```
https://iam.amazonaws.com/?Action=GenerateCredentialReport
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<GenerateCredentialReportResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
```

```
<GenerateCredentialReportResult>
  <Description>No report exists. Starting a new report generation task</Description>
  <State>STARTED</State>
</GenerateCredentialReportResult>
<ResponseMetadata>
  <RequestId>29f47818-99f5-11e1-a4c3-27EXAMPLE804</RequestId>
</ResponseMetadata>
</GenerateCredentialReportResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GenerateOrganizationsAccessReport

Generates a report for service last accessed data for AWS Organizations. You can generate a report for any entities (organization root, organizational unit, or account) or policies in your organization.

To call this operation, you must be signed in using your Organizations management account credentials. You can use your long-term IAM user or root user credentials, or temporary credentials from assuming an IAM role. SCPs must be enabled for your organization root. You must have the required IAM and Organizations permissions. For more information, see [Refining permissions using service last accessed data](#) in the *IAM User Guide*.

You can generate a service last accessed data report for entities by specifying only the entity's path. This data includes a list of services that are allowed by any service control policies (SCPs) that apply to the entity.

You can generate a service last accessed data report for a policy by specifying an entity's path and an optional Organizations policy ID. This data includes a list of services that are allowed by the specified SCP.

For each service in both report types, the data includes the most recent account activity that the policy allows to account principals in the entity or the entity's children. For important information about the data, reporting period, permissions required, troubleshooting, and supported Regions see [Reducing permissions using service last accessed data](#) in the *IAM User Guide*.

## Important

The data includes all attempts to access AWS, not just the successful ones. This includes all attempts that were made using the AWS Management Console, the AWS API through any of the SDKs, or any of the command line tools. An unexpected entry in the service last accessed data does not mean that an account has been compromised, because the request might have been denied. Refer to your CloudTrail logs as the authoritative source for information about all API calls and whether they were successful or denied access. For more information, see [Logging IAM events with CloudTrail](#) in the *IAM User Guide*.

This operation returns a JobId. Use this parameter in the [GetOrganizationsAccessReport \(p. 177\)](#) operation to check the status of the report generation. To check the status of this request, use the JobId parameter in the [GetOrganizationsAccessReport \(p. 177\)](#) operation and test the JobStatus response parameter. When the job is complete, you can retrieve the report.

To generate a service last accessed data report for entities, specify an entity path without specifying the optional Organizations policy ID. The type of entity that you specify determines the data returned in the report.

- **Root** – When you specify the organizations root as the entity, the resulting report lists all of the services allowed by SCPs that are attached to your root. For each service, the report includes data for all accounts in your organization except the management account, because the management account is not limited by SCPs.
- **OU** – When you specify an organizational unit (OU) as the entity, the resulting report lists all of the services allowed by SCPs that are attached to the OU and its parents. For each service, the report includes data for all accounts in the OU or its children. This data excludes the management account, because the management account is not limited by SCPs.
- **management account** – When you specify the management account, the resulting report lists all AWS services, because the management account is not limited by SCPs. For each service, the report includes data for only the management account.
- **Account** – When you specify another account as the entity, the resulting report lists all of the services allowed by SCPs that are attached to the account and its parents. For each service, the report includes data for only the specified account.

To generate a service last accessed data report for policies, specify an entity path and the optional Organizations policy ID. The type of entity that you specify determines the data returned for each service.

- **Root** – When you specify the root entity and a policy ID, the resulting report lists all of the services that are allowed by the specified SCP. For each service, the report includes data for all accounts in your organization to which the SCP applies. This data excludes the management account, because the management account is not limited by SCPs. If the SCP is not attached to any entities in the organization, then the report will return a list of services with no data.
- **OU** – When you specify an OU entity and a policy ID, the resulting report lists all of the services that are allowed by the specified SCP. For each service, the report includes data for all accounts in the OU or its children to which the SCP applies. This means that other accounts outside the OU that are affected by the SCP might not be included in the data. This data excludes the management account, because the management account is not limited by SCPs. If the SCP is not attached to the OU or one of its children, the report will return a list of services with no data.
- **management account** – When you specify the management account, the resulting report lists all AWS services, because the management account is not limited by SCPs. If you specify a policy ID in the CLI or API, the policy is ignored. For each service, the report includes data for only the management account.
- **Account** – When you specify another account entity and a policy ID, the resulting report lists all of the services that are allowed by the specified SCP. For each service, the report includes data for only the specified account. This means that other accounts in the organization that are affected by the SCP might not be included in the data. If the SCP is not attached to the account, the report will return a list of services with no data.

#### Note

Service last accessed data does not use other policy types when determining whether a principal could access a service. These other policy types include identity-based policies, resource-based policies, access control lists, IAM permissions boundaries, and AWS STS assume role policies. It only applies SCP logic. For more about the evaluation of policy types, see [Evaluating policies](#) in the *IAM User Guide*.

For more information about service last accessed data, see [Reducing policy scope by viewing user activity](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### EntityPath

The path of the AWS Organizations entity (root, OU, or account). You can build an entity path using the known structure of your organization. For example, assume that your account ID is 123456789012 and its parent OU ID is ou-rge0-awsabcde. The organization root ID is r-f6g7h8i9j0example and your organization ID is o-a1b2c3d4e5. Your entity path is o-a1b2c3d4e5/r-f6g7h8i9j0example/ou-rge0-awsabcde/123456789012.

Type: String

Length Constraints: Minimum length of 19. Maximum length of 427.

Pattern: ^o-[0-9a-z]{10,32}\r-[0-9a-z]{4,32}[0-9a-z-\r]\*

Required: Yes

### OrganizationsPolicyId

The identifier of the AWS Organizations service control policy (SCP). This parameter is optional.

This ID is used to generate information about when an account principal that is limited by the SCP attempted to access an AWS service.

Type: String

Pattern: ^p-[0-9a-zA-Z\_]{8,128}\$

Required: No

## Response Elements

The following element is returned by the service.

### JobId

The job identifier that you can use in the [GetOrganizationsAccessReport \(p. 177\)](#) operation.

Type: String

Length Constraints: Fixed length of 36.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### ReportGenerationLimitExceeded

The request failed because the maximum number of concurrent requests for this account are already running.

HTTP Status Code: 409

## Examples

### Example

This example illustrates one usage of `GenerateOrganizationsAccessReport`.

#### Sample Request

```
https://iam.amazonaws.com/?Action=GenerateOrganizationsAccessReport
&EntityPath=o-a1b2c3d4e5/r-f6g7h8i9j0example/ou-1a2b3c-k918m7n6o5example
&OrganizationsPolicyId=p-9189z4nw
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<JobId>examplea-1234-b567-cde8-90fg123abcd4</JobId>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GenerateServiceLastAccessedDetails

Generates a report that includes details about when an IAM resource (user, group, role, or policy) was last used in an attempt to access AWS services. Recent activity usually appears within four hours. IAM reports activity for at least the last 400 days, or less if your Region began supporting this feature within the last year. For more information, see [Regions where data is tracked](#).

## Important

The service last accessed data includes all attempts to access an AWS API, not just the successful ones. This includes all attempts that were made using the AWS Management Console, the AWS API through any of the SDKs, or any of the command line tools. An unexpected entry in the service last accessed data does not mean that your account has been compromised, because the request might have been denied. Refer to your CloudTrail logs as the authoritative source for information about all API calls and whether they were successful or denied access. For more information, see [Logging IAM events with CloudTrail](#) in the *IAM User Guide*.

The `GenerateServiceLastAccessedDetails` operation returns a `JobId`. Use this parameter in the following operations to retrieve the following details from your report:

- [GetServiceLastAccessedDetails \(p. 198\)](#) – Use this operation for users, groups, roles, or policies to list every AWS service that the resource could access using permissions policies. For each service, the response includes information about the most recent access attempt.

The `JobId` returned by `GenerateServiceLastAccessedDetail` must be used by the same role within a session, or by the same user when used to call `GetServiceLastAccessedDetail`.

- [GetServiceLastAccessedDetailsWithEntities \(p. 203\)](#) – Use this operation for groups and policies to list information about the associated entities (users or roles) that attempted to access a specific AWS service.

To check the status of the `GenerateServiceLastAccessedDetails` request, use the `JobId` parameter in the same operations and test the `JobStatus` response parameter.

For additional information about the permissions policies that allow an identity (user, group, or role) to access specific services, use the [ListPoliciesGrantingServiceAccess \(p. 274\)](#) operation.

## Note

Service last accessed data does not use other policy types when determining whether a resource could access a service. These other policy types include resource-based policies, access control lists, AWS Organizations policies, IAM permissions boundaries, and AWS STS assume role policies. It only applies permissions policy logic. For more about the evaluation of policy types, see [Evaluating policies](#) in the *IAM User Guide*.

For more information about service and action last accessed data, see [Reducing permissions using service last accessed data](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### Arn

The ARN of the IAM resource (user, group, role, or managed policy) used to generate information about when the resource was last used in an attempt to access an AWS service.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

#### Granularity

The level of detail that you want to generate. You can specify whether you want to generate information about the last attempt to access services or actions. If you specify service-level granularity, this operation generates only service data. If you specify action-level granularity, it generates service and action data. If you don't include this optional parameter, the operation generates service data.

Type: String

Valid Values: SERVICE\_LEVEL | ACTION\_LEVEL

Required: No

## Response Elements

The following element is returned by the service.

#### JobId

The JobId that you can use in the [GetServiceLastAccessedDetails \(p. 198\)](#) or [GetServiceLastAccessedDetailsWithEntities \(p. 203\)](#) operations. The JobId returned by GenerateServiceLastAccessedDetail must be used by the same role within a session, or by the same user when used to call GetServiceLastAccessedDetail.

Type: String

Length Constraints: Fixed length of 36.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

#### InvalidInput

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

#### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

## Examples

### Example

This example illustrates one usage of GenerateServiceLastAccessedDetails.

## Sample Request

```
https://iam.amazonaws.com/?Action=GenerateServiceLastAccessedDetails
&Arn=arn:aws:iam::123456789012:policy/ExamplePolicy1
&Version=2010-05-08
&AUTHPARAMS
```

## Sample Response

```
<JobId>examplef-1305-c245-eba4-71fe298bcda7</JobId>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetAccessKeyLastUsed

Retrieves information about when the specified access key was last used. The information includes the date and time of last use, along with the AWS service and Region that were specified in the last request made with that key.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### AccessKeyId

The identifier of an access key.

This parameter allows (through its [regex pattern](#)) a string of characters that can consist of any upper or lowercased letter or digit.

Type: String

Length Constraints: Minimum length of 16. Maximum length of 128.

Pattern: `[\w]+`

Required: Yes

## Response Elements

The following elements are returned by the service.

### AccessKeyLastUsed

Contains information about the last time the access key was used.

Type: [AccessKeyLastUsed \(p. 481\)](#) object

### UserName

The name of the IAM user that owns this access key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=, .@-]+`

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

## Examples

### Example

This example illustrates one usage of `GetAccessKeyLastUsed`.

#### Sample Request

```
https://iam.amazonaws.com/  
?Action=GetAccessKeyLastUsed  
&AccessKeyId=AKIAIOSFODNN7EXAMPLE  
&Version=2010-05-08  
&AUTHPARAMS
```

#### Sample Response

```
<GetAccessKeyLastUsedResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">  
  <GetAccessKeyLastUsedResult>  
    <AccessKeyLastUsed>  
      <Region>us-west-2</Region>  
      <LastUsedDate>2015-03-13T10:45:00Z</LastUsedDate>  
      <ServiceName>s3</ServiceName>  
    </AccessKeyLastUsed>  
    <UserName>bob</UserName>  
  </GetAccessKeyLastUsedResult>  
  <ResponseMetadata>  
    <RequestId>510a6abf-d022-11e4-abe8-9b0ebEXAMPLE</RequestId>  
  </ResponseMetadata>  
</GetAccessKeyLastUsedResponse>
```

### See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetAccountAuthorizationDetails

Retrieves information about all IAM users, groups, roles, and policies in your AWS account, including their relationships to one another. Use this operation to obtain a snapshot of the configuration of IAM permissions (users, groups, roles, and policies) in your account.

## Note

Policies returned by this operation are URL-encoded compliant with [RFC 3986](#). You can use a URL decoding method to convert the policy back to plain JSON text. For example, if you use Java, you can use the decode method of the `java.net.URLDecoder` utility class in the Java SDK. Other languages and SDKs provide similar functionality.

You can optionally filter the results using the `Filter` parameter. You can paginate the results using the `MaxItems` and `Marker` parameters.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### **Filter.member.N**

A list of entity types used to filter the results. Only the entities that match the types you specify are included in the output. Use the value `LocalManagedPolicy` to include customer managed policies.

The format for this parameter is a comma-separated (if more than one) list of strings. Each string value in the list must be one of the valid values listed below.

Type: Array of strings

Valid Values: `User` | `Role` | `Group` | `LocalManagedPolicy` | `AWSManagedPolicy`

Required: No

### **Marker**

Use this parameter only when paginating results and only after you receive a response indicating that the results are truncated. Set it to the value of the `Marker` element in the response that you received to indicate where the next call should start.

Type: String

Length Constraints: Minimum length of 1.

Pattern: `[\u0020-\u00FF]+`

Required: No

### **MaxItems**

Use this only when paginating results to indicate the maximum number of items you want in the response. If additional items exist beyond the maximum you specify, the `IsTruncated` response element is `true`.

If you do not include this parameter, the number of items defaults to 100. Note that IAM might return fewer results, even when there are more results available. In that case, the `IsTruncated` response element returns `true`, and `Marker` contains a value to include in the subsequent call that tells the service where to continue from.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

## Response Elements

The following elements are returned by the service.

### **GroupDetailList.member.N**

A list containing information about IAM groups.

Type: Array of [GroupDetail \(p. 498\)](#) objects

### **IsTruncated**

A flag that indicates whether there are more items to return. If your results were truncated, you can make a subsequent pagination request using the `Marker` request parameter to retrieve more items. Note that IAM might return fewer than the `MaxItems` number of results even when there are more results available. We recommend that you check `IsTruncated` after every call to ensure that you receive all your results.

Type: Boolean

### **Marker**

When `IsTruncated` is `true`, this element is present and contains the value to use for the `Marker` parameter in a subsequent pagination request.

Type: String

### **Policies.member.N**

A list containing information about managed policies.

Type: Array of [ManagedPolicyDetail \(p. 504\)](#) objects

### **RoleDetailList.member.N**

A list containing information about IAM roles.

Type: Array of [RoleDetail \(p. 530\)](#) objects

### **UserDetailList.member.N**

A list containing information about IAM users.

Type: Array of [UserDetail \(p. 558\)](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of GetAccountAuthorizationDetails.

#### Sample Request

```
https://iam.amazonaws.com/?Action=GetAccountAuthorizationDetails
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<GetAccountAuthorizationDetailsResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <GetAccountAuthorizationDetailsResult>
    <IsTruncated>true</IsTruncated>
    <UserDetailList>
      <member>
        <GroupList>
          <member>Admins</member>
        </GroupList>
        <AttachedManagedPolicies/>
        <UserId>AIDACKCEVSQ6C2EXAMPLE</UserId>
        <Path>/</Path>
        <UserName>Alice</UserName>
        <Arn>arn:aws:iam::123456789012:user/Alice</Arn>
        <CreateDate>2013-10-14T18:32:24Z</CreateDate>
      </member>
      <member>
        <GroupList>
          <member>Admins</member>
        </GroupList>
        <AttachedManagedPolicies/>
        <UserPolicyList>
          <member>
            <PolicyName>DenyBillingAndIAMPolicy</PolicyName>
            <PolicyDocument>
              {"Version": "2012-10-17", "Statement": {"Effect": "Deny", "Action": ["aws-portal:*", "iam:*"], "Resource": "*"}}
            </PolicyDocument>
          </member>
        </UserPolicyList>
        <UserId>AIDACKCEVSQ6C3EXAMPLE</UserId>
        <Path>/</Path>
        <UserName>Bob</UserName>
        <Arn>arn:aws:iam::123456789012:user/Bob</Arn>
        <CreateDate>2013-10-14T18:32:25Z</CreateDate>
      </member>
      <member>
        <GroupList>
          <member>Dev</member>
        </GroupList>
        <AttachedManagedPolicies/>
        <UserId>AIDACKCEVSQ6C4EXAMPLE</UserId>
        <Path>/</Path>
        <UserName>Charlie</UserName>
        <Arn>arn:aws:iam::123456789012:user/Charlie</Arn>
        <CreateDate>2013-10-14T18:33:56Z</CreateDate>
      </member>
      <member>
```

```
<GroupList>
  <member>Dev</member>
</GroupList>
<AttachedManagedPolicies/>
<UserId>AIDACKCEVSQ6C5EXAMPLE</UserId>
<Path>/</Path>
<UserName>Danielle</UserName>
<Arn>arn:aws:iam::123456789012:user/Danielle</Arn>
<CreateDate>2013-10-14T18:33:56Z</CreateDate>
</member>
<member>
  <GroupList>
    <member>Finance</member>
  </GroupList>
  <AttachedManagedPolicies/>
  <UserId>AIDACKCEVSQ6C6EXAMPLE</UserId>
  <Path>/</Path>
  <UserName>Elaine</UserName>
  <Arn>arn:aws:iam::123456789012:user/Elaine</Arn>
  <CreateDate>2013-10-14T18:57:48Z</CreateDate>
</member>
</UserDetailList>
<Marker>
  EXAMPLEkakv9BCuUNFDtxWSyfzetYwEx2Adc8dnzfvERF5S6YMyXKx41t6gC1/eeaCX3Jo94/
  bKqezEAg8TEVS99EKFLxm3jtbl25FDWEXAMPLE
</Marker>
<GroupDetailList>
  <member>
    <GroupId>AIDACKCEVSQ6C7EXAMPLE</GroupId>
    <AttachedManagedPolicies>
      <member>
        <PolicyName>AdministratorAccess</PolicyName>
        <PolicyArn>arn:aws:iam::aws:policy/AdministratorAccess</PolicyArn>
      </member>
    </AttachedManagedPolicies>
    <GroupName>Admins</GroupName>
    <Path>/</Path>
    <Arn>arn:aws:iam::123456789012:group/Admins</Arn>
    <CreateDate>2013-10-14T18:32:24Z</CreateDate>
    <GroupPolicyList/>
  </member>
  <member>
    <GroupId>AIDACKCEVSQ6C8EXAMPLE</GroupId>
    <AttachedManagedPolicies>
      <member>
        <PolicyName>PowerUserAccess</PolicyName>
        <PolicyArn>arn:aws:iam::aws:policy/PowerUserAccess</PolicyArn>
      </member>
    </AttachedManagedPolicies>
    <GroupName>Dev</GroupName>
    <Path>/</Path>
    <Arn>arn:aws:iam::123456789012:group/Dev</Arn>
    <CreateDate>2013-10-14T18:33:55Z</CreateDate>
    <GroupPolicyList/>
  </member>
  <member>
    <GroupId>AIDACKCEVSQ6C9EXAMPLE</GroupId>
    <AttachedManagedPolicies/>
    <GroupName>Finance</GroupName>
    <Path>/</Path>
    <Arn>arn:aws:iam::123456789012:group/Finance</Arn>
    <CreateDate>2013-10-14T18:57:48Z</CreateDate>
    <GroupPolicyList>
      <member>
        <PolicyName>policygen-201310141157</PolicyName>
        <PolicyDocument>
```

```
{"Version":"2012-10-17", "Statement":[{"Action":["aws-portal:*"], "Sid":"Stmt1381777017000", "Resource":["*"], "Effect":"Allow"}]}</PolicyDocument></member></GroupPolicyList></member></GroupDetailList><RoleDetailList><member><RolePolicyList/><AttachedManagedPolicies><member><PolicyName>AmazonS3FullAccess</PolicyName><PolicyArn>arn:aws:iam::aws:policy/AmazonS3FullAccess</PolicyArn></member><member><PolicyName>AmazonDynamoDBFullAccess</PolicyName><PolicyArn>arn:aws:iam::aws:policy/AmazonDynamoDBFullAccess</PolicyArn></member></AttachedManagedPolicies><InstanceProfileList><member><InstanceProfileName>EC2role</InstanceProfileName><Roles><member><Path>/</Path><Arn>arn:aws:iam::123456789012:role/EC2role</Arn><RoleName>EC2role</RoleName><AssumeRolePolicyDocument><Version>2012-10-17</Version><Statement>[{"Sid":"","Effect":"Allow","Principal":{"Service":"ec2.amazonaws.com"}, "Action":"sts:AssumeRole"}]</Statement></AssumeRolePolicyDocument><CreateDate>2014-07-30T17:09:20Z</CreateDate><RoleId>AROAFP4BKI7Y7TEXAMPLE</RoleId><RoleLastUsed><LastUsedDate>2019-11-20T17:09:20Z</LastUsedDate><Region>us-east-1</Region></RoleLastUsed></member></Roles><Path>/</Path><Arn>arn:aws:iam::123456789012:instance-profile/EC2role</Arn><InstanceProfileId>AIPAFFYRBHWXW2EXAMPLE</InstanceProfileId><CreateDate>2014-07-30T17:09:20Z</CreateDate></member></InstanceProfileList><Path>/</Path><Arn>arn:aws:iam::123456789012:role/EC2role</Arn><RoleName>EC2role</RoleName><AssumeRolePolicyDocument><Version>2012-10-17</Version><Statement>[{"Sid":"","Effect":"Allow", "Principal":{"Service":"ec2.amazonaws.com"}, "Action":"sts:AssumeRole"}]</Statement></AssumeRolePolicyDocument><CreateDate>2014-07-30T17:09:20Z</CreateDate><RoleId>AROAFP4BKI7Y7TEXAMPLE</RoleId></member></RoleDetailList><Policies><member><PolicyName>create-update-delete-set-managed-policies</PolicyName><DefaultVersionId>v1</DefaultVersionId><PolicyId>ANPAJ2UCCR6DPCEEXAMPLE</PolicyId><Path>/</Path><PolicyVersionList><member>
```

```

<Document>
  {"Version":"2012-10-17","Statement":[{"Effect":"Allow",
    "Action":["iam:CreatePolicy","iam:CreatePolicyVersion",
    "iam:DeletePolicy","iam:DeletePolicyVersion","iam:GetPolicy",
    "iam:GetPolicyVersion","iam>ListPolicies",
    "iam>ListPolicyVersions","iam:SetDefaultPolicyVersion"],
    "Resource":"*"}]}
</Document>
<IsDefaultVersion>true</IsDefaultVersion>
<VersionId>v1</VersionId>
<CreateDate>2015-02-06T19:58:34Z</CreateDate>
</member>
</PolicyVersionList>
<Arn>
  arn:aws:iam::123456789012:policy/create-update-delete-set-managed-policies
</Arn>
<AttachmentCount>1</AttachmentCount>
<CreateDate>2015-02-06T19:58:34Z</CreateDate>
<IsAttachable>true</IsAttachable>
<UpdateDate>2015-02-06T19:58:34Z</UpdateDate>
</member>
<member>
  <PolicyName>S3-read-only-specific-bucket</PolicyName>
  <DefaultVersionId>v1</DefaultVersionId>
  <PolicyId>ANPAJ4AE5446DAEXAMPLE</PolicyId>
  <Path>/</Path>
  <PolicyVersionList>
    <member>
      <Document>
        {"Version":"2012-10-17","Statement":[{"Effect":"Allow","Action":
          ["s3:Get*","s3>List*"],"Resource":["arn:aws:s3:::example-bucket",
          "arn:aws:s3:::example-bucket/*"]}]}
      </Document>
      <IsDefaultVersion>true</IsDefaultVersion>
      <VersionId>v1</VersionId>
      <CreateDate>2015-01-21T21:39:41Z</CreateDate>
    </member>
  </PolicyVersionList>
  <Arn>arn:aws:iam::123456789012:policy/S3-read-only-specific-bucket</Arn>
  <AttachmentCount>1</AttachmentCount>
  <CreateDate>2015-01-21T21:39:41Z</CreateDate>
  <IsAttachable>true</IsAttachable>
  <UpdateDate>2015-01-21T23:39:41Z</UpdateDate>
</member>
<member>
  <PolicyName>AWSOpsWorksRole</PolicyName>
  <DefaultVersionId>v1</DefaultVersionId>
  <PolicyId>ANPAE376NQ77WV6KGJEBE</PolicyId>
  <Path>/service-role/</Path>
  <PolicyVersionList>
    <member>
      <Document>
        {"Version":"2012-10-17","Statement":[{"Effect":"Allow","Action":
          ["cloudwatch:GetMetricStatistics","ec2:DescribeAccountAttributes",
          "ec2:DescribeAvailabilityZones","ec2:DescribeInstances",
          "ec2:DescribeKeyPairs","ec2:DescribeSecurityGroups","ec2:DescribeSubnets",
          "ec2:DescribeVpcs","elasticloadbalancing:DescribeInstanceHealth",
          "elasticloadbalancing:DescribeLoadBalancers","iam:GetRolePolicy",
          "iam>ListInstanceProfiles","iam>ListRoles","iam>ListUsers",
          "iam:PassRole","opsworks*","rds*"],"Resource":["*"]}]}
      </Document>
      <IsDefaultVersion>true</IsDefaultVersion>
      <VersionId>v1</VersionId>
      <CreateDate>2014-12-10T22:57:47Z</CreateDate>
    </member>
  </PolicyVersionList>

```

```
<Arn>arn:aws:iam::aws:policy/service-role/AWSOpsWorksRole</Arn>
<AttachmentCount>1</AttachmentCount>
<CreateDate>2015-02-06T18:41:27Z</CreateDate>
<IsAttachable>true</IsAttachable>
<UpdateDate>2015-02-06T18:41:27Z</UpdateDate>
</member>
<member>
  <PolicyName>AmazonEC2FullAccess</PolicyName>
  <DefaultVersionId>v1</DefaultVersionId>
  <PolicyId>ANPAE3QWE5YT46TQ34WLG</PolicyId>
  <Path>/</Path>
  <PolicyVersionList>
    <member>
      <Document>
        {"Version":"2012-10-17", "Statement":[{"Action":"ec2:*",
          "Effect":"Allow", "Resource": "*"}, {"Effect":"Allow",
          "Action":"elasticloadbalancing:*", "Resource": "*"}, {"Effect":"Allow",
          "Action":"cloudwatch:*", "Resource": "*"}, {"Effect":"Allow",
          "Action":"autoscaling:*", "Resource": "*"}]}
      </Document>
      <IsDefaultVersion>true</IsDefaultVersion>
      <VersionId>v1</VersionId>
      <CreateDate>2014-10-30T20:59:46Z</CreateDate>
    </member>
  </PolicyVersionList>
  <Arn>arn:aws:iam::aws:policy/AmazonEC2FullAccess</Arn>
  <AttachmentCount>1</AttachmentCount>
  <CreateDate>2015-02-06T18:40:15Z</CreateDate>
  <IsAttachable>true</IsAttachable>
  <UpdateDate>2015-02-06T18:40:15Z</UpdateDate>
</member>
</Policies>
</GetAccountAuthorizationDetailsResult>
<ResponseMetadata>
  <RequestId>92e79ae7-7399-11e4-8c85-4b53eEXAMPLE</RequestId>
</ResponseMetadata>
</GetAccountAuthorizationDetailsResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetAccountPasswordPolicy

Retrieves the password policy for the AWS account. This tells you the complexity requirements and mandatory rotation periods for the IAM user passwords in your account. For more information about using a password policy, see [Managing an IAM password policy](#).

## Response Elements

The following element is returned by the service.

### PasswordPolicy

A structure that contains details about the account's password policy.

Type: [PasswordPolicy \(p. 510\)](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of GetAccountPasswordPolicy.

#### Sample Request

```
https://iam.amazonaws.com/?Action=GetAccountPasswordPolicy
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<GetAccountPasswordPolicyResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <GetAccountPasswordPolicyResult>
    <PasswordPolicy>
      <AllowUsersToChangePassword>true</AllowUsersToChangePassword>
      <RequireUppercaseCharacters>true</RequireUppercaseCharacters>
      <RequireSymbols>true</RequireSymbols>
      <ExpirePasswords>false</ExpirePasswords>
```

```
<PasswordReusePrevention>12</PasswordReusePrevention>
<RequireLowercaseCharacters>true</RequireLowercaseCharacters>
<MaxPasswordAge>90</MaxPasswordAge>
<HardExpiry>false</HardExpiry>
<RequireNumbers>true</RequireNumbers>
<MinimumPasswordLength>12</MinimumPasswordLength>
</PasswordPolicy>
</GetAccountPasswordPolicyResult>
<ResponseMetadata>
  <RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
</ResponseMetadata>
</GetAccountPasswordPolicyResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetAccountSummary

Retrieves information about IAM entity usage and IAM quotas in the AWS account.

For information about IAM quotas, see [IAM and AWS STS quotas](#) in the *IAM User Guide*.

## Response Elements

The following element is returned by the service.

**SummaryMap** , SummaryMap.entry.N.key (key), SummaryMap.entry.N.value (value)

A set of key–value pairs containing information about IAM entity usage and IAM quotas.

Type: String to integer map

Valid Keys: Users | UsersQuota | Groups | GroupsQuota | ServerCertificates | ServerCertificatesQuota | UserPolicySizeQuota | GroupPolicySizeQuota | GroupsPerUserQuota | SigningCertificatesPerUserQuota | AccessKeysPerUserQuota | MFADevices | MFADevicesInUse | AccountMFAEnabled | AccountAccessKeysPresent | AccountSigningCertificatesPresent | AttachedPoliciesPerGroupQuota | AttachedPoliciesPerRoleQuota | AttachedPoliciesPerUserQuota | Policies | PoliciesQuota | PolicySizeQuota | PolicyVersionsInUse | PolicyVersionsInUseQuota | VersionsPerPolicyQuota | GlobalEndpointTokenVersion

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of GetAccountSummary.

#### Sample Request

```
https://iam.amazonaws.com/?Action=GetAccountSummary
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<GetAccountSummaryResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <GetAccountSummaryResult>
    <SummaryMap>
```

```
<entry>
  <key>Users</key>
  <value>32</value>
</entry>
<entry>
  <key>GroupPolicySizeQuota</key>
  <value>10240</value>
</entry>
<entry>
  <key>PolicyVersionsInUseQuota</key>
  <value>10000</value>
</entry>
<entry>
  <key>ServerCertificatesQuota</key>
  <value>20</value>
</entry>
<entry>
  <key>AccountSigningCertificatesPresent</key>
  <value>0</value>
</entry>
<entry>
  <key>AccountAccessKeysPresent</key>
  <value>0</value>
</entry>
<entry>
  <key>Groups</key>
  <value>7</value>
</entry>
<entry>
  <key>UsersQuota</key>
  <value>150</value>
</entry>
<entry>
  <key>RolePolicySizeQuota</key>
  <value>2048</value>
</entry>
<entry>
  <key>UserPolicySizeQuota</key>
  <value>10240</value>
</entry>
<entry>
  <key>GroupsPerUserQuota</key>
  <value>10</value>
</entry>
<entry>
  <key>AssumeRolePolicySizeQuota</key>
  <value>2048</value>
</entry>
<entry>
  <key>AttachedPoliciesPerGroupQuota</key>
  <value>2</value>
</entry>
<entry>
  <key>Roles</key>
  <value>18</value>
</entry>
<entry>
  <key>VersionsPerPolicyQuota</key>
  <value>5</value>
</entry>
<entry>
  <key>GroupsQuota</key>
  <value>50</value>
</entry>
<entry>
  <key>PolicySizeQuota</key>
```

```
    <value>5120</value>
  </entry>
  <entry>
    <key>Policies</key>
    <value>22</value>
  </entry>
  <entry>
    <key>RolesQuota</key>
    <value>250</value>
  </entry>
  <entry>
    <key>ServerCertificates</key>
    <value>1</value>
  </entry>
  <entry>
    <key>AttachedPoliciesPerRoleQuota</key>
    <value>2</value>
  </entry>
  <entry>
    <key>MFADevicesInUse</key>
    <value>4</value>
  </entry>
  <entry>
    <key>PoliciesQuota</key>
    <value>1000</value>
  </entry>
  <entry>
    <key>AccountMFAType</key>
    <value>1</value>
  </entry>
  <entry>
    <key>Providers</key>
    <value>3</value>
  </entry>
  <entry>
    <key>InstanceProfilesQuota</key>
    <value>100</value>
  </entry>
  <entry>
    <key>MFADevices</key>
    <value>4</value>
  </entry>
  <entry>
    <key>AccessKeysPerUserQuota</key>
    <value>2</value>
  </entry>
  <entry>
    <key>AttachedPoliciesPerUserQuota</key>
    <value>2</value>
  </entry>
  <entry>
    <key>SigningCertificatesPerUserQuota</key>
    <value>2</value>
  </entry>
  <entry>
    <key>PolicyVersionsInUse</key>
    <value>27</value>
  </entry>
  <entry>
    <key>InstanceProfiles</key>
    <value>12</value>
  </entry>
  <entry>
    <key>GlobalEndpointTokenVersion</key>
    <value>2</value>
  </entry>
```

```
</SummaryMap>
</GetAccountSummaryResult>
<ResponseMetadata>
  <RequestId>85cb9b90-ac28-11e4-a88d-97964EXAMPLE</RequestId>
</ResponseMetadata>
</GetAccountSummaryResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetContextKeysForCustomPolicy

Gets a list of all of the context keys referenced in the input policies. The policies are supplied as a list of one or more strings. To get the context keys from policies associated with an IAM user, group, or role, use [GetContextKeysForPrincipalPolicy \(p. 158\)](#).

Context keys are variables maintained by AWS and its services that provide details about the context of an API query request. Context keys can be evaluated by testing against a value specified in an IAM policy. Use `GetContextKeysForCustomPolicy` to understand what key names and values you must supply when you call [SimulateCustomPolicy \(p. 356\)](#). Note that all parameters are shown in unencoded form here for clarity but must be URL encoded to be included as a part of a real HTML request.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### **PolicyInputList.member.N**

A list of policies for which you want the list of context keys referenced in those policies. Each document is specified as a string containing the complete, valid JSON text of an IAM policy.

The [regex pattern](#) used to validate this parameter is a string of characters consisting of the following:

- Any printable ASCII character ranging from the space character (\u0020) through the end of the ASCII character range
- The printable characters in the Basic Latin and Latin-1 Supplement character set (through \u00FF)
- The special characters tab (\u0009), line feed (\u000A), and carriage return (\u000D)

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 131072.

Pattern: [\u0009\u000A\u000D\u0020-\u00FF]+

Required: Yes

## Response Elements

The following element is returned by the service.

### **ContextKeyNames.member.N**

The list of context keys that are referenced in the input policies.

Type: Array of strings

Length Constraints: Minimum length of 5. Maximum length of 256.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### InvalidInput

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

## Examples

### Example 1

In the following example, the request includes a policy as a string. The response shows that the policies use both `aws:CurrentTime` and `aws:username`.

#### Sample Request

```
https://iam.amazonaws.com/?Action=GetContextKeysForCustomPolicy
&PolicyInputList.member.1='{
  "Version": "2012-10-17",
  "Statement": {
    "Effect": "Allow",
    "Action": "dynamodb:*",
    "Resource": "arn:aws:dynamodb:us-east-2:ACCOUNT-ID-WITHOUT-HYPHENS:table/
${aws:username}",
    "Condition": {"DateGreaterThan": {"aws:CurrentTime": "2015-08-16T12:00:00Z"}}
  }
}'
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<GetContextKeysForCustomPolicyResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <GetContextKeysForCustomPolicyResult>
    <ContextKeyNames>
      <member>aws:username</member>
      <member>aws:CurrentTime</member>
    </ContextKeyNames>
  </GetContextKeysForCustomPolicyResult>
  <ResponseMetadata>
    <RequestId>d6808605-4c06-11e5-b121-bd8c7EXAMPLE</RequestId>
  </ResponseMetadata>
</GetContextKeysForCustomPolicyResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetContextKeysForPrincipalPolicy

Gets a list of all of the context keys referenced in all the IAM policies that are attached to the specified IAM entity. The entity can be an IAM user, group, or role. If you specify a user, then the request also includes all of the policies attached to groups that the user is a member of.

You can optionally include a list of one or more additional policies, specified as strings. If you want to include *only* a list of policies by string, use [GetContextKeysForCustomPolicy \(p. 155\)](#) instead.

**Note:** This operation discloses information about the permissions granted to other users. If you do not want users to see other user's permissions, then consider allowing them to use [GetContextKeysForCustomPolicy \(p. 155\)](#) instead.

Context keys are variables maintained by AWS and its services that provide details about the context of an API query request. Context keys can be evaluated by testing against a value in an IAM policy. Use [GetContextKeysForPrincipalPolicy \(p. 158\)](#) to understand what key names and values you must supply when you call [SimulatePrincipalPolicy \(p. 365\)](#).

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### PolicyInputList.member.N

An optional list of additional policies for which you want the list of context keys that are referenced.

The [regex pattern](#) used to validate this parameter is a string of characters consisting of the following:

- Any printable ASCII character ranging from the space character (\u0020) through the end of the ASCII character range
- The printable characters in the Basic Latin and Latin-1 Supplement character set (through \u00FF)
- The special characters tab (\u0009), line feed (\u000A), and carriage return (\u000D)

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 131072.

Pattern: [\u0009\u000A\u000D\u0020-\u00FF]+

Required: No

### PolicySourceArn

The ARN of a user, group, or role whose policies contain the context keys that you want listed. If you specify a user, the list includes context keys that are found in all policies that are attached to the user. The list also includes all groups that the user is a member of. If you pick a group or a role, then it includes only those context keys that are found in policies attached to that entity. Note that all parameters are shown in unencoded form here for clarity, but must be URL encoded to be included as a part of a real HTML request.

For more information about ARNs, see [Amazon Resource Names \(ARNs\)](#) in the [AWS General Reference](#).

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

## Response Elements

The following element is returned by the service.

### **ContextKeyNames.member.N**

The list of context keys that are referenced in the input policies.

Type: Array of strings

Length Constraints: Minimum length of 5. Maximum length of 256.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **InvalidInput**

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

## Examples

### Example 1

In the following example, the request includes the ARN for a user named Dave, and includes one additional policy. This enables you to evaluate the impact that policy would have if you attached it to the user. The response includes five context keys, four from policies attached to the user and one from the added policy. Note that all parameters are shown in unencoded form here for clarity, but must be URL encoded to be included as a part of a real HTML request.

#### Sample Request

```
https://iam.amazonaws.com/?Action=GetContextKeysForPrincipalPolicy
&PolicySourceArn=arn:aws:iam::123456789012:user/Dave
&PolicyInputList.member.1='{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": "dynamodb:*",
      "Resource": "arn:aws:dynamodb:us-east-2:ACCOUNT-ID-WITHOUT-HYPHENS:table/
      ${aws:username}",
      "Condition": {"DateGreaterThan": {"aws:CurrentTime": "2015-08-16T12:00:00Z"}}
    }
  ]
}'
```

```
}'
&Version=2010-05-08
&AUTHPARAMS
```

## Sample Response

```
<GetContextKeysForPrincipalPolicyResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <GetContextKeysForPrincipalPolicyResult>
    <ContextKeyNames>
      <member>aws:username</member>
      <member>aws:CurrentTime</member>
      <member>aws:username</member>
      <member>ec2:InstanceType</member>
      <member>aws:CurrentTime</member>
    </ContextKeyNames>
  </GetContextKeysForPrincipalPolicyResult>
  <ResponseMetadata>
    <RequestId>7ec754ab-4c08-11e5-b121-bd8c7EXAMPLE</RequestId>
  </ResponseMetadata>
</GetContextKeysForPrincipalPolicyResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetCredentialReport

Retrieves a credential report for the AWS account. For more information about the credential report, see [Getting credential reports](#) in the *IAM User Guide*.

## Response Elements

The following elements are returned by the service.

### Content

Contains the credential report. The report is Base64-encoded.

Type: Base64-encoded binary data object

### GeneratedTime

The date and time when the credential report was created, in [ISO 8601 date-time format](#).

Type: Timestamp

### ReportFormat

The format (MIME type) of the credential report.

Type: String

Valid Values: `text/csv`

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### ReportExpired

The request was rejected because the most recent credential report has expired. To generate a new credential report, use [GenerateCredentialReport \(p. 131\)](#). For more information about credential report expiration, see [Getting credential reports](#) in the *IAM User Guide*.

HTTP Status Code: 410

### ReportInProgress

The request was rejected because the credential report is still being generated.

HTTP Status Code: 404

### ReportNotPresent

The request was rejected because the credential report does not exist. To generate a credential report, use [GenerateCredentialReport \(p. 131\)](#).

HTTP Status Code: 410

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of GetCredentialReport.

#### Sample Request

```
https://iam.amazonaws.com/?Action=GetCredentialReport
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<GetCredentialReportResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
<GetCredentialReportResult>
  <Content>BASE-64 ENCODED FILE CONTENTS</Content>
  <ReportFormat>text/csv</ReportFormat>
  <GeneratedTime>2014-08-28T21:42:50Z</GeneratedTime>
</GetCredentialReportResult>
<ResponseMetadata>
  <RequestId>29f47818-99f5-11e1-a4c3-27EXAMPLE804</RequestId>
</ResponseMetadata>
</GetCredentialReportResponse>
```

### See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetGroup

Returns a list of IAM users that are in the specified IAM group. You can paginate the results using the `MaxItems` and `Marker` parameters.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### GroupName

The name of the group.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: Yes

### Marker

Use this parameter only when paginating results and only after you receive a response indicating that the results are truncated. Set it to the value of the `Marker` element in the response that you received to indicate where the next call should start.

Type: String

Length Constraints: Minimum length of 1.

Pattern: `[\u0020-\u00FF]+`

Required: No

### MaxItems

Use this only when paginating results to indicate the maximum number of items you want in the response. If additional items exist beyond the maximum you specify, the `IsTruncated` response element is `true`.

If you do not include this parameter, the number of items defaults to 100. Note that IAM might return fewer results, even when there are more results available. In that case, the `IsTruncated` response element returns `true`, and `Marker` contains a value to include in the subsequent call that tells the service where to continue from.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

## Response Elements

The following elements are returned by the service.

## Group

A structure that contains details about the group.

Type: [Group \(p. 496\)](#) object

## IsTruncated

A flag that indicates whether there are more items to return. If your results were truncated, you can make a subsequent pagination request using the `Marker` request parameter to retrieve more items. Note that IAM might return fewer than the `MaxItems` number of results even when there are more results available. We recommend that you check `IsTruncated` after every call to ensure that you receive all your results.

Type: Boolean

## Marker

When `IsTruncated` is `true`, this element is present and contains the value to use for the `Marker` parameter in a subsequent pagination request.

Type: String

## Users.member.N

A list of users in the group.

Type: Array of [User \(p. 556\)](#) objects

# Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

## NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

## ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

# Examples

## Example

This example illustrates one usage of `GetGroup`.

### Sample Request

```
https://iam.amazonaws.com/?Action=GetGroup
&GroupName=Admins
&Version=2010-05-08
&AUTHPARAMS
```

## Sample Response

```
<GetGroupResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <GetGroupResult>
    <Group>
      <Path>/</Path>
      <GroupName>Admins</GroupName>
      <GroupId>AGPACKCEVSQ6C2EXAMPLE</GroupId>
      <Arn>arn:aws:iam::123456789012:group/Admins</Arn>
    </Group>
    <Users>
      <member>
        <Path>/division_abc/subdivision_xyz/</Path>
        <UserName>Bob</UserName>
        <UserId>AIDACKCEVSQ6C2EXAMPLE</UserId>
        <Arn>
          arn:aws:iam::123456789012:user/division_abc/subdivision_xyz/Bob
        </Arn>
      </member>
      <member>
        <Path>/division_abc/subdivision_xyz/</Path>
        <UserName>Susan</UserName>
        <UserId>AIDACKCEVSQ6C2EXAMPLE</UserId>
        <Arn>
          arn:aws:iam::123456789012:user/division_abc/subdivision_xyz/Susan
        </Arn>
      </member>
    </Users>
    <IsTruncated>false</IsTruncated>
  </GetGroupResult>
  <ResponseMetadata>
    <RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
  </ResponseMetadata>
</GetGroupResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetGroupPolicy

Retrieves the specified inline policy document that is embedded in the specified IAM group.

## Note

Policies returned by this operation are URL-encoded compliant with [RFC 3986](#). You can use a URL decoding method to convert the policy back to plain JSON text. For example, if you use Java, you can use the decode method of the `java.net.URLDecoder` utility class in the Java SDK. Other languages and SDKs provide similar functionality.

An IAM group can also have managed policies attached to it. To retrieve a managed policy document that is attached to a group, use [GetPolicy \(p. 181\)](#) to determine the policy's default version, then use [GetPolicyVersion \(p. 184\)](#) to retrieve the policy document.

For more information about policies, see [Managed policies and inline policies](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### GroupName

The name of the group the policy is associated with.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: Yes

### PolicyName

The name of the policy document to get.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: Yes

## Response Elements

The following elements are returned by the service.

### GroupName

The group the policy is associated with.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [\w+=, .@-]+

#### **PolicyDocument**

The policy document.

IAM stores policies in JSON format. However, resources that were created using AWS CloudFormation templates can be formatted in YAML. AWS CloudFormation always converts a YAML policy to JSON format before submitting it to IAM.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 131072.

Pattern: [\u0009\u000A\u000D\u0020-\u00FF]+

#### **PolicyName**

The name of the policy.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [\w+=, .@-]+

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

#### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

#### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of GetGroupPolicy.

#### Sample Request

```
https://iam.amazonaws.com/?Action=GetGroupPolicy
&GroupName=Admins
&PolicyName=AdminRoot
&AUTHPARAMS
```

## Sample Response

```
<GetGroupPolicyResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <GetGroupPolicyResult>
    <GroupName>Admins</GroupName>
    <PolicyName>AdminRoot</PolicyName>
    <PolicyDocument>
      {"Version": "2012-10-17", "Statement": [{"Effect": "Allow", "Action": "*", "Resource": "*"}]}
    </PolicyDocument>
  </GetGroupPolicyResult>
  <ResponseMetadata>
    <RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
  </ResponseMetadata>
</GetGroupPolicyResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetInstanceProfile

Retrieves information about the specified instance profile, including the instance profile's path, GUID, ARN, and role. For more information about instance profiles, see [About instance profiles](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### InstanceProfileName

The name of the instance profile to get information about.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: Yes

## Response Elements

The following element is returned by the service.

### InstanceProfile

A structure containing details about the instance profile.

Type: [InstanceProfile \(p. 500\)](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of `GetInstanceProfile`.

#### Sample Request

```
https://iam.amazonaws.com/?Action=GetInstanceProfile
&InstanceProfileName=Webserver
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<GetInstanceProfileResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
<GetInstanceProfileResult>
  <InstanceProfile>
    <InstanceProfileId>AIPAD5AR02C5EXAMPLE3G</InstanceProfileId>
    <Roles>
      <member>
        <Path>/application_abc/component_xyz/</Path>
        <Arn>arn:aws:iam::123456789012:role/application_abc/component_xyz/S3Access</Arn>
        <RoleName>S3Access</RoleName>
        <AssumeRolePolicyDocument>
          {"Version":"2012-10-17", "Statement":[{"Effect":"Allow",
          "Principal":["Service":["ec2.amazonaws.com"]], "Action":["sts:AssumeRole"]}]}
```

</AssumeRolePolicyDocument>

```
<CreateDate>2012-05-09T15:45:35Z</CreateDate>
<RoleId>AROACVYKSVTSFEXAMPLE</RoleId>
      </member>
    </Roles>
    <InstanceProfileName>Webserver</InstanceProfileName>
    <Path>/application_abc/component_xyz/</Path>
    <Arn>arn:aws:iam::123456789012:instance-profile/application_abc/component_xyz/
Webserver</Arn>
      <CreateDate>2012-05-09T16:11:10Z</CreateDate>
    </InstanceProfile>
  </GetInstanceProfileResult>
</ResponseMetadata>
  <RequestId>37289fda-99f2-11e1-a4c3-27EXAMPLE804</RequestId>
</ResponseMetadata>
</GetInstanceProfileResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

# GetLoginProfile

Retrieves the user name for the specified IAM user. A login profile is created when you create a password for the user to access the AWS Management Console. If the user does not exist or does not have a password, the operation returns a 404 (NoSuchEntity) error.

If you create an IAM user with access to the console, the `CreateDate` reflects the date you created the initial password for the user.

If you create an IAM user with programmatic access, and then later add a password for the user to access the AWS Management Console, the `CreateDate` reflects the initial password creation date. A user with programmatic access does not have a login profile unless you create a password for the user to access the AWS Management Console.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### UserName

The name of the user whose login profile you want to retrieve.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w+=,.@-]+`

Required: Yes

## Response Elements

The following element is returned by the service.

### LoginProfile

A structure containing the user name and the profile creation date for the user.

Type: [LoginProfile \(p. 503\)](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of GetLoginProfile.

#### Sample Request

```
https://iam.amazonaws.com/?Action=GetLoginProfile
&UserName=Bob
&AUTHPARAMS
```

#### Sample Response

```
<GetLoginProfileResponse>
  <GetLoginProfileResult>
    <LoginProfile>
      <UserName>Bob</UserName>
      <CreateDate>2011-09-19T23:00:56Z</CreateDate>
    </LoginProfile>
  </GetLoginProfileResult>
  <ResponseMetadata>
    <RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
  </ResponseMetadata>
</GetLoginProfileResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetOpenIDConnectProvider

Returns information about the specified OpenID Connect (OIDC) provider resource object in IAM.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### OpenIDConnectProviderArn

The Amazon Resource Name (ARN) of the OIDC provider resource object in IAM to get information for. You can get a list of OIDC provider resource ARNs by using the [ListOpenIDConnectProviders \(p. 265\)](#) operation.

For more information about ARNs, see [Amazon Resource Names \(ARNs\)](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

## Response Elements

The following elements are returned by the service.

### ClientIDList.member.N

A list of client IDs (also known as audiences) that are associated with the specified IAM OIDC provider resource object. For more information, see [CreateOpenIDConnectProvider \(p. 39\)](#).

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 255.

### CreateDate

The date and time when the IAM OIDC provider resource object was created in the AWS account.

Type: Timestamp

### Tags.member.N

A list of tags that are attached to the specified IAM OIDC provider. The returned list of tags is sorted by tag key. For more information about tagging, see [Tagging IAM resources](#) in the *IAM User Guide*.

Type: Array of [Tag \(p. 553\)](#) objects

Array Members: Maximum number of 50 items.

### ThumbprintList.member.N

A list of certificate thumbprints that are associated with the specified IAM OIDC provider resource object. For more information, see [CreateOpenIDConnectProvider \(p. 39\)](#).

Type: Array of strings

Length Constraints: Fixed length of 40.

## Url

The URL that the IAM OIDC provider resource object is associated with. For more information, see [CreateOpenIDConnectProvider \(p. 39\)](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### InvalidInput

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of GetOpenIDConnectProvider.

### Sample Request

```
https://iam.amazonaws.com/?Action=GetOpenIDConnectProvider
&OpenIDConnectProviderArn=arn:aws:iam::123456789012:oidc-provider/example.com
&Version=2010-05-08
&AUTHPARAMS
```

### Sample Response

```
<GetOpenIDConnectProviderResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <GetOpenIDConnectProviderResult>
    <ThumbprintList>
      <member>c3768084dfb3d2b68b7897bf5f565da8eEXAMPLE</member>
    </ThumbprintList>
    <CreateDate>2014-10-09T03:32:51.398Z</CreateDate>
    <ClientIDList>
      <member>my-application-ID</member>
    </ClientIDList>
```

```
<Url>server.example.com</Url>
</GetOpenIDConnectProviderResult>
<ResponseMetadata>
  <RequestId>2c91531b-4f65-11e4-aefa-bfd6aEXAMPLE</RequestId>
</ResponseMetadata>
</GetOpenIDConnectProviderResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetOrganizationsAccessReport

Retrieves the service last accessed data report for AWS Organizations that was previously generated using the [GenerateOrganizationsAccessReport \(p. 133\)](#) operation. This operation retrieves the status of your report job and the report contents.

Depending on the parameters that you passed when you generated the report, the data returned could include different information. For details, see [GenerateOrganizationsAccessReport \(p. 133\)](#).

To call this operation, you must be signed in to the management account in your organization. SCPs must be enabled for your organization root. You must have permissions to perform this operation. For more information, see [Refining permissions using service last accessed data](#) in the *IAM User Guide*.

For each service that principals in an account (root users, IAM users, or IAM roles) could access using SCPs, the operation returns details about the most recent access attempt. If there was no attempt, the service is listed without details about the most recent attempt to access the service. If the operation fails, it returns the reason that it failed.

By default, the list is sorted by service namespace.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### JobId

The identifier of the request generated by the [GenerateOrganizationsAccessReport \(p. 133\)](#) operation.

Type: String

Length Constraints: Fixed length of 36.

Required: Yes

### Marker

Use this parameter only when paginating results and only after you receive a response indicating that the results are truncated. Set it to the value of the `Marker` element in the response that you received to indicate where the next call should start.

Type: String

Length Constraints: Minimum length of 1.

Pattern: `[\u0020-\u00FF]+`

Required: No

### MaxItems

Use this only when paginating results to indicate the maximum number of items you want in the response. If additional items exist beyond the maximum you specify, the `IsTruncated` response element is `true`.

If you do not include this parameter, the number of items defaults to 100. Note that IAM might return fewer results, even when there are more results available. In that case, the `IsTruncated` response element returns `true`, and `Marker` contains a value to include in the subsequent call that tells the service where to continue from.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

#### SortKey

The key that is used to sort the results. If you choose the namespace key, the results are returned in alphabetical order. If you choose the time key, the results are sorted numerically by the date and time.

Type: String

Valid Values: SERVICE\_NAMESPACE\_ASCENDING | SERVICE\_NAMESPACE\_DESCENDING | LAST\_AUTHENTICATED\_TIME\_ASCENDING | LAST\_AUTHENTICATED\_TIME\_DESCENDING

Required: No

## Response Elements

The following elements are returned by the service.

### AccessDetails.member.N

An object that contains details about the most recent attempt to access the service.

Type: Array of [AccessDetail \(p. 477\)](#) objects

### ErrorDetails

Contains information about the reason that the operation failed.

This data type is used as a response element in the [GetOrganizationsAccessReport \(p. 177\)](#), [GetServiceLastAccessedDetails \(p. 198\)](#), and [GetServiceLastAccessedDetailsWithEntities \(p. 203\)](#) operations.

Type: [ErrorDetails \(p. 492\)](#) object

### IsTruncated

A flag that indicates whether there are more items to return. If your results were truncated, you can make a subsequent pagination request using the Marker request parameter to retrieve more items. Note that IAM might return fewer than the MaxItems number of results even when there are more results available. We recommend that you check IsTruncated after every call to ensure that you receive all your results.

Type: Boolean

### JobCompletionDate

The date and time, in [ISO 8601 date-time format](#), when the generated report job was completed or failed.

This field is null if the job is still in progress, as indicated by a job status value of IN\_PROGRESS.

Type: Timestamp

### JobCreationDate

The date and time, in [ISO 8601 date-time format](#), when the report job was created.

Type: Timestamp

### JobStatus

The status of the job.

Type: String

Valid Values: IN\_PROGRESS | COMPLETED | FAILED

### Marker

When IsTruncated is true, this element is present and contains the value to use for the Marker parameter in a subsequent pagination request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 320.

Pattern: [\u0020-\u00FF]+

### NumberOfServicesAccessible

The number of services that the applicable SCPs allow account principals to access.

Type: Integer

### NumberOfServicesNotAccessed

The number of services that account principals are allowed but did not attempt to access.

Type: Integer

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

## Examples

### Example

This example illustrates one usage of GetOrganizationsAccessReport.

### Sample Request

```
https://iam.amazonaws.com/?Action=GetOrganizationsAccessReport
&JobId=examplea-1234-b567-cde8-90fg123abcd4
&Version=2010-05-08
&AUTHPARAMS
```

### Sample Response

```
<IsTruncated>false</IsTruncated>
```

```
<JobCompletionDate>2019-06-18T19:47:35.241Z</JobCompletionDate>
<JobCreationDate>2019-06-18T19:47:31.466Z</JobCreationDate>
<JobStatus>COMPLETED</JobStatus>
<NumberOfServicesAccessible>3</NumberOfServicesAccessible>
<NumberOfServicesNotAccessed>1</NumberOfServicesNotAccessed>
<AccessDetails>
  <member>
    <EntityPath>o-a1b2c3d4e5/r-f6g7h8i9j0example/ou-1a2b3c-
k918m7n6o5example/111122223333</EntityPath>
    <LastAuthenticatedTime>2019-05-25T16:29:52Z</LastAuthenticatedTime>
    <Region>us-west-2</Region>
    <ServiceName>Amazon DynamoDB</ServiceName>
    <ServiceNamespace>dynamodb</ServiceNamespace>
    <TotalAuthenticatedEntities>2</TotalAuthenticatedEntities>
  </member>
  <member>
    <EntityPath>o-a1b2c3d4e5/r-f6g7h8i9j0example/ou-1a2b3c-
k918m7n6o5example/123456789012</EntityPath>
    <LastAuthenticatedTime>2019-06-15T13:12:06Z</LastAuthenticatedTime>
    <Region>us-east-1</Region>
    <ServiceName>AWS Identity and Access Management</ServiceName>
    <ServiceNamespace>iam</ServiceNamespace>
    <TotalAuthenticatedEntities>5</TotalAuthenticatedEntities>
  </member>
  <member>
    <ServiceName>Amazon Simple Storage Service</ServiceName>
    <ServiceNamespace>s3</ServiceNamespace>
    <TotalAuthenticatedEntities>0</TotalAuthenticatedEntities>
  </member>
</AccessDetails>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetPolicy

Retrieves information about the specified managed policy, including the policy's default version and the total number of IAM users, groups, and roles to which the policy is attached. To retrieve the list of the specific users, groups, and roles that the policy is attached to, use [ListEntitiesForPolicy \(p. 237\)](#). This operation returns metadata about the policy. To retrieve the actual policy document for a specific version of the policy, use [GetPolicyVersion \(p. 184\)](#).

This operation retrieves information about managed policies. To retrieve information about an inline policy that is embedded with an IAM user, group, or role, use [GetUserPolicy \(p. 216\)](#), [GetGroupPolicy \(p. 166\)](#), or [GetRolePolicy \(p. 189\)](#).

For more information about policies, see [Managed policies and inline policies](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### PolicyArn

The Amazon Resource Name (ARN) of the managed policy that you want information about.

For more information about ARNs, see [Amazon Resource Names \(ARNs\)](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

## Response Elements

The following element is returned by the service.

### Policy

A structure containing details about the policy.

Type: [Policy \(p. 513\)](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### InvalidInput

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

#### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of GetPolicy.

#### Sample Request

```
https://iam.amazonaws.com/?Action=GetPolicy
&PolicyArn=arn:aws:iam::123456789012:policy/S3-read-only-example-bucket
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<GetPolicyResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <GetPolicyResult>
    <Policy>
      <PolicyName>S3-read-only-example-bucket</PolicyName>
      <Description>Allows read-only access to the example bucket</Description>
      <DefaultVersionId>v1</DefaultVersionId>
      <PolicyId>AGPACKCEVSQ6C2EXAMPLE</PolicyId>
      <Path>/</Path>
      <Arn>arn:aws:iam::123456789012:policy/S3-read-only-example-bucket</Arn>
      <AttachmentCount>9</AttachmentCount>
      <CreateDate>2014-09-15T17:36:14Z</CreateDate>
      <UpdateDate>2014-09-15T20:31:47Z</UpdateDate>
    </Policy>
  </GetPolicyResult>
  <ResponseMetadata>
    <RequestId>684f0917-3d22-11e4-a4a0-cffb9EXAMPLE</RequestId>
  </ResponseMetadata>
</GetPolicyResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# GetPolicyVersion

Retrieves information about the specified version of the specified managed policy, including the policy document.

## Note

Policies returned by this operation are URL-encoded compliant with [RFC 3986](#). You can use a URL decoding method to convert the policy back to plain JSON text. For example, if you use Java, you can use the decode method of the `java.net.URLDecoder` utility class in the Java SDK. Other languages and SDKs provide similar functionality.

To list the available versions for a policy, use [ListPolicyVersions \(p. 281\)](#).

This operation retrieves information about managed policies. To retrieve information about an inline policy that is embedded in a user, group, or role, use [GetUserPolicy \(p. 216\)](#), [GetGroupPolicy \(p. 166\)](#), or [GetRolePolicy \(p. 189\)](#).

For more information about the types of policies, see [Managed policies and inline policies](#) in the *IAM User Guide*.

For more information about managed policy versions, see [Versioning for managed policies](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### PolicyArn

The Amazon Resource Name (ARN) of the managed policy that you want information about.

For more information about ARNs, see [Amazon Resource Names \(ARNs\)](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

### VersionId

Identifies the policy version to retrieve.

This parameter allows (through its [regex pattern](#)) a string of characters that consists of the lowercase letter 'v' followed by one or two digits, and optionally followed by a period '.' and a string of letters and digits.

Type: String

Pattern: `v[1-9][0-9]*(\.[A-Za-z0-9-]*)?`

Required: Yes

## Response Elements

The following element is returned by the service.

## PolicyVersion

A structure containing details about the policy version.

Type: [PolicyVersion \(p. 522\)](#) object

# Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

## InvalidInput

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

## NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

## ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

# Examples

## Example

This example illustrates one usage of GetPolicyVersion.

### Sample Request

```
https://iam.amazonaws.com/?Action=GetPolicyVersion
&PolicyArn=arn:aws:iam::123456789012:policy/S3-read-only-example-bucket
&VersionId=v1
&Version=2010-05-08
&AUTHPARAMS
```

### Sample Response

```
<GetPolicyVersionResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <GetPolicyVersionResult>
    <PolicyVersion>
      <Document>
        {"Version": "2012-10-17", "Statement": [{"Effect": "Allow", "Action": ["s3:Get*", "s3>List*"], "Resource": ["arn:aws:s3:::EXAMPLE-BUCKET", "arn:aws:s3:::EXAMPLE-BUCKET/*"]}]}
      </Document>
      <IsDefaultVersion>true</IsDefaultVersion>
      <VersionId>v1</VersionId>
      <CreateDate>2014-09-15T20:31:47Z</CreateDate>
    </PolicyVersion>
  </GetPolicyVersionResult>
</GetPolicyVersionResponse>
```

```
</GetPolicyVersionResult>
<ResponseMetadata>
  <RequestId>d472f28e-3d23-11e4-a4a0-cffb9EXAMPLE</RequestId>
</ResponseMetadata>
</GetPolicyVersionResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## GetRole

Retrieves information about the specified role, including the role's path, GUID, ARN, and the role's trust policy that grants permission to assume the role. For more information about roles, see [Working with roles](#).

### Note

Policies returned by this operation are URL-encoded compliant with [RFC 3986](#). You can use a URL decoding method to convert the policy back to plain JSON text. For example, if you use Java, you can use the decode method of the `java.net.URLDecoder` utility class in the Java SDK. Other languages and SDKs provide similar functionality.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### RoleName

The name of the IAM role to get information about.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w+=,.@-]+`

Required: Yes

## Response Elements

The following element is returned by the service.

### Role

A structure containing details about the IAM role.

Type: [Role \(p. 527\)](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of GetRole.

#### Sample Request

```
https://iam.amazonaws.com/?Action=GetRole
&RoleName=S3Access
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<GetRoleResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
<GetRoleResult>
  <Role>
    <Path>/application_abc/component_xyz/</Path>
    <Arn>arn:aws:iam::123456789012:role/application_abc/component_xyz/S3Access</Arn>
    <RoleName>S3Access</RoleName>
    <AssumeRolePolicyDocument>
      {"Version": "2012-10-17", "Statement": [{"Effect": "Allow",
      "Principal": {"Service": ["ec2.amazonaws.com"]}, "Action": ["sts:AssumeRole"]}]}
    </AssumeRolePolicyDocument>
    <CreateDate>2012-05-08T23:34:01Z</CreateDate>
    <RoleId>AROADBQP57FF2AEXAMPLE</RoleId>
    <RoleLastUsed>
      <LastUsedDate>2019-11-20T17:09:20Z</LastUsedDate>
      <Region>us-east-1</Region>
    </RoleLastUsed>
  </Role>
</GetRoleResult>
<ResponseMetadata>
  <RequestId>df37e965-9967-11e1-a4c3-270EXAMPLE04</RequestId>
</ResponseMetadata>
</GetRoleResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetRolePolicy

Retrieves the specified inline policy document that is embedded with the specified IAM role.

## Note

Policies returned by this operation are URL-encoded compliant with [RFC 3986](#). You can use a URL decoding method to convert the policy back to plain JSON text. For example, if you use Java, you can use the decode method of the `java.net.URLDecoder` utility class in the Java SDK. Other languages and SDKs provide similar functionality.

An IAM role can also have managed policies attached to it. To retrieve a managed policy document that is attached to a role, use [GetPolicy \(p. 181\)](#) to determine the policy's default version, then use [GetPolicyVersion \(p. 184\)](#) to retrieve the policy document.

For more information about policies, see [Managed policies and inline policies](#) in the *IAM User Guide*.

For more information about roles, see [Using roles to delegate permissions and federate identities](#).

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### PolicyName

The name of the policy document to get.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: Yes

### RoleName

The name of the role associated with the policy.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w+=,.@-]+`

Required: Yes

## Response Elements

The following elements are returned by the service.

### **PolicyDocument**

The policy document.

IAM stores policies in JSON format. However, resources that were created using AWS CloudFormation templates can be formatted in YAML. AWS CloudFormation always converts a YAML policy to JSON format before submitting it to IAM.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 131072.

Pattern: [\u0009\u000A\u000D\u0020-\u00FF]+

### **PolicyName**

The name of the policy.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [\w+=, .@-]+

### **RoleName**

The role the policy is associated with.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [\w+=, .@-]+

## **Errors**

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## **Examples**

### **Example**

This example illustrates one usage of GetRolePolicy.

#### **Sample Request**

```
https://iam.amazonaws.com/?Action=GetRolePolicy
```

```
&PolicyName=S3AccessPolicy
&RoleName=S3Access
&Version=2010-05-08
&AUTHPARAMS
```

## Sample Response

```
<GetRolePolicyResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
<GetRolePolicyResult>
  <PolicyName>S3AccessPolicy</PolicyName>
  <RoleName>S3Access</RoleName>
  <PolicyDocument>
    {"Version":"2012-10-17", "Statement":[{"Effect":"Allow", "Action":["s3:*"], "Resource": ["*"]}]}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetSAMLProvider

Returns the SAML provider metadocument that was uploaded when the IAM SAML provider resource object was created or updated.

**Note**

This operation requires [Signature Version 4](#).

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

**SAMLProviderArn**

The Amazon Resource Name (ARN) of the SAML provider resource object in IAM to get information about.

For more information about ARNs, see [Amazon Resource Names \(ARNs\)](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

## Response Elements

The following elements are returned by the service.

**CreateDate**

The date and time when the SAML provider was created.

Type: Timestamp

**SAMLMetadataDocument**

The XML metadata document that includes information about an identity provider.

Type: String

Length Constraints: Minimum length of 1000. Maximum length of 10000000.

**Tags.member.N**

A list of tags that are attached to the specified IAM SAML provider. The returned list of tags is sorted by tag key. For more information about tagging, see [Tagging IAM resources](#) in the *IAM User Guide*.

Type: Array of [Tag \(p. 553\)](#) objects

Array Members: Maximum number of 50 items.

**ValidUntil**

The expiration date and time for the SAML provider.

Type: Timestamp

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### InvalidInput

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of GetSAMLProvider.

#### Sample Request

```
https://iam.amazonaws.com/?Action=GetSAMLProvider
&Name=arn:aws:iam::123456789012:saml-provider/MyUniversity
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<GetSAMLProviderResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
<GetSAMLProviderResult>
  <CreateDate>2012-05-09T16:27:11Z</CreateDate>
  <ValidUntil>2015-12-31T21:59:59Z</ValidUntil>
  <SAMLMetadataDocument>Pd9fexDssTkRgGNqs...DxptfEs==</SAMLMetadataDocument>
</GetSAMLProviderResult>
<ResponseMetadata>
  <RequestId>29f47818-99f5-11e1-a4c3-27EXAMPLE804</RequestId>
</ResponseMetadata>
</GetSAMLProviderResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetServerCertificate

Retrieves information about the specified server certificate stored in IAM.

For more information about working with server certificates, see [Working with server certificates](#) in the *IAM User Guide*. This topic includes a list of AWS services that can use the server certificates that you manage with IAM.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### **ServerCertificateName**

The name of the server certificate you want to retrieve information about.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: Yes

## Response Elements

The following element is returned by the service.

### **ServerCertificate**

A structure containing details about the server certificate.

Type: [ServerCertificate \(p. 536\)](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of GetServerCertificate.

#### Sample Request

```
https://iam.amazonaws.com/?Action=GetServerCertificate
&ServerCertificateName=ProdServerCert
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<GetServerCertificateResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
<GetServerCertificateResult>
  <ServerCertificate>
    <ServerCertificateMetadata>
      <ServerCertificateName>ProdServerCert</ServerCertificateName>
      <Path>/company/servercerts/</Path>
      <Arn>arn:aws:iam::123456789012:server-certificate/company/servercerts/
ProdServerCert</Arn>
      <UploadDate>2010-05-08T01:02:03.004Z</UploadDate>
      <ServerCertificateId>ASCACKCEVSQ6C2EXAMPLE</ServerCertificateId>
      <Expiration>2012-05-08T01:02:03.004Z</Expiration>
    </ServerCertificateMetadata>
    <CertificateBody>
      -----BEGIN CERTIFICATE-----
MIICdzCCAcECAgIBAgIGANC+Ha2wMA0GCSqGSIb3DQEBBQUAMFMxCzAJBgNVBAYT
A1VTMRMwEQYDVQQKEwpBbWF6b24uY29tMQwwCgYDVQQLEwNBV1MxITAfBgNVBAMT
GEFXUyBmA1pdGVkLUFc3VyYW5jZSBDDQTAefw0w0TAyMDQxNzE5MjdaFw0xMDAy
MDQxNzE5MjdaMF1xCzAJBgNVBAYTA1VTMRMwEQYDVQQKEwpBbWF6b24uY29tMRcw
FQYDVQQLEw5BV1MtRGV2ZWxvcGVyczEVMBMGA1UEAxMMNTdxND10c3ZwYjRtMIGf
MA0GCSqGSIb3DQEBAQUAA4GNADCBiQKBgQCpB/vs0wmT/00td1RqzKjttSBaPjbr
dqwNe9Br0yB08fw2+Ch5oonZYXfGUrT6mkYXH5fQot9HvASrzAKH0596FdJA6DmL
ywdWe10ggk7zFSX01Xv+3vPrJtaYxYo3eRip7w80PMki0v6M0XK8ubcTou0DeJbf
suDqcLnLDxwsvwIDAQABo1cwVTA0BgNVHQ8BAf8EBAMCBaAwFgYDVRO1AQH/BAww
CgYIKwYBBQUHAwIwDAYDVR0TAQH/BAIwADAdBgNVHQ4EFgQULGNaBphBumaKbDRK
CAi0mH8B3mowDQYJKoZIhvcNAQEFBQADgYEauKxhkXaCLGcqDuweKt0/AEw9ZePH
wir0XqsaIK2HZboqrbuebXEGsojK4Ks0WzwgrEynuHJwTn760xe39rSqXWI0Gr0Bax
wFpWHVjTFMKk+tSDG1lssLHyYWWdFFU4AnejRG0RJYNaRHgVTkjHphc5jEhHm0BX
AEaHzTpmEXAMPLE=
      -----END CERTIFICATE-----
    </CertificateBody>
  </ServerCertificate>
</GetServerCertificateResult>
<ResponseMetadata>
  <RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
</ResponseMetadata>
</GetServerCertificateResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetServiceLastAccessedDetails

Retrieves a service last accessed report that was created using the `GenerateServiceLastAccessedDetails` operation. You can use the `JobId` parameter in `GetServiceLastAccessedDetails` to retrieve the status of your report job. When the report is complete, you can retrieve the generated report. The report includes a list of AWS services that the resource (user, group, role, or managed policy) can access.

## Note

Service last accessed data does not use other policy types when determining whether a resource could access a service. These other policy types include resource-based policies, access control lists, AWS Organizations policies, IAM permissions boundaries, and AWS STS assume role policies. It only applies permissions policy logic. For more about the evaluation of policy types, see [Evaluating policies](#) in the *IAM User Guide*.

For each service that the resource could access using permissions policies, the operation returns details about the most recent access attempt. If there was no attempt, the service is listed without details about the most recent attempt to access the service. If the operation fails, the `GetServiceLastAccessedDetails` operation returns the reason that it failed.

The `GetServiceLastAccessedDetails` operation returns a list of services. This list includes the number of entities that have attempted to access the service and the date and time of the last attempt. It also returns the ARN of the following entity, depending on the resource ARN that you used to generate the report:

- **User** – Returns the user ARN that you used to generate the report
- **Group** – Returns the ARN of the group member (user) that last attempted to access the service
- **Role** – Returns the role ARN that you used to generate the report
- **Policy** – Returns the ARN of the user or role that last used the policy to attempt to access the service

By default, the list is sorted by service namespace.

If you specified `ACTION_LEVEL` granularity when you generated the report, this operation returns service and action last accessed data. This includes the most recent access attempt for each tracked action within a service. Otherwise, this operation returns only service data.

For more information about service and action last accessed data, see [Reducing permissions using service last accessed data](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### JobId

The ID of the request generated by the [GenerateServiceLastAccessedDetails \(p. 137\)](#) operation. The `JobId` returned by `GenerateServiceLastAccessedDetail` must be used by the same role within a session, or by the same user when used to call `GetServiceLastAccessedDetail`.

Type: String

Length Constraints: Fixed length of 36.

Required: Yes

### Marker

Use this parameter only when paginating results and only after you receive a response indicating that the results are truncated. Set it to the value of the `Marker` element in the response that you received to indicate where the next call should start.

Type: String

Length Constraints: Minimum length of 1.

Pattern: `[\u0020-\u00FF]+`

Required: No

### MaxItems

Use this only when paginating results to indicate the maximum number of items you want in the response. If additional items exist beyond the maximum you specify, the `IsTruncated` response element is `true`.

If you do not include this parameter, the number of items defaults to 100. Note that IAM might return fewer results, even when there are more results available. In that case, the `IsTruncated` response element returns `true`, and `Marker` contains a value to include in the subsequent call that tells the service where to continue from.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

## Response Elements

The following elements are returned by the service.

### Error

An object that contains details about the reason the operation failed.

Type: [ErrorDetails \(p. 492\)](#) object

### IsTruncated

A flag that indicates whether there are more items to return. If your results were truncated, you can make a subsequent pagination request using the `Marker` request parameter to retrieve more items. Note that IAM might return fewer than the `MaxItems` number of results even when there are more results available. We recommend that you check `IsTruncated` after every call to ensure that you receive all your results.

Type: Boolean

### JobCompletionDate

The date and time, in [ISO 8601 date-time format](#), when the generated report job was completed or failed.

This field is null if the job is still in progress, as indicated by a job status value of `IN_PROGRESS`.

Type: Timestamp

### JobCreationDate

The date and time, in [ISO 8601 date-time format](#), when the report job was created.

Type: Timestamp

#### JobStatus

The status of the job.

Type: String

Valid Values: IN\_PROGRESS | COMPLETED | FAILED

#### JobType

The type of job. Service jobs return information about when each service was last accessed. Action jobs also include information about when tracked actions within the service were last accessed.

Type: String

Valid Values: SERVICE\_LEVEL | ACTION\_LEVEL

#### Marker

When IsTruncated is true, this element is present and contains the value to use for the Marker parameter in a subsequent pagination request.

Type: String

#### ServicesLastAccessed.member.N

A ServiceLastAccessed object that contains details about the most recent attempt to access the service.

Type: Array of [ServiceLastAccessed \(p. 540\)](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

#### InvalidInput

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

#### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

## Examples

### Example

This example illustrates one usage of GetServiceLastAccessedDetails.

#### Sample Request

```
https://iam.amazonaws.com/?Action=GetServiceLastAccessedDetails
&JobId=examplef-1305-c245-eba4-71fe298bcda7
```

&Version=2010-05-08  
&AUTHPARAMS

## Sample Response

```
<IsTruncated>false</IsTruncated>
<JobCompletionDate>2018-10-24T19:47:35.241Z</JobCompletionDate>
<JobCreationDate>2018-10-24T19:47:31.466Z</JobCreationDate>
<JobStatus>COMPLETED</JobStatus>
<ServicesLastAccessed>
  <member>
    <ServiceName>AWS Identity and Access Management</ServiceName>
    <ServiceNamespace>iam</ServiceNamespace>
    <TotalAuthenticatedEntities>0</TotalAuthenticatedEntities>
  </member>
  <member>
    <LastAuthenticated>2018-10-24T19:11:00Z</LastAuthenticated>
    <LastAuthenticatedEntity>arn:aws:iam::123456789012:user/AWSExampleUser01</
    LastAuthenticatedEntity>
    <LastAuthenticatedRegion>us-east-1</LastAuthenticatedRegion>
    <ServiceName>Amazon Simple Storage Service</ServiceName>
    <ServiceNamespace>s3</ServiceNamespace>
    <TotalAuthenticatedEntities>3</TotalAuthenticatedEntities>
    <TrackedActionsLastAccessed>
      <member>
        <ActionName>CreateBucket</ActionName>
        <LastAccessedEntity>arn:aws:iam::123456789012:user/AWSExampleUser01</
        LastAccessedEntity>
        <LastAccessedRegion>us-east-1</LastAccessedRegion>
        <LastAccessedTime>2018-10-24T19:11:00Z</LastAccessedTime>
      </member>
      <member>
        <ActionName>PutBucketAcl</ActionName>
        <LastAccessedEntity></LastAccessedEntity>
        <LastAccessedRegion></LastAccessedRegion>
        <LastAccessedTime></LastAccessedTime>
      </member>
      <member>
        <ActionName>ListBucket</ActionName>
        <LastAccessedEntity>arn:aws:iam::123456789012:user/AWSExampleUser01</
        LastAccessedEntity>
        <LastAccessedRegion>us-east-1</LastAccessedRegion>
        <LastAccessedTime>2018-10-24T19:10:53Z</LastAccessedTime>
      </member>
    </TrackedActionsLastAccessed>
  </member>
</ServicesLastAccessed>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetServiceLastAccessedDetailsWithEntities

After you generate a group or policy report using the `GenerateServiceLastAccessedDetails` operation, you can use the `JobId` parameter in `GetServiceLastAccessedDetailsWithEntities`. This operation retrieves the status of your report job and a list of entities that could have used group or policy permissions to access the specified service.

- **Group** – For a group report, this operation returns a list of users in the group that could have used the group's policies in an attempt to access the service.
- **Policy** – For a policy report, this operation returns a list of entities (users or roles) that could have used the policy in an attempt to access the service.

You can also use this operation for user or role reports to retrieve details about those entities.

If the operation fails, the `GetServiceLastAccessedDetailsWithEntities` operation returns the reason that it failed.

By default, the list of associated entities is sorted by date, with the most recent access listed first.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### JobId

The ID of the request generated by the `GenerateServiceLastAccessedDetails` operation.

Type: String

Length Constraints: Fixed length of 36.

Required: Yes

### Marker

Use this parameter only when paginating results and only after you receive a response indicating that the results are truncated. Set it to the value of the `Marker` element in the response that you received to indicate where the next call should start.

Type: String

Length Constraints: Minimum length of 1.

Pattern: `[\u0020-\u00FF]+`

Required: No

### MaxItems

Use this only when paginating results to indicate the maximum number of items you want in the response. If additional items exist beyond the maximum you specify, the `IsTruncated` response element is `true`.

If you do not include this parameter, the number of items defaults to 100. Note that IAM might return fewer results, even when there are more results available. In that case, the `IsTruncated` response element returns `true`, and `Marker` contains a value to include in the subsequent call that tells the service where to continue from.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

#### ServiceNamespace

The service namespace for an AWS service. Provide the service namespace to learn when the IAM entity last attempted to access the specified service.

To learn the service namespace for a service, see [Actions, resources, and condition keys for AWS services](#) in the *IAM User Guide*. Choose the name of the service to view details for that service. In the first paragraph, find the service prefix. For example, (service prefix: a4b). For more information about service namespaces, see [AWS service namespaces](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [\w-]\*

Required: Yes

## Response Elements

The following elements are returned by the service.

#### EntityDetailsList.member.N

An EntityDetailsList object that contains details about when an IAM entity (user or role) used group or policy permissions in an attempt to access the specified AWS service.

Type: Array of [EntityDetails](#) (p. 489) objects

#### Error

An object that contains details about the reason the operation failed.

Type: [ErrorDetails](#) (p. 492) object

#### IsTruncated

A flag that indicates whether there are more items to return. If your results were truncated, you can make a subsequent pagination request using the Marker request parameter to retrieve more items. Note that IAM might return fewer than the MaxItems number of results even when there are more results available. We recommend that you check IsTruncated after every call to ensure that you receive all your results.

Type: Boolean

#### JobCompletionDate

The date and time, in [ISO 8601 date-time format](#), when the generated report job was completed or failed.

This field is null if the job is still in progress, as indicated by a job status value of IN\_PROGRESS.

Type: Timestamp

#### JobCreationDate

The date and time, in [ISO 8601 date-time format](#), when the report job was created.

Type: Timestamp

#### JobStatus

The status of the job.

Type: String

Valid Values: IN\_PROGRESS | COMPLETED | FAILED

#### Marker

When IsTruncated is true, this element is present and contains the value to use for the Marker parameter in a subsequent pagination request.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

#### InvalidInput

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

#### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

## Examples

### Example

This example illustrates one usage of `GetServiceLastAccessedDetailsWithEntities`.

#### Sample Request

```
https://iam.amazonaws.com/?Action=GetServiceLastAccessedDetailsWithEntities
&JobId=examplefe-1305-c245-eba4-71fe298bcda7
&ServiceNamespace=iam
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<EntityDetailsList>
  <member>
    <EntityInfo>
      <Arn>arn:aws:iam::123456789012:user/AWSExampleUser01</Arn>
      <Id>AIDAEX2EXAMPLEB6IGCDC</Id>
      <Name>AWSExampleUser01</Name>
      <Path>/</Path>
```

```
<Type>USER</Type>
</EntityInfo>
<LastAuthenticated>2018-10-24T19:10:00Z</LastAuthenticated>
</member>
<member>
<EntityInfo>
<Arn>arn:aws:iam::072398337363:role/AWSExampleRole01</Arn>
<Id>AROAEAW2EXAMPLENXSIU4</Id>
<Name>AWSExampleRole01</Name>
<Path>/</Path>
<Type>ROLE</Type>
</EntityInfo>
</member>
</EntityDetailsList>
<IsTruncated>false</IsTruncated>
<JobCompletionDate>2018-10-24T19:47:35.241Z</JobCompletionDate>
<JobCreationDate>2018-10-24T19:47:31.466Z</JobCreationDate>
<JobStatus>COMPLETED</JobStatus>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetServiceLinkedRoleDeletionStatus

Retrieves the status of your service-linked role deletion. After you use [DeleteServiceLinkedRole \(p. 103\)](#) to submit a service-linked role for deletion, you can use the `DeletionTaskId` parameter in `GetServiceLinkedRoleDeletionStatus` to check the status of the deletion. If the deletion fails, this operation returns the reason that it failed, if that information is returned by the service.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### **DeletionTaskId**

The deletion task identifier. This identifier is returned by the [DeleteServiceLinkedRole \(p. 103\)](#) operation in the format `task/aws-service-role/<service-principal-name>/<role-name>/<task-uuid>`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Required: Yes

## Response Elements

The following elements are returned by the service.

### **Reason**

An object that contains details about the reason the deletion failed.

Type: [DeletionTaskFailureReasonType \(p. 488\)](#) object

### **Status**

The status of the deletion.

Type: String

Valid Values: `SUCCEEDED` | `IN_PROGRESS` | `FAILED` | `NOT_STARTED`

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **InvalidInput**

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

#### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

The following example shows how to retrieve the status of the DeletionTaskId service-lined role deletion.

#### Sample Request

```
https://iam.amazonaws.com/?Action=GetServiceLinkedRoleDeletionStatus
&DeletionTaskId=task%2Faws-service-role%2Flex.amazonaws.com%2AWSServiceRoleForLexBots
%2Fec720f7a-c0ba-4838-be33-f72e1873dd52
&Version=2010-05-08
```

### Example

The following example shows the status of the successful DeletionTaskId service-lined role deletion.

#### Sample Response

```
<GetServiceLinkedRoleDeletionStatusResponse xmlns="https://iam.amazonaws.com/
doc/2010-05-08/">
  <GetServiceLinkedRoleDeletionStatusResult>
    <Status>SUCCEEDED</Status>
  </GetServiceLinkedRoleDeletionStatusResult>
  <ResponseMetadata>
    <RequestId>aa9259f4-8297-11e7-9f8f-8b008627ec76</RequestId>
  </ResponseMetadata>
</GetServiceLinkedRoleDeletionStatusResponse>
```

### Example

The following example shows the status of the failed DeletionTaskId service-lined role deletion.

#### Sample Response

```
<GetServiceLinkedRoleDeletionStatusResponse xmlns="https://iam.amazonaws.com/
doc/2010-05-08/">
  <GetServiceLinkedRoleDeletionStatusResult>
    <Status>FAILED</Status>
  </GetServiceLinkedRoleDeletionStatusResult>
  <DeletionTaskFailureReasonType>
    <Reason>role is being used</Reason>
    <RoleUsageList>
      <RoleUsageType>
        <Region>us-east-1</Region>
        <Resources>
          <Resource>arn1</Resource>
          <Resource>arn2</Resource>
        </Resources>
      </RoleUsageType>
    </RoleUsageList>
  </DeletionTaskFailureReasonType>
</GetServiceLinkedRoleDeletionStatusResponse>
```

```
</Resources>
</RoleUsageType>
<RoleUsageType>
  <Region>us-west-2</Region>
  <Resources>
    <Resource>arn3<Resource>
    <Resource>arn4<Resource>
  </Resources>
</RoleUsageType>
</RoleUsageList>
<DeletionTaskFailureReasonType>
<ResponseMetadata>
  <RequestId>aa9259f4-8297-11e7-9f8f-8b008627ec76</RequestId>
</ResponseMetadata>
</GetServiceLinkedRoleDeletionStatusResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## GetSSHPublicKey

Retrieves the specified SSH public key, including metadata about the key.

The SSH public key retrieved by this operation is used only for authenticating the associated IAM user to an CodeCommit repository. For more information about using SSH keys to authenticate to an CodeCommit repository, see [Set up CodeCommit for SSH connections](#) in the *CodeCommit User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### Encoding

Specifies the public key encoding format to use in the response. To retrieve the public key in ssh-rsa format, use SSH. To retrieve the public key in PEM format, use PEM.

Type: String

Valid Values: SSH | PEM

Required: Yes

### SSHPublicKeyId

The unique identifier for the SSH public key.

This parameter allows (through its [regex pattern](#)) a string of characters that can consist of any upper or lowercased letter or digit.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 128.

Pattern: `[\w]+`

Required: Yes

### UserName

The name of the IAM user associated with the SSH public key.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w+=,.@-]+`

Required: Yes

## Response Elements

The following element is returned by the service.

## SSHPublicKey

A structure containing details about the SSH public key.

Type: [SSHPublicKey \(p. 548\)](#) object

# Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

## NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

## UnrecognizedPublicKeyEncoding

The request was rejected because the public key encoding format is unsupported or unrecognized.

HTTP Status Code: 400

# Examples

## Example

This example illustrates one usage of GetSSHPublicKey.

### Sample Request

```
https://iam.amazonaws.com/?Action=GetSSHPublicKey
&Encoding=PEM
&SSHPublicKeyId=APKAEIVFHP46CEEXAMPLE
&UserName=Jane
&Version=2010-05-08
&AUTHPARAMS
```

### Sample Response

```
<GetSSHPublicKeyResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
<GetSSHPublicKeyResult>
  <SSHPublicKey>
    <UploadDate>2015-06-05T20:56:46Z</UploadDate>
    <Fingerprint>7a:1d:ea:9e:b0:80:ac:f8:ec:d8:dc:e6:a7:2c:fc:51</Fingerprint>
    <UserName>Jane</UserName>
    <SSHPublicKeyId>APKAEIVFHP46CEEXAMPLE</SSHPublicKeyId>
    <Status>Active</Status>
    <SSHPublicKeyBody>
      -----BEGIN PUBLIC KEY-----
      MIIBIjANBgkqhkiG9w0BAQEFAAOCAQ8AMIIIBCgKCAQEAsu+Wp09hhmqGTctHI1BE
      SJ/pq4GtAt9JJpIsDnjeB+mLbwnVJLFaaYzzoZuPOVhUc7yHMWjBLmfSEgJKFAH3
      n8m8R9D3UForC0rtKR2jJwAwF03Tp9wgnqzvPtLMnG7uBEuD/nHStanrd6bbBv83
      kDSy5jiuc4yEWtTAEtyp8C8BxFTxHuCQ/sX4IbjtJ8M1IKZ3hjcJ05u6ooWCxZzQ
      hXX1PDniK/RZn0+Y0aJR5umaAv23HAB7qx5H3A6WpyUyzXy0eTo9eAmUrET+JDXZ
      vqHufiDz0/M0Cfb+KV10J0s2AxNtRuIFA1cTq7NF+upTl0V+gK1YJhCvjSuRkJ/
      cwIDAQAB
```

```
-----END PUBLIC KEY-----
</SSHPublicKeyBody>
</SSHPublicKey>
</GetSSHPublicKeyResult>
<ResponseMetadata>
<RequestId>4817ee13-f36d-11e4-97db-33c4eEXAMPLE</RequestId>
</ResponseMetadata>
</GetSSHPublicKeyResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## GetUser

Retrieves information about the specified IAM user, including the user's creation date, path, unique ID, and ARN.

If you do not specify a user name, IAM determines the user name implicitly based on the AWS access key ID used to sign the request to this operation.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### UserName

The name of the user to get information about.

This parameter is optional. If it is not included, it defaults to the user making the request. This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=.,@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: No

## Response Elements

The following element is returned by the service.

### User

A structure containing details about the IAM user.

#### Important

Due to a service issue, password last used data does not include password use from May 3, 2018 22:50 PDT to May 23, 2018 14:08 PDT. This affects [last sign-in](#) dates shown in the IAM console and password last used dates in the [IAM credential report](#), and returned by this operation. If users signed in during the affected time, the password last used date that is returned is the date the user last signed in before May 3, 2018. For users that signed in after May 23, 2018 14:08 PDT, the returned password last used date is accurate.

You can use password last used information to identify unused credentials for deletion. For example, you might delete users who did not sign in to AWS in the last 90 days. In cases like this, we recommend that you adjust your evaluation window to include dates after May 23, 2018. Alternatively, if your users use access keys to access AWS programmatically you can refer to access key last used information because it is accurate for all dates.

Type: [User \(p. 556\)](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of GetUser.

#### Sample Request

```
https://iam.amazonaws.com/?Action= GetUser
&UserName=Bob
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
< GetUserResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  < GetUserResult>
    < User>
      < UserId>AIDACKCEVSQ6C2EXAMPLE</UserId>
      < Path>/division_abc/subdivision_xyz</Path>
      < UserName>Bob</UserName>
      < Arn>arn:aws:iam::123456789012:user/division_abc/subdivision_xyz/Bob</Arn>
      < CreateDate>2013-10-02T17:01:44Z</CreateDate>
      < PasswordLastUsed>2014-10-10T14:37:51Z</PasswordLastUsed>
    </User>
  </ GetUserResult>
  < ResponseMetadata>
    < RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
  </ ResponseMetadata>
</ GetUserResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetUserPolicy

Retrieves the specified inline policy document that is embedded in the specified IAM user.

## Note

Policies returned by this operation are URL-encoded compliant with [RFC 3986](#). You can use a URL decoding method to convert the policy back to plain JSON text. For example, if you use Java, you can use the decode method of the `java.net.URLDecoder` utility class in the Java SDK. Other languages and SDKs provide similar functionality.

An IAM user can also have managed policies attached to it. To retrieve a managed policy document that is attached to a user, use [GetPolicy \(p. 181\)](#) to determine the policy's default version. Then use [GetPolicyVersion \(p. 184\)](#) to retrieve the policy document.

For more information about policies, see [Managed policies and inline policies](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### PolicyName

The name of the policy document to get.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: Yes

### UserName

The name of the user who the policy is associated with.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: Yes

## Response Elements

The following elements are returned by the service.

### PolicyDocument

The policy document.

IAM stores policies in JSON format. However, resources that were created using AWS CloudFormation templates can be formatted in YAML. AWS CloudFormation always converts a YAML policy to JSON format before submitting it to IAM.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 131072.

Pattern: [\u0009\u000A\u000D\u0020-\u00FF]+

#### **PolicyName**

The name of the policy.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [\w+=, .@-]+

#### **UserName**

The user the policy is associated with.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [\w+=, .@-]+

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

#### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

#### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of GetUserPolicy.

#### Sample Request

```
https://iam.amazonaws.com/?Action= GetUserPolicy
&UserName=Bob
&PolicyName=AllAccessPolicy
&AUTHPARAMS
```

## Sample Response

```
< GetUserPolicyResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  < GetUserPolicyResult>
    < UserName>Bob</UserName>
    < PolicyName>AllAccessPolicy</PolicyName>
    < PolicyDocument>
      {"Version": "2012-10-17", "Statement": [{"Effect": "Allow", "Action": "*", "Resource": "*"}]}
    </PolicyDocument>
  </ GetUserPolicyResult>
  < ResponseMetadata>
    < RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
  </ ResponseMetadata>
</ GetUserPolicyResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## ListAccessKeys

Returns information about the access key IDs associated with the specified IAM user. If there is none, the operation returns an empty list.

Although each user is limited to a small number of keys, you can still paginate the results using the `MaxItems` and `Marker` parameters.

If the `UserName` is not specified, the user name is determined implicitly based on the AWS access key ID used to sign the request. If a temporary access key is used, then `UserName` is required. If a long-term key is assigned to the user, then `UserName` is not required. This operation works for access keys under the AWS account. Consequently, you can use this operation to manage AWS account root user credentials even if the AWS account has no associated users.

### **Note**

To ensure the security of your AWS account, the secret access key is accessible only during key and user creation.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### **Marker**

Use this parameter only when paginating results and only after you receive a response indicating that the results are truncated. Set it to the value of the `Marker` element in the response that you received to indicate where the next call should start.

Type: String

Length Constraints: Minimum length of 1.

Pattern: `[\u0020-\u00FF]+`

Required: No

### **MaxItems**

Use this only when paginating results to indicate the maximum number of items you want in the response. If additional items exist beyond the maximum you specify, the `IsTruncated` response element is `true`.

If you do not include this parameter, the number of items defaults to 100. Note that IAM might return fewer results, even when there are more results available. In that case, the `IsTruncated` response element returns `true`, and `Marker` contains a value to include in the subsequent call that tells the service where to continue from.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

### **UserName**

The name of the user.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [\w+=, .@-]+

Required: No

## Response Elements

The following elements are returned by the service.

### AccessKeyMetadata.member.N

A list of objects containing metadata about the access keys.

Type: Array of [AccessKeyMetadata \(p. 483\)](#) objects

### IsTruncated

A flag that indicates whether there are more items to return. If your results were truncated, you can make a subsequent pagination request using the Marker request parameter to retrieve more items. Note that IAM might return fewer than the MaxItems number of results even when there are more results available. We recommend that you check IsTruncated after every call to ensure that you receive all your results.

Type: Boolean

### Marker

When IsTruncated is true, this element is present and contains the value to use for the Marker parameter in a subsequent pagination request.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of ListAccessKeys.

## Sample Request

```
https://iam.amazonaws.com/?Action=ListAccessKeys
&UserName=Bob
&Version=2010-05-08
&AUTHPARAMS
```

## Sample Response

```
<ListAccessKeysResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ListAccessKeysResult>
    <UserName>Bob</UserName>
    <AccessKeyMetadata>
      <member>
        <UserName>Bob</UserName>
        <AccessKeyId>AKIA1234567890EXAMPLE</AccessKeyId>
        <Status>Active</Status>
        <CreateDate>2016-12-03T18:53:41Z</CreateDate>
      </member>
      <member>
        <UserName>Susan</UserName>
        <AccessKeyId>AKIA2345678901EXAMPLE</AccessKeyId>
        <Status>Inactive</Status>
        <CreateDate>2017-03-25T20:38:14Z</CreateDate>
      </member>
    </AccessKeyMetadata>
    <IsTruncated>false</IsTruncated>
  </ListAccessKeysResult>
  <ResponseMetadata>
    <RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
  </ResponseMetadata>
</ListAccessKeysResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## ListAccountAliases

Lists the account alias associated with the AWS account (Note: you can have only one). For information about using an AWS account alias, see [Using an alias for your AWS account ID](#) in the *IAM User Guide*.

### Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

#### Marker

Use this parameter only when paginating results and only after you receive a response indicating that the results are truncated. Set it to the value of the `Marker` element in the response that you received to indicate where the next call should start.

Type: String

Length Constraints: Minimum length of 1.

Pattern: `[\u0020-\u00FF]+`

Required: No

#### MaxItems

Use this only when paginating results to indicate the maximum number of items you want in the response. If additional items exist beyond the maximum you specify, the `IsTruncated` response element is `true`.

If you do not include this parameter, the number of items defaults to 100. Note that IAM might return fewer results, even when there are more results available. In that case, the `IsTruncated` response element returns `true`, and `Marker` contains a value to include in the subsequent call that tells the service where to continue from.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

## Response Elements

The following elements are returned by the service.

#### AccountAliases.member.N

A list of aliases associated with the account. AWS supports only one alias per account.

Type: Array of strings

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: `^ [a-zA-Z0-9](([a-zA-Z0-9]|-|(?|-))*[a-zA-Z0-9])? $`

#### IsTruncated

A flag that indicates whether there are more items to return. If your results were truncated, you can make a subsequent pagination request using the `Marker` request parameter to retrieve more items.

Note that IAM might return fewer than the `MaxItems` number of results even when there are more results available. We recommend that you check `IsTruncated` after every call to ensure that you receive all your results.

Type: Boolean

#### Marker

When `IsTruncated` is `true`, this element is present and contains the value to use for the `Marker` parameter in a subsequent pagination request.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

#### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of `ListAccountAliases`.

#### Sample Request

```
https://iam.amazonaws.com/?Action=ListAccountAliases
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<ListAccountAliasesResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
<ListAccountAliasesResult>
  <IsTruncated>false</IsTruncated>
  <AccountAliases>
    <member>example-corporation</member>
  </AccountAliases>
</ListAccountAliasesResult>
<ResponseMetadata>
  <RequestId>c5a076e9-f1b0-11df-8fbe-45274EXAMPLE</RequestId>
</ResponseMetadata>
</ListAccountAliasesResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListAttachedGroupPolicies

Lists all managed policies that are attached to the specified IAM group.

An IAM group can also have inline policies embedded with it. To list the inline policies for a group, use [ListGroupPolicies \(p. 241\)](#). For information about policies, see [Managed policies and inline policies](#) in the *IAM User Guide*.

You can paginate the results using the `MaxItems` and `Marker` parameters. You can use the `PathPrefix` parameter to limit the list of policies to only those matching the specified path prefix. If there are no policies attached to the specified group (or none that match the specified path prefix), the operation returns an empty list.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### GroupName

The name (friendly name, not ARN) of the group to list attached policies for.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: Yes

### Marker

Use this parameter only when paginating results and only after you receive a response indicating that the results are truncated. Set it to the value of the `Marker` element in the response that you received to indicate where the next call should start.

Type: String

Length Constraints: Minimum length of 1.

Pattern: `[\u0020-\u00FF]+`

Required: No

### MaxItems

Use this only when paginating results to indicate the maximum number of items you want in the response. If additional items exist beyond the maximum you specify, the `IsTruncated` response element is `true`.

If you do not include this parameter, the number of items defaults to 100. Note that IAM might return fewer results, even when there are more results available. In that case, the `IsTruncated` response element returns `true`, and `Marker` contains a value to include in the subsequent call that tells the service where to continue from.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

#### **PathPrefix**

The path prefix for filtering the results. This parameter is optional. If it is not included, it defaults to a slash (/), listing all policies.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of either a forward slash (/) by itself or a string that must begin and end with forward slashes. In addition, it can contain any ASCII character from the ! (\u0021) through the DEL character (\u007F), including most punctuation characters, digits, and upper and lowercased letters.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: ((/[A-Za-z0-9\.,\+@=\_-]+)\*)/

Required: No

## Response Elements

The following elements are returned by the service.

#### **AttachedPolicies.member.N**

A list of the attached policies.

Type: Array of [AttachedPolicy \(p. 486\)](#) objects

#### **IsTruncated**

A flag that indicates whether there are more items to return. If your results were truncated, you can make a subsequent pagination request using the `Marker` request parameter to retrieve more items. Note that IAM might return fewer than the `MaxItems` number of results even when there are more results available. We recommend that you check `IsTruncated` after every call to ensure that you receive all your results.

Type: Boolean

#### **Marker**

When `IsTruncated` is `true`, this element is present and contains the value to use for the `Marker` parameter in a subsequent pagination request.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

#### **InvalidInput**

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of ListAttachedGroupPolicies.

#### Sample Request

```
https://iam.amazonaws.com/?Action=ListAttachedGroupPolicies
&GroupName=ReadOnlyUsers
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<ListAttachedGroupPoliciesResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ListAttachedGroupPoliciesResult>
    <AttachedPolicies>
      <member>
        <PolicyName>ReadOnlyAccess</PolicyName>
        <PolicyArn>arn:aws:iam::aws:policy/ReadOnlyAccess</PolicyArn>
      </member>
    </AttachedPolicies>
    <IsTruncated>false</IsTruncated>
  </ListAttachedGroupPoliciesResult>
  <ResponseMetadata>
    <RequestId>710f2d3f-3df1-11e4-9d0d-6f969EXAMPLE</RequestId>
  </ResponseMetadata>
</ListAttachedGroupPoliciesResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

# ListAttachedRolePolicies

Lists all managed policies that are attached to the specified IAM role.

An IAM role can also have inline policies embedded with it. To list the inline policies for a role, use [ListRolePolicies \(p. 284\)](#). For information about policies, see [Managed policies and inline policies](#) in the [IAM User Guide](#).

You can paginate the results using the `MaxItems` and `Marker` parameters. You can use the `PathPrefix` parameter to limit the list of policies to only those matching the specified path prefix. If there are no policies attached to the specified role (or none that match the specified path prefix), the operation returns an empty list.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### Marker

Use this parameter only when paginating results and only after you receive a response indicating that the results are truncated. Set it to the value of the `Marker` element in the response that you received to indicate where the next call should start.

Type: String

Length Constraints: Minimum length of 1.

Pattern: [\u0020-\u00FF]+

Required: No

### MaxItems

Use this only when paginating results to indicate the maximum number of items you want in the response. If additional items exist beyond the maximum you specify, the `IsTruncated` response element is `true`.

If you do not include this parameter, the number of items defaults to 100. Note that IAM might return fewer results, even when there are more results available. In that case, the `IsTruncated` response element returns `true`, and `Marker` contains a value to include in the subsequent call that tells the service where to continue from.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

### PathPrefix

The path prefix for filtering the results. This parameter is optional. If it is not included, it defaults to a slash (/), listing all policies.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of either a forward slash (/) by itself or a string that must begin and end with forward slashes. In addition, it can contain any ASCII character from the ! (\u0021) through the DEL character (\u007F), including most punctuation characters, digits, and upper and lowercased letters.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: ((/[A-Za-z0-9\.,\+@\=-\_-]+)\*)/

Required: No

#### **RoleName**

The name (friendly name, not ARN) of the role to list attached policies for.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w+=,.@-]+`

Required: Yes

## Response Elements

The following elements are returned by the service.

#### **AttachedPolicies.member.N**

A list of the attached policies.

Type: Array of [AttachedPolicy \(p. 486\)](#) objects

#### **IsTruncated**

A flag that indicates whether there are more items to return. If your results were truncated, you can make a subsequent pagination request using the `Marker` request parameter to retrieve more items. Note that IAM might return fewer than the `MaxItems` number of results even when there are more results available. We recommend that you check `IsTruncated` after every call to ensure that you receive all your results.

Type: Boolean

#### **Marker**

When `IsTruncated` is `true`, this element is present and contains the value to use for the `Marker` parameter in a subsequent pagination request.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

#### **InvalidInput**

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of ListAttachedRolePolicies.

#### Sample Request

```
https://iam.amazonaws.com/?Action=ListAttachedRolePolicies
&RoleName=ReadOnlyRole
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<ListAttachedRolePoliciesResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ListAttachedRolePoliciesResult>
    <AttachedPolicies>
      <member>
        <PolicyName>ReadOnlyAccess</PolicyName>
        <PolicyArn>arn:aws:iam::aws:policy/ReadOnlyAccess</PolicyArn>
      </member>
    </AttachedPolicies>
    <IsTruncated>false</IsTruncated>
  </ListAttachedRolePoliciesResult>
  <ResponseMetadata>
    <RequestId>9a3b490d-3ea5-11e4-9d0d-6f969EXAMPLE</RequestId>
  </ResponseMetadata>
</ListAttachedRolePoliciesResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

# ListAttachedUserPolicies

Lists all managed policies that are attached to the specified IAM user.

An IAM user can also have inline policies embedded with it. To list the inline policies for a user, use [ListUserPolicies \(p. 314\)](#). For information about policies, see [Managed policies and inline policies](#) in the [IAM User Guide](#).

You can paginate the results using the `MaxItems` and `Marker` parameters. You can use the `PathPrefix` parameter to limit the list of policies to only those matching the specified path prefix. If there are no policies attached to the specified group (or none that match the specified path prefix), the operation returns an empty list.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### Marker

Use this parameter only when paginating results and only after you receive a response indicating that the results are truncated. Set it to the value of the `Marker` element in the response that you received to indicate where the next call should start.

Type: String

Length Constraints: Minimum length of 1.

Pattern: [\u0020-\u00FF]+

Required: No

### MaxItems

Use this only when paginating results to indicate the maximum number of items you want in the response. If additional items exist beyond the maximum you specify, the `IsTruncated` response element is `true`.

If you do not include this parameter, the number of items defaults to 100. Note that IAM might return fewer results, even when there are more results available. In that case, the `IsTruncated` response element returns `true`, and `Marker` contains a value to include in the subsequent call that tells the service where to continue from.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

### PathPrefix

The path prefix for filtering the results. This parameter is optional. If it is not included, it defaults to a slash (/), listing all policies.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of either a forward slash (/) by itself or a string that must begin and end with forward slashes. In addition, it can contain any ASCII character from the ! (\u0021) through the DEL character (\u007F), including most punctuation characters, digits, and upper and lowercased letters.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: ((/[A-Za-z0-9\.,\+@\=-\_-]+)\*)/

Required: No

#### **UserName**

The name (friendly name, not ARN) of the user to list attached policies for.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w+=,.@-]+`

Required: Yes

## Response Elements

The following elements are returned by the service.

#### **AttachedPolicies.member.N**

A list of the attached policies.

Type: Array of [AttachedPolicy \(p. 486\)](#) objects

#### **IsTruncated**

A flag that indicates whether there are more items to return. If your results were truncated, you can make a subsequent pagination request using the `Marker` request parameter to retrieve more items. Note that IAM might return fewer than the `MaxItems` number of results even when there are more results available. We recommend that you check `IsTruncated` after every call to ensure that you receive all your results.

Type: Boolean

#### **Marker**

When `IsTruncated` is `true`, this element is present and contains the value to use for the `Marker` parameter in a subsequent pagination request.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

#### **InvalidInput**

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of ListAttachedUserPolicies.

#### Sample Request

```
https://iam.amazonaws.com/?Action=ListAttachedUserPolicies
&UserName=Alice
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<ListAttachedUserPoliciesResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ListAttachedUserPoliciesResult>
    <AttachedPolicies>
      <member>
        <PolicyName>AdministratorAccess</PolicyName>
        <PolicyArn>arn:aws:iam::aws:policy/AdministratorAccess</PolicyArn>
      </member>
    </AttachedPolicies>
    <IsTruncated>false</IsTruncated>
  </ListAttachedUserPoliciesResult>
  <ResponseMetadata>
    <RequestId>75980e78-3ea6-11e4-9d0d-6f969EXAMPLE</RequestId>
  </ResponseMetadata>
</ListAttachedUserPoliciesResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

# ListEntitiesForPolicy

Lists all IAM users, groups, and roles that the specified managed policy is attached to.

You can use the optional `EntityFilter` parameter to limit the results to a particular type of entity (users, groups, or roles). For example, to list only the roles that are attached to the specified policy, set `EntityFilter` to `Role`.

You can paginate the results using the `MaxItems` and `Marker` parameters.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### **EntityFilter**

The entity type to use for filtering the results.

For example, when `EntityFilter` is `Role`, only the roles that are attached to the specified policy are returned. This parameter is optional. If it is not included, all attached entities (users, groups, and roles) are returned. The argument for this parameter must be one of the valid values listed below.

Type: String

Valid Values: `User` | `Role` | `Group` | `LocalManagedPolicy` | `AWSManagedPolicy`

Required: No

### **Marker**

Use this parameter only when paginating results and only after you receive a response indicating that the results are truncated. Set it to the value of the `Marker` element in the response that you received to indicate where the next call should start.

Type: String

Length Constraints: Minimum length of 1.

Pattern: `[\u0020-\u00FF]+`

Required: No

### **MaxItems**

Use this only when paginating results to indicate the maximum number of items you want in the response. If additional items exist beyond the maximum you specify, the `IsTruncated` response element is `true`.

If you do not include this parameter, the number of items defaults to 100. Note that IAM might return fewer results, even when there are more results available. In that case, the `IsTruncated` response element returns `true`, and `Marker` contains a value to include in the subsequent call that tells the service where to continue from.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

### **PathPrefix**

The path prefix for filtering the results. This parameter is optional. If it is not included, it defaults to a slash (/), listing all entities.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of either a forward slash (/) by itself or a string that must begin and end with forward slashes. In addition, it can contain any ASCII character from the ! (\u0021) through the DEL character (\u007F), including most punctuation characters, digits, and upper and lowercased letters.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: (\u002F)|(\\u002F[\u0021-\u007F]+\u002F)

Required: No

### **PolicyArn**

The Amazon Resource Name (ARN) of the IAM policy for which you want the versions.

For more information about ARNs, see [Amazon Resource Names \(ARNs\)](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

### **PolicyUsageFilter**

The policy usage method to use for filtering the results.

To list only permissions policies, set PolicyUsageFilter to `PermissionsPolicy`. To list only the policies used to set permissions boundaries, set the value to `PermissionsBoundary`.

This parameter is optional. If it is not included, all policies are returned.

Type: String

Valid Values: `PermissionsPolicy` | `PermissionsBoundary`

Required: No

## **Response Elements**

The following elements are returned by the service.

### **IsTruncated**

A flag that indicates whether there are more items to return. If your results were truncated, you can make a subsequent pagination request using the `Marker` request parameter to retrieve more items. Note that IAM might return fewer than the `MaxItems` number of results even when there are more results available. We recommend that you check `IsTruncated` after every call to ensure that you receive all your results.

Type: Boolean

### Marker

When `IsTruncated` is `true`, this element is present and contains the value to use for the `Marker` parameter in a subsequent pagination request.

Type: String

### PolicyGroups.member.N

A list of IAM groups that the policy is attached to.

Type: Array of [PolicyGroup \(p. 519\)](#) objects

### PolicyRoles.member.N

A list of IAM roles that the policy is attached to.

Type: Array of [PolicyRole \(p. 520\)](#) objects

### PolicyUsers.member.N

A list of IAM users that the policy is attached to.

Type: Array of [PolicyUser \(p. 521\)](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### InvalidInput

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of `ListEntitiesForPolicy`.

### Sample Request

```
https://iam.amazonaws.com/?Action=ListEntitiesForPolicy
&PolicyArn=arn:aws:iam::123456789012:policy/EC2-Devs
&Version=2010-05-08
```

&amp;AUTHPARAMS

## Sample Response

```
<ListEntitiesForPolicyResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ListEntitiesForPolicyResult>
    <PolicyRoles>
      <member>
        <RoleName>DevRole</RoleName>
      </member>
    </PolicyRoles>
    <PolicyGroups>
      <member>
        <GroupName>Dev</GroupName>
      </member>
    </PolicyGroups>
    <IsTruncated>false</IsTruncated>
    <PolicyUsers>
      <member>
        <UserName>Alice</UserName>
      </member>
      <member>
        <UserName>Bob</UserName>
      </member>
    </PolicyUsers>
  </ListEntitiesForPolicyResult>
  <ResponseMetadata>
    <RequestId>eb358e22-9d1f-11e4-93eb-190ecEXAMPLE</RequestId>
  </ResponseMetadata>
</ListEntitiesForPolicyResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListGroupPolicies

Lists the names of the inline policies that are embedded in the specified IAM group.

An IAM group can also have managed policies attached to it. To list the managed policies that are attached to a group, use [ListAttachedGroupPolicies \(p. 225\)](#). For more information about policies, see [Managed policies and inline policies](#) in the *IAM User Guide*.

You can paginate the results using the `MaxItems` and `Marker` parameters. If there are no inline policies embedded with the specified group, the operation returns an empty list.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### GroupName

The name of the group to list policies for.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: Yes

### Marker

Use this parameter only when paginating results and only after you receive a response indicating that the results are truncated. Set it to the value of the `Marker` element in the response that you received to indicate where the next call should start.

Type: String

Length Constraints: Minimum length of 1.

Pattern: `[\u0020-\u00FF]+`

Required: No

### MaxItems

Use this only when paginating results to indicate the maximum number of items you want in the response. If additional items exist beyond the maximum you specify, the `IsTruncated` response element is `true`.

If you do not include this parameter, the number of items defaults to 100. Note that IAM might return fewer results, even when there are more results available. In that case, the `IsTruncated` response element returns `true`, and `Marker` contains a value to include in the subsequent call that tells the service where to continue from.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

## Response Elements

The following elements are returned by the service.

### **IsTruncated**

A flag that indicates whether there are more items to return. If your results were truncated, you can make a subsequent pagination request using the `Marker` request parameter to retrieve more items. Note that IAM might return fewer than the `MaxItems` number of results even when there are more results available. We recommend that you check `IsTruncated` after every call to ensure that you receive all your results.

Type: Boolean

### **Marker**

When `IsTruncated` is `true`, this element is present and contains the value to use for the `Marker` parameter in a subsequent pagination request.

Type: String

### **PolicyNames.member.N**

A list of policy names.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of `ListGroupPolicies`.

## Sample Request

```
https://iam.amazonaws.com/?Action=ListGroupPolicies
&GroupName=Admins
&AUTHPARAMS
```

## Sample Response

```
<ListGroupPoliciesResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ListGroupPoliciesResult>
    <PolicyNames>
      <member>AdminRoot</member>
      <member>KeyPolicy</member>
    </PolicyNames>
    <IsTruncated>false</IsTruncated>
  </ListGroupPoliciesResult>
  <ResponseMetadata>
    <RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
  </ResponseMetadata>
</ListGroupPoliciesResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListGroups

Lists the IAM groups that have the specified path prefix.

You can paginate the results using the `MaxItems` and `Marker` parameters.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### Marker

Use this parameter only when paginating results and only after you receive a response indicating that the results are truncated. Set it to the value of the `Marker` element in the response that you received to indicate where the next call should start.

Type: String

Length Constraints: Minimum length of 1.

Pattern: [\u0020-\u00FF]+

Required: No

### MaxItems

Use this only when paginating results to indicate the maximum number of items you want in the response. If additional items exist beyond the maximum you specify, the `IsTruncated` response element is `true`.

If you do not include this parameter, the number of items defaults to 100. Note that IAM might return fewer results, even when there are more results available. In that case, the `IsTruncated` response element returns `true`, and `Marker` contains a value to include in the subsequent call that tells the service where to continue from.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

### PathPrefix

The path prefix for filtering the results. For example, the prefix `/division_abc/` `subdivision_xyz/` gets all groups whose path starts with `/division_abc/subdivision_xyz/`.

This parameter is optional. If it is not included, it defaults to a slash (/), listing all groups. This parameter allows (through its [regex pattern](#)) a string of characters consisting of either a forward slash (/) by itself or a string that must begin and end with forward slashes. In addition, it can contain any ASCII character from the ! (\u0021) through the DEL character (\u007F), including most punctuation characters, digits, and upper and lowercased letters.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: \u002F[\u0021-\u007F]\*

Required: No

## Response Elements

The following elements are returned by the service.

### **Groups.member.N**

A list of groups.

Type: Array of [Group \(p. 496\)](#) objects

### **IsTruncated**

A flag that indicates whether there are more items to return. If your results were truncated, you can make a subsequent pagination request using the `Marker` request parameter to retrieve more items. Note that IAM might return fewer than the `MaxItems` number of results even when there are more results available. We recommend that you check `IsTruncated` after every call to ensure that you receive all your results.

Type: Boolean

### **Marker**

When `IsTruncated` is `true`, this element is present and contains the value to use for the `Marker` parameter in a subsequent pagination request.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of `ListGroups`.

#### Sample Request

```
https://iam.amazonaws.com/?Action=ListGroups
&PathPrefix=/division_abc/subdivision_xyz/
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<ListGroupsResponse>
  <ListGroupsResult>
    <Groups>
      <member>
```

```
<Path>/division_abc/subdivision_xyz/</Path>
<GroupName>Admins</GroupName>
<GroupId>AGPACKCEVSQ6C2EXAMPLE</GroupId>
<Arn>arn:aws:iam::123456789012:group/Admins</Arn>
</member>
<member>
  <Path>/division_abc/subdivision_xyz/product_1234/engineering/
  </Path>
  <GroupName>Test</GroupName>
  <GroupId>AGP2MAB8DPLSRHEXAMPLE</GroupId>
  <Arn>arn:aws:iam::123456789012:group
    /division_abc/subdivision_xyz/product_1234/engineering/Test</Arn>
</member>
<member>
  <Path>/division_abc/subdivision_xyz/product_1234/</Path>
  <GroupName>Managers</GroupName>
  <GroupId>AGPI0DR4TAW7CSEXAMPLE</GroupId>
  <Arn>arn:aws:iam::123456789012
    :group/division_abc/subdivision_xyz/product_1234/Managers</Arn>
</member>
</Groups>
<IsTruncated>false</IsTruncated>
</ListGroupsResult>
<ResponseMetadata>
  <RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
</ResponseMetadata>
</ListGroupsResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## ListGroupsForUser

Lists the IAM groups that the specified IAM user belongs to.

You can paginate the results using the `MaxItems` and `Marker` parameters.

### Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

#### Marker

Use this parameter only when paginating results and only after you receive a response indicating that the results are truncated. Set it to the value of the `Marker` element in the response that you received to indicate where the next call should start.

Type: String

Length Constraints: Minimum length of 1.

Pattern: [\u0020-\u00FF]+

Required: No

#### MaxItems

Use this only when paginating results to indicate the maximum number of items you want in the response. If additional items exist beyond the maximum you specify, the `IsTruncated` response element is `true`.

If you do not include this parameter, the number of items defaults to 100. Note that IAM might return fewer results, even when there are more results available. In that case, the `IsTruncated` response element returns `true`, and `Marker` contains a value to include in the subsequent call that tells the service where to continue from.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

#### UserName

The name of the user to list groups for.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [\w+=,.@-]+

Required: Yes

### Response Elements

The following elements are returned by the service.

## Groups.member.N

A list of groups.

Type: Array of [Group \(p. 496\)](#) objects

## IsTruncated

A flag that indicates whether there are more items to return. If your results were truncated, you can make a subsequent pagination request using the `Marker` request parameter to retrieve more items. Note that IAM might return fewer than the `MaxItems` number of results even when there are more results available. We recommend that you check `IsTruncated` after every call to ensure that you receive all your results.

Type: Boolean

## Marker

When `IsTruncated` is `true`, this element is present and contains the value to use for the `Marker` parameter in a subsequent pagination request.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of `ListGroupsForUser`.

### Sample Request

```
https://iam.amazonaws.com/?Action=ListGroupsForUser
&UserName=Bob
&Version=2010-05-08
&AUTHPARAMS
```

### Sample Response

```
<ListGroupsForUserResponse>
  <ListGroupsForUserResult>
```

```
<Groups>
  <member>
    <Path>/</Path>
    <GroupName>Admins</GroupName>
    <GroupId>AGPACKCEVSQ6C2EXAMPLE</GroupId>
    <Arn>arn:aws:iam::123456789012:group/Admins</Arn>
  </member>
</Groups>
<IsTruncated>false</IsTruncated>
</ListGroupsForUserResult>
<ResponseMetadata>
  <RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
</ResponseMetadata>
</ListGroupsForUserResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListInstanceProfiles

Lists the instance profiles that have the specified path prefix. If there are none, the operation returns an empty list. For more information about instance profiles, see [About instance profiles](#).

## Note

IAM resource-listing operations return a subset of the available attributes for the resource. For example, this operation does not return tags, even though they are an attribute of the returned object. To view all of the information for an instance profile, see [GetInstanceProfile \(p. 169\)](#).

You can paginate the results using the `MaxItems` and `Marker` parameters.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### Marker

Use this parameter only when paginating results and only after you receive a response indicating that the results are truncated. Set it to the value of the `Marker` element in the response that you received to indicate where the next call should start.

Type: String

Length Constraints: Minimum length of 1.

Pattern: [\\u0020-\\u00FF]+

Required: No

### MaxItems

Use this only when paginating results to indicate the maximum number of items you want in the response. If additional items exist beyond the maximum you specify, the `IsTruncated` response element is `true`.

If you do not include this parameter, the number of items defaults to 100. Note that IAM might return fewer results, even when there are more results available. In that case, the `IsTruncated` response element returns `true`, and `Marker` contains a value to include in the subsequent call that tells the service where to continue from.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

### PathPrefix

The path prefix for filtering the results. For example, the prefix `/application_abc/component_xyz/` gets all instance profiles whose path starts with `/application_abc/component_xyz/`.

This parameter is optional. If it is not included, it defaults to a slash (/), listing all instance profiles. This parameter allows (through its [regex pattern](#)) a string of characters consisting of either a forward slash (/) by itself or a string that must begin and end with forward slashes. In addition, it can contain any ASCII character from the ! (\u0021) through the DEL character (\u007F), including most punctuation characters, digits, and upper and lowercased letters.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: \u002F[\u0021-\u007F]\*

Required: No

## Response Elements

The following elements are returned by the service.

### InstanceProfiles.member.N

A list of instance profiles.

Type: Array of [InstanceProfile \(p. 500\)](#) objects

### IsTruncated

A flag that indicates whether there are more items to return. If your results were truncated, you can make a subsequent pagination request using the Marker request parameter to retrieve more items. Note that IAM might return fewer than the MaxItems number of results even when there are more results available. We recommend that you check IsTruncated after every call to ensure that you receive all your results.

Type: Boolean

### Marker

When IsTruncated is true, this element is present and contains the value to use for the Marker parameter in a subsequent pagination request.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of ListInstanceProfiles.

### Sample Request

```
https://iam.amazonaws.com/?Action=ListInstanceProfiles
&MaxItems=100
&PathPrefix=/application_abc/
```

&Version=2010-05-08  
&AUTHPARAMS

## Sample Response

```
<ListInstanceProfilesResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
<ListInstanceProfilesResult>
  <IsTruncated>false</IsTruncated>
  <InstanceProfiles>
    <member>
      <Arn>arn:aws:iam::123456789012:instance-profile/application_abc/component_xyz/Database</Arn>
      <CreateDate>2012-05-09T16:27:03Z</CreateDate>
      <InstanceProfileId>AIPA1234567890EXAMPLE</InstanceProfileId>
      <InstanceProfileName>Database</InstanceProfileName>
      <Path>/</Path>,
      <Roles>
        <member>
          <Arn>arn:aws:iam::123456789012:role/ec2instancerole-MyADFTSTestServer</Arn>
          <AssumeRolePolicyDocument>{ ... JSON POLICY DOCUMENT HERE ... }</AssumeRolePolicyDocument>
          <CreateDate>2016-04-27T21:18:27Z</CreateDate>
          <Path>/</Path>
          <RoleId>AROA1234567890EXAMPLE</RoleId>
          <RoleName>ec2instancerole-MyADFTSTestServer</RoleName>
        </member>
      </Roles>
    </member>
    <member>
      <Arn>arn:aws:iam::123456789012:instance-profile/application_abc/component_xyz/Webserver</Arn>
      <CreateDate>2012-05-09T16:27:11Z</CreateDate>
      <InstanceProfileId>AIPA2345678901EXAMPLE</InstanceProfileId>
      <InstanceProfileName>Webserver</InstanceProfileName>
      <Path>/application_abc/component_xyz/</Path>
      <Roles/>
    </member>
  </InstanceProfiles>
</ListInstanceProfilesResult>
<ResponseMetadata>
  <RequestId>fd74fa8d-99f3-11e1-a4c3-27EXAMPLE804</RequestId>
</ResponseMetadata>
</ListInstanceProfilesResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListInstanceProfilesForRole

Lists the instance profiles that have the specified associated IAM role. If there are none, the operation returns an empty list. For more information about instance profiles, go to [About instance profiles](#).

You can paginate the results using the `MaxItems` and `Marker` parameters.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### Marker

Use this parameter only when paginating results and only after you receive a response indicating that the results are truncated. Set it to the value of the `Marker` element in the response that you received to indicate where the next call should start.

Type: String

Length Constraints: Minimum length of 1.

Pattern: `[\u0020-\u00FF]+`

Required: No

### MaxItems

Use this only when paginating results to indicate the maximum number of items you want in the response. If additional items exist beyond the maximum you specify, the `IsTruncated` response element is `true`.

If you do not include this parameter, the number of items defaults to 100. Note that IAM might return fewer results, even when there are more results available. In that case, the `IsTruncated` response element returns `true`, and `Marker` contains a value to include in the subsequent call that tells the service where to continue from.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

### RoleName

The name of the role to list instance profiles for.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w+=,.@-]+`

Required: Yes

## Response Elements

The following elements are returned by the service.

### **InstanceProfiles.member.N**

A list of instance profiles.

Type: Array of [InstanceProfile \(p. 500\)](#) objects

### **IsTruncated**

A flag that indicates whether there are more items to return. If your results were truncated, you can make a subsequent pagination request using the `Marker` request parameter to retrieve more items. Note that IAM might return fewer than the `MaxItems` number of results even when there are more results available. We recommend that you check `IsTruncated` after every call to ensure that you receive all your results.

Type: Boolean

### **Marker**

When `IsTruncated` is `true`, this element is present and contains the value to use for the `Marker` parameter in a subsequent pagination request.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of `ListInstanceProfilesForRole`.

### Sample Request

```
https://iam.amazonaws.com/?Action=ListInstanceProfilesForRole
&MaxItems=100
&RoleName=S3Access
&Version=2010-05-08
&AUTHPARAMS
```

## Sample Response

```
<ListInstanceProfilesForRoleResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
<ListInstanceProfilesForRoleResult>
<IsTruncated>false</IsTruncated>
<InstanceProfiles>
  <member>
    <Id>AIPACZLS2EYYXMEXAMPLE</Id>
    <Roles>
      <member>
        <Path>/application_abc/component_xyz/</Path>
        <Arn>arn:aws:iam::123456789012:role/application_abc/component_xyz/S3Access</Arn>
        <RoleName>S3Access</RoleName>
        <AssumeRolePolicyDocument>
          {"Version": "2012-10-17", "Statement": [{"Effect": "Allow", "Principal": {"Service": ["ec2.amazonaws.com"]}, "Action": ["sts:AssumeRole"]}]}
```

```
</AssumeRolePolicyDocument>
<CreateDate>2012-05-09T15:45:35Z</CreateDate>
<RoleId>AROACSVTSZYK3EXAMPLE</RoleId>
```

```
</member>
</Roles>
<InstanceProfileName>Webserver</InstanceProfileName>
<Path>/application_abc/component_xyz/</Path>
<Arn>arn:aws:iam::123456789012:instance-profile/application_abc/component_xyz/
```

```
Webserver</Arn>
<CreateDate>2012-05-09T16:27:11Z</CreateDate>
```

```
</member>
</InstanceProfiles>
</ListInstanceProfilesForRoleResult>
<ResponseMetadata>
  <RequestId>6a8c3992-99f4-11e1-a4c3-27EXAMPLE804</RequestId>
</ResponseMetadata>
</ListInstanceProfilesForRoleResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListInstanceProfileTags

Lists the tags that are attached to the specified IAM instance profile. The returned list of tags is sorted by tag key. For more information about tagging, see [Tagging IAM resources](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### InstanceProfileName

The name of the IAM instance profile whose tags you want to see.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: Yes

### Marker

Use this parameter only when paginating results and only after you receive a response indicating that the results are truncated. Set it to the value of the `Marker` element in the response that you received to indicate where the next call should start.

Type: String

Length Constraints: Minimum length of 1.

Pattern: `[\u0020-\u00FF]+`

Required: No

### MaxItems

Use this only when paginating results to indicate the maximum number of items you want in the response. If additional items exist beyond the maximum you specify, the `IsTruncated` response element is `true`.

If you do not include this parameter, the number of items defaults to 100. Note that IAM might return fewer results, even when there are more results available. In that case, the `IsTruncated` response element returns `true`, and `Marker` contains a value to include in the subsequent call that tells the service where to continue from.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

## Response Elements

The following elements are returned by the service.

### **IsTruncated**

A flag that indicates whether there are more items to return. If your results were truncated, you can make a subsequent pagination request using the `Marker` request parameter to retrieve more items. Note that IAM might return fewer than the `MaxItems` number of results even when there are more results available. We recommend that you check `IsTruncated` after every call to ensure that you receive all your results.

Type: Boolean

### **Marker**

When `IsTruncated` is `true`, this element is present and contains the value to use for the `Marker` parameter in a subsequent pagination request.

Type: String

### **Tags.member.N**

The list of tags that are currently attached to the IAM instance profile. Each tag consists of a key name and an associated value. If no tags are attached to the specified resource, the response contains an empty list.

Type: Array of [Tag \(p. 553\)](#) objects

Array Members: Maximum number of 50 items.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

The following example is formatted with line breaks for legibility.

This example shows how to list the tags attached to an IAM instance profile whose name is `Webserver`.

### Sample Request

```
POST / HTTP/1.1
Host: https://iam.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.11.143 Python/3.6.1 Linux/3.2.45-0.6.wd.865.49.315.metal1.x86_64
botocore/1.7.1
```

```
X-Amz-Date: 20170929T182447Z
Authorization: <auth details>
Content-Length: 55
Content-Type: application/x-www-form-urlencoded

Action=ListInstanceProfileTags&Version=2010-05-08&InstanceProfileName=Webserver
```

## Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE
Content-Type: text/xml
Content-Length: 484
Date: Fri, 29 Sep 2017 18:24:47 GMT

<ListInstanceProfileTagsResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ListInstanceProfileTagsResult>
    <IsTruncated>false</IsTruncated>
    <Tags>
      <member>
        <Key>Cost-Center</Key>
        <Value>12345</Value>
      </member>
      <member>
        <Key>Team</Key>
        <Value>Engineering</Value>
      </member>
    </Tags>
  </ListInstanceProfileTagsResult>
  <ResponseMetadata>
    <RequestId>EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE</RequestId>
  </ResponseMetadata>
</ListInstanceProfileTagsResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## ListMFADevices

Lists the MFA devices for an IAM user. If the request includes a IAM user name, then this operation lists all the MFA devices associated with the specified user. If you do not specify a user name, IAM determines the user name implicitly based on the AWS access key ID signing the request for this operation.

You can paginate the results using the `MaxItems` and `Marker` parameters.

### Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

#### Marker

Use this parameter only when paginating results and only after you receive a response indicating that the results are truncated. Set it to the value of the `Marker` element in the response that you received to indicate where the next call should start.

Type: String

Length Constraints: Minimum length of 1.

Pattern: [\u0020-\u00FF]+

Required: No

#### MaxItems

Use this only when paginating results to indicate the maximum number of items you want in the response. If additional items exist beyond the maximum you specify, the `IsTruncated` response element is `true`.

If you do not include this parameter, the number of items defaults to 100. Note that IAM might return fewer results, even when there are more results available. In that case, the `IsTruncated` response element returns `true`, and `Marker` contains a value to include in the subsequent call that tells the service where to continue from.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

#### UserName

The name of the user whose MFA devices you want to list.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [\w+=,.@-]+

Required: No

## Response Elements

The following elements are returned by the service.

### **IsTruncated**

A flag that indicates whether there are more items to return. If your results were truncated, you can make a subsequent pagination request using the `Marker` request parameter to retrieve more items. Note that IAM might return fewer than the `MaxItems` number of results even when there are more results available. We recommend that you check `IsTruncated` after every call to ensure that you receive all your results.

Type: Boolean

### **Marker**

When `IsTruncated` is `true`, this element is present and contains the value to use for the `Marker` parameter in a subsequent pagination request.

Type: String

### **MFADevices.member.N**

A list of MFA devices.

Type: Array of [MFADevice \(p. 507\)](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of `ListMFADevices`.

#### Sample Request

```
https://iam.amazonaws.com/?Action=ListMFADevices
&UserName=Bob
&Version=2010-05-08
&AUTHPARAMS
```

## Sample Response

```
<ListMFADevicesResponse>
  <ListMFADevicesResult>
    <MFADevices>
      <member>
        <UserName>Bob</UserName>
        <SerialNumber>R1234</SerialNumber>
      </member>
    </MFADevices>
    <IsTruncated>false</IsTruncated>
  </ListMFADevicesResult>
  <ResponseMetadata>
    <RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
  </ResponseMetadata>
</ListMFADevicesResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListMFADeviceTags

Lists the tags that are attached to the specified IAM virtual multi-factor authentication (MFA) device. The returned list of tags is sorted by tag key. For more information about tagging, see [Tagging IAM resources](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### Marker

Use this parameter only when paginating results and only after you receive a response indicating that the results are truncated. Set it to the value of the `Marker` element in the response that you received to indicate where the next call should start.

Type: String

Length Constraints: Minimum length of 1.

Pattern: `[\u0020-\u00FF]+`

Required: No

### MaxItems

Use this only when paginating results to indicate the maximum number of items you want in the response. If additional items exist beyond the maximum you specify, the `IsTruncated` response element is `true`.

If you do not include this parameter, the number of items defaults to 100. Note that IAM might return fewer results, even when there are more results available. In that case, the `IsTruncated` response element returns `true`, and `Marker` contains a value to include in the subsequent call that tells the service where to continue from.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

### SerialNumber

The unique identifier for the IAM virtual MFA device whose tags you want to see. For virtual MFA devices, the serial number is the same as the ARN.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 9. Maximum length of 256.

Pattern: `[\w+=/:,.@-]+`

Required: Yes

## Response Elements

The following elements are returned by the service.

### **IsTruncated**

A flag that indicates whether there are more items to return. If your results were truncated, you can make a subsequent pagination request using the `Marker` request parameter to retrieve more items. Note that IAM might return fewer than the `MaxItems` number of results even when there are more results available. We recommend that you check `IsTruncated` after every call to ensure that you receive all your results.

Type: Boolean

### **Marker**

When `IsTruncated` is `true`, this element is present and contains the value to use for the `Marker` parameter in a subsequent pagination request.

Type: String

### **Tags.member.N**

The list of tags that are currently attached to the virtual MFA device. Each tag consists of a key name and an associated value. If no tags are attached to the specified resource, the response contains an empty list.

Type: Array of [Tag \(p. 553\)](#) objects

Array Members: Maximum number of 50 items.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **InvalidInput**

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

The following example is formatted with line breaks for legibility.

The following example shows how to list the tags attached to an MFA device named `taggedrole`.

## Sample Request

```
POST / HTTP/1.1
Host: https://iam.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.11.143 Python/3.6.1 Linux/3.2.45-0.6.wd.865.49.315.metal1.x86_64
    botocore/1.7.1
X-Amz-Date: 20170926T201509Z
Authorization: <auth details>
Content-Length: 58
Content-Type: application/x-www-form-urlencoded
Action=ListMFADeviceTags&Version=2010-05-08&SerialNumber=arn:aws:iam::123456789012:mfa/
ExampleName
```

## Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE
Content-Type: text/xml
Content-Length: 447
Date: Tue, 26 Sep 2017 20:15:09 GMT

<ListMFADeviceTagsResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ListMFADeviceTagsResult>
    <IsTruncated>false</IsTruncated>
    <Tags>
      <member>
        <Key>Dept</Key>
        <Value>Accounting</Value>
      </member>
      <member>
        <Key>Cost Center</Key>
        <Value>12345</Value>
      </member>
    </Tags>
  </ListMFADeviceTagsResult>
  <ResponseMetadata>
    <RequestId>EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE</RequestId>
  </ResponseMetadata>
</ListMFADeviceTagsResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListOpenIDConnectProviders

Lists information about the IAM OpenID Connect (OIDC) provider resource objects defined in the AWS account.

## Note

IAM resource-listing operations return a subset of the available attributes for the resource. For example, this operation does not return tags, even though they are an attribute of the returned object. To view all of the information for an OIDC provider, see [GetOpenIDConnectProvider \(p. 174\)](#).

## Response Elements

The following element is returned by the service.

### OpenIDConnectProviderList.member.N

The list of IAM OIDC provider resource objects defined in the AWS account.

Type: Array of [OpenIDConnectProviderListEntry \(p. 508\)](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of ListOpenIDConnectProviders.

#### Sample Request

```
https://iam.amazonaws.com/?Action=ListOpenIDConnectProviders
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<ListOpenIDConnectProvidersResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ListOpenIDConnectProvidersResult>
    <OpenIDConnectProviderList>
      <member>
        <Arn>arn:aws:iam::123456789012:oidc-provider/server.example.com</Arn>
      </member>
      <member>
        <Arn>arn:aws:iam::123456789012:oidc-provider/server.example.org</Arn>
      </member>
    </OpenIDConnectProviderList>
  </ListOpenIDConnectProvidersResult>
</ListOpenIDConnectProvidersResponse>
```

```
</OpenIDConnectProviderList>
</ListOpenIDConnectProvidersResult>
<ResponseMetadata>
  <RequestId>de2c0228-4f63-11e4-aefa-bfd6aEXAMPLE</RequestId>
</ResponseMetadata>
</ListOpenIDConnectProvidersResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListOpenIDConnectProviderTags

Lists the tags that are attached to the specified OpenID Connect (OIDC)-compatible identity provider. The returned list of tags is sorted by tag key. For more information, see [About web identity federation](#).

For more information about tagging, see [Tagging IAM resources](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### Marker

Use this parameter only when paginating results and only after you receive a response indicating that the results are truncated. Set it to the value of the `Marker` element in the response that you received to indicate where the next call should start.

Type: String

Length Constraints: Minimum length of 1.

Pattern: `[\u0020-\u00FF]+`

Required: No

### MaxItems

Use this only when paginating results to indicate the maximum number of items you want in the response. If additional items exist beyond the maximum you specify, the `IsTruncated` response element is `true`.

If you do not include this parameter, the number of items defaults to 100. Note that IAM might return fewer results, even when there are more results available. In that case, the `IsTruncated` response element returns `true`, and `Marker` contains a value to include in the subsequent call that tells the service where to continue from.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

### OpenIDConnectProviderArn

The ARN of the OpenID Connect (OIDC) identity provider whose tags you want to see.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

## Response Elements

The following elements are returned by the service.

### **IsTruncated**

A flag that indicates whether there are more items to return. If your results were truncated, you can make a subsequent pagination request using the `Marker` request parameter to retrieve more items. Note that IAM might return fewer than the `MaxItems` number of results even when there are more results available. We recommend that you check `IsTruncated` after every call to ensure that you receive all your results.

Type: Boolean

### **Marker**

When `IsTruncated` is `true`, this element is present and contains the value to use for the `Marker` parameter in a subsequent pagination request.

Type: String

### **Tags.member.N**

The list of tags that are currently attached to the OpenID Connect (OIDC) identity provider. Each tag consists of a key name and an associated value. If no tags are attached to the specified resource, the response contains an empty list.

Type: Array of [Tag \(p. 553\)](#) objects

Array Members: Maximum number of 50 items.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **InvalidInput**

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

The following example is formatted with line breaks for legibility.

This example shows how to list the tags that are attached to an OIDC identity provider whose ARN is `arn:aws:iam::123456789012:oidc-provider/GoogleProvider`.

## Sample Request

```
POST / HTTP/1.1
Host: https://iam.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.11.143 Python/3.6.1 Linux/3.2.45-0.6.wd.865.49.315.meta11.x86_64
    botocore/1.7.1
X-Amz-Date: 20170929T182447Z
Authorization: <auth details>
Content-Length: 55
Content-Type: application/x-www-form-urlencoded

Action=ListOpenIDConnectProviderTags&Version=2010-05-08&OpenIDConnectProviderArn=arn:aws:iam::123456789012:provider/GoogleProvider
```

## Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE
Content-Type: text/xml
Content-Length: 484
Date: Fri, 29 Sep 2017 18:24:47 GMT

<ListOpenIDConnectProviderTagsResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ListOpenIDConnectProviderTagsResult>
    <IsTruncated>false</IsTruncated>
    <Tags>
      <member>
        <Key>Dept</Key>
        <Value>12345</Value>
      </member>
      <member>
        <Key>Team</Key>
        <Value>Accounting</Value>
      </member>
    </Tags>
  </ListOpenIDConnectProviderTagsResult>
  <ResponseMetadata>
    <RequestId>EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE</RequestId>
  </ResponseMetadata>
</ListOpenIDConnectProviderTagsResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## ListPolicies

Lists all the managed policies that are available in your AWS account, including your own customer-defined managed policies and all AWS managed policies.

You can filter the list of policies that is returned using the optional `OnlyAttached`, `Scope`, and `PathPrefix` parameters. For example, to list only the customer managed policies in your AWS account, set `Scope` to `Local`. To list only AWS managed policies, set `Scope` to `AWS`.

You can paginate the results using the `MaxItems` and `Marker` parameters.

For more information about managed policies, see [Managed policies and inline policies](#) in the *IAM User Guide*.

### **Note**

IAM resource-listing operations return a subset of the available attributes for the resource. For example, this operation does not return tags, even though they are an attribute of the returned object. To view all of the information for a customer managed policy, see [GetPolicy \(p. 181\)](#).

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### **Marker**

Use this parameter only when paginating results and only after you receive a response indicating that the results are truncated. Set it to the value of the `Marker` element in the response that you received to indicate where the next call should start.

Type: String

Length Constraints: Minimum length of 1.

Pattern: `[\u0020-\u00FF]+`

Required: No

### **MaxItems**

Use this only when paginating results to indicate the maximum number of items you want in the response. If additional items exist beyond the maximum you specify, the `IsTruncated` response element is `true`.

If you do not include this parameter, the number of items defaults to 100. Note that IAM might return fewer results, even when there are more results available. In that case, the `IsTruncated` response element returns `true`, and `Marker` contains a value to include in the subsequent call that tells the service where to continue from.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

### **OnlyAttached**

A flag to filter the results to only the attached policies.

When `OnlyAttached` is `true`, the returned list contains only the policies that are attached to an IAM user, group, or role. When `OnlyAttached` is `false`, or when the parameter is not included, all policies are returned.

Type: Boolean

Required: No

#### **PathPrefix**

The path prefix for filtering the results. This parameter is optional. If it is not included, it defaults to a slash (/), listing all policies. This parameter allows (through its [regex pattern](#)) a string of characters consisting of either a forward slash (/) by itself or a string that must begin and end with forward slashes. In addition, it can contain any ASCII character from the ! (\u0021) through the DEL character (\u007F), including most punctuation characters, digits, and upper and lowercased letters.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: ((/[A-Za-z0-9\.\,\+\@=\_-]+)\*)/

Required: No

#### **PolicyUsageFilter**

The policy usage method to use for filtering the results.

To list only permissions policies, set PolicyUsageFilter to PermissionsPolicy. To list only the policies used to set permissions boundaries, set the value to PermissionsBoundary.

This parameter is optional. If it is not included, all policies are returned.

Type: String

Valid Values: PermissionsPolicy | PermissionsBoundary

Required: No

#### **Scope**

The scope to use for filtering the results.

To list only AWS managed policies, set Scope to AWS. To list only the customer managed policies in your AWS account, set Scope to Local.

This parameter is optional. If it is not included, or if it is set to All, all policies are returned.

Type: String

Valid Values: All | AWS | Local

Required: No

## Response Elements

The following elements are returned by the service.

#### **IsTruncated**

A flag that indicates whether there are more items to return. If your results were truncated, you can make a subsequent pagination request using the Marker request parameter to retrieve more items. Note that IAM might return fewer than the MaxItems number of results even when there are more results available. We recommend that you check IsTruncated after every call to ensure that you receive all your results.

Type: Boolean

#### Marker

When `IsTruncated` is `true`, this element is present and contains the value to use for the `Marker` parameter in a subsequent pagination request.

Type: String

#### Policies.member.N

A list of policies.

Type: Array of [Policy \(p. 513\)](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

#### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of `ListPolicies`.

#### Sample Request

```
https://iam.amazonaws.com/?Action=ListPolicies
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<ListPoliciesResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ListPoliciesResult>
    <IsTruncated>true</IsTruncated>
    <Marker>EXAMPLEkakv9BCuUNFDtxWSyfzetYwEx2ADc8dnzf vERF5S6YMvXKx41t6gC1/eeaCX3Jo94/bKqezEAg8TEVS
99EKFLxm3jtbpl25FDWEXAMPLE
    </Marker>
    <Policies>
      <member>
        <Arn>arn:aws:iam::123456789012:policy/ExamplePolicy</Arn>
        <AttachmentCount>2</AttachmentCount>
        <CreateDate>2014-09-15T17:36:14Z</CreateDate>
        <DefaultVersionId>v1</DefaultVersionId>
        <IsAttachable>true</IsAttachable>
        <Path>/</Path>
        <PermissionsBoundaryUsageCount>0</PermissionsBoundaryUsageCount>
        <PolicyId>AGPACKCEVSQ6C2EXAMPLE</PolicyId>
        <PolicyName>ExamplePolicy</PolicyName>
        <UpdateDate>2014-09-15T20:31:47Z</UpdateDate>
```

```
</member>
<member>
  <Arn>arn:aws:iam::aws:policy/PowerUserAccess</Arn>
  <AttachmentCount>0</AttachmentCount>
  <CreateDate>2014-08-21T20:25:01Z</CreateDate>
  <DefaultVersionId>v1</DefaultVersionId>
  <IsAttachable>true</IsAttachable>
  <Path>/</Path>
  <PermissionsBoundaryUsageCount>0</PermissionsBoundaryUsageCount>
  <PolicyId>AGPACKCEVSQ6C2EXAMPLE</PolicyId>
  <PolicyName>PowerUserAccess</PolicyName>
  <UpdateDate>2014-08-21T20:25:01Z</UpdateDate>
</member>
<member>
  <Arn>arn:aws:iam::aws:policy/AdministratorAccess</Arn>
  <AttachmentCount>1</AttachmentCount>
  <CreateDate>2014-08-21T20:11:25Z</CreateDate>
  <DefaultVersionId>v1</DefaultVersionId>
  <IsAttachable>true</IsAttachable>
  <Path>/</Path>
  <PermissionsBoundaryUsageCount>1</PermissionsBoundaryUsageCount>
  <PolicyId>AGPACKCEVSQ6C2EXAMPLE</PolicyId>
  <PolicyName>AdministratorAccess</PolicyName>
  <UpdateDate>2014-08-21T20:11:25Z</UpdateDate>
</member>
<member>
  <Arn>arn:aws:iam::aws:policy/ReadOnlyAccess</Arn>
  <AttachmentCount>6</AttachmentCount>
  <CreateDate>2014-08-21T20:31:44Z</CreateDate>
  <DefaultVersionId>v1</DefaultVersionId>
  <IsAttachable>true</IsAttachable>
  <Path>/</Path>
  <PermissionsBoundaryUsageCount>2</PermissionsBoundaryUsageCount>
  <PolicyId>AGPACKCEVSQ6C2EXAMPLE</PolicyId>
  <PolicyName>ReadOnlyAccess</PolicyName>
  <UpdateDate>2014-08-21T20:31:44Z</UpdateDate>
</member>
</Policies>
</ListPoliciesResult>
<ResponseMetadata>
  <RequestId>6207e832-3eb7-11e4-9d0d-6f969EXAMPLE</RequestId>
</ResponseMetadata>
</ListPoliciesResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListPoliciesGrantingServiceAccess

Retrieves a list of policies that the IAM identity (user, group, or role) can use to access each specified service.

## Note

This operation does not use other policy types when determining whether a resource could access a service. These other policy types include resource-based policies, access control lists, AWS Organizations policies, IAM permissions boundaries, and AWS STS assume role policies. It only applies permissions policy logic. For more about the evaluation of policy types, see [Evaluating policies](#) in the *IAM User Guide*.

The list of policies returned by the operation depends on the ARN of the identity that you provide.

- **User** – The list of policies includes the managed and inline policies that are attached to the user directly. The list also includes any additional managed and inline policies that are attached to the group to which the user belongs.
- **Group** – The list of policies includes only the managed and inline policies that are attached to the group directly. Policies that are attached to the group's user are not included.
- **Role** – The list of policies includes only the managed and inline policies that are attached to the role.

For each managed policy, this operation returns the ARN and policy name. For each inline policy, it returns the policy name and the entity to which it is attached. Inline policies do not have an ARN. For more information about these policy types, see [Managed policies and inline policies](#) in the *IAM User Guide*.

Policies that are attached to users and roles as permissions boundaries are not returned. To view which managed policy is currently used to set the permissions boundary for a user or role, use the [GetUser](#) (p. 213) or [GetRole](#) (p. 187) operations.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 563).

### Arn

The ARN of the IAM identity (user, group, or role) whose policies you want to list.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

### Marker

Use this parameter only when paginating results and only after you receive a response indicating that the results are truncated. Set it to the value of the `Marker` element in the response that you received to indicate where the next call should start.

Type: String

Length Constraints: Minimum length of 1.

Pattern: `[\u0020-\u00FF]+`

Required: No

### **ServiceNamespaces.member.N**

The service namespace for the AWS services whose policies you want to list.

To learn the service namespace for a service, see [Actions, resources, and condition keys for AWS services](#) in the *IAM User Guide*. Choose the name of the service to view details for that service. In the first paragraph, find the service prefix. For example, (service prefix: a4b). For more information about service namespaces, see [AWS service namespaces](#) in the *AWS General Reference*.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 200 items.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [\w-]\*

Required: Yes

## Response Elements

The following elements are returned by the service.

### **IsTruncated**

A flag that indicates whether there are more items to return. If your results were truncated, you can make a subsequent pagination request using the `Marker` request parameter to retrieve more items. We recommend that you check `IsTruncated` after every call to ensure that you receive all your results.

Type: Boolean

### **Marker**

When `IsTruncated` is `true`, this element is present and contains the value to use for the `Marker` parameter in a subsequent pagination request.

Type: String

### **PoliciesGrantingServiceAccess.member.N**

A `ListPoliciesGrantingServiceAccess` object that contains details about the permissions policies attached to the specified identity (user, group, or role).

Type: Array of [ListPoliciesGrantingServiceAccessEntry](#) (p. 502) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 565).

### **InvalidInput**

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

## Examples

### Example

This example illustrates one usage of ListPoliciesGrantingServiceAccess.

#### Sample Request

```
https://iam.amazonaws.com/?Action=ListPoliciesGrantingServiceAccess
&Arn=arn:aws:iam::123456789012:user/ExampleUser01
&ServiceNamespace.member.1=iam
&ServiceNamespace.member.2=ec2
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<IsTruncated>false</IsTruncated>
<PoliciesGrantingServiceAccess>
  <member>
    <Policies>
      <member>
        <PolicyArn>arn:aws:iam::123456789012:policy/ExampleIamPolicy</PolicyArn>
        <PolicyName>ExampleIamPolicy</PolicyName>
        <PolicyType>MANAGED</PolicyType>
      </member>
      <member>
        <EntityName>AWSExampleGroup1</EntityName>
        <EntityType>GROUP</EntityType>
        <PolicyName>policygen-AWSExampleGroup1-201810241414</PolicyName>
        <PolicyType>INLINE</PolicyType>
      </member>
    </Policies>
    <ServiceNamespace>iam</ServiceNamespace>
  </member>
  <member>
    <Policies>
      <member>
        <PolicyArn>arn:aws:iam::123456789012:policy/ExampleEc2Policy</PolicyArn>
        <PolicyName>ExampleEc2Policy</PolicyName>
        <PolicyType>MANAGED</PolicyType>
      </member>
    </Policies>
    <ServiceNamespace>ec2</ServiceNamespace>
  </member>
</PoliciesGrantingServiceAccess>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## ListPolicyTags

Lists the tags that are attached to the specified IAM customer managed policy. The returned list of tags is sorted by tag key. For more information about tagging, see [Tagging IAM resources](#) in the *IAM User Guide*.

### Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

#### Marker

Use this parameter only when paginating results and only after you receive a response indicating that the results are truncated. Set it to the value of the `Marker` element in the response that you received to indicate where the next call should start.

Type: String

Length Constraints: Minimum length of 1.

Pattern: [\\u0020-\\u00FF]+

Required: No

#### MaxItems

Use this only when paginating results to indicate the maximum number of items you want in the response. If additional items exist beyond the maximum you specify, the `IsTruncated` response element is `true`.

If you do not include this parameter, the number of items defaults to 100. Note that IAM might return fewer results, even when there are more results available. In that case, the `IsTruncated` response element returns `true`, and `Marker` contains a value to include in the subsequent call that tells the service where to continue from.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

#### PolicyArn

The ARN of the IAM customer managed policy whose tags you want to see.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

### Response Elements

The following elements are returned by the service.

### **IsTruncated**

A flag that indicates whether there are more items to return. If your results were truncated, you can make a subsequent pagination request using the `Marker` request parameter to retrieve more items. Note that IAM might return fewer than the `MaxItems` number of results even when there are more results available. We recommend that you check `IsTruncated` after every call to ensure that you receive all your results.

Type: Boolean

### **Marker**

When `IsTruncated` is `true`, this element is present and contains the value to use for the `Marker` parameter in a subsequent pagination request.

Type: String

### **Tags.member.N**

The list of tags that are currently attached to the IAM customer managed policy. Each tag consists of a key name and an associated value. If no tags are attached to the specified resource, the response contains an empty list.

Type: Array of [Tag \(p. 553\)](#) objects

Array Members: Maximum number of 50 items.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **InvalidInput**

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

The following example is formatted with line breaks for legibility.

This example shows how to list the tags that are attached to an IAM customer managed policy whose ARN is `arn:aws:iam::123456789012:policy/UsersManageOwnCredentials`.

## Sample Request

```
POST / HTTP/1.1
Host: https://iam.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.11.143 Python/3.6.1 Linux/3.2.45-0.6.wd.865.49.315.meta11.x86_64
botocore/1.7.1
X-Amz-Date: 20170929T182447Z
Authorization: <auth details>
Content-Length: 55
Content-Type: application/x-www-form-urlencoded

Action=ListPolicyTags&Version=2010-05-08&PolicyArn=arn:aws:iam::123456789012:policy/
UsersManageOwnCredentials
```

## Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE
Content-Type: text/xml
Content-Length: 484
Date: Fri, 29 Sep 2017 18:24:47 GMT

<ListPolicyTagsResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ListPolicyTagsResult>
    <IsTruncated>false</IsTruncated>
    <Tags>
      <member>
        <Key>Dept</Key>
        <Value>12345</Value>
      </member>
      <member>
        <Key>Team</Key>
        <Value>Accounting</Value>
      </member>
    </Tags>
  </ListPolicyTagsResult>
  <ResponseMetadata>
    <RequestId>EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE</RequestId>
  </ResponseMetadata>
</ListPolicyTagsResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListPolicyVersions

Lists information about the versions of the specified managed policy, including the version that is currently set as the policy's default version.

For more information about managed policies, see [Managed policies and inline policies](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### Marker

Use this parameter only when paginating results and only after you receive a response indicating that the results are truncated. Set it to the value of the `Marker` element in the response that you received to indicate where the next call should start.

Type: String

Length Constraints: Minimum length of 1.

Pattern: [\u0020-\u00FF]+

Required: No

### MaxItems

Use this only when paginating results to indicate the maximum number of items you want in the response. If additional items exist beyond the maximum you specify, the `IsTruncated` response element is `true`.

If you do not include this parameter, the number of items defaults to 100. Note that IAM might return fewer results, even when there are more results available. In that case, the `IsTruncated` response element returns `true`, and `Marker` contains a value to include in the subsequent call that tells the service where to continue from.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

### PolicyArn

The Amazon Resource Name (ARN) of the IAM policy for which you want the versions.

For more information about ARNs, see [Amazon Resource Names \(ARNs\)](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

## Response Elements

The following elements are returned by the service.

### **IsTruncated**

A flag that indicates whether there are more items to return. If your results were truncated, you can make a subsequent pagination request using the `Marker` request parameter to retrieve more items. Note that IAM might return fewer than the `MaxItems` number of results even when there are more results available. We recommend that you check `IsTruncated` after every call to ensure that you receive all your results.

Type: Boolean

### **Marker**

When `IsTruncated` is `true`, this element is present and contains the value to use for the `Marker` parameter in a subsequent pagination request.

Type: String

### **Versions.member.N**

A list of policy versions.

For more information about managed policy versions, see [Versioning for managed policies](#) in the *IAM User Guide*.

Type: Array of [PolicyVersion \(p. 522\)](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **InvalidInput**

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of `ListPolicyVersions`.

### Sample Request

```
https://iam.amazonaws.com/?Action=ListPolicyVersions
```

```
&PolicyArn=arn:aws:iam::123456789012:policy/S3-read-only-example-bucket
&Version=2010-05-08
&AUTHPARAMS
```

## Sample Response

```
<ListPolicyVersionsResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ListPolicyVersionsResult>
    <Versions>
      <member>
        <IsDefaultVersion>false</IsDefaultVersion>
        <VersionId>v3</VersionId>
        <CreateDate>2014-09-17T22:32:43Z</CreateDate>
      </member>
      <member>
        <IsDefaultVersion>true</IsDefaultVersion>
        <VersionId>v2</VersionId>
        <CreateDate>2014-09-15T20:31:47Z</CreateDate>
      </member>
      <member>
        <IsDefaultVersion>false</IsDefaultVersion>
        <VersionId>v1</VersionId>
        <CreateDate>2014-09-15T17:36:14Z</CreateDate>
      </member>
    </Versions>
    <IsTruncated>false</IsTruncated>
  </ListPolicyVersionsResult>
  <ResponseMetadata>
    <RequestId>a31d1a86-3eba-11e4-9d0d-6f969EXAMPLE</RequestId>
  </ResponseMetadata>
</ListPolicyVersionsResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## ListRolePolicies

Lists the names of the inline policies that are embedded in the specified IAM role.

An IAM role can also have managed policies attached to it. To list the managed policies that are attached to a role, use [ListAttachedRolePolicies \(p. 229\)](#). For more information about policies, see [Managed policies and inline policies](#) in the *IAM User Guide*.

You can paginate the results using the `MaxItems` and `Marker` parameters. If there are no inline policies embedded with the specified role, the operation returns an empty list.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### Marker

Use this parameter only when paginating results and only after you receive a response indicating that the results are truncated. Set it to the value of the `Marker` element in the response that you received to indicate where the next call should start.

Type: String

Length Constraints: Minimum length of 1.

Pattern: `[\u0020-\u00FF]+`

Required: No

### MaxItems

Use this only when paginating results to indicate the maximum number of items you want in the response. If additional items exist beyond the maximum you specify, the `IsTruncated` response element is `true`.

If you do not include this parameter, the number of items defaults to 100. Note that IAM might return fewer results, even when there are more results available. In that case, the `IsTruncated` response element returns `true`, and `Marker` contains a value to include in the subsequent call that tells the service where to continue from.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

### RoleName

The name of the role to list policies for.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=, .@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w+=, .@-]+`

Required: Yes

## Response Elements

The following elements are returned by the service.

### **IsTruncated**

A flag that indicates whether there are more items to return. If your results were truncated, you can make a subsequent pagination request using the `Marker` request parameter to retrieve more items. Note that IAM might return fewer than the `MaxItems` number of results even when there are more results available. We recommend that you check `IsTruncated` after every call to ensure that you receive all your results.

Type: Boolean

### **Marker**

When `IsTruncated` is true, this element is present and contains the value to use for the `Marker` parameter in a subsequent pagination request.

Type: String

### **PolicyNames.member.N**

A list of policy names.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=, .@-]+`

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of `ListRolePolicies`.

#### Sample Request

```
https://iam.amazonaws.com/?Action=ListRolePolicies
```

```
&RoleName=S3Access
&Version=2010-05-08
&AUTHPARAMS
```

## Sample Response

```
<ListRolePoliciesResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
<ListRolePoliciesResult>
  <PolicyNames>
    <member>CloudwatchPutMetricPolicy</member>
    <member>S3AccessPolicy</member>
  </PolicyNames>
  <IsTruncated>false</IsTruncated>
</ListRolePoliciesResult>
<ResponseMetadata>
  <RequestId>8c7e1816-99f0-11e1-a4c3-27EXAMPLE804</RequestId>
</ResponseMetadata>
</ListRolePoliciesResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## ListRoles

Lists the IAM roles that have the specified path prefix. If there are none, the operation returns an empty list. For more information about roles, see [Working with roles](#).

### Note

IAM resource-listing operations return a subset of the available attributes for the resource. For example, this operation does not return tags, even though they are an attribute of the returned object. To view all of the information for a role, see [GetRole \(p. 187\)](#).

You can paginate the results using the `MaxItems` and `Marker` parameters.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### Marker

Use this parameter only when paginating results and only after you receive a response indicating that the results are truncated. Set it to the value of the `Marker` element in the response that you received to indicate where the next call should start.

Type: String

Length Constraints: Minimum length of 1.

Pattern: `[\u0020-\u00FF]+`

Required: No

### MaxItems

Use this only when paginating results to indicate the maximum number of items you want in the response. If additional items exist beyond the maximum you specify, the `IsTruncated` response element is `true`.

If you do not include this parameter, the number of items defaults to 100. Note that IAM might return fewer results, even when there are more results available. In that case, the `IsTruncated` response element returns `true`, and `Marker` contains a value to include in the subsequent call that tells the service where to continue from.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

### PathPrefix

The path prefix for filtering the results. For example, the prefix `/application_abc/component_xyz/` gets all roles whose path starts with `/application_abc/component_xyz/`.

This parameter is optional. If it is not included, it defaults to a slash (/), listing all roles. This parameter allows (through its [regex pattern](#)) a string of characters consisting of either a forward slash (/) by itself or a string that must begin and end with forward slashes. In addition, it can contain any ASCII character from the ! (\u0021) through the DEL character (\u007F), including most punctuation characters, digits, and upper and lowercased letters.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: \u002F[\u0021-\u007F]\*

Required: No

## Response Elements

The following elements are returned by the service.

### **IsTruncated**

A flag that indicates whether there are more items to return. If your results were truncated, you can make a subsequent pagination request using the `Marker` request parameter to retrieve more items. Note that IAM might return fewer than the `MaxItems` number of results even when there are more results available. We recommend that you check `IsTruncated` after every call to ensure that you receive all your results.

Type: Boolean

### **Marker**

When `IsTruncated` is `true`, this element is present and contains the value to use for the `Marker` parameter in a subsequent pagination request.

Type: String

### **Roles.member.N**

A list of roles.

Type: Array of [Role \(p. 527\)](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of `ListRoles`.

### Sample Request

```
https://iam.amazonaws.com/?Action=ListRoles
&MaxItems=100
&PathPrefix=/application_abc/
&Version=2010-05-08
&AUTHPARAMS
```

## Sample Response

```
<ListRolesResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
<ListRolesResult>
<IsTruncated>false</IsTruncated>
<Roles>
<member>
<Path>/application_abc/component_xyz</Path>
<Arn>arn:aws:iam::123456789012:role/application_abc/component_xyz/S3Access</Arn>
<RoleName>S3Access</RoleName>
<AssumeRolePolicyDocument>
{"Version":"2012-10-17","Statement":[{"Effect":"Allow",
"Principal":{"Service":["ec2.amazonaws.com"]}, "Action":["sts:AssumeRole"]}]}
```

</AssumeRolePolicyDocument>

```
<CreateDate>2012-05-09T15:45:35Z</CreateDate>
<RoleId>AROACVSVTSZYEXAMPLEYK</RoleId>
</member>
<member>
<Path>/application_abc/component_xyz</Path>
<Arn>arn:aws:iam::123456789012:role/application_abc/component_xyz/SDBAccess</Arn>
<RoleName>SDBAccess</RoleName>
<AssumeRolePolicyDocument>
{"Version":"2012-10-17","Statement":[{"Effect":"Allow",
"Principal":{"Service":["ec2.amazonaws.com"]}, "Action":["sts:AssumeRole"]}]}
```

</AssumeRolePolicyDocument>

```
<CreateDate>2012-05-09T15:45:45Z</CreateDate>
<RoleId>AROAC2ICXG32EXAMPLEWK</RoleId>
</member>
</Roles>
</ListRolesResult>
<ResponseMetadata>
<RequestId>20f7279f-99ee-11e1-a4c3-27EXAMPLE804</RequestId>
</ResponseMetadata>
</ListRolesResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## ListRoleTags

Lists the tags that are attached to the specified role. The returned list of tags is sorted by tag key. For more information about tagging, see [Tagging IAM resources](#) in the *IAM User Guide*.

### Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

#### Marker

Use this parameter only when paginating results and only after you receive a response indicating that the results are truncated. Set it to the value of the `Marker` element in the response that you received to indicate where the next call should start.

Type: String

Length Constraints: Minimum length of 1.

Pattern: [\u0020-\u00FF]+

Required: No

#### MaxItems

Use this only when paginating results to indicate the maximum number of items you want in the response. If additional items exist beyond the maximum you specify, the `IsTruncated` response element is `true`.

If you do not include this parameter, the number of items defaults to 100. Note that IAM might return fewer results, even when there are more results available. In that case, the `IsTruncated` response element returns `true`, and `Marker` contains a value to include in the subsequent call that tells the service where to continue from.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

#### RoleName

The name of the IAM role for which you want to see the list of tags.

This parameter accepts (through its [regex pattern](#)) a string of characters that consist of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: \_+=,.@-

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [\w+=,.@-]+

Required: Yes

### Response Elements

The following elements are returned by the service.

### **IsTruncated**

A flag that indicates whether there are more items to return. If your results were truncated, you can make a subsequent pagination request using the `Marker` request parameter to retrieve more items. Note that IAM might return fewer than the `MaxItems` number of results even when there are more results available. We recommend that you check `IsTruncated` after every call to ensure that you receive all your results.

Type: Boolean

### **Marker**

When `IsTruncated` is `true`, this element is present and contains the value to use for the `Marker` parameter in a subsequent pagination request.

Type: String

### **Tags.member.N**

The list of tags that are currently attached to the role. Each tag consists of a key name and an associated value. If no tags are attached to the specified resource, the response contains an empty list.

Type: Array of [Tag \(p. 553\)](#) objects

Array Members: Maximum number of 50 items.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

The following example is formatted with line breaks for legibility.

The following example shows how to list the tags attached to a role named `taggedrole`.

### Sample Request

```
POST / HTTP/1.1
Host: https://iam.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.11.143 Python/3.6.1 Linux/3.2.45-0.6.wd.865.49.315.metal1.x86_64
botocore/1.7.1
```

```
X-Amz-Date: 20170926T201509Z
Authorization: <auth details>
Content-Length: 58
Content-Type: application/x-www-form-urlencoded
Action=ListRoleTags&Version=2010-05-08&RoleName=taggedrole
```

## Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE
Content-Type: text/xml
Content-Length: 447
Date: Tue, 26 Sep 2017 20:15:09 GMT

<ListRoleTagsResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ListRoleTagsResult>
    <IsTruncated>false</IsTruncated>
    <Tags>
      <member>
        <Key>Dept</Key>
        <Value>Accounting</Value>
      </member>
      <member>
        <Key>Cost Center</Key>
        <Value>12345</Value>
      </member>
    </Tags>
  </ListRoleTagsResult>
  <ResponseMetadata>
    <RequestId>EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE</RequestId>
  </ResponseMetadata>
</ListRoleTagsResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListSAMLProviders

Lists the SAML provider resource objects defined in IAM in the account. IAM resource-listing operations return a subset of the available attributes for the resource. For example, this operation does not return tags, even though they are an attribute of the returned object. To view all of the information for a SAML provider, see [GetSAMLProvider \(p. 192\)](#).

**Important**

This operation requires [Signature Version 4](#).

## Response Elements

The following element is returned by the service.

**SAMLProviderList.member.N**

The list of SAML provider resource objects defined in IAM for this AWS account.

Type: Array of [SAMLProviderListEntry \(p. 535\)](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

**ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of ListSAMLProviders.

#### Sample Request

```
https://iam.amazonaws.com/?Action=ListSAMLProviders
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<ListSAMLProvidersResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
<ListSAMLProvidersResult>
<SAMLProviderList>
<member>
<Arn>arn:aws:iam::123456789012:saml-provider/MyUniversity</Arn>
<ValidUntil>2032-05-09T16:27:11Z</ValidUntil>
<CreateDate>2012-05-09T16:27:03Z</CreateDate>
</member>
<member>
<Arn>arn:aws:iam::123456789012:saml-provider/MyUniversity</Arn>
```

```
<ValidUntil>2015-03-11T13:11:02Z</ValidUntil>
<CreateDate>2012-05-09T16:27:11Z</CreateDate>
</member>
</SAMLProviderList>
</ListSAMLProvidersResult>
<ResponseMetadata>
<RequestId>fd74fa8d-99f3-11e1-a4c3-27EXAMPLE804</RequestId>
</ResponseMetadata>
</ListSAMLProvidersResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListSAMLProviderTags

Lists the tags that are attached to the specified Security Assertion Markup Language (SAML) identity provider. The returned list of tags is sorted by tag key. For more information, see [About SAML 2.0-based federation](#).

For more information about tagging, see [Tagging IAM resources](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### Marker

Use this parameter only when paginating results and only after you receive a response indicating that the results are truncated. Set it to the value of the `Marker` element in the response that you received to indicate where the next call should start.

Type: String

Length Constraints: Minimum length of 1.

Pattern: `[\u0020-\u00FF]+`

Required: No

### MaxItems

Use this only when paginating results to indicate the maximum number of items you want in the response. If additional items exist beyond the maximum you specify, the `IsTruncated` response element is `true`.

If you do not include this parameter, the number of items defaults to 100. Note that IAM might return fewer results, even when there are more results available. In that case, the `IsTruncated` response element returns `true`, and `Marker` contains a value to include in the subsequent call that tells the service where to continue from.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

### SAMLProviderArn

The ARN of the Security Assertion Markup Language (SAML) identity provider whose tags you want to see.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

## Response Elements

The following elements are returned by the service.

### **IsTruncated**

A flag that indicates whether there are more items to return. If your results were truncated, you can make a subsequent pagination request using the `Marker` request parameter to retrieve more items. Note that IAM might return fewer than the `MaxItems` number of results even when there are more results available. We recommend that you check `IsTruncated` after every call to ensure that you receive all your results.

Type: Boolean

### **Marker**

When `IsTruncated` is `true`, this element is present and contains the value to use for the `Marker` parameter in a subsequent pagination request.

Type: String

### **Tags.member.N**

The list of tags that are currently attached to the Security Assertion Markup Language (SAML) identity provider. Each tag consists of a key name and an associated value. If no tags are attached to the specified resource, the response contains an empty list.

Type: Array of [Tag \(p. 553\)](#) objects

Array Members: Maximum number of 50 items.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **InvalidInput**

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

The following example is formatted with line breaks for legibility.

This example shows how to list the tags that are attached to a SAML identity provider whose ARN is `arn:aws:iam::123456789012:saml-provider/ADFSProvider`.

## Sample Request

```
POST / HTTP/1.1
Host: https://iam.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.11.143 Python/3.6.1 Linux/3.2.45-0.6.wd.865.49.315.metal1.x86_64
    botocore/1.7.1
X-Amz-Date: 20170929T182447Z
Authorization: <auth details>
Content-Length: 55
Content-Type: application/x-www-form-urlencoded

Action=ListSAMLProviderTags&Version=2010-05-08&SAMLProviderArn=arn:aws:iam::123456789012:saml-
provider/ADFSProvider
```

## Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE
Content-Type: text/xml
Content-Length: 484
Date: Fri, 29 Sep 2017 18:24:47 GMT

<ListSAMLProviderTagsResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ListSAMLProviderTagsResult>
    <IsTruncated>false</IsTruncated>
    <Tags>
      <member>
        <Key>Dept</Key>
        <Value>12345</Value>
      </member>
      <member>
        <Key>Team</Key>
        <Value>Accounting</Value>
      </member>
    </Tags>
  </ListSAMLProviderTagsResult>
  <ResponseMetadata>
    <RequestId>EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE</RequestId>
    <RequestId>EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE</RequestId>
  </ResponseMetadata>
</ListSAMLProviderTagsResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

# ListServerCertificates

Lists the server certificates stored in IAM that have the specified path prefix. If none exist, the operation returns an empty list.

You can paginate the results using the `MaxItems` and `Marker` parameters.

For more information about working with server certificates, see [Working with server certificates](#) in the *IAM User Guide*. This topic also includes a list of AWS services that can use the server certificates that you manage with IAM.

## Note

IAM resource-listing operations return a subset of the available attributes for the resource. For example, this operation does not return tags, even though they are an attribute of the returned object. To view all of the information for a servercertificate, see [GetServerCertificate \(p. 195\)](#).

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### Marker

Use this parameter only when paginating results and only after you receive a response indicating that the results are truncated. Set it to the value of the `Marker` element in the response that you received to indicate where the next call should start.

Type: String

Length Constraints: Minimum length of 1.

Pattern: `[\u0020-\u00FF]+`

Required: No

### MaxItems

Use this only when paginating results to indicate the maximum number of items you want in the response. If additional items exist beyond the maximum you specify, the `IsTruncated` response element is `true`.

If you do not include this parameter, the number of items defaults to 100. Note that IAM might return fewer results, even when there are more results available. In that case, the `IsTruncated` response element returns `true`, and `Marker` contains a value to include in the subsequent call that tells the service where to continue from.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

### PathPrefix

The path prefix for filtering the results. For example: `/company/servercerts` would get all server certificates for which the path starts with `/company/servercerts`.

This parameter is optional. If it is not included, it defaults to a slash (/), listing all server certificates. This parameter allows (through its [regex pattern](#)) a string of characters consisting of either a forward slash (/) by itself or a string that must begin and end with forward slashes. In addition, it can contain

any ASCII character from the ! (\u0021) through the DEL character (\u007F), including most punctuation characters, digits, and upper and lowercased letters.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: \u002F[\u0021-\u007F]\*

Required: No

## Response Elements

The following elements are returned by the service.

### **IsTruncated**

A flag that indicates whether there are more items to return. If your results were truncated, you can make a subsequent pagination request using the `Marker` request parameter to retrieve more items. Note that IAM might return fewer than the `MaxItems` number of results even when there are more results available. We recommend that you check `IsTruncated` after every call to ensure that you receive all your results.

Type: Boolean

### **Marker**

When `IsTruncated` is `true`, this element is present and contains the value to use for the `Marker` parameter in a subsequent pagination request.

Type: String

### **ServerCertificateMetadataList.member.N**

A list of server certificates.

Type: Array of [ServerCertificateMetadata \(p. 538\)](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of `ListServerCertificates`.

#### Sample Request

```
https://iam.amazonaws.com/?Action=ListServerCertificates
```

```
&PathPrefix=/company/servercerts
&Version=2010-05-08
&AUTHPARAMS
```

## Sample Response

```
<ListServerCertificatesResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
<ListServerCertificatesResult>
  <IsTruncated>false</IsTruncated>
  <ServerCertificateMetadataList>
    <member>
      <ServerCertificateName>ProdServerCert</ServerCertificateName>
      <Path>/company/servercerts/</Path>
      <Arn>arn:aws:iam::123456789012:server-certificate/company/servercerts/
ProdServerCert</Arn>
      <UploadDate>2010-05-08T01:02:03.004Z</UploadDate>
      <ServerCertificateId>ASCACKCEVSQ6CEXAMPLE1</ServerCertificateId>
      <Expiration>2012-05-08T01:02:03.004Z</Expiration>
    </member>
    <member>
      <ServerCertificateName>BetaServerCert</ServerCertificateName>
      <Path>/company/servercerts/</Path>
      <Arn>arn:aws:iam::123456789012:server-certificate/company/servercerts/
BetaServerCert</Arn>
      <UploadDate>2010-05-08T02:03:01.004Z</UploadDate>
      <ServerCertificateId>ASCACKCEVSQ6CEXAMPLE2</ServerCertificateId>
      <Expiration>2012-05-08T02:03:01.004Z</Expiration>
    </member>
    <member>
      <ServerCertificateName>TestServerCert</ServerCertificateName>
      <Path>/company/servercerts/</Path>
      <Arn>arn:aws:iam::123456789012:server-certificate/company/servercerts/
TestServerCert</Arn>
      <UploadDate>2010-05-08T03:01:02.004Z</UploadDate>
      <ServerCertificateId>ASCACKCEVSQ6CEXAMPLE3</ServerCertificateId>
      <Expiration>2012-05-08T03:01:02.004Z</Expiration>
    </member>
  </ServerCertificateMetadataList>
</ListServerCertificatesResult>
<ResponseMetadata>
  <RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
</ResponseMetadata>
</ListServerCertificatesResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListServerCertificateTags

Lists the tags that are attached to the specified IAM server certificate. The returned list of tags is sorted by tag key. For more information about tagging, see [Tagging IAM resources](#) in the *IAM User Guide*.

## Note

For certificates in a Region supported by AWS Certificate Manager (ACM), we recommend that you don't use IAM server certificates. Instead, use ACM to provision, manage, and deploy your server certificates. For more information about IAM server certificates, [Working with server certificates](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### Marker

Use this parameter only when paginating results and only after you receive a response indicating that the results are truncated. Set it to the value of the `Marker` element in the response that you received to indicate where the next call should start.

Type: String

Length Constraints: Minimum length of 1.

Pattern: `[\u0020-\u00FF]+`

Required: No

### MaxItems

Use this only when paginating results to indicate the maximum number of items you want in the response. If additional items exist beyond the maximum you specify, the `IsTruncated` response element is `true`.

If you do not include this parameter, the number of items defaults to 100. Note that IAM might return fewer results, even when there are more results available. In that case, the `IsTruncated` response element returns `true`, and `Marker` contains a value to include in the subsequent call that tells the service where to continue from.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

### ServerCertificateName

The name of the IAM server certificate whose tags you want to see.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: Yes

## Response Elements

The following elements are returned by the service.

### **IsTruncated**

A flag that indicates whether there are more items to return. If your results were truncated, you can make a subsequent pagination request using the `Marker` request parameter to retrieve more items. Note that IAM might return fewer than the `MaxItems` number of results even when there are more results available. We recommend that you check `IsTruncated` after every call to ensure that you receive all your results.

Type: Boolean

### **Marker**

When `IsTruncated` is `true`, this element is present and contains the value to use for the `Marker` parameter in a subsequent pagination request.

Type: String

### **Tags.member.N**

The list of tags that are currently attached to the IAM server certificate. Each tag consists of a key name and an associated value. If no tags are attached to the specified resource, the response contains an empty list.

Type: Array of [Tag \(p. 553\)](#) objects

Array Members: Maximum number of 50 items.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

The following example is formatted with line breaks for legibility.

This example shows how to list the tags that are attached to an IAM server certificate whose name is `ProdServerCert`.

## Sample Request

```
POST / HTTP/1.1
Host: https://iam.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.11.143 Python/3.6.1 Linux/3.2.45-0.6.wd.865.49.315.meta11.x86_64
    botocore/1.7.1
X-Amz-Date: 20170929T182447Z
Authorization: <auth details>
Content-Length: 55
Content-Type: application/x-www-form-urlencoded

Action=ListServerCertificateTags&Version=2010-05-08&ServerCertificateName=ProdServerCert
```

## Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE
Content-Type: text/xml
Content-Length: 484
Date: Fri, 29 Sep 2017 18:24:47 GMT

<ListServerCertificateTagsResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ListServerCertificateTagsResult>
    <IsTruncated>false</IsTruncated>
    <Tags>
      <member>
        <Key>Dept</Key>
        <Value>12345</Value>
      </member>
      <member>
        <Key>Team</Key>
        <Value>Accounting</Value>
      </member>
    </Tags>
  </ListServerCertificateTagsResult>
  <ResponseMetadata>
    <RequestId>EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE</RequestId>
  </ResponseMetadata>
</ListServerCertificateTagsResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListServiceSpecificCredentials

Returns information about the service-specific credentials associated with the specified IAM user. If none exists, the operation returns an empty list. The service-specific credentials returned by this operation are used only for authenticating the IAM user to a specific service. For more information about using service-specific credentials to authenticate to an AWS service, see [Set up service-specific credentials](#) in the [CodeCommit User Guide](#).

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### **ServiceName**

Filters the returned results to only those for the specified AWS service. If not specified, then AWS returns service-specific credentials for all services.

Type: String

Required: No

### **UserName**

The name of the user whose service-specific credentials you want information about. If this value is not specified, then the operation assumes the user whose credentials are used to call the operation.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w+=,.@-]+`

Required: No

## Response Elements

The following element is returned by the service.

### **ServiceSpecificCredentials.member.N**

A list of structures that each contain details about a service-specific credential.

Type: Array of [ServiceSpecificCredentialMetadata \(p. 544\)](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

#### NotSupportedException

The specified service does not support service-specific credentials.

HTTP Status Code: 404

## Examples

### Example

The following example shows how to get the list of all service-specific credentials for the IAM user named Anika.

#### Sample Request

```
https://iam.amazonaws.com/?Action=ListServiceSpecificCredentials
&UserName=anika
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<ListServiceSpecificCredentialsResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ListServiceSpecificCredentialsResult>
    <ServiceSpecificCredentials>
      <member>
        <ServiceName>codecommit.amazonaws.com</ServiceName>
        <UserName>anika</UserName>
        <ServiceUserName>anika-at-123456789012</ServiceUserName>
        <ServiceSpecificCredentialId>ACCA12345ABCDEEXAMPLE</ServiceSpecificCredentialId>
        <Status>Active</Status>
        <CreateDate>2016-11-01T17:44:54Z</CreateDate>
      </member>
      <member>
        <ServiceName>codecommit.amazonaws.com</ServiceName>
        <UserName>anika</UserName>
        <ServiceUserName>anika+1-at-123456789012</ServiceUserName>
        <ServiceSpecificCredentialId>ACCA67890FGHIEXAMPLE</ServiceSpecificCredentialId>
        <Status>Active</Status>
        <CreateDate>2016-11-01T18:22:26Z</CreateDate>
      </member>
    </ServiceSpecificCredentials>
  </ListServiceSpecificCredentialsResult>
  <ResponseMetadata>
    <RequestId>EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE</RequestId>
  </ResponseMetadata>
</ListServiceSpecificCredentialsResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListSigningCertificates

Returns information about the signing certificates associated with the specified IAM user. If none exists, the operation returns an empty list.

Although each user is limited to a small number of signing certificates, you can still paginate the results using the `MaxItems` and `Marker` parameters.

If the `UserName` field is not specified, the user name is determined implicitly based on the AWS access key ID used to sign the request for this operation. This operation works for access keys under the AWS account. Consequently, you can use this operation to manage AWS account root user credentials even if the AWS account has no associated users.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### Marker

Use this parameter only when paginating results and only after you receive a response indicating that the results are truncated. Set it to the value of the `Marker` element in the response that you received to indicate where the next call should start.

Type: String

Length Constraints: Minimum length of 1.

Pattern: [\u0020-\u00FF]+

Required: No

### MaxItems

Use this only when paginating results to indicate the maximum number of items you want in the response. If additional items exist beyond the maximum you specify, the `IsTruncated` response element is `true`.

If you do not include this parameter, the number of items defaults to 100. Note that IAM might return fewer results, even when there are more results available. In that case, the `IsTruncated` response element returns `true`, and `Marker` contains a value to include in the subsequent call that tells the service where to continue from.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

### UserName

The name of the IAM user whose signing certificates you want to examine.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: \_+=,.@-

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=, .@-]+`

Required: No

## Response Elements

The following elements are returned by the service.

### **Certificates.member.N**

A list of the user's signing certificate information.

Type: Array of [SigningCertificate \(p. 546\)](#) objects

### **IsTruncated**

A flag that indicates whether there are more items to return. If your results were truncated, you can make a subsequent pagination request using the `Marker` request parameter to retrieve more items. Note that IAM might return fewer than the `MaxItems` number of results even when there are more results available. We recommend that you check `IsTruncated` after every call to ensure that you receive all your results.

Type: Boolean

### **Marker**

When `IsTruncated` is `true`, this element is present and contains the value to use for the `Marker` parameter in a subsequent pagination request.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of `ListSigningCertificates`.

#### Sample Request

```
https://iam.amazonaws.com/?Action=ListSigningCertificates
```

```
&UserName=Bob
&Version=2010-05-08
&AUTHPARAMS
```

## Sample Response

```
<ListSigningCertificatesResponse>
  <ListSigningCertificatesResult>
    <UserName>Bob</UserName>
    <Certificates>
      <member>
        <UserName>Bob</UserName>
        <CertificateId>TA7SMEXAMPLE260BPJE7EXAMPLE</CertificateId>
        <CertificateBody>
-----BEGIN CERTIFICATE-----
MIICdzCCAECgAwIBAgIGANC+Ha2wMA0GCSqGSIb3DQEBCUAMFmxCzAJBgNVBAYT
A1VTMRMwEQYDVQQKEwpBbWF6b24uY29tMQwwCgYDVQQLEwNBV1MxITAfBgNVBAMT
GEFXUyBmA1pdGVkLUFc3VYw5jZSB0TAEfW0w0TAyMDQxNzE5MjdaFw0xMDAy
MDQxNzE5MjdaMF1xCzAJBgNVBAYTA1VTMRMwEQYDVQQKEwpBbWF6b24uY29tMRCw
FQYDVQQLEw5BV1MtRGV2ZWxvcGVyczEVMBMGA1UEAxMMNTdxND10c3ZwYjRtMIGf
MA0GCSqGSIb3DQEBAQUAA4GNADCBiQKBgQCpB/vs0wmT/00td1RqzKjttSBaPjbr
dqwNe9Br0yB08fw2+Ch5oonZYXfGUrT6mkYXH5fQot9HvASrzAKH0596FdJA6Dml
ywdWe10ggk7zFSX01Xv+3vPrJtaYxYo3eRip7w80PMki0v6M0XK8ubcTou0DeJbf
suDqcLnLDxwsvwIDAQABo1cwVTA0BgNVHQ8BAf8EBAMCBaAwFgYDVRO1AQH/BAww
CgYIKwYBBQUHwIwDAYDVR0TAQH/BAIwADAdBgNVHQ4EFgQULGNaBphBumaKbDRK
CAi0mH8B3mowDQYJKoZIhvcNAQEFBQADgYEAKxhkXaCLGcqDuweKt0/AEw9ZePH
wR0XqsaIK2HZboqruebXEGsojK4Ks0WzwgrEynuHJwTn760xe39rSqXWI0Gr0Bax
wFpWHVjTFMkk+tSDG1lssLHyYWWdFFU4AnejRG0RJYNaRHgVTkjHphc5jEhHm0BX
AEaHzTpmEXAMPLE=
-----END CERTIFICATE-----
        </CertificateBody>
        <Status>Active</Status>
      </member>
    </Certificates>
    <IsTruncated>false</IsTruncated>
  </ListSigningCertificatesResult>
  <ResponseMetadata>
    <RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
  </ResponseMetadata>
</ListSigningCertificatesResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListSSHPublicKeys

Returns information about the SSH public keys associated with the specified IAM user. If none exists, the operation returns an empty list.

The SSH public keys returned by this operation are used only for authenticating the IAM user to an CodeCommit repository. For more information about using SSH keys to authenticate to an CodeCommit repository, see [Set up CodeCommit for SSH connections](#) in the *CodeCommit User Guide*.

Although each user is limited to a small number of keys, you can still paginate the results using the `MaxItems` and `Marker` parameters.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### **Marker**

Use this parameter only when paginating results and only after you receive a response indicating that the results are truncated. Set it to the value of the `Marker` element in the response that you received to indicate where the next call should start.

Type: String

Length Constraints: Minimum length of 1.

Pattern: [\u0020-\u00FF]+

Required: No

### **MaxItems**

Use this only when paginating results to indicate the maximum number of items you want in the response. If additional items exist beyond the maximum you specify, the `IsTruncated` response element is `true`.

If you do not include this parameter, the number of items defaults to 100. Note that IAM might return fewer results, even when there are more results available. In that case, the `IsTruncated` response element returns `true`, and `Marker` contains a value to include in the subsequent call that tells the service where to continue from.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

### **UserName**

The name of the IAM user to list SSH public keys for. If none is specified, the `UserName` field is determined implicitly based on the AWS access key used to sign the request.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: \_+=,.@-

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [\\w+=, .@-]+

Required: No

## Response Elements

The following elements are returned by the service.

### **IsTruncated**

A flag that indicates whether there are more items to return. If your results were truncated, you can make a subsequent pagination request using the `Marker` request parameter to retrieve more items. Note that IAM might return fewer than the `MaxItems` number of results even when there are more results available. We recommend that you check `IsTruncated` after every call to ensure that you receive all your results.

Type: Boolean

### **Marker**

When `IsTruncated` is `true`, this element is present and contains the value to use for the `Marker` parameter in a subsequent pagination request.

Type: String

### **SSHPublicKeys.member.N**

A list of the SSH public keys assigned to IAM user.

Type: Array of [SSHPublicKeyMetadata \(p. 550\)](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

## Examples

### Example

This example illustrates one usage of `ListSSHPublicKeys`.

#### Sample Request

```
https://iam.amazonaws.com/?Action=ListSSHPublicKeys
&UserName=Jane
&Version=2010-05-08
&AUTHPARAMS
```

## Sample Response

```
<ListSSHPublicKeysResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ListSSHPublicKeysResult>
    <IsTruncated>false</IsTruncated>
    <SSHPublicKeys>
      <member>
        <UploadDate>2015-06-05T20:56:46Z</UploadDate>
        <UserName>Jane</UserName>
        <SSHPublicKeyId>APKAEIVFHP46CEEXAMPLE</SSHPublicKeyId>
        <Status>Active</Status>
      </member>
    </SSHPublicKeys>
  </ListSSHPublicKeysResult>
  <ResponseMetadata>
    <RequestId>9f8e2d77-f36c-11e4-97db-33c4eEXAMPLE</RequestId>
  </ResponseMetadata>
</ListSSHPublicKeysResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListUserPolicies

Lists the names of the inline policies embedded in the specified IAM user.

An IAM user can also have managed policies attached to it. To list the managed policies that are attached to a user, use [ListAttachedUserPolicies \(p. 233\)](#). For more information about policies, see [Managed policies and inline policies](#) in the *IAM User Guide*.

You can paginate the results using the `MaxItems` and `Marker` parameters. If there are no inline policies embedded with the specified user, the operation returns an empty list.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### Marker

Use this parameter only when paginating results and only after you receive a response indicating that the results are truncated. Set it to the value of the `Marker` element in the response that you received to indicate where the next call should start.

Type: String

Length Constraints: Minimum length of 1.

Pattern: `[\u0020-\u00FF]+`

Required: No

### MaxItems

Use this only when paginating results to indicate the maximum number of items you want in the response. If additional items exist beyond the maximum you specify, the `IsTruncated` response element is `true`.

If you do not include this parameter, the number of items defaults to 100. Note that IAM might return fewer results, even when there are more results available. In that case, the `IsTruncated` response element returns `true`, and `Marker` contains a value to include in the subsequent call that tells the service where to continue from.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

### UserName

The name of the user to list policies for.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=, @-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=, .@-]+`

Required: Yes

## Response Elements

The following elements are returned by the service.

### **IsTruncated**

A flag that indicates whether there are more items to return. If your results were truncated, you can make a subsequent pagination request using the `Marker` request parameter to retrieve more items. Note that IAM might return fewer than the `MaxItems` number of results even when there are more results available. We recommend that you check `IsTruncated` after every call to ensure that you receive all your results.

Type: Boolean

### **Marker**

When `IsTruncated` is true, this element is present and contains the value to use for the `Marker` parameter in a subsequent pagination request.

Type: String

### **PolicyNames.member.N**

A list of policy names.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=, .@-]+`

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of `ListUserPolicies`.

#### Sample Request

```
https://iam.amazonaws.com/?Action=ListUserPolicies
```

```
&UserName=Bob  
&AUTHPARAMS
```

## Sample Response

```
<ListUserPoliciesResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">  
  <ListUserPoliciesResult>  
    <PolicyNames>  
      <member>AllAccessPolicy</member>  
      <member>KeyPolicy</member>  
    </PolicyNames>  
    <IsTruncated>false</IsTruncated>  
  </ListUserPoliciesResult>  
  <ResponseMetadata>  
    <RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>  
  </ResponseMetadata>  
</ListUserPoliciesResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListUsers

Lists the IAM users that have the specified path prefix. If no path prefix is specified, the operation returns all users in the AWS account. If there are none, the operation returns an empty list.

## Note

IAM resource-listing operations return a subset of the available attributes for the resource. For example, this operation does not return tags, even though they are an attribute of the returned object. To view all of the information for a user, see  [GetUser \(p. 213\)](#).

You can paginate the results using the `MaxItems` and `Marker` parameters.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### Marker

Use this parameter only when paginating results and only after you receive a response indicating that the results are truncated. Set it to the value of the `Marker` element in the response that you received to indicate where the next call should start.

Type: String

Length Constraints: Minimum length of 1.

Pattern: `[\u0020-\u00FF]+`

Required: No

### MaxItems

Use this only when paginating results to indicate the maximum number of items you want in the response. If additional items exist beyond the maximum you specify, the `IsTruncated` response element is `true`.

If you do not include this parameter, the number of items defaults to 100. Note that IAM might return fewer results, even when there are more results available. In that case, the `IsTruncated` response element returns `true`, and `Marker` contains a value to include in the subsequent call that tells the service where to continue from.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

### PathPrefix

The path prefix for filtering the results. For example: `/division_abc/subdivision_xyz/`, which would get all user names whose path starts with `/division_abc/subdivision_xyz/`.

This parameter is optional. If it is not included, it defaults to a slash (/), listing all user names. This parameter allows (through its [regex pattern](#)) a string of characters consisting of either a forward slash (/) by itself or a string that must begin and end with forward slashes. In addition, it can contain any ASCII character from the ! (\u0021) through the DEL character (\u007F), including most punctuation characters, digits, and upper and lowercased letters.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: \u002F[\u0021-\u007F]\*

Required: No

## Response Elements

The following elements are returned by the service.

### **IsTruncated**

A flag that indicates whether there are more items to return. If your results were truncated, you can make a subsequent pagination request using the `Marker` request parameter to retrieve more items. Note that IAM might return fewer than the `MaxItems` number of results even when there are more results available. We recommend that you check `IsTruncated` after every call to ensure that you receive all your results.

Type: Boolean

### **Marker**

When `IsTruncated` is `true`, this element is present and contains the value to use for the `Marker` parameter in a subsequent pagination request.

Type: String

### **Users.member.N**

A list of users.

Type: Array of [User \(p. 556\)](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of `ListUsers`.

#### Sample Request

```
https://iam.amazonaws.com/?Action=ListUsers
&PathPrefix=/division_abc/subdivision_xyz/product_1234/engineering/
&Version=2010-05-08
&AUTHPARAMS
```

## Sample Response

```
<ListUsersResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ListUsersResult>
    <Users>
      <member>
        <UserId>AID2MAB8DPLSRHEXAMPLE</UserId>
        <Path>/division_abc/subdivision_xyz/engineering/</Path>
        <UserName>Andrew</UserName>
        <Arn>arn:aws:iam::123456789012:user/division_abc/subdivision_xyz/engineering/
        Andrew</Arn>
        <CreateDate>2012-09-05T19:38:48Z</CreateDate>
        <PasswordLastUsed>2014-09-08T21:47:36Z</PasswordLastUsed>
      </member>
      <member>
        <UserId>AIDI0DR4TAW7CSEXAMPLE</UserId>
        <Path>/division_abc/subdivision_xyz/engineering/</Path>
        <UserName>Jackie</UserName>
        <Arn>arn:aws:iam::123456789012:user/division_abc/subdivision_xyz/engineering/
        Jackie</Arn>
        <CreateDate>2014-04-09T15:43:45Z</CreateDate>
        <PasswordLastUsed>2014-09-24T16:18:07Z</PasswordLastUsed>
      </member>
    </Users>
    <IsTruncated>false</IsTruncated>
  </ListUsersResult>
  <ResponseMetadata>
    <RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
  </ResponseMetadata>
</ListUsersResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## ListUserTags

Lists the tags that are attached to the specified IAM user. The returned list of tags is sorted by tag key. For more information about tagging, see [Tagging IAM resources](#) in the *IAM User Guide*.

### Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

#### Marker

Use this parameter only when paginating results and only after you receive a response indicating that the results are truncated. Set it to the value of the `Marker` element in the response that you received to indicate where the next call should start.

Type: String

Length Constraints: Minimum length of 1.

Pattern: [\u0020-\u00FF]+

Required: No

#### MaxItems

Use this only when paginating results to indicate the maximum number of items you want in the response. If additional items exist beyond the maximum you specify, the `IsTruncated` response element is `true`.

If you do not include this parameter, the number of items defaults to 100. Note that IAM might return fewer results, even when there are more results available. In that case, the `IsTruncated` response element returns `true`, and `Marker` contains a value to include in the subsequent call that tells the service where to continue from.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

#### UserName

The name of the IAM user whose tags you want to see.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: \_+=,.@-

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [\w+=,.@-]+

Required: Yes

### Response Elements

The following elements are returned by the service.

### **IsTruncated**

A flag that indicates whether there are more items to return. If your results were truncated, you can make a subsequent pagination request using the `Marker` request parameter to retrieve more items. Note that IAM might return fewer than the `MaxItems` number of results even when there are more results available. We recommend that you check `IsTruncated` after every call to ensure that you receive all your results.

Type: Boolean

### **Marker**

When `IsTruncated` is `true`, this element is present and contains the value to use for the `Marker` parameter in a subsequent pagination request.

Type: String

### **Tags.member.N**

The list of tags that are currently attached to the user. Each tag consists of a key name and an associated value. If no tags are attached to the specified resource, the response contains an empty list.

Type: Array of [Tag \(p. 553\)](#) objects

Array Members: Maximum number of 50 items.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

The following example is formatted with line breaks for legibility.

This example shows how to list the tags attached to a user whose IAM user name is `anika`.

### Sample Request

```
POST / HTTP/1.1
Host: https://iam.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.11.143 Python/3.6.1 Linux/3.2.45-0.6.wd.865.49.315.metal1.x86_64
botocore/1.7.1
```

```
X-Amz-Date: 20170929T182447Z
Authorization: <auth details>
Content-Length: 55
Content-Type: application/x-www-form-urlencoded

Action=ListUserTags&Version=2010-05-08&UserName=anika
```

## Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE
Content-Type: text/xml
Content-Length: 484
Date: Fri, 29 Sep 2017 18:24:47 GMT

<ListUserTagsResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ListUserTagsResult>
    <IsTruncated>false</IsTruncated>
    <Tags>
      <member>
        <Key>Dept</Key>
        <Value>12345</Value>
      </member>
      <member>
        <Key>Team</Key>
        <Value>Accounting</Value>
      </member>
    </Tags>
  </ListUserTagsResult>
  <ResponseMetadata>
    <RequestId>EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE</RequestId>
  </ResponseMetadata>
</ListUserTagsResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListVirtualMFADevices

Lists the virtual MFA devices defined in the AWS account by assignment status. If you do not specify an assignment status, the operation returns a list of all virtual MFA devices. Assignment status can be Assigned, Unassigned, or Any.

## **Note**

IAM resource-listing operations return a subset of the available attributes for the resource. For example, this operation does not return tags, even though they are an attribute of the returned object. To view tag information for a virtual MFA device, see [ListMFADeviceTags \(p. 262\)](#).

You can paginate the results using the `MaxItems` and `Marker` parameters.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### **AssignmentStatus**

The status (Unassigned or Assigned) of the devices to list. If you do not specify an `AssignmentStatus`, the operation defaults to Any, which lists both assigned and unassigned virtual MFA devices.,

Type: String

Valid Values: Assigned | Unassigned | Any

Required: No

### **Marker**

Use this parameter only when paginating results and only after you receive a response indicating that the results are truncated. Set it to the value of the `Marker` element in the response that you received to indicate where the next call should start.

Type: String

Length Constraints: Minimum length of 1.

Pattern: [\u0020-\u00FF]+

Required: No

### **MaxItems**

Use this only when paginating results to indicate the maximum number of items you want in the response. If additional items exist beyond the maximum you specify, the `IsTruncated` response element is `true`.

If you do not include this parameter, the number of items defaults to 100. Note that IAM might return fewer results, even when there are more results available. In that case, the `IsTruncated` response element returns `true`, and `Marker` contains a value to include in the subsequent call that tells the service where to continue from.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

## Response Elements

The following elements are returned by the service.

### **IsTruncated**

A flag that indicates whether there are more items to return. If your results were truncated, you can make a subsequent pagination request using the `Marker` request parameter to retrieve more items. Note that IAM might return fewer than the `MaxItems` number of results even when there are more results available. We recommend that you check `IsTruncated` after every call to ensure that you receive all your results.

Type: Boolean

### **Marker**

When `IsTruncated` is `true`, this element is present and contains the value to use for the `Marker` parameter in a subsequent pagination request.

Type: String

### **VirtualMFADevices.member.N**

The list of virtual MFA devices in the current account that match the `AssignmentStatus` value that was passed in the request.

Type: Array of [VirtualMFADevice \(p. 561\)](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

## Examples

### Example

This example illustrates one usage of `ListVirtualMFADevices`.

#### Sample Request

```
https://iam.amazonaws.com/?Action=ListVirtualMFADevices
&AssignmentStatus=Any
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<ListVirtualMFADevicesResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
<ListVirtualMFADevicesResult>
<IsTruncated>false</IsTruncated>
<VirtualMFADevices>
<member>
<EnableDate>2011-12-11T12:31:16Z</EnableDate>
<SerialNumber>
arn:aws:iam::123456789012:mfa/MyCustomUser
</SerialNumber>
<User>
```

```
<Arn>arn:aws:iam::123456789012:user</MyCustomUser>
<CreateDate>2012-10-13T22:00:36Z</CreateDate>
<PasswordLastUsed>1540408180</PasswordLastUsed>
<Path>/</Path>
<UserId>AIDAEEXAMPLE36EXAMPLEC</UserId>
<UserName>MyCustomUser</UserName>
</User>
</member>
<member>
<EnableDate>2011-10-31T20:45:02Z</EnableDate>
<SerialNumber>
arn:aws:iam:::mfa/ExampleUser
</SerialNumber>
<User>
<Arn>arn:aws:iam::111122223333:user/ExampleUser</Arn>
<CreateDate>2011-07-01T17:23:07Z</CreateDate>
<PasswordLastUsed>1380057478</PasswordLastUsed>
<Path>/</Path>
<UserId>AIDEXAMPLE4EXAMPLEXYZ</UserId>
<UserName>ExampleUser</UserName>
</User>
</member>
</VirtualMFADevices>
</ListVirtualMFADevicesResult>
<ResponseMetadata>
<RequestId>b61ce1b1-0401-11e1-b2f8-2dEXAMPLEbfc</RequestId>
</ResponseMetadata>
</ListVirtualMFADevicesResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# PutGroupPolicy

Adds or updates an inline policy document that is embedded in the specified IAM group.

A user can also have managed policies attached to it. To attach a managed policy to a group, use [AttachGroupPolicy \(p. 13\)](#). To create a new managed policy, use [CreatePolicy \(p. 43\)](#). For information about policies, see [Managed policies and inline policies](#) in the *IAM User Guide*.

For information about the maximum number of inline policies that you can embed in a group, see [IAM and AWS STS quotas](#) in the *IAM User Guide*.

## Note

Because policy documents can be large, you should use POST rather than GET when calling PutGroupPolicy. For general information about using the Query API with IAM, see [Making query requests](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### GroupName

The name of the group to associate the policy with.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: Yes

### PolicyDocument

The policy document.

You must provide policies in JSON format in IAM. However, for AWS CloudFormation templates formatted in YAML, you can provide the policy in JSON or YAML format. AWS CloudFormation always converts a YAML policy to JSON format before submitting it to = IAM.

The [regex pattern](#) used to validate this parameter is a string of characters consisting of the following:

- Any printable ASCII character ranging from the space character (`\u0020`) through the end of the ASCII character range
- The printable characters in the Basic Latin and Latin-1 Supplement character set (through `\u00FF`)
- The special characters tab (`\u0009`), line feed (`\u000A`), and carriage return (`\u000D`)

Type: String

Length Constraints: Minimum length of 1. Maximum length of 131072.

Pattern: `[\u0009\u000A\u000D\u0020-\u00FF]+`

Required: Yes

#### **PolicyName**

The name of the policy document.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

#### **LimitExceeded**

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

#### **MalformedPolicyDocument**

The request was rejected because the policy document was malformed. The error message describes the specific error.

HTTP Status Code: 400

#### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

#### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of PutGroupPolicy.

#### Sample Request

```
https://iam.amazonaws.com/?Action=PutGroupPolicy  
&GroupName=Admins
```

```
&PolicyName=AdminRoot
&PolicyDocument={"Version":"2012-10-17","Statement": [{"Effect":"Allow","Action":"*","Resource":"*"}]}
&Version=2010-05-08
&AUTHPARAMS
```

## Sample Response

```
<PutGroupPolicyResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
<ResponseMetadata>
  <RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
</ResponseMetadata>
</PutGroupPolicyResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# PutRolePermissionsBoundary

Adds or updates the policy that is specified as the IAM role's permissions boundary. You can use an AWS managed policy or a customer managed policy to set the boundary for a role. Use the boundary to control the maximum permissions that the role can have. Setting a permissions boundary is an advanced feature that can affect the permissions for the role.

You cannot set the boundary for a service-linked role.

## Important

Policies used as permissions boundaries do not provide permissions. You must also attach a permissions policy to the role. To learn how the effective permissions for a role are evaluated, see [IAM JSON policy evaluation logic](#) in the IAM User Guide.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### PermissionsBoundary

The ARN of the policy that is used to set the permissions boundary for the role.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

### RoleName

The name (friendly name, not ARN) of the IAM role for which you want to set the permissions boundary.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [\w+=, .@-]+

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### InvalidInput

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### **PolicyNotAttachable**

The request failed because AWS service role policies can only be attached to the service-linked role for that service.

HTTP Status Code: 400

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

### **UnmodifiableEntity**

The request was rejected because only the service that depends on the service-linked role can modify or delete the role on your behalf. The error message includes the name of the service that depends on this service-linked role. You must request the change through that service.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# PutRolePolicy

Adds or updates an inline policy document that is embedded in the specified IAM role.

When you embed an inline policy in a role, the inline policy is used as part of the role's access (permissions) policy. The role's trust policy is created at the same time as the role, using [CreateRole \(p. 50\)](#). You can update a role's trust policy using [UpdateAssumeRolePolicy \(p. 431\)](#). For more information about IAM roles, see [Using roles to delegate permissions and federate identities](#).

A role can also have a managed policy attached to it. To attach a managed policy to a role, use [AttachRolePolicy \(p. 16\)](#). To create a new managed policy, use [CreatePolicy \(p. 43\)](#). For information about policies, see [Managed policies and inline policies](#) in the *IAM User Guide*.

For information about the maximum number of inline policies that you can embed with a role, see [IAM and AWS STS quotas](#) in the *IAM User Guide*.

## Note

Because policy documents can be large, you should use POST rather than GET when calling `PutRolePolicy`. For general information about using the Query API with IAM, see [Making query requests](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### PolicyDocument

The policy document.

You must provide policies in JSON format in IAM. However, for AWS CloudFormation templates formatted in YAML, you can provide the policy in JSON or YAML format. AWS CloudFormation always converts a YAML policy to JSON format before submitting it to IAM.

The [regex pattern](#) used to validate this parameter is a string of characters consisting of the following:

- Any printable ASCII character ranging from the space character (\u0020) through the end of the ASCII character range
- The printable characters in the Basic Latin and Latin-1 Supplement character set (through \u00FF)
- The special characters tab (\u0009), line feed (\u000A), and carriage return (\u000D)

Type: String

Length Constraints: Minimum length of 1. Maximum length of 131072.

Pattern: [\u0009\u000A\u000D\u0020-\u00FF]+

Required: Yes

### PolicyName

The name of the policy document.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: \_+=,.@-

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=, .@-]+`

Required: Yes

#### **RoleName**

The name of the role to associate the policy with.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w+=, .@-]+`

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

#### **LimitExceeded**

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

#### **MalformedPolicyDocument**

The request was rejected because the policy document was malformed. The error message describes the specific error.

HTTP Status Code: 400

#### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

#### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

#### **UnmodifiableEntity**

The request was rejected because only the service that depends on the service-linked role can modify or delete the role on your behalf. The error message includes the name of the service that depends on this service-linked role. You must request the change through that service.

HTTP Status Code: 400

## Examples

### Example

This example illustrates one usage of PutRolePolicy.

#### Sample Request

```
https://iam.amazonaws.com/?Action=PutRolePolicy
&RoleName=S3Access
&PolicyName=S3AccessPolicy
&PolicyDocument={"Version":"2012-10-17","Statement":
>{"Effect":"Allow","Action":"s3:*","Resource":"*"}
}
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<PutRolePolicyResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
<ResponseMetadata>
<RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
</ResponseMetadata>
</PutRolePolicyResponse>
```

### See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# PutUserPermissionsBoundary

Adds or updates the policy that is specified as the IAM user's permissions boundary. You can use an AWS managed policy or a customer managed policy to set the boundary for a user. Use the boundary to control the maximum permissions that the user can have. Setting a permissions boundary is an advanced feature that can affect the permissions for the user.

## Important

Policies that are used as permissions boundaries do not provide permissions. You must also attach a permissions policy to the user. To learn how the effective permissions for a user are evaluated, see [IAM JSON policy evaluation logic](#) in the IAM User Guide.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### PermissionsBoundary

The ARN of the policy that is used to set the permissions boundary for the user.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

### UserName

The name (friendly name, not ARN) of the IAM user for which you want to set the permissions boundary.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w+=, .@-]+`

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### InvalidInput

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

**PolicyNotAttachable**

The request failed because AWS service role policies can only be attached to the service-linked role for that service.

HTTP Status Code: 400

**ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# PutUserPolicy

Adds or updates an inline policy document that is embedded in the specified IAM user.

An IAM user can also have a managed policy attached to it. To attach a managed policy to a user, use [AttachUserPolicy \(p. 19\)](#). To create a new managed policy, use [CreatePolicy \(p. 43\)](#). For information about policies, see [Managed policies and inline policies](#) in the *IAM User Guide*.

For information about the maximum number of inline policies that you can embed in a user, see [IAM and AWS STS quotas](#) in the *IAM User Guide*.

## Note

Because policy documents can be large, you should use POST rather than GET when calling PutUserPolicy. For general information about using the Query API with IAM, see [Making query requests](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### PolicyDocument

The policy document.

You must provide policies in JSON format in IAM. However, for AWS CloudFormation templates formatted in YAML, you can provide the policy in JSON or YAML format. AWS CloudFormation always converts a YAML policy to JSON format before submitting it to IAM.

The [regex pattern](#) used to validate this parameter is a string of characters consisting of the following:

- Any printable ASCII character ranging from the space character (\u0020) through the end of the ASCII character range
- The printable characters in the Basic Latin and Latin-1 Supplement character set (through \u00FF)
- The special characters tab (\u0009), line feed (\u000A), and carriage return (\u000D)

Type: String

Length Constraints: Minimum length of 1. Maximum length of 131072.

Pattern: [\u0009\u000A\u000D\u0020-\u00FF]+

Required: Yes

### PolicyName

The name of the policy document.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: \_+=,.@-

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [\w+=,.@-]+

Required: Yes

#### **UserName**

The name of the user to associate the policy with.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

#### **LimitExceeded**

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

#### **MalformedPolicyDocument**

The request was rejected because the policy document was malformed. The error message describes the specific error.

HTTP Status Code: 400

#### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

#### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of PutUserPolicy.

#### Sample Request

```
https://iam.amazonaws.com/?Action=PutUserPolicy  
&UserName=Bob
```

```
&PolicyName=AllAccessPolicy
&PolicyDocument={"Version":"2012-10-17","Statement": [{"Effect":"Allow","Action":"*","Resource":"*"}]}
&Version=2010-05-08
&AUTHPARAMS
```

## Sample Response

```
<PutUserPolicyResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
<ResponseMetadata>
<RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
</ResponseMetadata>
</PutUserPolicyResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# RemoveClientIDFromOpenIDConnectProvider

Removes the specified client ID (also known as audience) from the list of client IDs registered for the specified IAM OpenID Connect (OIDC) provider resource object.

This operation is idempotent; it does not fail or return an error if you try to remove a client ID that does not exist.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### **ClientID**

The client ID (also known as audience) to remove from the IAM OIDC provider resource. For more information about client IDs, see [CreateOpenIDConnectProvider \(p. 39\)](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

### **OpenIDConnectProviderArn**

The Amazon Resource Name (ARN) of the IAM OIDC provider resource to remove the client ID from. You can get a list of OIDC provider ARNs by using the [ListOpenIDConnectProviders \(p. 265\)](#) operation.

For more information about ARNs, see [Amazon Resource Names \(ARNs\)](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **InvalidInput**

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of RemoveClientIDFromOpenIDConnectProvider.

#### Sample Request

```
https://iam.amazonaws.com/?Action=RemoveClientIDFromOpenIDConnectProvider
&ClientID=my-application-ID
&OpenIDConnectProviderArn=arn:aws:iam::123456789012:oidc-provider/server.example.com
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<RemoveClientIDFromOpenIDConnectProviderResponse xmlns="https://iam.amazonaws.com/
doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>1a5214df-4f67-11e4-aefa-bfd6aEXAMPLE</RequestId>
  </ResponseMetadata>
</RemoveClientIDFromOpenIDConnectProviderResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# RemoveRoleFromInstanceProfile

Removes the specified IAM role from the specified EC2 instance profile.

## Important

Make sure that you do not have any Amazon EC2 instances running with the role you are about to remove from the instance profile. Removing a role from an instance profile that is associated with a running instance might break any applications running on the instance.

For more information about IAM roles, see [Working with roles](#). For more information about instance profiles, see [About instance profiles](#).

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### InstanceProfileName

The name of the instance profile to update.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: Yes

### RoleName

The name of the role to remove.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w+=,.@-]+`

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### LimitExceeded

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

### UnmodifiableEntity

The request was rejected because only the service that depends on the service-linked role can modify or delete the role on your behalf. The error message includes the name of the service that depends on this service-linked role. You must request the change through that service.

HTTP Status Code: 400

## Examples

### Example

This example illustrates one usage of RemoveRoleFromInstanceProfile.

#### Sample Request

```
https://iam.amazonaws.com/?Action=RemoveRoleFromInstanceProfile
&InstanceProfileName=Webserver
&RoleName=S3Access
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<RemoveRoleFromInstanceProfileResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
<ResponseMetadata>
  <RequestId>29f47818-99f5-11e1-a4c3-27EXAMPLE804</RequestId>
</ResponseMetadata>
</RemoveRoleFromInstanceProfileResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

# RemoveUserFromGroup

Removes the specified user from the specified group.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### GroupName

The name of the group to update.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: Yes

### UserName

The name of the user to remove.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### LimitExceeded

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of RemoveUserFromGroup.

#### Sample Request

```
https://iam.amazonaws.com/?Action=RemoveUserFromGroup
&GroupName=Managers
&UserName=Bob
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<RemoveUserFromGroupResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
  </ResponseMetadata>
</RemoveUserFromGroupResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ResetServiceSpecificCredential

Resets the password for a service-specific credential. The new password is AWS generated and cryptographically strong. It cannot be configured by the user. Resetting the password immediately invalidates the previous password associated with this user.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### ServiceSpecificCredentialId

The unique identifier of the service-specific credential.

This parameter allows (through its [regex pattern](#)) a string of characters that can consist of any upper or lowercased letter or digit.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 128.

Pattern: `[\w]+`

Required: Yes

### UserName

The name of the IAM user associated with the service-specific credential. If this value is not specified, then the operation assumes the user whose credentials are used to call the operation.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w+=,.@-]+`

Required: No

## Response Elements

The following element is returned by the service.

### ServiceSpecificCredential

A structure with details about the updated service-specific credential, including the new password.

#### Important

This is the **only** time that you can access the password. You cannot recover the password later, but you can reset it again.

Type: [ServiceSpecificCredential \(p. 542\)](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

## Examples

### Example

The following example shows how to request a new password for an existing service-specific credential that is associated with a specific IAM user.

#### Sample Request

```
https://iam.amazonaws.com/?Action=ResetServiceSpecificCredential
&UserName=Jane
&ServiceSpecificCredentialId=ACCA12345ABCDEEXAMPLE
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<ResetServiceSpecificCredentialResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResetServiceSpecificCredentialResult>
    <ServiceSpecificCredential>
      <CreateDate>2016-10-15T20:56:46.012Z</CreateDate>
      <ServiceName>codecommit.amazonaws.com</ServiceName>
      <ServiceUserName>Jane-123456789012</ServiceUserName>
      <ServicePassword>wJalrXUtnFEMI/K7MDENGPxRfiCYzEXAMPLE</ServicePassword>
      <ServiceSpecificCredentialId>ACCA12345ABCDEEXAMPLE</ServiceSpecificCredentialId>
      <Status>Active</Status>
      <UserName>Jane</UserName>
    </ServiceSpecificCredential>
  </ResetServiceSpecificCredentialResult>
  <ResponseMetadata>
    <RequestId>EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE</RequestId>
  </ResponseMetadata>
</ResetServiceSpecificCredentialResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ResyncMFADevice

Synchronizes the specified MFA device with its IAM resource object on the AWS servers.

For more information about creating and working with virtual MFA devices, see [Using a virtual MFA device](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### **AuthenticationCode1**

An authentication code emitted by the device.

The format for this parameter is a sequence of six digits.

Type: String

Length Constraints: Fixed length of 6.

Pattern: [\d]+

Required: Yes

### **AuthenticationCode2**

A subsequent authentication code emitted by the device.

The format for this parameter is a sequence of six digits.

Type: String

Length Constraints: Fixed length of 6.

Pattern: [\d]+

Required: Yes

### **SerialNumber**

Serial number that uniquely identifies the MFA device.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: \_+=,.@-

Type: String

Length Constraints: Minimum length of 9. Maximum length of 256.

Pattern: [\w+=/:,.@-]+

Required: Yes

### **UserName**

The name of the user whose MFA device you want to resynchronize.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: \_+=,.@-

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [\w+=, .@-]+

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### InvalidAuthenticationCode

The request was rejected because the authentication code was not recognized. The error message describes the specific error.

HTTP Status Code: 403

### LimitExceeded

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of ResyncMFADevice.

### Sample Request

```
https://iam.amazonaws.com/?Action=ResyncMFADevice
&UserName=Bob
&SerialNumber=R1234
&AuthenticationCode1=234567
&AuthenticationCode2=987654
&Version=2010-05-08
&AUTHPARAMS
```

### Sample Response

```
<ResyncMFADeviceResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
```

```
<ResponseMetadata>
  <RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
</ResponseMetadata>
</ResyncMFADeviceResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# SetDefaultPolicyVersion

Sets the specified version of the specified policy as the policy's default (operative) version.

This operation affects all users, groups, and roles that the policy is attached to. To list the users, groups, and roles that the policy is attached to, use [ListEntitiesForPolicy \(p. 237\)](#).

For information about managed policies, see [Managed policies and inline policies](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### PolicyArn

The Amazon Resource Name (ARN) of the IAM policy whose default version you want to set.

For more information about ARNs, see [Amazon Resource Names \(ARNs\)](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

### VersionId

The version of the policy to set as the default (operative) version.

For more information about managed policy versions, see [Versioning for managed policies](#) in the *IAM User Guide*.

Type: String

Pattern: v[1-9][0-9]\*(\.[A-Za-z0-9-]\*)?

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### InvalidInput

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### LimitExceeded

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of SetDefaultPolicyVersion.

#### Sample Request

```
https://iam.amazonaws.com/?Action=SetDefaultPolicyVersion
&PolicyArn=arn:aws:iam::123456789012:policy/S3-read-only-example-bucket
&VersionId=v3
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<SetDefaultPolicyVersionResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
<ResponseMetadata>
  <RequestId>35f241af-3ebc-11e4-9d0d-6f969EXAMPLE</RequestId>
</ResponseMetadata>
</SetDefaultPolicyVersionResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# SetSecurityTokenServicePreferences

Sets the specified version of the global endpoint token as the token version used for the AWS account.

By default, AWS Security Token Service (AWS STS) is available as a global service, and all AWS STS requests go to a single endpoint at `https://sts.amazonaws.com`. AWS recommends using Regional AWS STS endpoints to reduce latency, build in redundancy, and increase session token availability. For information about Regional endpoints for AWS STS, see [AWS Security Token Service endpoints and quotas](#) in the *AWS General Reference*.

If you make an AWS STS call to the global endpoint, the resulting session tokens might be valid in some Regions but not others. It depends on the version that is set in this operation. Version 1 tokens are valid only in AWS Regions that are available by default. These tokens do not work in manually enabled Regions, such as Asia Pacific (Hong Kong). Version 2 tokens are valid in all Regions. However, version 2 tokens are longer and might affect systems where you temporarily store tokens. For information, see [Activating and deactivating AWS STS in an AWS Region](#) in the *IAM User Guide*.

To view the current session token version, see the `GlobalEndpointTokenVersion` entry in the response of the [GetAccountSummary \(p. 151\)](#) operation.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### **GlobalEndpointTokenVersion**

The version of the global endpoint token. Version 1 tokens are valid only in AWS Regions that are available by default. These tokens do not work in manually enabled Regions, such as Asia Pacific (Hong Kong). Version 2 tokens are valid in all Regions. However, version 2 tokens are longer and might affect systems where you temporarily store tokens.

For information, see [Activating and deactivating AWS STS in an AWS Region](#) in the *IAM User Guide*.

Type: String

Valid Values: `v1Token` | `v2Token`

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of `SetSecurityTokenServicePreferences`.

## Sample Request

```
https://iam.amazonaws.com/?Action=SetSecurityTokenServicePreferences
&GlobalEndpointTokenVersion=v2Token
&Version=2010-05-08
&AUTHPARAMS
```

## Sample Response

```
<SetSecurityTokenServicePreferences xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
<ResponseMetadata>
    <RequestId>31a241af-1ebc-12b4-9d0d-8f876EXAMPLE</RequestId>
</ResponseMetadata>
</SetSecurityTokenServicePreferences>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# SimulateCustomPolicy

Simulate how a set of IAM policies and optionally a resource-based policy works with a list of API operations and AWS resources to determine the policies' effective permissions. The policies are provided as strings.

The simulation does not perform the API operations; it only checks the authorization to determine if the simulated policies allow or deny the operations. You can simulate resources that don't exist in your account.

If you want to simulate existing policies that are attached to an IAM user, group, or role, use [SimulatePrincipalPolicy \(p. 365\)](#) instead.

Context keys are variables that are maintained by AWS and its services and which provide details about the context of an API query request. You can use the Condition element of an IAM policy to evaluate context keys. To get the list of context keys that the policies require for correct simulation, use [GetContextKeysForCustomPolicy \(p. 155\)](#).

If the output is long, you can use MaxItems and Marker parameters to paginate the results.

For more information about using the policy simulator, see [Testing IAM policies with the IAM policy simulator](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### ActionNames.member.N

A list of names of API operations to evaluate in the simulation. Each operation is evaluated against each resource. Each operation must include the service identifier, such as `iam:CreateUser`. This operation does not support using wildcards (\*) in an action name.

Type: Array of strings

Length Constraints: Minimum length of 3. Maximum length of 128.

Required: Yes

### CallerArn

The ARN of the IAM user that you want to use as the simulated caller of the API operations. `CallerArn` is required if you include a `ResourcePolicy` so that the policy's `Principal` element has a value to use in evaluating the policy.

You can specify only the ARN of an IAM user. You cannot specify the ARN of an assumed role, federated user, or a service principal.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

### ContextEntries.member.N

A list of context keys and corresponding values for the simulation to use. Whenever a context key is evaluated in one of the simulated IAM permissions policies, the corresponding value is supplied.

Type: Array of [ContextEntry \(p. 487\)](#) objects

Required: No

#### Marker

Use this parameter only when paginating results and only after you receive a response indicating that the results are truncated. Set it to the value of the `Marker` element in the response that you received to indicate where the next call should start.

Type: String

Length Constraints: Minimum length of 1.

Pattern: `[\u0020-\u00FF]+`

Required: No

#### MaxItems

Use this only when paginating results to indicate the maximum number of items you want in the response. If additional items exist beyond the maximum you specify, the `IsTruncated` response element is `true`.

If you do not include this parameter, the number of items defaults to 100. Note that IAM might return fewer results, even when there are more results available. In that case, the `IsTruncated` response element returns `true`, and `Marker` contains a value to include in the subsequent call that tells the service where to continue from.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

#### PermissionsBoundaryPolicyInputList.member.N

The IAM permissions boundary policy to simulate. The permissions boundary sets the maximum permissions that an IAM entity can have. You can input only one permissions boundary when you pass a policy to this operation. For more information about permissions boundaries, see [Permissions boundaries for IAM entities](#) in the *IAM User Guide*. The policy input is specified as a string that contains the complete, valid JSON text of a permissions boundary policy.

The maximum length of the policy document that you can pass in this operation, including whitespace, is listed below. To view the maximum character counts of a managed policy with no whitespaces, see [IAM and AWS STS character quotas](#).

The [regex pattern](#) used to validate this parameter is a string of characters consisting of the following:

- Any printable ASCII character ranging from the space character (`\u0020`) through the end of the ASCII character range
- The printable characters in the Basic Latin and Latin-1 Supplement character set (through `\u00FF`)
- The special characters tab (`\u0009`), line feed (`\u000A`), and carriage return (`\u000D`)

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 131072.

Pattern: `[\u0009\u000A\u000D\u0020-\u00FF]+`

Required: No

#### **PolicyInputList.member.N**

A list of policy documents to include in the simulation. Each document is specified as a string containing the complete, valid JSON text of an IAM policy. Do not include any resource-based policies in this parameter. Any resource-based policy must be submitted with the `ResourcePolicy` parameter. The policies cannot be "scope-down" policies, such as you could include in a call to [GetFederationToken](#) or one of the [AssumeRole](#) API operations. In other words, do not use policies designed to restrict what a user can do while using the temporary credentials.

The maximum length of the policy document that you can pass in this operation, including whitespace, is listed below. To view the maximum character counts of a managed policy with no whitespaces, see [IAM and AWS STS character quotas](#).

The [regex pattern](#) used to validate this parameter is a string of characters consisting of the following:

- Any printable ASCII character ranging from the space character (`\u0020`) through the end of the ASCII character range
- The printable characters in the Basic Latin and Latin-1 Supplement character set (through `\u00FF`)
- The special characters tab (`\u0009`), line feed (`\u000A`), and carriage return (`\u000D`)

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 131072.

Pattern: `[\u0009\u000A\u000D\u0020-\u00FF]+`

Required: Yes

#### **ResourceArns.member.N**

A list of ARNs of AWS resources to include in the simulation. If this parameter is not provided, then the value defaults to \* (all resources). Each API in the `ActionNames` parameter is evaluated for each resource in this list. The simulation determines the access result (allowed or denied) of each combination and reports it in the response. You can simulate resources that don't exist in your account.

The simulation does not automatically retrieve policies for the specified resources. If you want to include a resource policy in the simulation, then you must include the policy as a string in the `ResourcePolicy` parameter.

If you include a `ResourcePolicy`, then it must be applicable to all of the resources included in the simulation or you receive an invalid input error.

For more information about ARNs, see [Amazon Resource Names \(ARNs\)](#) in the [AWS General Reference](#).

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

#### **ResourceHandlingOption**

Specifies the type of simulation to run. Different API operations that support resource-based policies require different combinations of resources. By specifying the type of simulation to run, you enable the policy simulator to enforce the presence of the required resources to ensure reliable simulation

results. If your simulation does not match one of the following scenarios, then you can omit this parameter. The following list shows each of the supported scenario values and the resources that you must define to run the simulation.

Each of the EC2 scenarios requires that you specify instance, image, and security group resources. If your scenario includes an EBS volume, then you must specify that volume as a resource. If the EC2 scenario includes VPC, then you must supply the network interface resource. If it includes an IP subnet, then you must specify the subnet resource. For more information on the EC2 scenario options, see [Supported platforms](#) in the *Amazon EC2 User Guide*.

- **EC2-VPC-InstanceStore**

instance, image, security group, network interface

- **EC2-VPC-InstanceStore-Subnet**

instance, image, security group, network interface, subnet

- **EC2-VPC-EBS**

instance, image, security group, network interface, volume

- **EC2-VPC-EBS-Subnet**

instance, image, security group, network interface, subnet, volume

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

**ResourceOwner**

An ARN representing the AWS account ID that specifies the owner of any simulated resource that does not identify its owner in the resource ARN. Examples of resource ARNs include an S3 bucket or object. If `ResourceOwner` is specified, it is also used as the account owner of any `ResourcePolicy` included in the simulation. If the `ResourceOwner` parameter is not specified, then the owner of the resources and the resource policy defaults to the account of the identity provided in `CallerArn`. This parameter is required only if you specify a resource-based policy and account that owns the resource is different from the account that owns the simulated calling user `CallerArn`.

The ARN for an account uses the following syntax: `arn:aws:iam::AWS-account-ID:root`. For example, to represent the account with the 112233445566 ID, use the following ARN: `arn:aws:iam::112233445566-ID:root`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

**ResourcePolicy**

A resource-based policy to include in the simulation provided as a string. Each resource in the simulation is treated as if it had this policy attached. You can include only one resource-based policy in a simulation.

The maximum length of the policy document that you can pass in this operation, including whitespace, is listed below. To view the maximum character counts of a managed policy with no whitespaces, see [IAM and AWS STS character quotas](#).

The [regex pattern](#) used to validate this parameter is a string of characters consisting of the following:

- Any printable ASCII character ranging from the space character (\u0020) through the end of the ASCII character range
- The printable characters in the Basic Latin and Latin-1 Supplement character set (through \u00FF)
- The special characters tab (\u0009), line feed (\u000A), and carriage return (\u000D)

Type: String

Length Constraints: Minimum length of 1. Maximum length of 131072.

Pattern: [\u0009\u000A\u000D\u0020-\u00FF]+

Required: No

## Response Elements

The following elements are returned by the service.

### **EvaluationResults.member.N**

The results of the simulation.

Type: Array of [EvaluationResult \(p. 493\)](#) objects

### **IsTruncated**

A flag that indicates whether there are more items to return. If your results were truncated, you can make a subsequent pagination request using the Marker request parameter to retrieve more items. Note that IAM might return fewer than the MaxItems number of results even when there are more results available. We recommend that you check IsTruncated after every call to ensure that you receive all your results.

Type: Boolean

### **Marker**

When IsTruncated is true, this element is present and contains the value to use for the Marker parameter in a subsequent pagination request.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **InvalidInput**

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### **PolicyEvaluation**

The request failed because a provided policy could not be successfully evaluated. An additional detailed message indicates the source of the failure.

HTTP Status Code: 500

## Examples

### Example: Using Context Keys in a Policy Simulation

This example specifies a policy by string and supplies a ContextEntry to use for the context key that the policy references. Note that all parameters are shown in unencoded form here for clarity but must be URL encoded to be included as a part of a real HTML request. The results show that the policy allows s3>ListBucket access to the S3 bucket named teambucket.

#### Sample Request

```
https://iam.amazonaws.com/Action=SimulateCustomPolicy
&ActionNames.member.1=s3>ListBucket
&ResourceArns.member.1=arn:aws:s3:::teambucket
&ContextEntries.member.1.ContextKeyName=aws:MultiFactorAuthPresent
&ContextEntries.member.1.ContextKeyType=boolean
&ContextEntries.member.1.ContextKeyValues.member.1=true
&PermissionsBoundaryPolicyInputList.member.1={
  "Version":"2012-10-17",
  "Statement":{
    "Effect":"Deny",
    "Action":["iam:GetRole","iam:CreateRole","iam:DeleteRole"],
    "Resource": "*"
  }
}
&PolicyInputList.member.1={
  "Version":"2012-10-17",
  "Statement":{
    "Effect":"Allow",
    "Action":"s3>ListBucket",
    "Resource": "arn:aws:s3:::teambucket",
    "Condition":{
      "Bool": {"aws:MultiFactorAuthPresent": "true"}
    }
  }
}
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<SimulateCustomPolicyResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
<SimulateCustomPolicyResult>
  <IsTruncated>false</IsTruncated>
  <EvaluationResults>
    <member>
      <MatchedStatements>
        <member>
          <SourcePolicyId>PolicyInputList.1</SourcePolicyId>
          <StartPosition>
            <Column>4</Column>
            <Line>11</Line>
          </StartPosition>
          <EndPosition>
            <Column>16</Column>
            <Line>4</Line>
          </EndPosition>
        </member>
      </MatchedStatements>
    </member>
  </EvaluationResults>
</SimulateCustomPolicyResult>
</SimulateCustomPolicyResponse>
```

```
</MatchedStatements>
<MissingContextValues/>
<EvalResourceName>arn:aws:s3:::teambucket</EvalResourceName>
<EvalDecision>allowed</EvalDecision>
<EvalActionName>s3>ListBucket</EvalActionName>
</member>
</EvaluationResults>
</SimulateCustomPolicyResult>
<ResponseMetadata>
  <RequestId>1cdb5b0a-4c15-11e5-b121-bd8c7EXAMPLE</RequestId>
</ResponseMetadata>
</SimulateCustomPolicyResponse>
```

## Example: Same-Account Simulation

This example specifies an identity-based policy and a permissions boundary for the user Mateo. Both policies allow IAM actions only. However, a resource-based policy permits Mateo to perform the actions `s3:Put*` or `s3>List*` on the Production bucket. As a result, the simulation allows the action. Note that for same-account simulations where a resource ARN is specified, the `EvalDecisionDetails` parameter is returned, but the response is empty.

### Sample Request

```
https://iam.amazonaws.com/Action=SimulateCustomPolicy
&ActionNames.member.1=s3:PutObject
&CallerArn=arn:aws:iam::111122223333:user/mateo
&ResourceArns.member.1=arn:aws:s3:::production/Test
&ResourceOwner=arn:aws:iam::111122223333:root
&PermissionsBoundaryPolicyInputList.member.1='{
  "Version":"2012-10-17",
  "Statement":{
    "Effect":"Allow",
    "Action":["iam:*"],
    "Resource": "*"
  }
}'
&PolicyInputList.member.1='{
  "Version":"2012-10-17",
  "Statement":{
    "Effect":"Allow",
    "Action":["iam:*"],
    "Resource": "*"
  }
}'
&ResourcePolicy='{
  "Version":"2012-10-17",
  "Statement":{
    "Effect":"Allow",
    "Principal":["AWS":"arn:aws:iam::111122223333:user/mateo"]
    "Action":["s3>List*","s3:Put*"],
    "Resource": "arn:aws:s3:::production/*"
  }
}'
&Version=2010-05-08
&AUTHPARAMS
```

### Sample Response

```
<SimulateCustomPolicyResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <SimulateCustomPolicyResult>
    <IsTruncated>false</IsTruncated>
    <EvaluationResults>
```

```

<member>
  <EvalDecisionDetails/>
  <PermissionsBoundaryDecisionDetail>
    <AllowedByPermissionsBoundary>false</AllowedByPermissionsBoundary>
  </PermissionsBoundaryDecisionDetail>
  <MatchedStatements>
    <member>
      <SourcePolicyId>ResourcePolicy</SourcePolicyId>
      <EndPosition>
        <Column>259</Column>
        <Line>1</Line>
      </EndPosition>
      <SourcePolicyType>Resource Policy</SourcePolicyType>
      <StartPosition>
        <Column>68</Column>
        <Line>1</Line>
      </StartPosition>
    </member>
  </MatchedStatements>
  <MissingContextValues/>
  <EvalResourceName>arn:aws:s3:::production/Test</EvalResourceName>
  <EvalDecision>allowed</EvalDecision>
  <EvalActionName>s3:PutObject</EvalActionName>
  <ResourceSpecificResults>
    <member>
      <PermissionsBoundaryDecisionDetail>
        <AllowedByPermissionsBoundary>false</
AllowedByPermissionsBoundary>
      </PermissionsBoundaryDecisionDetail>
      <MatchedStatements>
        <member>
          <SourcePolicyId>ResourcePolicy</SourcePolicyId>
          <EndPosition>
            <Column>259</Column>
            <Line>1</Line>
          </EndPosition>
          <SourcePolicyType>Resource Policy</SourcePolicyType>
          <StartPosition>
            <Column>68</Column>
            <Line>1</Line>
          </StartPosition>
        </member>
      </MatchedStatements>
      <EvalResourceDecision>allowed</EvalResourceDecision>
      <MissingContextValues/>
      <EvalResourceName>arn:aws:s3:::production/Test</EvalResourceName>
    </member>
  </ResourceSpecificResults>
</member>
</EvaluationResults>
</SimulateCustomPolicyResult>
<ResponseMetadata>
  <RequestId>7b2092ca-5d35-499d-bc6d-e9b49EXAMPLE</RequestId>
</ResponseMetadata>
</SimulateCustomPolicyResponse>

```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# SimulatePrincipalPolicy

Simulate how a set of IAM policies attached to an IAM entity works with a list of API operations and AWS resources to determine the policies' effective permissions. The entity can be an IAM user, group, or role. If you specify a user, then the simulation also includes all of the policies that are attached to groups that the user belongs to. You can simulate resources that don't exist in your account.

You can optionally include a list of one or more additional policies specified as strings to include in the simulation. If you want to simulate only policies specified as strings, use [SimulateCustomPolicy \(p. 356\)](#) instead.

You can also optionally include one resource-based policy to be evaluated with each of the resources included in the simulation.

The simulation does not perform the API operations; it only checks the authorization to determine if the simulated policies allow or deny the operations.

**Note:** This operation discloses information about the permissions granted to other users. If you do not want users to see other user's permissions, then consider allowing them to use [SimulateCustomPolicy \(p. 356\)](#) instead.

Context keys are variables maintained by AWS and its services that provide details about the context of an API query request. You can use the Condition element of an IAM policy to evaluate context keys. To get the list of context keys that the policies require for correct simulation, use [GetContextKeysForPrincipalPolicy \(p. 158\)](#).

If the output is long, you can use the `MaxItems` and `Marker` parameters to paginate the results.

For more information about using the policy simulator, see [Testing IAM policies with the IAM policy simulator](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### ActionNames.member.N

A list of names of API operations to evaluate in the simulation. Each operation is evaluated for each resource. Each operation must include the service identifier, such as `iam:CreateUser`.

Type: Array of strings

Length Constraints: Minimum length of 3. Maximum length of 128.

Required: Yes

### CallerArn

The ARN of the IAM user that you want to specify as the simulated caller of the API operations. If you do not specify a `CallerArn`, it defaults to the ARN of the user that you specify in `PolicySourceArn`, if you specified a user. If you include both a `PolicySourceArn` (for example, `arn:aws:iam::123456789012:user/David`) and a `CallerArn` (for example, `arn:aws:iam::123456789012:user/Bob`), the result is that you simulate calling the API operations as Bob, as if Bob had David's policies.

You can specify only the ARN of an IAM user. You cannot specify the ARN of an assumed role, federated user, or a service principal.

**CallerArn** is required if you include a `ResourcePolicy` and the `PolicySourceArn` is not the ARN for an IAM user. This is required so that the resource-based policy's `Principal` element has a value to use in evaluating the policy.

For more information about ARNs, see [Amazon Resource Names \(ARNs\)](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

#### **ContextEntries.member.N**

A list of context keys and corresponding values for the simulation to use. Whenever a context key is evaluated in one of the simulated IAM permissions policies, the corresponding value is supplied.

Type: Array of [ContextEntry \(p. 487\)](#) objects

Required: No

#### **Marker**

Use this parameter only when paginating results and only after you receive a response indicating that the results are truncated. Set it to the value of the `Marker` element in the response that you received to indicate where the next call should start.

Type: String

Length Constraints: Minimum length of 1.

Pattern: [\u0020-\u00FF]+

Required: No

#### **MaxItems**

Use this only when paginating results to indicate the maximum number of items you want in the response. If additional items exist beyond the maximum you specify, the `IsTruncated` response element is `true`.

If you do not include this parameter, the number of items defaults to 100. Note that IAM might return fewer results, even when there are more results available. In that case, the `IsTruncated` response element returns `true`, and `Marker` contains a value to include in the subsequent call that tells the service where to continue from.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

#### **PermissionsBoundaryPolicyInputList.member.N**

The IAM permissions boundary policy to simulate. The permissions boundary sets the maximum permissions that the entity can have. You can input only one permissions boundary when you pass a policy to this operation. An IAM entity can only have one permissions boundary in effect at a time. For example, if a permissions boundary is attached to an entity and you pass in a different permissions boundary policy using this parameter, then the new permissions boundary policy is used for the simulation. For more information about permissions boundaries, see [Permissions boundaries for IAM entities](#) in the *IAM User Guide*. The policy input is specified as a string containing the complete, valid JSON text of a permissions boundary policy.

The maximum length of the policy document that you can pass in this operation, including whitespace, is listed below. To view the maximum character counts of a managed policy with no whitespaces, see [IAM and AWS STS character quotas](#).

The [regex pattern](#) used to validate this parameter is a string of characters consisting of the following:

- Any printable ASCII character ranging from the space character (\u0020) through the end of the ASCII character range
- The printable characters in the Basic Latin and Latin-1 Supplement character set (through \u00FF)
- The special characters tab (\u0009), line feed (\u000A), and carriage return (\u000D)

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 131072.

Pattern: [\u0009\u000A\u000D\u0020-\u00FF]+

Required: No

#### **PolicyInputList.member.N**

An optional list of additional policy documents to include in the simulation. Each document is specified as a string containing the complete, valid JSON text of an IAM policy.

The [regex pattern](#) used to validate this parameter is a string of characters consisting of the following:

- Any printable ASCII character ranging from the space character (\u0020) through the end of the ASCII character range
- The printable characters in the Basic Latin and Latin-1 Supplement character set (through \u00FF)
- The special characters tab (\u0009), line feed (\u000A), and carriage return (\u000D)

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 131072.

Pattern: [\u0009\u000A\u000D\u0020-\u00FF]+

Required: No

#### **PolicySourceArn**

The Amazon Resource Name (ARN) of a user, group, or role whose policies you want to include in the simulation. If you specify a user, group, or role, the simulation includes all policies that are associated with that entity. If you specify a user, the simulation also includes all policies that are attached to any groups the user belongs to.

The maximum length of the policy document that you can pass in this operation, including whitespace, is listed below. To view the maximum character counts of a managed policy with no whitespaces, see [IAM and AWS STS character quotas](#).

For more information about ARNs, see [Amazon Resource Names \(ARNs\)](#) in the [AWS General Reference](#).

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

### **ResourceArns.member.N**

A list of ARNs of AWS resources to include in the simulation. If this parameter is not provided, then the value defaults to \* (all resources). Each API in the ActionNames parameter is evaluated for each resource in this list. The simulation determines the access result (allowed or denied) of each combination and reports it in the response. You can simulate resources that don't exist in your account.

The simulation does not automatically retrieve policies for the specified resources. If you want to include a resource policy in the simulation, then you must include the policy as a string in the ResourcePolicy parameter.

For more information about ARNs, see [Amazon Resource Names \(ARNs\)](#) in the *AWS General Reference*.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

### **ResourceHandlingOption**

Specifies the type of simulation to run. Different API operations that support resource-based policies require different combinations of resources. By specifying the type of simulation to run, you enable the policy simulator to enforce the presence of the required resources to ensure reliable simulation results. If your simulation does not match one of the following scenarios, then you can omit this parameter. The following list shows each of the supported scenario values and the resources that you must define to run the simulation.

Each of the EC2 scenarios requires that you specify instance, image, and security group resources. If your scenario includes an EBS volume, then you must specify that volume as a resource. If the EC2 scenario includes VPC, then you must supply the network interface resource. If it includes an IP subnet, then you must specify the subnet resource. For more information on the EC2 scenario options, see [Supported platforms](#) in the *Amazon EC2 User Guide*.

- **EC2-VPC-InstanceStore**

instance, image, security group, network interface

- **EC2-VPC-InstanceStore-Subnet**

instance, image, security group, network interface, subnet

- **EC2-VPC-EBS**

instance, image, security group, network interface, volume

- **EC2-VPC-EBS-Subnet**

instance, image, security group, network interface, subnet, volume

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

### **ResourceOwner**

An AWS account ID that specifies the owner of any simulated resource that does not identify its owner in the resource ARN. Examples of resource ARNs include an S3 bucket or object. If ResourceOwner is specified, it is also used as the account owner of any ResourcePolicy included in the simulation. If the ResourceOwner parameter is not specified, then the owner of the resources

and the resource policy defaults to the account of the identity provided in `CallerArn`. This parameter is required only if you specify a resource-based policy and account that owns the resource is different from the account that owns the simulated calling user `CallerArn`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

#### **ResourcePolicy**

A resource-based policy to include in the simulation provided as a string. Each resource in the simulation is treated as if it had this policy attached. You can include only one resource-based policy in a simulation.

The maximum length of the policy document that you can pass in this operation, including whitespace, is listed below. To view the maximum character counts of a managed policy with no whitespaces, see [IAM and AWS STS character quotas](#).

The [regex pattern](#) used to validate this parameter is a string of characters consisting of the following:

- Any printable ASCII character ranging from the space character (\u0020) through the end of the ASCII character range
- The printable characters in the Basic Latin and Latin-1 Supplement character set (through \u00FF)
- The special characters tab (\u0009), line feed (\u000A), and carriage return (\u000D)

Type: String

Length Constraints: Minimum length of 1. Maximum length of 131072.

Pattern: [\u0009\u000A\u000D\u0020-\u00FF]+

Required: No

## Response Elements

The following elements are returned by the service.

#### **EvaluationResults.member.N**

The results of the simulation.

Type: Array of [EvaluationResult](#) (p. 493) objects

#### **IsTruncated**

A flag that indicates whether there are more items to return. If your results were truncated, you can make a subsequent pagination request using the `Marker` request parameter to retrieve more items. Note that IAM might return fewer than the `MaxItems` number of results even when there are more results available. We recommend that you check `IsTruncated` after every call to ensure that you receive all your results.

Type: Boolean

#### **Marker**

When `IsTruncated` is `true`, this element is present and contains the value to use for the `Marker` parameter in a subsequent pagination request.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### InvalidInput

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### PolicyEvaluation

The request failed because a provided policy could not be successfully evaluated. An additional detailed message indicates the source of the failure.

HTTP Status Code: 500

## Examples

### Example: Simulating a Policy

This example simulates calling the Amazon S3 API operations `GetObject`, `PutObject`, and `DeleteObject` for a specific S3 bucket. The simulation includes all policies that are attached to the user Jill. In this example, the user Jill has only the managed policy "AmazonS3ReadOnlyAccess" attached. Note that all parameters are shown in unencoded form here for clarity but must be URL encoded to be included as a part of a real HTML request. In the results, the simulation shows that Jill can add new files to the bucket because of the additional policy specified as a string parameter. In addition, she can read from the bucket because of the managed policy attached to the user. However, she cannot delete anything from the S3 bucket because of the default `implicitDeny`.

#### Sample Request

```
https://iam.amazonaws.com/Action=SimulatePrincipalPolicy
&ActionNames.member.1=s3:PutObject
&ActionNames.member.2=s3:GetObject
&ActionNames.member.3=s3:DeleteObject
&ResourceArns.member.1="arn:aws:s3:::my-test-bucket"
&PolicySourceArn=arn:aws:iam::user/Jill
&PolicyInputList.member.1='{
  "Version": "2012-10-17",
  "Statement": {
    "Effect": "Allow",
    "Action": "s3:PutObject",
    "Resource": "arn:aws:s3:::my-test-bucket"
  }
}'
```

```
}'
&Version=2010-05-08
&AUTHPARAMS
```

## Sample Response

```
<SimulatePrincipalPolicyResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <SimulatePrincipalPolicyResult>
    <IsTruncated>false</IsTruncated>
    <EvaluationResults>
      <member>
        <MatchedStatements>
          <member>
            <SourcePolicyId>PolicyInputList.1</SourcePolicyId>
            <StartPosition>
              <Column>4</Column>
              <Line>7</Line>
            </StartPosition>
            <EndPosition>
              <Column>16</Column>
              <Line>3</Line>
            </EndPosition>
          </member>
        </MatchedStatements>
        <MissingContextValues/>
        <EvalResourceName>arn:aws:s3:::my-test-bucket</EvalResourceName>
        <EvalDecision>allowed</EvalDecision>
        <EvalActionName>s3:PutObject</EvalActionName>
      </member>
      <member>
        <MatchedStatements>
          <member>
            <SourcePolicyId>AmazonS3ReadOnlyAccess</SourcePolicyId>
            <StartPosition>
              <Column>6</Column>
              <Line>11</Line>
            </StartPosition>
            <EndPosition>
              <Column>17</Column>
              <Line>3</Line>
            </EndPosition>
          </member>
        </MatchedStatements>
        <MissingContextValues/>
        <EvalResourceName>arn:aws:s3:::my-test-bucket</EvalResourceName>
        <EvalDecision>allowed</EvalDecision>
        <EvalActionName>s3:GetObject</EvalActionName>
      </member>
      <member>
        <MatchedStatements/>
        <MissingContextValues/>
        <EvalResourceName>arn:aws:s3:::my-test-bucket</EvalResourceName>
        <EvalDecision>implicitDeny</EvalDecision>
        <EvalActionName>s3:DeleteObject</EvalActionName>
      </member>
    </EvaluationResults>
  </SimulatePrincipalPolicyResult>
  <ResponseMetadata>
    <RequestId>004d7059-4c14-11e5-b121-bd8c7EXAMPLE</RequestId>
  </ResponseMetadata>
</SimulatePrincipalPolicyResponse>
```

## Example: Same-Account Simulation

This example evaluates policies in the same account only. The simulated user Mateo has an identity-based policy attached that allows the `iam:GetRole` action. The permissions boundary policy specified in the simulation allows all IAM and S3 actions. Note that for same-account simulations where a resource ARN is specified, the `EvalDecisionDetails` parameter is returned, but the response is empty.

### Sample Request

```
https://iam.amazonaws.com/Action=SimulatePrincipalPolicy
&ActionNames.member.1=iam:GetRole
&ResourceArns.member.1="arn:aws:iam::111122223333:role/pol-sim-test"
&PolicySourceArn=arn:aws:iam::111122223333:user/mateo
&PermissionsBoundaryPolicyInputList.member.1='{
    "Version":"2012-10-17",
    "Statement":{
        "Effect":"Allow",
        "Action":["iam:*","s3:*"],
        "Resource": "*"
    }
}'
&Version=2010-05-08
&AUTHPARAMS
```

### Sample Response

```
<SimulatePrincipalPolicyResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <SimulatePrincipalPolicyResult>
    <IsTruncated>false</IsTruncated>
    <EvaluationResults>
      <member>
        <EvalDecisionDetails/>
        <PermissionsBoundaryDecisionDetail>
          <AllowedByPermissionsBoundary>true</AllowedByPermissionsBoundary>
        </PermissionsBoundaryDecisionDetail>
        <MatchedStatements>
          <member>
            <SourcePolicyId>user_admin_AdminUser</SourcePolicyId>
            <EndPosition>
              <Column>84</Column>
              <Line>1</Line>
            </EndPosition>
            <SourcePolicyType>IAM Policy</SourcePolicyType>
            <StartPosition>
              <Column>38</Column>
              <Line>1</Line>
            </StartPosition>
          </member>
        </MatchedStatements>
        <MissingContextValues/>
        <EvalResourceName>arn:aws:iam::111122223333:role/pol-sim-test</EvalResourceName>
        <EvalDecision>allowed</EvalDecision>
        <EvalActionName>iam:GetRole</EvalActionName>
        <ResourceSpecificResults>
          <member>
            <PermissionsBoundaryDecisionDetail>
              <AllowedByPermissionsBoundary>true</AllowedByPermissionsBoundary>
            </PermissionsBoundaryDecisionDetail>
          </member>
        </ResourceSpecificResults>
      </member>
    </EvaluationResults>
  </SimulatePrincipalPolicyResult>
</SimulatePrincipalPolicyResponse>
```

```

<member>
  <SourcePolicyId>user_admin_AdminUser</SourcePolicyId>
  <EndPosition>
    <Column>84</Column>
    <Line>1</Line>
  </EndPosition>
  <SourcePolicyType>IAM Policy</SourcePolicyType>
  <StartPosition>
    <Column>38</Column>
    <Line>1</Line>
  </StartPosition>
</member>
</MatchedStatements>
<EvalResourceDecision>allowed</EvalResourceDecision>
<MissingContextValues/>
<EvalResourceName>arn:aws:iam::111122223333:role/pol-sim-test</
EvalResourceName>
</member>
</ResourceSpecificResults>
</member>
</EvaluationResults>
</SimulatePrincipalPolicyResult>
<ResponseMetadata>
  <RequestId>896e97bd-ff20-47d0-9f91-5d696EXAMPLE</RequestId>
</ResponseMetadata>
</SimulatePrincipalPolicyResponse>

```

## Example: Cross-Account Simulation

This example is for a simulation that evaluates policies in two accounts. The resource-based policy allows the `s3:PutObject` action for the user Arnav on Mary's bucket in Account 2. However, the overall result of the simulation for the action is implicitly denied. Arnav's identity-based policy in Account 1 does not allow the action. Additionally, the permissions boundary set for Arnav in Account 1 does not allow S3 actions. The results of each of the policy types included in the simulation is returned in the `EvalDecisionDetails` parameter.

### Sample Request

```

https://iam.amazonaws.com/Action=SimulatePrincipalPolicy
&ActionNames.member.1=s3:PutObject
&ResourceArns.member.1="arn:aws:s3:::mary/Test"
&ResourceOwner=arn:aws:iam::123456789012:root
&PolicySourceArn=arn:aws:iam::44445556666:user/arnav
&PermissionsBoundaryPolicyInputList.member.1='{
  "Version":"2012-10-17",
  "Statement":{
    "Effect":"Allow",
    "Action": {"iam:*"},
    "Resource": {"*"}
  }
}'
&ResourcePolicy='{
  "Version":"2012-10-17",
  "Statement":{
    "Effect":"Allow",
    "Principal": {"AWS": "arn:aws:iam::44445556666:user/arnav"},
    "Action": {"s3>List*","s3:Put*"},
    "Resource": {"arn:aws:s3:::mary/*"}
  }
}'
&Version=2010-05-08
&AUTHPARAMS

```

## Sample Response

```
SimulatePrincipalPolicyResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">  <SimulatePrincipalPolicyResult>    <IsTruncated>false</IsTruncated>    <EvaluationResults>      <member>        <EvalDecisionDetails>          <entry>            <key>IAM Policy</key>            <value>implicitDeny</value>          </entry>          <entry>            <key>Resource Policy</key>            <value>allowed</value>          </entry>          <entry>            <key>Permissions Boundary Policy</key>            <value>implicitDeny</value>          </entry>        </EvalDecisionDetails>        <PermissionsBoundaryDecisionDetail>          <AllowedByPermissionsBoundary>false</AllowedByPermissionsBoundary>        </PermissionsBoundaryDecisionDetail>        <MatchedStatements/>        <MissingContextValues/>        <EvalResourceName>arn:aws:s3:::mary/Test</EvalResourceName>        <EvalDecision>implicitDeny</EvalDecision>        <EvalActionName>s3:PutObject</EvalActionName>        <ResourceSpecificResults>          <member>            <EvalDecisionDetails>              <entry>                <key>Permissions Boundary Policy</key>                <value>implicitDeny</value>              </entry>              <entry>                <key>IAM Policy</key>                <value>implicitDeny</value>              </entry>              <entry>                <key>Resource Policy</key>                <value>allowed</value>              </entry>            </EvalDecisionDetails>            <PermissionsBoundaryDecisionDetail>              <AllowedByPermissionsBoundary>false</AllowedByPermissionsBoundary>          </ResourceSpecificResults>          <member>            <SourcePolicyId>ResourcePolicy</SourcePolicyId>            <StartPosition>              <Column>259</Column>              <Line>1</Line>            </StartPosition>            <SourcePolicyType>Resource Policy</SourcePolicyType>            <StartPosition>              <Column>68</Column>              <Line>1</Line>            </StartPosition>          </member>        </MatchedStatements>        <EvalResourceDecision>implicitDeny</EvalResourceDecision>        <MissingContextValues/>    </EvaluationResults>  </SimulatePrincipalPolicyResult>
```

```
        <EvalResourceName>arn:aws:s3:::mary/Test</EvalResourceName>
        </member>
    </ResourceSpecificResults>
</member>
</EvaluationResults>
</SimulatePrincipalPolicyResult>
<ResponseMetadata>
    <RequestId>3ebb073c-781a-437e-81a9-2a88eEXAMPLE</RequestId>
</ResponseMetadata>
</SimulatePrincipalPolicyResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# TagInstanceProfile

Adds one or more tags to an IAM instance profile. If a tag with the same key name already exists, then that tag is overwritten with the new value.

Each tag consists of a key name and an associated value. By assigning tags to your resources, you can do the following:

- **Administrative grouping and discovery** - Attach tags to resources to aid in organization and search. For example, you could search for all resources with the key name *Project* and the value *MyImportantProject*. Or search for all resources with the key name *Cost Center* and the value *41200*.
- **Access control** - Include tags in IAM user-based and resource-based policies. You can use tags to restrict access to only an IAM instance profile that has a specified tag attached. For examples of policies that show how to use tags to control access, see [Control access using IAM tags](#) in the *IAM User Guide*.

## Note

- If any one of the tags is invalid or if you exceed the allowed maximum number of tags, then the entire request fails and the resource is not created. For more information about tagging, see [Tagging IAM resources](#) in the *IAM User Guide*.
- AWS always interprets the tag Value as a single string. If you need to store an array, you can store comma-separated values in the string. However, you must interpret the value in your code.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### InstanceProfileName

The name of the IAM instance profile to which you want to add tags.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: Yes

### Tags.member.N

The list of tags that you want to attach to the IAM instance profile. Each tag consists of a key name and an associated value.

Type: Array of [Tag \(p. 553\)](#) objects

Array Members: Maximum number of 50 items.

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### ConcurrentModification

The request was rejected because multiple requests to change this object were submitted simultaneously. Wait a few minutes and submit your request again.

HTTP Status Code: 409

### InvalidInput

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### LimitExceeded

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

The following example is formatted with line breaks for legibility.

The following example shows how to add tags to an existing instance profile.

### Sample Request

```
POST / HTTP/1.1
Host: https://iam.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.11.143 Python/3.6.1 Linux/3.2.45-0.6.wd.865.49.315.metal1.x86_64
botocore/1.7.1
X-Amz-Date: 20170929T181747Z
Authorization: <auth details>
Content-Length: 99
Content-Type: application/x-www-form-urlencoded

Action=TagInstanceProfile&Version=2010-05-08&InstanceProfileName=Webserver
&Tags.member.1.Key=Dept&Tags.member.1.Value=Accounting
```

```
&Tags.member.2.Key=Cost Center&Tags.member.2.Value=12345
```

## Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE
Content-Type: text/xml
Content-Length: 194
Date: Fri, 29 Sep 2017 18:17:47 GMT

<TagInstanceProfileResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE</RequestId>
  </ResponseMetadata>
</TagInstanceProfileResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# TagMFADevice

Adds one or more tags to an IAM virtual multi-factor authentication (MFA) device. If a tag with the same key name already exists, then that tag is overwritten with the new value.

A tag consists of a key name and an associated value. By assigning tags to your resources, you can do the following:

- **Administrative grouping and discovery** - Attach tags to resources to aid in organization and search. For example, you could search for all resources with the key name *Project* and the value *MyImportantProject*. Or search for all resources with the key name *Cost Center* and the value *41200*.
- **Access control** - Include tags in IAM user-based and resource-based policies. You can use tags to restrict access to only an IAM virtual MFA device that has a specified tag attached. For examples of policies that show how to use tags to control access, see [Control access using IAM tags](#) in the *IAM User Guide*.

## Note

- If any one of the tags is invalid or if you exceed the allowed maximum number of tags, then the entire request fails and the resource is not created. For more information about tagging, see [Tagging IAM resources](#) in the *IAM User Guide*.
- AWS always interprets the tag Value as a single string. If you need to store an array, you can store comma-separated values in the string. However, you must interpret the value in your code.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### SerialNumber

The unique identifier for the IAM virtual MFA device to which you want to add tags. For virtual MFA devices, the serial number is the same as the ARN.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 9. Maximum length of 256.

Pattern: `[\w+=/:,.@-]+`

Required: Yes

### Tags.member.N

The list of tags that you want to attach to the IAM virtual MFA device. Each tag consists of a key name and an associated value.

Type: Array of [Tag \(p. 553\)](#) objects

Array Members: Maximum number of 50 items.

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### ConcurrentModification

The request was rejected because multiple requests to change this object were submitted simultaneously. Wait a few minutes and submit your request again.

HTTP Status Code: 409

### InvalidInput

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### LimitExceeded

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

The following example is formatted with line breaks for legibility.

The following example shows how to add tags to an existing virtual MFA device.

### Sample Request

```
POST / HTTP/1.1
Host: https://iam.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.11.143 Python/3.6.1 Linux/3.2.45-0.6.wd.865.49.315.metal1.x86_64
botocore/1.7.1
X-Amz-Date: 20170929T181747Z
Authorization: <auth details>
Content-Length: 99
Content-Type: application/x-www-form-urlencoded

Action=TagMFADevice&Version=2010-05-08&SerialNumber=arn:aws:iam::123456789012:mfa/
ExampleName
&Tags.member.1.Key=Dept&Tags.member.1.Value=Accounting
```

```
&Tags.member.2.Key=Cost Center&Tags.member.2.Value=12345
```

## Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE
Content-Type: text/xml
Content-Length: 194
Date: Fri, 29 Sep 2017 18:17:47 GMT

<TagMFADeviceResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE</RequestId>
  </ResponseMetadata>
</TagMFADeviceResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# TagOpenIDConnectProvider

Adds one or more tags to an OpenID Connect (OIDC)-compatible identity provider. For more information about these providers, see [About web identity federation](#). If a tag with the same key name already exists, then that tag is overwritten with the new value.

A tag consists of a key name and an associated value. By assigning tags to your resources, you can do the following:

- **Administrative grouping and discovery** - Attach tags to resources to aid in organization and search. For example, you could search for all resources with the key name *Project* and the value *MyImportantProject*. Or search for all resources with the key name *Cost Center* and the value *41200*.
- **Access control** - Include tags in IAM user-based and resource-based policies. You can use tags to restrict access to only an OIDC provider that has a specified tag attached. For examples of policies that show how to use tags to control access, see [Control access using IAM tags](#) in the *IAM User Guide*.

## Note

- If any one of the tags is invalid or if you exceed the allowed maximum number of tags, then the entire request fails and the resource is not created. For more information about tagging, see [Tagging IAM resources](#) in the *IAM User Guide*.
- AWS always interprets the tag Value as a single string. If you need to store an array, you can store comma-separated values in the string. However, you must interpret the value in your code.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### OpenIDConnectProviderArn

The ARN of the OIDC identity provider in IAM to which you want to add tags.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

### Tags.member.N

The list of tags that you want to attach to the OIDC identity provider in IAM. Each tag consists of a key name and an associated value.

Type: Array of [Tag \(p. 553\)](#) objects

Array Members: Maximum number of 50 items.

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### ConcurrentModification

The request was rejected because multiple requests to change this object were submitted simultaneously. Wait a few minutes and submit your request again.

HTTP Status Code: 409

### InvalidInput

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### LimitExceeded

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

The following example is formatted with line breaks for legibility.

The following example shows how to add tags to an existing OIDC provider.

### Sample Request

```
POST / HTTP/1.1
Host: https://iam.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.11.143 Python/3.6.1 Linux/3.2.45-0.6.wd.865.49.315.metal1.x86_64
botocore/1.7.1
X-Amz-Date: 20170929T181747Z
Authorization: <auth details>
Content-Length: 99
Content-Type: application/x-www-form-urlencoded

Action=TagOpenIDConnectProvider&Version=2010-05-08&OpenIDConnectProviderArn=arn:aws:iam::123456789012:provider/GoogleProvider
&Tags.member.1.Key=Dept&Tags.member.1.Value=Accounting
```

```
&Tags.member.2.Key=Cost Center&Tags.member.2.Value=12345
```

## Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE
Content-Type: text/xml
Content-Length: 194
Date: Fri, 29 Sep 2017 18:17:47 GMT

<TagOpenIDConnectProviderResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE</RequestId>
  </ResponseMetadata>
</TagOpenIDConnectProviderResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# TagPolicy

Adds one or more tags to an IAM customer managed policy. If a tag with the same key name already exists, then that tag is overwritten with the new value.

A tag consists of a key name and an associated value. By assigning tags to your resources, you can do the following:

- **Administrative grouping and discovery** - Attach tags to resources to aid in organization and search. For example, you could search for all resources with the key name *Project* and the value *MyImportantProject*. Or search for all resources with the key name *Cost Center* and the value *41200*.
- **Access control** - Include tags in IAM user-based and resource-based policies. You can use tags to restrict access to only an IAM customer managed policy that has a specified tag attached. For examples of policies that show how to use tags to control access, see [Control access using IAM tags](#) in the *IAM User Guide*.

## Note

- If any one of the tags is invalid or if you exceed the allowed maximum number of tags, then the entire request fails and the resource is not created. For more information about tagging, see [Tagging IAM resources](#) in the *IAM User Guide*.
- AWS always interprets the tag Value as a single string. If you need to store an array, you can store comma-separated values in the string. However, you must interpret the value in your code.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### PolicyArn

The ARN of the IAM customer managed policy to which you want to add tags.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

### Tags.member.N

The list of tags that you want to attach to the IAM customer managed policy. Each tag consists of a key name and an associated value.

Type: Array of [Tag \(p. 553\)](#) objects

Array Members: Maximum number of 50 items.

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### ConcurrentModification

The request was rejected because multiple requests to change this object were submitted simultaneously. Wait a few minutes and submit your request again.

HTTP Status Code: 409

### InvalidInput

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### LimitExceeded

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

The following example is formatted with line breaks for legibility.

The following example shows how to add tags to an existing policy.

### Sample Request

```
POST / HTTP/1.1
Host: https://iam.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.11.143 Python/3.6.1 Linux/3.2.45-0.6.wd.865.49.315.metal1.x86_64
botocore/1.7.1
X-Amz-Date: 20170929T181747Z
Authorization: <auth details>
Content-Length: 99
Content-Type: application/x-www-form-urlencoded

Action=TagPolicy&Version=2010-05-08&PolicyArn=arn:aws:iam::123456789012:policy/
UsersManageOwnCredentials
&Tags.member.1.Key=Dept&Tags.member.1.Value=Accounting
```

```
&Tags.member.2.Key=Cost Center&Tags.member.2.Value=12345
```

## Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE
Content-Type: text/xml
Content-Length: 194
Date: Fri, 29 Sep 2017 18:17:47 GMT

<TagPolicyResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE</RequestId>
  </ResponseMetadata>
</TagPolicyResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## TagRole

Adds one or more tags to an IAM role. The role can be a regular role or a service-linked role. If a tag with the same key name already exists, then that tag is overwritten with the new value.

A tag consists of a key name and an associated value. By assigning tags to your resources, you can do the following:

- **Administrative grouping and discovery** - Attach tags to resources to aid in organization and search. For example, you could search for all resources with the key name *Project* and the value *MyImportantProject*. Or search for all resources with the key name *Cost Center* and the value *41200*.
- **Access control** - Include tags in IAM user-based and resource-based policies. You can use tags to restrict access to only an IAM role that has a specified tag attached. You can also restrict access to only those resources that have a certain tag attached. For examples of policies that show how to use tags to control access, see [Control access using IAM tags](#) in the *IAM User Guide*.
- **Cost allocation** - Use tags to help track which individuals and teams are using which AWS resources.

### Note

- If any one of the tags is invalid or if you exceed the allowed maximum number of tags, then the entire request fails and the resource is not created. For more information about tagging, see [Tagging IAM resources](#) in the *IAM User Guide*.
- AWS always interprets the tag Value as a single string. If you need to store an array, you can store comma-separated values in the string. However, you must interpret the value in your code.

For more information about tagging, see [Tagging IAM identities](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### RoleName

The name of the IAM role to which you want to add tags.

This parameter accepts (through its [regex pattern](#)) a string of characters that consist of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w+=,.@-]+`

Required: Yes

### Tags.member.N

The list of tags that you want to attach to the IAM role. Each tag consists of a key name and an associated value.

Type: Array of [Tag \(p. 553\)](#) objects

Array Members: Maximum number of 50 items.

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### ConcurrentModification

The request was rejected because multiple requests to change this object were submitted simultaneously. Wait a few minutes and submit your request again.

HTTP Status Code: 409

### InvalidInput

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### LimitExceeded

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

The following example is formatted with line breaks for legibility.

The following example shows how to add tags to an existing role.

### Sample Request

```
POST / HTTP/1.1
Host: https://iam.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.11.143 Python/3.6.1 Linux/3.2.45-0.6.wd.865.49.315.metal1.x86_64
botocore/1.7.1
X-Amz-Date: 20170929T180252Z
Authorization: <auth details>
Content-Length: 97
Content-Type: application/x-www-form-urlencoded
```

```
Action=TagRole&Version=2010-05-08&RoleName=taggedrole
&Tags.member.1.Key=Dept&Tags.member.1.Value=Accounting
&Tags.member.2.Key=Cost Center&Tags.member.2.Value=12345
```

## Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE
Content-Type: text/xml
Content-Length: 194
Date: Fri, 29 Sep 2017 18:02:51 GMT

<TagRoleResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE</RequestId>
  </ResponseMetadata>
</TagRoleResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# TagSAMLProvider

Adds one or more tags to a Security Assertion Markup Language (SAML) identity provider. For more information about these providers, see [About SAML 2.0-based federation](#). If a tag with the same key name already exists, then that tag is overwritten with the new value.

A tag consists of a key name and an associated value. By assigning tags to your resources, you can do the following:

- **Administrative grouping and discovery** - Attach tags to resources to aid in organization and search. For example, you could search for all resources with the key name *Project* and the value *MyImportantProject*. Or search for all resources with the key name *Cost Center* and the value *41200*.
- **Access control** - Include tags in IAM user-based and resource-based policies. You can use tags to restrict access to only a SAML identity provider that has a specified tag attached. For examples of policies that show how to use tags to control access, see [Control access using IAM tags](#) in the *IAM User Guide*.

## Note

- If any one of the tags is invalid or if you exceed the allowed maximum number of tags, then the entire request fails and the resource is not created. For more information about tagging, see [Tagging IAM resources](#) in the *IAM User Guide*.
- AWS always interprets the tag Value as a single string. If you need to store an array, you can store comma-separated values in the string. However, you must interpret the value in your code.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### SAMLProviderArn

The ARN of the SAML identity provider in IAM to which you want to add tags.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

### Tags.member.N

The list of tags that you want to attach to the SAML identity provider in IAM. Each tag consists of a key name and an associated value.

Type: Array of [Tag \(p. 553\)](#) objects

Array Members: Maximum number of 50 items.

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### ConcurrentModification

The request was rejected because multiple requests to change this object were submitted simultaneously. Wait a few minutes and submit your request again.

HTTP Status Code: 409

### InvalidInput

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### LimitExceeded

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

The following example is formatted with line breaks for legibility.

The following example shows how to add tags to an existing SAML identity provider.

### Sample Request

```
POST / HTTP/1.1
Host: https://iam.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.11.143 Python/3.6.1 Linux/3.2.45-0.6.wd.865.49.315.metal1.x86_64
botocore/1.7.1
X-Amz-Date: 20170929T181747Z
Authorization: <auth details>
Content-Length: 99
Content-Type: application/x-www-form-urlencoded

Action=TagSAMLProvider&Version=2010-05-08&SAMLProviderArn=arn:aws:iam::123456789012:saml-
provider/ADFSProvider
&Tags.member.1.Key=Dept&Tags.member.1.Value=Accounting
```

```
&Tags.member.2.Key=Cost Center&Tags.member.2.Value=12345
```

## Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE
Content-Type: text/xml
Content-Length: 194
Date: Fri, 29 Sep 2017 18:17:47 GMT

<TagSAMLProviderResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE</RequestId>
  </ResponseMetadata>
</TagSAMLProviderResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# TagServerCertificate

Adds one or more tags to an IAM server certificate. If a tag with the same key name already exists, then that tag is overwritten with the new value.

## Note

For certificates in a Region supported by AWS Certificate Manager (ACM), we recommend that you don't use IAM server certificates. Instead, use ACM to provision, manage, and deploy your server certificates. For more information about IAM server certificates, [Working with server certificates](#) in the *IAM User Guide*.

A tag consists of a key name and an associated value. By assigning tags to your resources, you can do the following:

- **Administrative grouping and discovery** - Attach tags to resources to aid in organization and search. For example, you could search for all resources with the key name *Project* and the value *MyImportantProject*. Or search for all resources with the key name *Cost Center* and the value *41200*.
- **Access control** - Include tags in IAM user-based and resource-based policies. You can use tags to restrict access to only a server certificate that has a specified tag attached. For examples of policies that show how to use tags to control access, see [Control access using IAM tags](#) in the *IAM User Guide*.
- **Cost allocation** - Use tags to help track which individuals and teams are using which AWS resources.

## Note

- If any one of the tags is invalid or if you exceed the allowed maximum number of tags, then the entire request fails and the resource is not created. For more information about tagging, see [Tagging IAM resources](#) in the *IAM User Guide*.
- AWS always interprets the tag Value as a single string. If you need to store an array, you can store comma-separated values in the string. However, you must interpret the value in your code.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### ServerCertificateName

The name of the IAM server certificate to which you want to add tags.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: Yes

### Tags.member.N

The list of tags that you want to attach to the IAM server certificate. Each tag consists of a key name and an associated value.

Type: Array of [Tag \(p. 553\)](#) objects

Array Members: Maximum number of 50 items.

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **ConcurrentModification**

The request was rejected because multiple requests to change this object were submitted simultaneously. Wait a few minutes and submit your request again.

HTTP Status Code: 409

### **InvalidInput**

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### **LimitExceeded**

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

The following example is formatted with line breaks for legibility.

The following example shows how to add tags to an existing server certificate.

### Sample Request

```
POST / HTTP/1.1
Host: https://iam.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.11.143 Python/3.6.1 Linux/3.2.45-0.6.wd.865.49.315.metal1.x86_64
botocore/1.7.1
X-Amz-Date: 20170929T181747Z
```

```
Authorization: <auth details>
Content-Length: 99
Content-Type: application/x-www-form-urlencoded

Action=TagServerCertificate&Version=2010-05-08&ServerCertificateName=ExampleServerCert
&Tags.member.1.Key=Dept&Tags.member.1.Value=Accounting
&Tags.member.2.Key=Cost Center&Tags.member.2.Value=12345
```

## Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE
Content-Type: text/xml
Content-Length: 194
Date: Fri, 29 Sep 2017 18:17:47 GMT

<TagServerCertificateResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE</RequestId>
  </ResponseMetadata>
</TagServerCertificateResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# TagUser

Adds one or more tags to an IAM user. If a tag with the same key name already exists, then that tag is overwritten with the new value.

A tag consists of a key name and an associated value. By assigning tags to your resources, you can do the following:

- **Administrative grouping and discovery** - Attach tags to resources to aid in organization and search. For example, you could search for all resources with the key name *Project* and the value *MyImportantProject*. Or search for all resources with the key name *Cost Center* and the value *41200*.
- **Access control** - Include tags in IAM user-based and resource-based policies. You can use tags to restrict access to only an IAM requesting user that has a specified tag attached. You can also restrict access to only those resources that have a certain tag attached. For examples of policies that show how to use tags to control access, see [Control access using IAM tags](#) in the *IAM User Guide*.
- **Cost allocation** - Use tags to help track which individuals and teams are using which AWS resources.

## Note

- If any one of the tags is invalid or if you exceed the allowed maximum number of tags, then the entire request fails and the resource is not created. For more information about tagging, see [Tagging IAM resources](#) in the *IAM User Guide*.
- AWS always interprets the tag Value as a single string. If you need to store an array, you can store comma-separated values in the string. However, you must interpret the value in your code.

For more information about tagging, see [Tagging IAM identities](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### Tags.member.N

The list of tags that you want to attach to the IAM user. Each tag consists of a key name and an associated value.

Type: Array of [Tag \(p. 553\)](#) objects

Array Members: Maximum number of 50 items.

Required: Yes

### UserName

The name of the IAM user to which you want to add tags.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **ConcurrentModification**

The request was rejected because multiple requests to change this object were submitted simultaneously. Wait a few minutes and submit your request again.

HTTP Status Code: 409

### **InvalidInput**

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### **LimitExceeded**

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

The following example is formatted with line breaks for legibility.

The following example shows how to add tags to an existing user.

### Sample Request

```
POST / HTTP/1.1
Host: https://iam.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.11.143 Python/3.6.1 Linux/3.2.45-0.6.wd.865.49.315.meta1.x86_64
botocore/1.7.1
X-Amz-Date: 20170929T181747Z
Authorization: <auth details>
Content-Length: 99
Content-Type: application/x-www-form-urlencoded
```

```
Action=TagUser&Version=2010-05-08&UserName=anika
&Tags.member.1.Key=Dept&Tags.member.1.Value=Accounting
&Tags.member.2.Key=Cost Center&Tags.member.2.Value=12345
```

## Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE
Content-Type: text/xml
Content-Length: 194
Date: Fri, 29 Sep 2017 18:17:47 GMT

<TagUserResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE</RequestId>
  </ResponseMetadata>
</TagUserResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UntagInstanceProfile

Removes the specified tags from the IAM instance profile. For more information about tagging, see [Tagging IAM resources](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### InstanceProfileName

The name of the IAM instance profile from which you want to remove tags.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: Yes

### TagKeys.member.N

A list of key names as a simple array of strings. The tags with matching keys are removed from the specified instance profile.

Type: Array of strings

Array Members: Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\p{L}\p{Z}\p{N}_.:/+=\@-]+`

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### ConcurrentModification

The request was rejected because multiple requests to change this object were submitted simultaneously. Wait a few minutes and submit your request again.

HTTP Status Code: 409

### InvalidInput

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

The following example is formatted with line breaks for legibility.

The following example shows how to remove tags that are attached to an instance profile whose name is Webserver.

### Sample Request

```
POST / HTTP/1.1
Host: https://iam.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.11.143 Python/3.6.1 Linux/3.2.45-0.6.wd.865.49.315.metal1.x86_64
botocore/1.7.1
X-Amz-Date: 20170929T183048Z
Authorization: <auth details>
Content-Length: 74
Content-Type: application/x-www-form-urlencoded

Action=UntagInstanceProfile&Version=2010-05-08&InstanceProfileName=Webserver
&TagKeys.member.1=Dept
```

### Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE
Content-Type: text/xml
Content-Length: 198
Date: Fri, 29 Sep 2017 18:30:47 GMT

<UntagInstanceProfileResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE</RequestId>
  </ResponseMetadata>
</UntagInstanceProfileResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UntagMFADevice

Removes the specified tags from the IAM virtual multi-factor authentication (MFA) device. For more information about tagging, see [Tagging IAM resources](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### SerialNumber

The unique identifier for the IAM virtual MFA device from which you want to remove tags. For virtual MFA devices, the serial number is the same as the ARN.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 9. Maximum length of 256.

Pattern: `[\w+=/:,.@-]+`

Required: Yes

### TagKeys.member.N

A list of key names as a simple array of strings. The tags with matching keys are removed from the specified instance profile.

Type: Array of strings

Array Members: Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\p{L}\p{Z}\p{N}_.:/+=\-\@]+`

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### ConcurrentModification

The request was rejected because multiple requests to change this object were submitted simultaneously. Wait a few minutes and submit your request again.

HTTP Status Code: 409

### InvalidInput

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

The following example is formatted with line breaks for legibility.

The following example shows how to remove tags that are attached to a virtual MFA device whose serial number is `arn:aws:iam::123456789012:mfa/ExampleName`.

### Sample Request

```
POST / HTTP/1.1
Host: https://iam.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.11.143 Python/3.6.1 Linux/3.2.45-0.6.wd.865.49.315.metal1.x86_64
botocore/1.7.1
X-Amz-Date: 20170929T183048Z
Authorization: <auth details>
Content-Length: 74
Content-Type: application/x-www-form-urlencoded

Action=UntagMFADevice&Version=2010-05-08&SerialNumber=arn:aws:iam::123456789012:mfa/
ExampleName
&TagKeys.member.1=Dept
```

### Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE
Content-Type: text/xml
Content-Length: 198
Date: Fri, 29 Sep 2017 18:30:47 GMT

<UntagMFADeviceResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE</RequestId>
  </ResponseMetadata>
</UntagMFADeviceResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UntagOpenIDConnectProvider

Removes the specified tags from the specified OpenID Connect (OIDC)-compatible identity provider in IAM. For more information about OIDC providers, see [About web identity federation](#). For more information about tagging, see [Tagging IAM resources](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### OpenIDConnectProviderArn

The ARN of the OIDC provider in IAM from which you want to remove tags.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

### TagKeys.member.N

A list of key names as a simple array of strings. The tags with matching keys are removed from the specified OIDC provider.

Type: Array of strings

Array Members: Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\p{L}\p{Z}\p{N}_.:/+=\-\@]+`

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### ConcurrentModification

The request was rejected because multiple requests to change this object were submitted simultaneously. Wait a few minutes and submit your request again.

HTTP Status Code: 409

### InvalidInput

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

The following example is formatted with line breaks for legibility.

The following example shows how to remove tags that are attached to an OIDC provider whose ARN is `arn:aws:iam::123456789012:oidc-provider/GoogleProvider`.

### Sample Request

```
POST / HTTP/1.1
Host: https://iam.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.11.143 Python/3.6.1 Linux/3.2.45-0.6.wd.865.49.315.metal1.x86_64
botocore/1.7.1
X-Amz-Date: 20170929T183048Z
Authorization: <auth details>
Content-Length: 74
Content-Type: application/x-www-form-urlencoded

Action=UntagOpenIDConnectProvider&Version=2010-05-08&OpenIDConnectProviderArn=arn:aws:iam::123456789012
provider/GoogleProvider
&TagKeys.member.1=Dept
```

### Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE
Content-Type: text/xml
Content-Length: 198
Date: Fri, 29 Sep 2017 18:30:47 GMT

<UntagOpenIDConnectProviderResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE</RequestId>
  </ResponseMetadata>
</UntagOpenIDConnectProviderResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UntagPolicy

Removes the specified tags from the customer managed policy. For more information about tagging, see [Tagging IAM resources](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### PolicyArn

The ARN of the IAM customer managed policy from which you want to remove tags.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

### TagKeys.member.N

A list of key names as a simple array of strings. The tags with matching keys are removed from the specified policy.

Type: Array of strings

Array Members: Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\p{L}\p{Z}\p{N}_.:/+=\-\@]+`

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### ConcurrentModification

The request was rejected because multiple requests to change this object were submitted simultaneously. Wait a few minutes and submit your request again.

HTTP Status Code: 409

### InvalidInput

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

#### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

The following example is formatted with line breaks for legibility.

The following example shows how to remove tags that are attached to a policy whose ARN is `arn:aws:iam::123456789012:policy/UsersManageOwnCredentials`.

### Sample Request

```
POST / HTTP/1.1
Host: https://iam.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.11.143 Python/3.6.1 Linux/3.2.45-0.6.wd.865.49.315.metal1.x86_64
    botocore/1.7.1
X-Amz-Date: 20170929T183048Z
Authorization: <auth details>
Content-Length: 74
Content-Type: application/x-www-form-urlencoded

Action=UntagPolicy&Version=2010-05-08&PolicyArn=arn:aws:iam::123456789012:policy/
UsersManageOwnCredentials
    &TagKeys.member.1=Dept
```

### Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE
Content-Type: text/xml
Content-Length: 198
Date: Fri, 29 Sep 2017 18:30:47 GMT

<UntagPolicyResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
    <ResponseMetadata>
        <RequestId>EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE</RequestId>
    </ResponseMetadata>
</UntagPolicyResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UntagRole

Removes the specified tags from the role. For more information about tagging, see [Tagging IAM resources](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### **RoleName**

The name of the IAM role from which you want to remove tags.

This parameter accepts (through its [regex pattern](#)) a string of characters that consist of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w+=,.@-]+`

Required: Yes

### **TagKeys.member.N**

A list of key names as a simple array of strings. The tags with matching keys are removed from the specified role.

Type: Array of strings

Array Members: Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\p{L}\p{Z}\p{N}_.:/=+\-@]+`

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **ConcurrentModification**

The request was rejected because multiple requests to change this object were submitted simultaneously. Wait a few minutes and submit your request again.

HTTP Status Code: 409

### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

The following example is formatted with line breaks for legibility.

The following example shows how to remove a tag with the key `Dept` from a role named `taggedrole`.

### Sample Request

```
POST / HTTP/1.1
Host: https://iam.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.11.143 Python/3.6.1 Linux/3.2.45-0.6.wd.865.49.315.metal1.x86_64
    botocore/1.7.1
X-Amz-Date: 20170929T182851Z
Authorization: <auth details>
Content-Length: 78
Content-Type: application/x-www-form-urlencoded

Action=UntagRole&Version=2010-05-08&RoleName=taggedrole
&TagKeys.member.1=Dept
```

### Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE
Content-Type: text/xml
Content-Length: 198
Date: Fri, 29 Sep 2017 18:28:50 GMT

<UntagRoleResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
    <ResponseMetadata>
        <RequestId>EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE</RequestId>
    </ResponseMetadata>
</UntagRoleResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

# UntagSAMLProvider

Removes the specified tags from the specified Security Assertion Markup Language (SAML) identity provider in IAM. For more information about these providers, see [About web identity federation](#). For more information about tagging, see [Tagging IAM resources](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### SAMLProviderArn

The ARN of the SAML identity provider in IAM from which you want to remove tags.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

### TagKeys.member.N

A list of key names as a simple array of strings. The tags with matching keys are removed from the specified SAML identity provider.

Type: Array of strings

Array Members: Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\p{L}\p{Z}\p{N}_.:/+=\-\@]+`

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### ConcurrentModification

The request was rejected because multiple requests to change this object were submitted simultaneously. Wait a few minutes and submit your request again.

HTTP Status Code: 409

### InvalidInput

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

The following example is formatted with line breaks for legibility.

The following example shows how to remove tags that are attached to a SAML provider whose ARN is `arn:aws:iam::123456789012:saml-provider/ADFSProvider`.

### Sample Request

```
POST / HTTP/1.1
Host: https://iam.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.11.143 Python/3.6.1 Linux/3.2.45-0.6.wd.865.49.315.metal1.x86_64
botocore/1.7.1
X-Amz-Date: 20170929T183048Z
Authorization: <auth details>
Content-Length: 74
Content-Type: application/x-www-form-urlencoded

Action=UntagSAMLProvider&Version=2010-05-08&SAMLProviderArn=arn:aws:iam::123456789012:saml-
provider/ADFSProvider
&TagKeys.member.1=Dept
```

### Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE
Content-Type: text/xml
Content-Length: 198
Date: Fri, 29 Sep 2017 18:30:47 GMT

<UntagSAMLProviderResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE</RequestId>
  </ResponseMetadata>
</UntagSAMLProviderResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UntagServerCertificate

Removes the specified tags from the IAM server certificate. For more information about tagging, see [Tagging IAM resources](#) in the *IAM User Guide*.

## **Note**

For certificates in a Region supported by AWS Certificate Manager (ACM), we recommend that you don't use IAM server certificates. Instead, use ACM to provision, manage, and deploy your server certificates. For more information about IAM server certificates, [Working with server certificates](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### **ServerCertificateName**

The name of the IAM server certificate from which you want to remove tags.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: Yes

### **TagKeys.member.N**

A list of key names as a simple array of strings. The tags with matching keys are removed from the specified IAM server certificate.

Type: Array of strings

Array Members: Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\p{L}\p{Z}\p{N}_.:/=+\-@]+`

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **ConcurrentModification**

The request was rejected because multiple requests to change this object were submitted simultaneously. Wait a few minutes and submit your request again.

HTTP Status Code: 409

### InvalidInput

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

The following example is formatted with line breaks for legibility.

The following example shows how to remove tags that are attached to a server certificate whose name is ExampleServerCert.

### Sample Request

```
POST / HTTP/1.1
Host: https://iam.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.11.143 Python/3.6.1 Linux/3.2.45-0.6.wd.865.49.315.metal1.x86_64
botocore/1.7.1
X-Amz-Date: 20170929T183048Z
Authorization: <auth details>
Content-Length: 74
Content-Type: application/x-www-form-urlencoded

Action=UntagServerCertificate&Version=2010-05-08&ServerCertificateName=ExampleServerCert
&TagKeys.member.1=Dept
```

### Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE
Content-Type: text/xml
Content-Length: 198
Date: Fri, 29 Sep 2017 18:30:47 GMT

<UntagServerCertificateResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE</RequestId>
  </ResponseMetadata>
</UntagServerCertificateResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UntagUser

Removes the specified tags from the user. For more information about tagging, see [Tagging IAM resources](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### TagKeys.member.N

A list of key names as a simple array of strings. The tags with matching keys are removed from the specified user.

Type: Array of strings

Array Members: Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [\p{L}\p{Z}\p{N}\_.:/=+\-@]+

Required: Yes

### UserName

The name of the IAM user from which you want to remove tags.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: \_+=,.@-

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [\w+=,.@-]+

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### ConcurrentModification

The request was rejected because multiple requests to change this object were submitted simultaneously. Wait a few minutes and submit your request again.

HTTP Status Code: 409

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

The following example is formatted with line breaks for legibility.

The following example shows how to remove tags that are attached to a user whose IAM user name is anika.

### Sample Request

```
POST / HTTP/1.1
Host: https://iam.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.11.143 Python/3.6.1 Linux/3.2.45-0.6.wd.865.49.315.metal1.x86_64
    botocore/1.7.1
X-Amz-Date: 20170929T183048Z
Authorization: <auth details>
Content-Length: 74
Content-Type: application/x-www-form-urlencoded

Action=UntagUser&Version=2010-05-08&UserName=anika
    &TagKeys.member.1=Dept
```

### Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE
Content-Type: text/xml
Content-Length: 198
Date: Fri, 29 Sep 2017 18:30:47 GMT

<UntagUserResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
    <ResponseMetadata>
        <RequestId>EXAMPLE8-90ab-cdef-fedc-ba987EXAMPLE</RequestId>
    </ResponseMetadata>
</UntagUserResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateAccessKey

Changes the status of the specified access key from Active to Inactive, or vice versa. This operation can be used to disable a user's key as part of a key rotation workflow.

If the `UserName` is not specified, the user name is determined implicitly based on the AWS access key ID used to sign the request. If a temporary access key is used, then `UserName` is required. If a long-term key is assigned to the user, then `UserName` is not required. This operation works for access keys under the AWS account. Consequently, you can use this operation to manage AWS account root user credentials even if the AWS account has no associated users.

For information about rotating keys, see [Managing keys and certificates](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### AccessKeyId

The access key ID of the secret access key you want to update.

This parameter allows (through its [regex pattern](#)) a string of characters that can consist of any upper or lowercased letter or digit.

Type: String

Length Constraints: Minimum length of 16. Maximum length of 128.

Pattern: `[\w]+`

Required: Yes

### Status

The status you want to assign to the secret access key. Active means that the key can be used for programmatic calls to AWS, while Inactive means that the key cannot be used.

Type: String

Valid Values: Active | Inactive

Required: Yes

### UserName

The name of the user whose key you want to update.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: No

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **LimitExceeded**

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of `UpdateAccessKey`.

#### Sample Request

```
https://iam.amazonaws.com/?Action=UpdateAccessKey
&UserName=Bob
&AccessKeyId=AKIAIOSFODNN7EXAMPLE
&Status=Inactive
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<UpdateAccessKeyResponse>
  <ResponseMetadata>
    <RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
  </ResponseMetadata>
</UpdateAccessKeyResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateAccountPasswordPolicy

Updates the password policy settings for the AWS account.

## Note

This operation does not support partial updates. No parameters are required, but if you do not specify a parameter, that parameter's value reverts to its default value. See the **Request Parameters** section for each parameter's default value. Also note that some parameters do not allow the default parameter to be explicitly set. Instead, to invoke the default value, do not include that parameter when you invoke the operation.

For more information about using a password policy, see [Managing an IAM password policy](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### AllowUsersToChangePassword

Allows all IAM users in your account to use the AWS Management Console to change their own passwords. For more information, see [Permitting IAM users to change their own passwords](#) in the *IAM User Guide*.

If you do not specify a value for this parameter, then the operation uses the default value of `false`. The result is that IAM users in the account do not automatically have permissions to change their own password.

Type: Boolean

Required: No

### HardExpiry

Prevents IAM users who are accessing the account via the AWS Management Console from setting a new console password after their password has expired. The IAM user cannot access the console until an administrator resets the password.

If you do not specify a value for this parameter, then the operation uses the default value of `false`. The result is that IAM users can change their passwords after they expire and continue to sign in as the user.

## Note

In the AWS Management Console, the custom password policy option **Allow users to change their own password** gives IAM users permissions to `iam:ChangePassword` for only their user and to the `iam:GetAccountPasswordPolicy` action. This option does not attach a permissions policy to each user, rather the permissions are applied at the account-level for all users by IAM. IAM users with `iam:ChangePassword` permission and active access keys can reset their own expired console password using the AWS CLI or API.

Type: Boolean

Required: No

### MaxPasswordAge

The number of days that an IAM user password is valid.

If you do not specify a value for this parameter, then the operation uses the default value of `0`. The result is that IAM user passwords never expire.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1095.

Required: No

#### **MinimumPasswordLength**

The minimum number of characters allowed in an IAM user password.

If you do not specify a value for this parameter, then the operation uses the default value of 6.

Type: Integer

Valid Range: Minimum value of 6. Maximum value of 128.

Required: No

#### **PasswordReusePrevention**

Specifies the number of previous passwords that IAM users are prevented from reusing.

If you do not specify a value for this parameter, then the operation uses the default value of 0. The result is that IAM users are not prevented from reusing previous passwords.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 24.

Required: No

#### **RequireLowercaseCharacters**

Specifies whether IAM user passwords must contain at least one lowercase character from the ISO basic Latin alphabet (a to z).

If you do not specify a value for this parameter, then the operation uses the default value of `false`. The result is that passwords do not require at least one lowercase character.

Type: Boolean

Required: No

#### **RequireNumbers**

Specifies whether IAM user passwords must contain at least one numeric character (0 to 9).

If you do not specify a value for this parameter, then the operation uses the default value of `false`. The result is that passwords do not require at least one numeric character.

Type: Boolean

Required: No

#### **RequireSymbols**

Specifies whether IAM user passwords must contain at least one of the following non-alphanumeric characters:

`! @ # $ % ^ & * ( ) _ + - = [ ] { } | '`

If you do not specify a value for this parameter, then the operation uses the default value of `false`. The result is that passwords do not require at least one symbol character.

Type: Boolean

Required: No

#### **RequireUppercaseCharacters**

Specifies whether IAM user passwords must contain at least one uppercase character from the ISO basic Latin alphabet (A to Z).

If you do not specify a value for this parameter, then the operation uses the default value of `false`. The result is that passwords do not require at least one uppercase character.

Type: Boolean

Required: No

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

#### **LimitExceeded**

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

#### **MalformedPolicyDocument**

The request was rejected because the policy document was malformed. The error message describes the specific error.

HTTP Status Code: 400

#### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

#### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of `UpdateAccountPasswordPolicy`.

#### Sample Request

```
https://iam.amazonaws.com/?Action=UpdateAccountPasswordPolicy
&AllowUsersToChangePassword=true
&HardExpiry=false
&MaxPasswordAge=90
&MinimumPasswordLength=12
&PasswordReusePrevention=12
&RequireLowercaseCharacters=true
```

```
&RequireNumbers=true
&RequireSymbols=true
&RequireUppercaseCharacters=true
&Version=2010-05-08
&AUTHPARAMS
```

## Sample Response

```
<UpdateAccountPasswordPolicyResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
  </ResponseMetadata>
</UpdateAccountPasswordPolicyResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateAssumeRolePolicy

Updates the policy that grants an IAM entity permission to assume a role. This is typically referred to as the "role trust policy". For more information about roles, see [Using roles to delegate permissions and federate identities](#).

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### PolicyDocument

The policy that grants an entity permission to assume the role.

You must provide policies in JSON format in IAM. However, for AWS CloudFormation templates formatted in YAML, you can provide the policy in JSON or YAML format. AWS CloudFormation always converts a YAML policy to JSON format before submitting it to IAM.

The [regex pattern](#) used to validate this parameter is a string of characters consisting of the following:

- Any printable ASCII character ranging from the space character (\u0020) through the end of the ASCII character range
- The printable characters in the Basic Latin and Latin-1 Supplement character set (through \u00FF)
- The special characters tab (\u0009), line feed (\u000A), and carriage return (\u000D)

Type: String

Length Constraints: Minimum length of 1. Maximum length of 131072.

Pattern: [\u0009\u000A\u000D\u0020-\u00FF]+

Required: Yes

### RoleName

The name of the role to update with the new policy.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: \_+=,.@-

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [\w+=,.@-]+

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### LimitExceeded

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

#### **MalformedPolicyDocument**

The request was rejected because the policy document was malformed. The error message describes the specific error.

HTTP Status Code: 400

#### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

#### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

#### **UnmodifiableEntity**

The request was rejected because only the service that depends on the service-linked role can modify or delete the role on your behalf. The error message includes the name of the service that depends on this service-linked role. You must request the change through that service.

HTTP Status Code: 400

## Examples

### Example

This example illustrates one usage of `UpdateAssumeRolePolicy`.

#### Sample Request

```
https://iam.amazonaws.com/?Action=UpdateAssumeRolePolicy
&PolicyDocument={"Version":"2012-10-17","Statement":[{"Effect":"Allow",
"Principal":{"Service":["ec2.amazonaws.com"]},"Action":["sts:AssumeRole"]}]}
&RoleName=S3AccessForEC2Instances
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<UpdateAssumeRolePolicyResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
<ResponseMetadata>
  <RequestId>309c1671-99ed-11e1-a4c3-270EXAMPLE04</RequestId>
</ResponseMetadata>
</UpdateAssumeRolePolicyResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateGroup

Updates the name and/or the path of the specified IAM group.

## Important

You should understand the implications of changing a group's path or name. For more information, see [Renaming users and groups](#) in the *IAM User Guide*.

## Note

The person making the request (the principal), must have permission to change the role group with the old name and the new name. For example, to change the group named Managers to MGRs, the principal must have a policy that allows them to update both groups. If the principal has permission to update the Managers group, but not the MGRs group, then the update fails. For more information about permissions, see [Access management](#).

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### GroupName

Name of the IAM group to update. If you're changing the name of the group, this is the original name.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: Yes

### NewGroupName

New name for the IAM group. Only include this if changing the group's name.

IAM user, group, role, and policy names must be unique within the account. Names are not distinguished by case. For example, you cannot create resources named both "MyResource" and "myresource".

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: No

### NewPath

New path for the IAM group. Only include this if changing the group's path.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of either a forward slash (/) by itself or a string that must begin and end with forward slashes. In addition, it can contain any ASCII character from the ! (\u0021) through the DEL character (\u007F), including most punctuation characters, digits, and upper and lowercased letters.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: (\u002F)|(\\u002F[\u0021-\u007F]+\u002F)

Required: No

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **EntityAlreadyExists**

The request was rejected because it attempted to create a resource that already exists.

HTTP Status Code: 409

### **LimitExceeded**

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of UpdateGroup.

### Sample Request

```
https://iam.amazonaws.com/?Action=UpdateGroup
&GroupName=Test
&NewGroupName=Test_1
&Version=2010-05-08
&AUTHPARAMS
```

### Sample Response

```
<UpdateGroupResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
  </ResponseMetadata>
```

```
</UpdateGroupResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateLoginProfile

Changes the password for the specified IAM user. You can use the AWS CLI, the AWS API, or the [Users](#) page in the IAM console to change the password for any IAM user. Use [ChangePassword \(p. 22\)](#) to change your own password in the [My Security Credentials](#) page in the AWS Management Console.

For more information about modifying passwords, see [Managing passwords](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### Password

The new password for the specified IAM user.

The [regex pattern](#) used to validate this parameter is a string of characters consisting of the following:

- Any printable ASCII character ranging from the space character (\u0020) through the end of the ASCII character range
- The printable characters in the Basic Latin and Latin-1 Supplement character set (through \u00FF)
- The special characters tab (\u0009), line feed (\u000A), and carriage return (\u000D)

However, the format can be further restricted by the account administrator by setting a password policy on the AWS account. For more information, see [UpdateAccountPasswordPolicy \(p. 427\)](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [\u0009\u000A\u000D\u0020-\u00FF]+

Required: No

### PasswordResetRequired

Allows this new password to be used only once by requiring the specified IAM user to set a new password on next sign-in.

Type: Boolean

Required: No

### UserName

The name of the user whose password you want to update.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: \_+=,.@-

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [\w+=,.@-]+

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **EntityTemporarilyUnmodifiable**

The request was rejected because it referenced an entity that is temporarily unmodifiable, such as a user name that was deleted and then recreated. The error indicates that the request is likely to succeed if you try again after waiting several minutes. The error message describes the entity.

HTTP Status Code: 409

### **LimitExceeded**

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### **PasswordPolicyViolation**

The request was rejected because the provided password did not meet the requirements imposed by the account password policy.

HTTP Status Code: 400

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of `UpdateLoginProfile`.

### Sample Request

```
https://iam.amazonaws.com/?Action=UpdateLoginProfile
&UserName=Bob
&Password=^L[p*#Z*8o)K
&Version=2010-05-08
&AUTHPARAMS
```

### Sample Response

```
<UpdateLoginProfileResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
  </ResponseMetadata>
```

```
</UpdateLoginProfileResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateOpenIDConnectProviderThumbprint

Replaces the existing list of server certificate thumbprints associated with an OpenID Connect (OIDC) provider resource object with a new list of thumbprints.

The list that you pass with this operation completely replaces the existing list of thumbprints. (The lists are not merged.)

Typically, you need to update a thumbprint only when the identity provider certificate changes, which occurs rarely. However, if the provider's certificate *does* change, any attempt to assume an IAM role that specifies the OIDC provider as a principal fails until the certificate thumbprint is updated.

#### **Note**

AWS secures communication with some OIDC identity providers (IdPs) through our library of trusted certificate authorities (CAs) instead of using a certificate thumbprint to verify your IdP server certificate. These OIDC IdPs include Google, and those that use an Amazon S3 bucket to host a JSON Web Key Set (JWKS) endpoint. In these cases, your legacy thumbprint remains in your configuration, but is no longer used for validation.

#### **Note**

Trust for the OIDC provider is derived from the provider certificate and is validated by the thumbprint. Therefore, it is best to limit access to the `UpdateOpenIDConnectProviderThumbprint` operation to highly privileged users.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### **OpenIDConnectProviderArn**

The Amazon Resource Name (ARN) of the IAM OIDC provider resource object for which you want to update the thumbprint. You can get a list of OIDC provider ARNs by using the [ListOpenIDConnectProviders \(p. 265\)](#) operation.

For more information about ARNs, see [Amazon Resource Names \(ARNs\)](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

### **ThumbprintList.member.N**

A list of certificate thumbprints that are associated with the specified IAM OpenID Connect provider. For more information, see [CreateOpenIDConnectProvider \(p. 39\)](#).

Type: Array of strings

Length Constraints: Fixed length of 40.

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### InvalidInput

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of `UpdateOpenIDConnectProviderThumbprint`.

#### Sample Request

```
https://iam.amazonaws.com/?Action=UpdateOpenIDConnectProviderThumbprint
&ThumbprintList.list.1=c3768084dfb3d2b68b7897bf5f565da8eEXAMPLE
&OpenIDConnectProviderArn=arn:aws:iam::123456789012:oidc-provider/server.example.com
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<UpdateOpenIDConnectProviderThumbprintResponse xmlns="https://iam.amazonaws.com/
doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>29b6031c-4f66-11e4-afca-bfd6aEXAMPLE</RequestId>
  </ResponseMetadata>
</UpdateOpenIDConnectProviderThumbprintResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

# UpdateRole

Updates the description or maximum session duration setting of a role.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### Description

The new description that you want to apply to the specified role.

Type: String

Length Constraints: Maximum length of 1000.

Pattern: [\p{L}\p{M}\p{Z}\p{S}\p{N}\p{P}]\*

Required: No

### MaxSessionDuration

The maximum session duration (in seconds) that you want to set for the specified role. If you do not specify a value for this setting, the default value of one hour is applied. This setting can have a value from 1 hour to 12 hours.

Anyone who assumes the role from the AWS CLI or API can use the DurationSeconds API parameter or the duration-seconds AWS CLI parameter to request a longer session. The MaxSessionDuration setting determines the maximum duration that can be requested using the DurationSeconds parameter. If users don't specify a value for the DurationSeconds parameter, their security credentials are valid for one hour by default. This applies when you use the AssumeRole\* API operations or the assume-role\* AWS CLI operations but does not apply when you use those operations to create a console URL. For more information, see [Using IAM roles](#) in the *IAM User Guide*.

Type: Integer

Valid Range: Minimum value of 3600. Maximum value of 43200.

Required: No

### RoleName

The name of the role that you want to modify.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [\w+=, .@-]+

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

**NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

**ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

**UnmodifiableEntity**

The request was rejected because only the service that depends on the service-linked role can modify or delete the role on your behalf. The error message includes the name of the service that depends on this service-linked role. You must request the change through that service.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateRoleDescription

Use [UpdateRole \(p. 443\)](#) instead.

Modifies only the description of a role. This operation performs the same function as the `Description` parameter in the `UpdateRole` operation.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### Description

The new description that you want to apply to the specified role.

Type: String

Length Constraints: Maximum length of 1000.

Pattern: `[\p{L}\p{M}\p{Z}\p{S}\p{N}\p{P}]^*`

Required: Yes

### RoleName

The name of the role that you want to modify.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w+=, .@-]^+`

Required: Yes

## Response Elements

The following element is returned by the service.

### Role

A structure that contains details about the modified role.

Type: [Role \(p. 527\)](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

**ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

**UnmodifiableEntity**

The request was rejected because only the service that depends on the service-linked role can modify or delete the role on your behalf. The error message includes the name of the service that depends on this service-linked role. You must request the change through that service.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateSAMLProvider

Updates the metadata document for an existing SAML provider resource object.

**Note**

This operation requires [Signature Version 4](#).

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

**SAMLMetadataDocument**

An XML document generated by an identity provider (IdP) that supports SAML 2.0. The document includes the issuer's name, expiration information, and keys that can be used to validate the SAML authentication response (assertions) that are received from the IdP. You must generate the metadata document using the identity management software that is used as your organization's IdP.

Type: String

Length Constraints: Minimum length of 1000. Maximum length of 10000000.

Required: Yes

**SAMLProviderArn**

The Amazon Resource Name (ARN) of the SAML provider to update.

For more information about ARNs, see [Amazon Resource Names \(ARNs\)](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

## Response Elements

The following element is returned by the service.

**SAMLProviderArn**

The Amazon Resource Name (ARN) of the SAML provider that was updated.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

**InvalidInput**

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

#### LimitExceeded

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

#### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

#### ServiceFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of UpdateSAMLProvider.

#### Sample Request

```
https://iam.amazonaws.com/?Action=UpdateSAMLProvider
&Name=arn:aws:iam::123456789012:saml-provider/MyUniversity
&SAMLMetadataDocument=VGhpcyBpcyB3aGVyZSB5b3UgcHV0IHRoZSBTQU1MIHByb3ZpZGVyIG1ldGFkYXRhIGRvY3VtZW50
LCBCYXN1NjQtZW5jb2RlZCBpbnRvIGEgYmlnIHN0cmluZy4=
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<UpdateSAMLProviderResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
<UpdateSAMLProviderResult>
  <SAMLProviderArn>arn:aws:iam::123456789012:saml-provider/MyUniversity</SAMLProviderArn>
</UpdateSAMLProviderResult>
<ResponseMetadata>
  <RequestId>29f47818-99f5-11e1-a4c3-27EXAMPLE804</RequestId>
</ResponseMetadata>
</UpdateSAMLProviderResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateServerCertificate

Updates the name and/or the path of the specified server certificate stored in IAM.

For more information about working with server certificates, see [Working with server certificates](#) in the *IAM User Guide*. This topic also includes a list of AWS services that can use the server certificates that you manage with IAM.

## Important

You should understand the implications of changing a server certificate's path or name. For more information, see [Renaming a server certificate](#) in the *IAM User Guide*.

## Note

The person making the request (the principal), must have permission to change the server certificate with the old name and the new name. For example, to change the certificate named ProductionCert to ProdCert, the principal must have a policy that allows them to update both certificates. If the principal has permission to update the ProductionCert group, but not the ProdCert certificate, then the update fails. For more information about permissions, see [Access management](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### NewPath

The new path for the server certificate. Include this only if you are updating the server certificate's path.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of either a forward slash (/) by itself or a string that must begin and end with forward slashes. In addition, it can contain any ASCII character from the ! (\u0021) through the DEL character (\u007F), including most punctuation characters, digits, and upper and lowercased letters.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: (\u002F)|(\\u002F[\u0021-\u007F]+\u002F)

Required: No

### NewServerCertificateName

The new name for the server certificate. Include this only if you are updating the server certificate's name. The name of the certificate cannot contain any spaces.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: \_+=,.@-

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [\w+=,.@-]+

Required: No

### **ServerCertificateName**

The name of the server certificate that you want to update.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **EntityAlreadyExists**

The request was rejected because it attempted to create a resource that already exists.

HTTP Status Code: 409

### **LimitExceeded**

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of `UpdateServerCertificate`.

### Sample Request

```
https://iam.amazonaws.com/?Action=UpdateServerCertificate
&ServerCertificateName=OldProdServerCertName
&NewServerCertificateName>NewProdServerCertName
&Version=2010-05-08
&AUTHPARAMS
```

## Sample Response

```
<UpdateServerCertificateResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
<ResponseMetadata>
  <RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
</ResponseMetadata>
</UpdateServerCertificateResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateServiceSpecificCredential

Sets the status of a service-specific credential to Active or Inactive. Service-specific credentials that are inactive cannot be used for authentication to the service. This operation can be used to disable a user's service-specific credential as part of a credential rotation work flow.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### ServiceSpecificCredentialId

The unique identifier of the service-specific credential.

This parameter allows (through its [regex pattern](#)) a string of characters that can consist of any upper or lowercased letter or digit.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 128.

Pattern: `[\w]+`

Required: Yes

### Status

The status to be assigned to the service-specific credential.

Type: String

Valid Values: Active | Inactive

Required: Yes

### UserName

The name of the IAM user associated with the service-specific credential. If you do not specify this value, then the operation assumes the user whose credentials are used to call the operation.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w+=,.@-]+`

Required: No

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

## Examples

### Example

The following example shows how to set the state to "Active" for a service-specific credential associated with the specified IAM user.

#### Sample Request

```
https://iam.amazonaws.com/?Action=UpdateServiceSpecificCredential
&ServiceSpecificCredentialId=ACCA12345ABCDEXAMPLE
&UserName=Anika
&Status=Active
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<UpdateServiceSpecificCredentialResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>EXAMPLE8-90ab-cdef-fecd-ba987EXAMPLE</RequestId>
  </ResponseMetadata>
</UpdateServiceSpecificCredentialResponse>
```

### See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateSigningCertificate

Changes the status of the specified user signing certificate from active to disabled, or vice versa. This operation can be used to disable an IAM user's signing certificate as part of a certificate rotation work flow.

If the `UserName` field is not specified, the user name is determined implicitly based on the AWS access key ID used to sign the request. This operation works for access keys under the AWS account. Consequently, you can use this operation to manage AWS account root user credentials even if the AWS account has no associated users.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### CertificateId

The ID of the signing certificate you want to update.

This parameter allows (through its [regex pattern](#)) a string of characters that can consist of any upper or lowercased letter or digit.

Type: String

Length Constraints: Minimum length of 24. Maximum length of 128.

Pattern: `[\w]+`

Required: Yes

### Status

The status you want to assign to the certificate. Active means that the certificate can be used for programmatic calls to AWS. Inactive means that the certificate cannot be used.

Type: String

Valid Values: Active | Inactive

Required: Yes

### UserName

The name of the IAM user the signing certificate belongs to.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: No

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **LimitExceeded**

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of `UpdateSigningCertificate`.

#### Sample Request

```
https://iam.amazonaws.com/?Action=UpdateSigningCertificate
&UserName=Bob
&CertificateId=TA7SMP42TDN5Z260BPJE7EXAMPLE
&Status=Inactive
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<UpdateSigningCertificateResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>EXAMPLE8-90ab-cdef-fecd-ba987EXAMPLE</RequestId>
  </ResponseMetadata>
</UpdateSigningCertificateResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

# UpdateSSHPublicKey

Sets the status of an IAM user's SSH public key to active or inactive. SSH public keys that are inactive cannot be used for authentication. This operation can be used to disable a user's SSH public key as part of a key rotation work flow.

The SSH public key affected by this operation is used only for authenticating the associated IAM user to an CodeCommit repository. For more information about using SSH keys to authenticate to an CodeCommit repository, see [Set up CodeCommit for SSH connections](#) in the *CodeCommit User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### SSHPublicKeyId

The unique identifier for the SSH public key.

This parameter allows (through its [regex pattern](#)) a string of characters that can consist of any upper or lowercased letter or digit.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 128.

Pattern: `[\w]+`

Required: Yes

### Status

The status to assign to the SSH public key. Active means that the key can be used for authentication with an CodeCommit repository. Inactive means that the key cannot be used.

Type: String

Valid Values: Active | Inactive

Required: Yes

### UserName

The name of the IAM user associated with the SSH public key.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w+=,.@-]+`

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

## NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

# Examples

## Example

This example illustrates one usage of UpdateSSHPublicKey.

### Sample Request

```
https://iam.amazonaws.com/?Action=UpdateSSHPublicKey
&SSHPublicKeyId=APKAEIVFHP46CEXAMPLE
&Status=Inactive
&UserName=Jane
&Version=2010-05-08
&AUTHPARAMS
```

### Sample Response

```
<UpdateSSHPublicKeyResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <ResponseMetadata>
    <RequestId>d3d9215c-f36b-11e4-97ab-c53b2EXAMPLE</RequestId>
  </ResponseMetadata>
</UpdateSSHPublicKeyResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateUser

Updates the name and/or the path of the specified IAM user.

## Important

You should understand the implications of changing an IAM user's path or name. For more information, see [Renaming an IAM user](#) and [Renaming an IAM group](#) in the *IAM User Guide*.

## Note

To change a user name, the requester must have appropriate permissions on both the source object and the target object. For example, to change Bob to Robert, the entity making the request must have permission on Bob and Robert, or must have permission on all (\*). For more information about permissions, see [Permissions and policies](#).

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### NewPath

New path for the IAM user. Include this parameter only if you're changing the user's path.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of either a forward slash (/) by itself or a string that must begin and end with forward slashes. In addition, it can contain any ASCII character from the ! (\u0021) through the DEL character (\u007F), including most punctuation characters, digits, and upper and lowercased letters.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: (\u002F)|(\\u002F[\u0021-\u007F]+\u002F)

Required: No

### NewUserName

New name for the user. Include this parameter only if you're changing the user's name.

IAM user, group, role, and policy names must be unique within the account. Names are not distinguished by case. For example, you cannot create resources named both "MyResource" and "myresource".

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [\w+=,.@-]+

Required: No

### UserName

Name of the user to update. If you're changing the name of the user, this is the original user name.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: \_+=,.@-

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=, .@-]+`

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **ConcurrentModification**

The request was rejected because multiple requests to change this object were submitted simultaneously. Wait a few minutes and submit your request again.

HTTP Status Code: 409

### **EntityAlreadyExists**

The request was rejected because it attempted to create a resource that already exists.

HTTP Status Code: 409

### **EntityTemporarilyUnmodifiable**

The request was rejected because it referenced an entity that is temporarily unmodifiable, such as a user name that was deleted and then recreated. The error indicates that the request is likely to succeed if you try again after waiting several minutes. The error message describes the entity.

HTTP Status Code: 409

### **LimitExceeded**

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of `UpdateUser`.

#### Sample Request

```
https://iam.amazonaws.com/?Action=UpdateUser
```

```
&UserName=Bob
&NewUserName=Robert
&Version=2010-05-08
&AUTHPARAMS
```

## Sample Response

```
<UpdateUserResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
<UpdateUserResult>
<User>
<Path>/division_abc/subdivision_xyz/</Path>
<UserName>Robert</UserName>
<UserId>AIDACKCEVSQ6C2EXAMPLE</UserId>
<Arn>arn:aws::123456789012:user/division_abc/subdivision_xyz/Robert
</Arn>
</User>
</UpdateUserResult>
<ResponseMetadata>
<RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
</ResponseMetadata>
</UpdateUserResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UploadServerCertificate

Uploads a server certificate entity for the AWS account. The server certificate entity includes a public key certificate, a private key, and an optional certificate chain, which should all be PEM-encoded.

We recommend that you use [AWS Certificate Manager](#) to provision, manage, and deploy your server certificates. With ACM you can request a certificate, deploy it to AWS resources, and let ACM handle certificate renewals for you. Certificates provided by ACM are free. For more information about using ACM, see the [AWS Certificate Manager User Guide](#).

For more information about working with server certificates, see [Working with server certificates](#) in the *IAM User Guide*. This topic includes a list of AWS services that can use the server certificates that you manage with IAM.

For information about the number of server certificates you can upload, see [IAM and AWS STS quotas](#) in the *IAM User Guide*.

## Note

Because the body of the public key certificate, private key, and the certificate chain can be large, you should use POST rather than GET when calling `UploadServerCertificate`. For information about setting up signatures and authorization through the API, see [Signing AWS API requests](#) in the *AWS General Reference*. For general information about using the Query API with IAM, see [Calling the API by making HTTP query requests](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### **CertificateBody**

The contents of the public key certificate in PEM-encoded format.

The [regex pattern](#) used to validate this parameter is a string of characters consisting of the following:

- Any printable ASCII character ranging from the space character (\u0020) through the end of the ASCII character range
- The printable characters in the Basic Latin and Latin-1 Supplement character set (through \u00FF)
- The special characters tab (\u0009), line feed (\u000A), and carriage return (\u000D)

Type: String

Length Constraints: Minimum length of 1. Maximum length of 16384.

Pattern: [\u0009\u000A\u000D\u0020-\u00FF]+

Required: Yes

### **CertificateChain**

The contents of the certificate chain. This is typically a concatenation of the PEM-encoded public key certificates of the chain.

The [regex pattern](#) used to validate this parameter is a string of characters consisting of the following:

- Any printable ASCII character ranging from the space character (\u0020) through the end of the ASCII character range

- The printable characters in the Basic Latin and Latin-1 Supplement character set (through \u00FF)
- The special characters tab (\u0009), line feed (\u000A), and carriage return (\u000D)

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2097152.

Pattern: [\u0009\u000A\u000D\u0020-\u00FF]+

Required: No

#### Path

The path for the server certificate. For more information about paths, see [IAM identifiers in the IAM User Guide](#).

This parameter is optional. If it is not included, it defaults to a slash (/). This parameter allows (through its [regex pattern](#)) a string of characters consisting of either a forward slash (/) by itself or a string that must begin and end with forward slashes. In addition, it can contain any ASCII character from the ! (\u0021) through the DEL character (\u007F), including most punctuation characters, digits, and upper and lowercased letters.

#### Note

If you are uploading a server certificate specifically for use with Amazon CloudFront distributions, you must specify a path using the path parameter. The path must begin with /cloudfront and must include a trailing slash (for example, /cloudfront/test/).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: (\u002F)|( \u002F[\u0021-\u007F]+\u002F)

Required: No

#### PrivateKey

The contents of the private key in PEM-encoded format.

The [regex pattern](#) used to validate this parameter is a string of characters consisting of the following:

- Any printable ASCII character ranging from the space character (\u0020) through the end of the ASCII character range
- The printable characters in the Basic Latin and Latin-1 Supplement character set (through \u00FF)
- The special characters tab (\u0009), line feed (\u000A), and carriage return (\u000D)

Type: String

Length Constraints: Minimum length of 1. Maximum length of 16384.

Pattern: [\u0009\u000A\u000D\u0020-\u00FF]+

Required: Yes

#### ServerCertificateName

The name for the server certificate. Do not include the path in this value. The name of the certificate cannot contain any spaces.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: `_+=,.@-`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=,.@-]+`

Required: Yes

#### Tags.member.N

A list of tags that you want to attach to the new IAM server certificate resource. Each tag consists of a key name and an associated value. For more information about tagging, see [Tagging IAM resources](#) in the *IAM User Guide*.

##### Note

If any one of the tags is invalid or if you exceed the allowed maximum number of tags, then the entire request fails and the resource is not created.

Type: Array of [Tag \(p. 553\)](#) objects

Array Members: Maximum number of 50 items.

Required: No

## Response Elements

The following elements are returned by the service.

#### ServerCertificateMetadata

The meta information of the uploaded server certificate without its certificate body, certificate chain, and private key.

Type: [ServerCertificateMetadata \(p. 538\)](#) object

#### Tags.member.N

A list of tags that are attached to the new IAM server certificate. The returned list of tags is sorted by tag key. For more information about tagging, see [Tagging IAM resources](#) in the *IAM User Guide*.

Type: Array of [Tag \(p. 553\)](#) objects

Array Members: Maximum number of 50 items.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

#### ConcurrentModification

The request was rejected because multiple requests to change this object were submitted simultaneously. Wait a few minutes and submit your request again.

HTTP Status Code: 409

### **EntityAlreadyExists**

The request was rejected because it attempted to create a resource that already exists.

HTTP Status Code: 409

### **InvalidInput**

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

### **KeyPairMismatch**

The request was rejected because the public key certificate and the private key do not match.

HTTP Status Code: 400

### **LimitExceeded**

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### **MalformedCertificate**

The request was rejected because the certificate was malformed or expired. The error message describes the specific error.

HTTP Status Code: 400

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of UploadServerCertificate.

### Sample Request

```
https://iam.amazonaws.com/?Action=UploadServerCertificate
&ServerCertificateName=ProdServerCert
&Path=/company/servercerts/
&CertificateBody=
-----BEGIN CERTIFICATE-----
MIICdzCC AeCgAwIBAgIGANC+Ha2wMA0GCSqGSIb3DQEBBQUAMFMxCzAJBgNVBAYT
A1VTMRMwEQYDVQQKEwpBbWF6b24uY29tMQwwCgYDVQQLEwNBV1MxITAfBgNVBAMT
GEFXUyBMaW1pdGVkLUFzc3VyYW5jZSBDBQTAeFw0wOTAyMDQxNzE5MjdaFw0xMDAY
MDQxNzE5MjdaMFIxCzAJBgNVBAYTA1VTMRMwEQYDVQQKEwpBbWF6b24uY29tMRcw
FQYDVQQLEw5BV1MtRGV2ZWxvcGVyczEVMBMGA1UEAxMMNTdxND10c3ZwYjRtMIGf
MA0GCSqGSIb3DQEBAQUAA4GNADCBiQKBgQCpB/vs0wmT/00td1RqzKjttSBaPjbr
dqwNe9Br0yB08fw2+Ch5oonZYXfGUrT6mkYXH5fQot9HvASrzAKH0596FdJA6DmL
ywdWe10ggk7zFSX01Xv+3vPrJtaYxYo3eRip7w80PMki0v6M0XK8ubcTou0eJbf
suDqcLnLDxwsvwIDAQABo1cwVTA0BgnVHQ8BAf8EBAMCBaAwFgYDVR01AQH/BAww
CgYIKwYBBQUH AwIwDAYDVR0TAQH/BAIwADAdBgNVHQ4EFgQULGNaBphBumaKbDRK
CAi0mH8B3mowDQYJKoZIhvcNAQEFBQADgYEAuXhkXaCLGcqDuweKt0/AEw9ZePH
```

```
-----BEGIN CERTIFICATE-----  
&PrivateKey=  
-----BEGIN DSA PRIVATE KEY-----  
MIIBBugIBTTKBgQD33xToXPJ6hr37L3+KNi3/7DgywlBcv1FPPSHiw30Ru0/22mT  
8Cy5fT89WwNvZ3BPWKU60Z38TQ3eWjNc/3U3+oqVNG2poX5nCP0t01b96HYX2mR  
3FTdH6FRKbQEhpDzZ6tRrjTHjMX6sT3JRWkBd2c4bGu+HUH01H7QvrCTeQIVTKMs  
TCKCyrLiGhUWuUGNJUMU6y6zToGTH184Tz7TPwDGDXuy/Dk5s4jTVr+xicROC/gS  
Qrs4Dzz3T1ze61vU8S1KT9Us0B5FUJNTTPCPey+Lo4mmK6b23XdTyCIT8e2fsm2j  
jHHC1pIPiTkdLS3j6ZYjF8LY6TENFng+LDY/xwP017TJV0D3J/WXC2J9CEYq9o34  
kq6Wn3CgYTuo54nUgnoCb3xdg8C0Frg+oTb1kHTSzs3w5o/GGgKK7TDF3U1Jjq  
vhNyJQ6kWBrQRR1Xp5KYQ4c/Dm5kef+62mH53HpcCELguWVcffuVQpmq3EWL9Zp9  
jobTJQ2VHjb5IVxi06HRSd27di3njyrzUuJCyHSDTqwLJmTThpd60TIUTL3Tc4m2  
62TITdw53KWJEXAMPLE=  
-----END DSA PRIVATE KEY-----  
&Version=2010-05-08  
&AUTHPARAMS
```

## Sample Response

```
<UploadServerCertificateResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">  
<UploadServerCertificateResult>  
  <ServerCertificateMetadata>  
    <ServerCertificateName>ProdServerCert</ServerCertificateName>  
    <Path>/company/servercerts/</Path>  
    <Arn>arn:aws:iam::123456789012:server-certificate/company/servercerts/ProdServerCert</Arn>  
    <UploadDate>2010-05-08T01:02:03.004Z</UploadDate>  
    <ServerCertificateId>ASCACKCEVSQ6C2EXAMPLE</ServerCertificateId>  
    <Expiration>2012-05-08T01:02:03.004Z</Expiration>  
  </ServerCertificateMetadata>  
</UploadServerCertificateResult>  
<ResponseMetadata>  
  <RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>  
</ResponseMetadata>  
</UploadServerCertificateResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UploadSigningCertificate

Uploads an X.509 signing certificate and associates it with the specified IAM user. Some AWS services require you to use certificates to validate requests that are signed with a corresponding private key. When you upload the certificate, its default status is Active.

For information about when you would use an X.509 signing certificate, see [Managing server certificates in IAM](#) in the *IAM User Guide*.

If the `UserName` is not specified, the IAM user name is determined implicitly based on the AWS access key ID used to sign the request. This operation works for access keys under the AWS account. Consequently, you can use this operation to manage AWS account root user credentials even if the AWS account has no associated users.

## Note

Because the body of an X.509 certificate can be large, you should use POST rather than GET when calling `UploadSigningCertificate`. For information about setting up signatures and authorization through the API, see [Signing AWS API requests](#) in the *AWS General Reference*. For general information about using the Query API with IAM, see [Making query requests](#) in the *IAM User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### `CertificateBody`

The contents of the signing certificate.

The [regex pattern](#) used to validate this parameter is a string of characters consisting of the following:

- Any printable ASCII character ranging from the space character (\u0020) through the end of the ASCII character range
- The printable characters in the Basic Latin and Latin-1 Supplement character set (through \u00FF)
- The special characters tab (\u0009), line feed (\u000A), and carriage return (\u000D)

Type: String

Length Constraints: Minimum length of 1. Maximum length of 16384.

Pattern: [\u0009\u000A\u000D\u0020-\u00FF]+

Required: Yes

### `UserName`

The name of the user the signing certificate is for.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: \_+=,.@-

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=, .@-]+`

Required: No

## Response Elements

The following element is returned by the service.

### **Certificate**

Information about the certificate.

Type: [SigningCertificate \(p. 546\)](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### **DuplicateCertificate**

The request was rejected because the same certificate is associated with an IAM user in the account.

HTTP Status Code: 409

### **EntityAlreadyExists**

The request was rejected because it attempted to create a resource that already exists.

HTTP Status Code: 409

### **InvalidCertificate**

The request was rejected because the certificate is invalid.

HTTP Status Code: 400

### **LimitExceeded**

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### **MalformedCertificate**

The request was rejected because the certificate was malformed or expired. The error message describes the specific error.

HTTP Status Code: 400

### **NoSuchEntity**

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### **ServiceFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## Examples

### Example

This example illustrates one usage of `UploadSigningCertificate`.

#### Sample Request

```
https://iam.amazonaws.com/?Action=UploadSigningCertificate
&UserName=Bob
&CertificateBody=
-----BEGIN CERTIFICATE-----
MIICdzCCAeCgAwIBAgIGANC+Ha2wMA0GCSqGSIb3DQEBCUAMFMxCzAJBgNVBAYT
A1VTMRMwEQYDVQQKEwpBbWF6b24uY29tMQwwCgYDVQQLEwNBV1MxITAfBgNVBAMT
GEFXUyBmA1pdGVkLUFc3VYw5jZSBQTAeFw0wOTAYMDQxNzE5MjdaFw0xMDAY
MDQxNzE5MjdaMF1xCzAJBgNVBAYTA1VTMRMwEQYDVQQKEwpBbWF6b24uY29tMRCw
FQYDVQQLEw5BV1M1tRGV2ZwvcGVyczEVMBMGA1UEAxMMNTdxND10c3ZwYjRtMIGf
MA0GCSqGSIb3DQEBAQUAA4GNADCBiQKBgQCpB/vs0wmT/00td1RqzKjttSBaPjbr
dqwNe9Br0yB08fw2+Ch5oonZYxfGUrT6mkYXH5fQot9HvASrzAKH0596FdJA6DmL
ywdWe10ggk7zFSX01Xv+3vPrJtaYxYo3eRIp7w80PMki0v6M0XK8ubcTou0DeJbf
suDqcLnLDxwsvwIDAQABo1cwVTAOBgNVHQ8BAf8EBAMCBaAwFgYDVRO1AQH/BAww
CgYIKwYBBQUHAWiDAYDVR0TAQH/BAiwADAdBgNVHQ4EFgQULGNaBphBumaKbDRK
CAi0mH8B3mowDQYJKoZIhvcNAQEFBQADgYEAuKxhkXaCLGcqDuweKt0/AEw9ZePH
wR0XqsaIK2HZboqtruebXEGsojK4Ks0WzwgrEynuHJwTn760xe39rSqXWI0Gr0Bax
wFpWHVjTFMKK+tSDG1lssLHyYwWdFFU4AnejRGORJYNaRHgVTkjhphc5jEhHm0BX
AEaHzTpmEXAMPLE=
-----END CERTIFICATE-----
&Version=2010-05-08
&AUTHPARAMS
```

#### Sample Response

```
<UploadSigningCertificateResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <UploadSigningCertificateResult>
    <Certificate>
      <UserName>Bob</UserName>
      <CertificateId>TA7SMP42TDN5Z260BPJE7EXAMPLE</CertificateId>
      <CertificateBody>
-----BEGIN CERTIFICATE-----
MIICdzCCAeCgAwIBAgIGANC+Ha2wMA0GCSqGSIb3DQEBCUAMFMxCzAJBgNVBAYT
A1VTMRMwEQYDVQQKEwpBbWF6b24uY29tMQwwCgYDVQQLEwNBV1MxITAfBgNVBAMT
GEFXUyBmA1pdGVkLUFc3VYw5jZSBQTAeFw0wOTAYMDQxNzE5MjdaFw0xMDAY
MDQxNzE5MjdaMF1xCzAJBgNVBAYTA1VTMRMwEQYDVQQKEwpBbWF6b24uY29tMRCw
FQYDVQQLEw5BV1M1tRGV2ZwvcGVyczEVMBMGA1UEAxMMNTdxND10c3ZwYjRtMIGf
MA0GCSqGSIb3DQEBAQUAA4GNADCBiQKBgQCpB/vs0wmT/00td1RqzKjttSBaPjbr
dqwNe9Br0yB08fw2+Ch5oonZYxfGUrT6mkYXH5fQot9HvASrzAKH0596FdJA6DmL
ywdWe10ggk7zFSX01Xv+3vPrJtaYxYo3eRIp7w80PMki0v6M0XK8ubcTou0DeJbf
suDqcLnLDxwsvwIDAQABo1cwVTAOBgNVHQ8BAf8EBAMCBaAwFgYDVRO1AQH/BAww
CgYIKwYBBQUHAWiDAYDVR0TAQH/BAiwADAdBgNVHQ4EFgQULGNaBphBumaKbDRK
CAi0mH8B3mowDQYJKoZIhvcNAQEFBQADgYEAuKxhkXaCLGcqDuweKt0/AEw9ZePH
wR0XqsaIK2HZboqtruebXEGsojK4Ks0WzwgrEynuHJwTn760xe39rSqXWI0Gr0Bax
wFpWHVjTFMKK+tSDG1lssLHyYwWdFFU4AnejRGORJYNaRHgVTkjhphc5jEhHm0BX
AEaHzTpmEXAMPLE=
-----END CERTIFICATE-----
      </CertificateBody>
      <Status>Active</Status>
    </Certificate>
  </UploadSigningCertificateResult>
  <ResponseMetadata>
    <RequestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</RequestId>
  </ResponseMetadata>
</UploadSigningCertificateResponse>
```

```
</UploadSigningCertificateResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UploadSSHPublicKey

Uploads an SSH public key and associates it with the specified IAM user.

The SSH public key uploaded by this operation can be used only for authenticating the associated IAM user to an CodeCommit repository. For more information about using SSH keys to authenticate to an CodeCommit repository, see [Set up CodeCommit for SSH connections](#) in the *CodeCommit User Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 563\)](#).

### SSHPublicKeyBody

The SSH public key. The public key must be encoded in ssh-rsa format or PEM format. The minimum bit-length of the public key is 2048 bits. For example, you can generate a 2048-bit key, and the resulting PEM file is 1679 bytes long.

The [regex pattern](#) used to validate this parameter is a string of characters consisting of the following:

- Any printable ASCII character ranging from the space character (\u0020) through the end of the ASCII character range
- The printable characters in the Basic Latin and Latin-1 Supplement character set (through \u00FF)
- The special characters tab (\u0009), line feed (\u000A), and carriage return (\u000D)

Type: String

Length Constraints: Minimum length of 1. Maximum length of 16384.

Pattern: [\u0009\u000A\u000D\u0020-\u00FF]+

Required: Yes

### UserName

The name of the IAM user to associate the SSH public key with.

This parameter allows (through its [regex pattern](#)) a string of characters consisting of upper and lowercase alphanumeric characters with no spaces. You can also include any of the following characters: \_+=,.@-

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [\w+=,.@-]+

Required: Yes

## Response Elements

The following element is returned by the service.

### SSHPublicKey

Contains information about the SSH public key.

Type: [SSHPublicKey \(p. 548\)](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 565\)](#).

### DuplicateSSHPublicKey

The request was rejected because the SSH public key is already associated with the specified IAM user.

HTTP Status Code: 400

### InvalidPublicKey

The request was rejected because the public key is malformed or otherwise invalid.

HTTP Status Code: 400

### LimitExceeded

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error message describes the limit exceeded.

HTTP Status Code: 409

### NoSuchEntity

The request was rejected because it referenced a resource entity that does not exist. The error message describes the resource.

HTTP Status Code: 404

### UnrecognizedPublicKeyEncoding

The request was rejected because the public key encoding format is unsupported or unrecognized.

HTTP Status Code: 400

## Examples

### Example

This example illustrates one usage of `UploadSSHPublicKey`.

### Sample Request

```
https://iam.amazonaws.com/?Action=UploadSSHPublicKey
&SSHPublicKeyBody=ssh-rsa AAAAB3NzaC1yc2EAAAQABAAQCy75ak72GGaoZNy0cjUERIn
+mrga0C30kmkiw0eN4H6YtvCdUksVppjP0hm485WFRzvIcxAMeuZ9ISAk8AfefybxH0PdQWhELSu0p
HaMnADAU7d0n3CCer08+0sycbu4E$4P+cdK1qet3ptsG/zeQNLLm0K5zjIRa1MAS3KnwLwHEVPEe4JD
+xfghu00nwzUgpneGNwk7m7qihYLFnNCFdeU80eIr9Fmc75g5o1Hm6ZoC/bccAHurHkfcDpanJTLnFL
R50j14CZSsRP4kNdm+oe5+IPM78w4J9v4pXU4mizYDE21G4gUDVx0rs0X661MihX6A1VgmEK+NK5GQq
n9z jane@example.com
&UserName=Jane
&Version=2010-05-08
&AUTHPARAMS
```

## Sample Response

```
<UploadSSHPublicKeyResponse xmlns="https://iam.amazonaws.com/doc/2010-05-08/">
  <UploadSSHPublicKeyResult>
    <PublicKey>
      <UploadDate>2015-06-05T20:56:46.012Z</UploadDate>
      <Fingerprint>7a:1d:ea:9e:b0:80:ac:f8:ec:d8:dc:e6:a7:2c:fc:51</Fingerprint>
      <UserName>Jane</UserName>
      <SSHPublicKeyId>APKAEIVFHP46CEEXAMPLE</SSHPublicKeyId>
      <Status>Active</Status>
      <SSHPublicKeyBody>
        ssh-rsa AAAAB3NzaC1yc2EAAAQABAAQCy75ak72GGaoZNy0cjUERIn+mrga0C30k
        mkiw0eN4H6YtvCdUksVppjP0hm485WFRzvIcxamEuZ9ISAk8AfefybxH0PdQWhELSu0pHa
        MnADAU7d0n3CCer08+0sycbu4ES4P+cdK1qet3ptsG/zeQNLLm0K5zjIRa1MAS3KnwLwHEV
        PEe4JD+xfghu00nwzUgpneGNwk7m7qihYLFnNCFdeU80eIr9Fmc75g5olHm6ZoC/bccAHur
        HkfcDpanJTLNfLR50j14CZSsRP4kNdm+oe5+IPM78w4J9v4pXU4mizYDE21G4gUDVx0rs0X
        661MihX6ArVgmEK+NK5Gqgn9z jane@example.com
      </SSHPublicKeyBody>
    </PublicKey>
  </UploadSSHPublicKeyResult>
  <ResponseMetadata>
    <RequestId>3da97a2f-f369-11e4-97ab-c53b2EXAMPLE</RequestId>
  </ResponseMetadata>
</UploadSSHPublicKeyResponse>
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# Data Types

The AWS Identity and Access Management API contains several data types that various actions use. This section describes each data type in detail.

## **Note**

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AccessDetail \(p. 477\)](#)
- [AccessKey \(p. 479\)](#)
- [AccessKeyLastUsed \(p. 481\)](#)
- [AccessKeyMetadata \(p. 483\)](#)
- [AttachedPermissionsBoundary \(p. 485\)](#)
- [AttachedPolicy \(p. 486\)](#)
- [ContextEntry \(p. 487\)](#)
- [DeletionTaskFailureReasonType \(p. 488\)](#)
- [EntityDetails \(p. 489\)](#)
- [EntityInfo \(p. 490\)](#)
- [ErrorDetails \(p. 492\)](#)
- [EvaluationResult \(p. 493\)](#)
- [Group \(p. 496\)](#)
- [GroupDetail \(p. 498\)](#)
- [InstanceProfile \(p. 500\)](#)
- [ListPoliciesGrantingServiceAccessEntry \(p. 502\)](#)
- [LoginProfile \(p. 503\)](#)
- [ManagedPolicyDetail \(p. 504\)](#)
- [MFADevice \(p. 507\)](#)
- [OpenIDConnectProviderListEntry \(p. 508\)](#)
- [OrganizationsDecisionDetail \(p. 509\)](#)
- [PasswordPolicy \(p. 510\)](#)
- [PermissionsBoundaryDecisionDetail \(p. 512\)](#)
- [Policy \(p. 513\)](#)
- [PolicyDetail \(p. 516\)](#)
- [PolicyGrantingServiceAccess \(p. 517\)](#)
- [PolicyGroup \(p. 519\)](#)
- [PolicyRole \(p. 520\)](#)
- [PolicyUser \(p. 521\)](#)
- [PolicyVersion \(p. 522\)](#)
- [Position \(p. 524\)](#)
- [ResourceSpecificResult \(p. 525\)](#)
- [Role \(p. 527\)](#)
- [RoleDetail \(p. 530\)](#)
- [RoleLastUsed \(p. 533\)](#)

- [RoleUsageType \(p. 534\)](#)
- [SAMLProviderListEntry \(p. 535\)](#)
- [ServerCertificate \(p. 536\)](#)
- [ServerCertificateMetadata \(p. 538\)](#)
- [ServiceLastAccessed \(p. 540\)](#)
- [ServiceSpecificCredential \(p. 542\)](#)
- [ServiceSpecificCredentialMetadata \(p. 544\)](#)
- [SigningCertificate \(p. 546\)](#)
- [SSHPublicKey \(p. 548\)](#)
- [SSHPublicKeyMetadata \(p. 550\)](#)
- [Statement \(p. 552\)](#)
- [Tag \(p. 553\)](#)
- [TrackedActionLastAccessed \(p. 554\)](#)
- [User \(p. 556\)](#)
- [UserDetail \(p. 558\)](#)
- [VirtualMFADevice \(p. 561\)](#)

## AccessDetail

An object that contains details about when a principal in the reported AWS Organizations entity last attempted to access an AWS service. A principal can be an IAM user, an IAM role, or the AWS account root user within the reported Organizations entity.

This data type is a response element in the [GetOrganizationsAccessReport \(p. 177\)](#) operation.

## Contents

### EntityPath

The path of the Organizations entity (root, organizational unit, or account) from which an authenticated principal last attempted to access the service. AWS does not report unauthenticated requests.

This field is null if no principals (IAM users, IAM roles, or root users) in the reported Organizations entity attempted to access the service within the [tracking period](#).

Type: String

Length Constraints: Minimum length of 19. Maximum length of 427.

Pattern: ^o-[0-9a-z]{10,32}\r-[0-9a-z]{4,32}[0-9a-z-\r]\*

Required: No

### LastAuthenticatedTime

The date and time, in [ISO 8601 date-time format](#), when an authenticated principal most recently attempted to access the service. AWS does not report unauthenticated requests.

This field is null if no principals in the reported Organizations entity attempted to access the service within the [tracking period](#).

Type: Timestamp

Required: No

### Region

The Region where the last service access attempt occurred.

This field is null if no principals in the reported Organizations entity attempted to access the service within the [tracking period](#).

Type: String

Required: No

### ServiceName

The name of the service in which access was attempted.

Type: String

Required: Yes

### ServiceNamespace

The namespace of the service in which access was attempted.

To learn the service namespace of a service, see [Actions, resources, and condition keys for AWS services](#) in the *Service Authorization Reference*. Choose the name of the service to view details for that service. In the first paragraph, find the service prefix. For example, (service prefix: a4b). For more information about service namespaces, see [AWS service namespaces](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w-]*`

Required: Yes

#### **TotalAuthenticatedEntities**

The number of accounts with authenticated principals (root users, IAM users, and IAM roles) that attempted to access the service in the tracking period.

Type: Integer

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# AccessKey

Contains information about an AWS access key.

This data type is used as a response element in the [CreateAccessKey \(p. 25\)](#) and [ListAccessKeys \(p. 219\)](#) operations.

## Note

The `SecretAccessKey` value is returned only in response to [CreateAccessKey \(p. 25\)](#). You can get a secret access key only when you first create an access key; you cannot recover the secret access key later. If you lose a secret access key, you must create a new access key.

## Contents

### AccessKeyId

The ID for this access key.

Type: String

Length Constraints: Minimum length of 16. Maximum length of 128.

Pattern: `[\w]+`

Required: Yes

### CreateDate

The date when the access key was created.

Type: Timestamp

Required: No

### SecretAccessKey

The secret key used to sign requests.

Type: String

Required: Yes

### Status

The status of the access key. `Active` means that the key is valid for API calls, while `Inactive` means it is not.

Type: String

Valid Values: `Active` | `Inactive`

Required: Yes

### UserName

The name of the IAM user that the access key is associated with.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w+=, .@-]+`

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# AccessKeyLastUsed

Contains information about the last time an AWS access key was used since IAM began tracking this information on April 22, 2015.

This data type is used as a response element in the [GetAccessKeyLastUsed \(p. 140\)](#) operation.

## Contents

### LastUsedDate

The date and time, in [ISO 8601 date-time format](#), when the access key was most recently used. This field is null in the following situations:

- The user does not have an access key.
- An access key exists but has not been used since IAM began tracking this information.
- There is no sign-in data associated with the user.

Type: Timestamp

Required: Yes

### Region

The AWS Region where this access key was most recently used. The value for this field is "N/A" in the following situations:

- The user does not have an access key.
- An access key exists but has not been used since IAM began tracking this information.
- There is no sign-in data associated with the user.

For more information about AWS Regions, see [Regions and endpoints](#) in the Amazon Web Services General Reference.

Type: String

Required: Yes

### ServiceName

The name of the AWS service with which this access key was most recently used. The value of this field is "N/A" in the following situations:

- The user does not have an access key.
- An access key exists but has not been used since IAM started tracking this information.
- There is no sign-in data associated with the user.

Type: String

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

# AccessKeyMetadata

Contains information about an AWS access key, without its secret key.

This data type is used as a response element in the [ListAccessKeys \(p. 219\)](#) operation.

## Contents

### AccessKeyId

The ID for this access key.

Type: String

Length Constraints: Minimum length of 16. Maximum length of 128.

Pattern: `[\w]+`

Required: No

### CreateDate

The date when the access key was created.

Type: Timestamp

Required: No

### Status

The status of the access key. Active means that the key is valid for API calls; Inactive means it is not.

Type: String

Valid Values: Active | Inactive

Required: No

### UserName

The name of the IAM user that the key is associated with.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w+=, .@-]+`

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)



# AttachedPermissionsBoundary

Contains information about an attached permissions boundary.

An attached permissions boundary is a managed policy that has been attached to a user or role to set the permissions boundary.

For more information about permissions boundaries, see [Permissions boundaries for IAM identities](#) in the *IAM User Guide*.

## Contents

### PermissionsBoundaryArn

The ARN of the policy used to set the permissions boundary for the user or role.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: No

### PermissionsBoundaryType

The permissions boundary usage type that indicates what type of IAM resource is used as the permissions boundary for an entity. This data type can only have a value of Policy.

Type: String

Valid Values: `PermissionsBoundaryPolicy`

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# AttachedPolicy

Contains information about an attached policy.

An attached policy is a managed policy that has been attached to a user, group, or role. This data type is used as a response element in the [ListAttachedGroupPolicies \(p. 225\)](#), [ListAttachedRolePolicies \(p. 229\)](#), [ListAttachedUserPolicies \(p. 233\)](#), and [GetAccountAuthorizationDetails \(p. 142\)](#) operations.

For more information about managed policies, refer to [Managed policies and inline policies](#) in the *IAM User Guide*.

## Contents

### PolicyArn

The Amazon Resource Name (ARN). ARNs are unique identifiers for AWS resources.

For more information about ARNs, go to [Amazon Resource Names \(ARNs\)](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: No

### PolicyName

The friendly name of the attached policy.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=, .@-]+`

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ContextEntry

Contains information about a condition context key. It includes the name of the key and specifies the value (or values, if the context key supports multiple values) to use in the simulation. This information is used when evaluating the Condition elements of the input policies.

This data type is used as an input parameter to [SimulateCustomPolicy \(p. 356\)](#) and [SimulatePrincipalPolicy \(p. 365\)](#).

## Contents

### ContextKeyName

The full name of a condition context key, including the service prefix. For example, aws:SourceIp or s3:VersionId.

Type: String

Length Constraints: Minimum length of 5. Maximum length of 256.

Required: No

### ContextKeyType

The data type of the value (or values) specified in the ContextKeyValues parameter.

Type: String

Valid Values: string | stringList | numeric | numericList | boolean | booleanList | ip | ipList | binary | binaryList | date | dateList

Required: No

### ContextKeyValues.member.N

The value (or values, if the condition context key supports multiple values) to provide to the simulation when the key is referenced by a Condition element in an input policy.

Type: Array of strings

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# DeletionTaskFailureReasonType

The reason that the service-linked role deletion failed.

This data type is used as a response element in the [GetServiceLinkedRoleDeletionStatus \(p. 207\)](#) operation.

## Contents

### Reason

A short description of the reason that the service-linked role deletion failed.

Type: String

Length Constraints: Maximum length of 1000.

Required: No

### RoleUsageList.member.N

A list of objects that contains details about the service-linked role deletion failure, if that information is returned by the service. If the service-linked role has active sessions or if any resources that were used by the role have not been deleted from the linked service, the role can't be deleted. This parameter includes a list of the resources that are associated with the role and the Region in which the resources are being used.

Type: Array of [RoleUsageType \(p. 534\)](#) objects

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# EntityDetails

An object that contains details about when the IAM entities (users or roles) were last used in an attempt to access the specified AWS service.

This data type is a response element in the [GetServiceLastAccessedDetailsWithEntities \(p. 203\)](#) operation.

## Contents

### EntityInfo

The EntityInfo object that contains details about the entity (user or role).

Type: [EntityInfo \(p. 490\)](#) object

Required: Yes

### LastAuthenticated

The date and time, in [ISO 8601 date-time format](#), when the authenticated entity last attempted to access AWS. AWS does not report unauthenticated requests.

This field is null if no IAM entities attempted to access the service within the [tracking period](#).

Type: Timestamp

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# EntityInfo

Contains details about the specified entity (user or role).

This data type is an element of the [EntityDetails \(p. 489\)](#) object.

## Contents

### Arn

The Amazon Resource Name (ARN). ARNs are unique identifiers for AWS resources.

For more information about ARNs, go to [Amazon Resource Names \(ARNs\)](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

### Id

The identifier of the entity (user or role).

Type: String

Length Constraints: Minimum length of 16. Maximum length of 128.

Pattern: [\w]+

Required: Yes

### Name

The name of the entity (user or role).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [\w+=, .@-]+

Required: Yes

### Path

The path to the entity (user or role). For more information about paths, see [IAM identifiers](#) in the *IAM User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: (\u002F)|(\\u002F[\u0021-\u007F]+\u002F)

Required: No

### Type

The type of entity (user or role).

Type: String

Valid Values: USER | ROLE | GROUP

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

## ErrorDetails

Contains information about the reason that the operation failed.

This data type is used as a response element in the [GetOrganizationsAccessReport \(p. 177\)](#), [GetServiceLastAccessedDetails \(p. 198\)](#), and [GetServiceLastAccessedDetailsWithEntities \(p. 203\)](#) operations.

## Contents

### Code

The error code associated with the operation failure.

Type: String

Required: Yes

### Message

Detailed information about the reason that the operation failed.

Type: String

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# EvaluationResult

Contains the results of a simulation.

This data type is used by the return parameter of [SimulateCustomPolicy \(p. 356\)](#) and [SimulatePrincipalPolicy \(p. 365\)](#).

## Contents

### **EvalActionName**

The name of the API operation tested on the indicated resource.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Required: Yes

### **EvalDecision**

The result of the simulation.

Type: String

Valid Values: allowed | explicitDeny | implicitDeny

Required: Yes

### **EvalDecisionDetails , EvalDecisionDetails.entry.N.key (key) , EvalDecisionDetails.entry.N.value (value)**

Additional details about the results of the cross-account evaluation decision. This parameter is populated for only cross-account simulations. It contains a brief summary of how each policy type contributes to the final evaluation decision.

If the simulation evaluates policies within the same account and includes a resource ARN, then the parameter is present but the response is empty. If the simulation evaluates policies within the same account and specifies all resources (\*), then the parameter is not returned.

When you make a cross-account request, AWS evaluates the request in the trusting account and the trusted account. The request is allowed only if both evaluations return true. For more information about how policies are evaluated, see [Evaluating policies within a single account](#).

If an AWS Organizations SCP included in the evaluation denies access, the simulation ends. In this case, policy evaluation does not proceed any further and this parameter is not returned.

Type: String to string map

Key Length Constraints: Minimum length of 3. Maximum length of 256.

Valid Values: allowed | explicitDeny | implicitDeny

Required: No

### **EvalResourceName**

The ARN of the resource that the indicated API operation was tested on.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

#### **MatchedStatements.member.N**

A list of the statements in the input policies that determine the result for this scenario. Remember that even if multiple statements allow the operation on the resource, if only one statement denies that operation, then the explicit deny overrides any allow. In addition, the deny statement is the only entry included in the result.

Type: Array of [Statement \(p. 552\)](#) objects

Required: No

#### **MissingContextValues.member.N**

A list of context keys that are required by the included input policies but that were not provided by one of the input parameters. This list is used when the resource in a simulation is "\*", either explicitly, or when the ResourceArns parameter blank. If you include a list of resources, then any missing context values are instead included under the ResourceSpecificResults section. To discover the context keys used by a set of policies, you can call [GetContextKeysForCustomPolicy \(p. 155\)](#) or [GetContextKeysForPrincipalPolicy \(p. 158\)](#).

Type: Array of strings

Length Constraints: Minimum length of 5. Maximum length of 256.

Required: No

#### **OrganizationsDecisionDetail**

A structure that details how Organizations and its service control policies affect the results of the simulation. Only applies if the simulated user's account is part of an organization.

Type: [OrganizationsDecisionDetail \(p. 509\)](#) object

Required: No

#### **PermissionsBoundaryDecisionDetail**

Contains information about the effect that a permissions boundary has on a policy simulation when the boundary is applied to an IAM entity.

Type: [PermissionsBoundaryDecisionDetail \(p. 512\)](#) object

Required: No

#### **ResourceSpecificResults.member.N**

The individual results of the simulation of the API operation specified in EvalActionName on each resource.

Type: Array of [ResourceSpecificResult \(p. 525\)](#) objects

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

# Group

Contains information about an IAM group entity.

This data type is used as a response element in the following operations:

- [CreateGroup \(p. 30\)](#)
- [GetGroup \(p. 163\)](#)
- [ListGroups \(p. 244\)](#)

## Contents

### Arn

The Amazon Resource Name (ARN) specifying the group. For more information about ARNs and how to use them in policies, see [IAM identifiers](#) in the *IAM User Guide*.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

### CreateDate

The date and time, in [ISO 8601 date-time format](#), when the group was created.

Type: Timestamp

Required: Yes

### GroupId

The stable and unique string identifying the group. For more information about IDs, see [IAM identifiers](#) in the *IAM User Guide*.

Type: String

Length Constraints: Minimum length of 16. Maximum length of 128.

Pattern: `[\w]+`

Required: Yes

### GroupName

The friendly name that identifies the group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=, .@-]+`

Required: Yes

### Path

The path to the group. For more information about paths, see [IAM identifiers](#) in the *IAM User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: (\u002F)|(\\u002F[\u0021-\u007F]+\u002F)

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# GroupDetail

Contains information about an IAM group, including all of the group's policies.

This data type is used as a response element in the [GetAccountAuthorizationDetails \(p. 142\)](#) operation.

## Contents

### Arn

The Amazon Resource Name (ARN). ARNs are unique identifiers for AWS resources.

For more information about ARNs, go to [Amazon Resource Names \(ARNs\)](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: No

### AttachedManagedPolicies.member.N

A list of the managed policies attached to the group.

Type: Array of [AttachedPolicy \(p. 486\)](#) objects

Required: No

### CreateDate

The date and time, in [ISO 8601 date-time format](#), when the group was created.

Type: Timestamp

Required: No

### GroupId

The stable and unique string identifying the group. For more information about IDs, see [IAM identifiers](#) in the *IAM User Guide*.

Type: String

Length Constraints: Minimum length of 16. Maximum length of 128.

Pattern: `[\w]+`

Required: No

### GroupName

The friendly name that identifies the group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=, .@-]+`

Required: No

### **GroupPolicyList.member.N**

A list of the inline policies embedded in the group.

Type: Array of [PolicyDetail \(p. 516\)](#) objects

Required: No

### **Path**

The path to the group. For more information about paths, see [IAM identifiers](#) in the *IAM User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: (\u002F)|(\\u002F[\u0021-\u007F]+\u002F)

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# InstanceProfile

Contains information about an instance profile.

This data type is used as a response element in the following operations:

- [CreateInstanceProfile \(p. 33\)](#)
- [GetInstanceProfile \(p. 169\)](#)
- [ListInstanceProfiles \(p. 250\)](#)
- [ListInstanceProfilesForRole \(p. 253\)](#)

## Contents

### Arn

The Amazon Resource Name (ARN) specifying the instance profile. For more information about ARNs and how to use them in policies, see [IAM identifiers](#) in the *IAM User Guide*.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

### CreateDate

The date when the instance profile was created.

Type: Timestamp

Required: Yes

### InstanceProfileId

The stable and unique string identifying the instance profile. For more information about IDs, see [IAM identifiers](#) in the *IAM User Guide*.

Type: String

Length Constraints: Minimum length of 16. Maximum length of 128.

Pattern: `[\w]+`

Required: Yes

### InstanceProfileName

The name identifying the instance profile.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=, .@-]+`

Required: Yes

### Path

The path to the instance profile. For more information about paths, see [IAM identifiers](#) in the *IAM User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: (\u002F)|(\\u002F[\u0021-\u007F]+\u002F)

Required: Yes

**Roles.member.N**

The role associated with the instance profile.

Type: Array of [Role \(p. 527\)](#) objects

Required: Yes

**Tags.member.N**

A list of tags that are attached to the instance profile. For more information about tagging, see [Tagging IAM resources](#) in the *IAM User Guide*.

Type: Array of [Tag \(p. 553\)](#) objects

Array Members: Maximum number of 50 items.

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ListPoliciesGrantingServiceAccessEntry

Contains details about the permissions policies that are attached to the specified identity (user, group, or role).

This data type is used as a response element in the [ListPoliciesGrantingServiceAccess \(p. 274\)](#) operation.

## Contents

### **Policies.member.N**

The PoliciesGrantingServiceAccess object that contains details about the policy.

Type: Array of [PolicyGrantingServiceAccess \(p. 517\)](#) objects

Required: No

### **ServiceNamespace**

The namespace of the service that was accessed.

To learn the service namespace of a service, see [Actions, resources, and condition keys for AWS services](#) in the *Service Authorization Reference*. Choose the name of the service to view details for that service. In the first paragraph, find the service prefix. For example, (service prefix: a4b). For more information about service namespaces, see [AWS service namespaces](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w-]*`

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# LoginProfile

Contains the user name and password create date for a user.

This data type is used as a response element in the [CreateLoginProfile \(p. 36\)](#) and [GetLoginProfile \(p. 172\)](#) operations.

## Contents

### **CreateDate**

The date when the password for the user was created.

Type: `Timestamp`

Required: Yes

### **PasswordResetRequired**

Specifies whether the user is required to set a new password on next sign-in.

Type: `Boolean`

Required: No

### **UserName**

The name of the user, which can be used for signing in to the AWS Management Console.

Type: `String`

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w+=, .@-]+`

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ManagedPolicyDetail

Contains information about a managed policy, including the policy's ARN, versions, and the number of principal entities (users, groups, and roles) that the policy is attached to.

This data type is used as a response element in the [GetAccountAuthorizationDetails \(p. 142\)](#) operation.

For more information about managed policies, see [Managed policies and inline policies](#) in the *IAM User Guide*.

## Contents

### Arn

The Amazon Resource Name (ARN). ARNs are unique identifiers for AWS resources.

For more information about ARNs, go to [Amazon Resource Names \(ARNs\)](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: No

### AttachmentCount

The number of principal entities (users, groups, and roles) that the policy is attached to.

Type: Integer

Required: No

### CreateDate

The date and time, in [ISO 8601 date-time format](#), when the policy was created.

Type: Timestamp

Required: No

### DefaultVersionId

The identifier for the version of the policy that is set as the default (operative) version.

For more information about policy versions, see [Versioning for managed policies](#) in the *IAM User Guide*.

Type: String

Pattern: `v[1-9][0-9]*(\.[A-Za-z0-9-]*)?`

Required: No

### Description

A friendly description of the policy.

Type: String

Length Constraints: Maximum length of 1000.

Required: No

**IsAttachable**

Specifies whether the policy can be attached to an IAM user, group, or role.

Type: Boolean

Required: No

**Path**

The path to the policy.

For more information about paths, see [IAM identifiers](#) in the *IAM User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: ((/[A-Za-z0-9\.,\+@=\_-]+)\*)/

Required: No

**PermissionsBoundaryUsageCount**

The number of entities (users and roles) for which the policy is used as the permissions boundary.

For more information about permissions boundaries, see [Permissions boundaries for IAM identities](#) in the *IAM User Guide*.

Type: Integer

Required: No

**PolicyId**

The stable and unique string identifying the policy.

For more information about IDs, see [IAM identifiers](#) in the *IAM User Guide*.

Type: String

Length Constraints: Minimum length of 16. Maximum length of 128.

Pattern: [\w]+

Required: No

**PolicyName**

The friendly name (not ARN) identifying the policy.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [\w+=,.@-]+

Required: No

**PolicyVersionList.member.N**

A list containing information about the versions of the policy.

Type: Array of [PolicyVersion](#) (p. 522) objects

Required: No

### UpdateDate

The date and time, in [ISO 8601 date-time format](#), when the policy was last updated.

When a policy has only one version, this field contains the date and time when the policy was created. When a policy has more than one version, this field contains the date and time when the most recent policy version was created.

Type: [Timestamp](#)

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# MFADevice

Contains information about an MFA device.

This data type is used as a response element in the [ListMFADevices \(p. 259\)](#) operation.

## Contents

### **EnableDate**

The date when the MFA device was enabled for the user.

Type: `Timestamp`

Required: Yes

### **SerialNumber**

The serial number that uniquely identifies the MFA device. For virtual MFA devices, the serial number is the device ARN.

Type: `String`

Length Constraints: Minimum length of 9. Maximum length of 256.

Pattern: `[\w+=/:,.@-]+`

Required: Yes

### **UserName**

The user with whom the MFA device is associated.

Type: `String`

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w+=,.@-]+`

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# OpenIDConnectProviderListEntry

Contains the Amazon Resource Name (ARN) for an IAM OpenID Connect provider.

## Contents

### Arn

The Amazon Resource Name (ARN). ARNs are unique identifiers for AWS resources.

For more information about ARNs, go to [Amazon Resource Names \(ARNs\)](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# OrganizationsDecisionDetail

Contains information about the effect that Organizations has on a policy simulation.

## Contents

### AllowedByOrganizations

Specifies whether the simulated operation is allowed by the Organizations service control policies that impact the simulated user's account.

Type: Boolean

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# PasswordPolicy

Contains information about the account password policy.

This data type is used as a response element in the [GetAccountPasswordPolicy \(p. 149\)](#) operation.

## Contents

### AllowUsersToChangePassword

Specifies whether IAM users are allowed to change their own password. Gives IAM users permissions to `iam:ChangePassword` for only their user and to the `iam:GetAccountPasswordPolicy` action. This option does not attach a permissions policy to each user, rather the permissions are applied at the account-level for all users by IAM.

Type: Boolean

Required: No

### ExpirePasswords

Indicates whether passwords in the account expire. Returns true if `MaxPasswordAge` contains a value greater than 0. Returns false if `MaxPasswordAge` is 0 or not present.

Type: Boolean

Required: No

### HardExpiry

Specifies whether IAM users are prevented from setting a new password via the AWS Management Console after their password has expired. The IAM user cannot access the console until an administrator resets the password. IAM users with `iam:ChangePassword` permission and active access keys can reset their own expired console password using the AWS CLI or API.

Type: Boolean

Required: No

### MaxPasswordAge

The number of days that an IAM user password is valid.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1095.

Required: No

### MinimumPasswordLength

Minimum length to require for IAM user passwords.

Type: Integer

Valid Range: Minimum value of 6. Maximum value of 128.

Required: No

### PasswordReusePrevention

Specifies the number of previous passwords that IAM users are prevented from reusing.

---

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 24.

Required: No

#### **RequireLowercaseCharacters**

Specifies whether IAM user passwords must contain at least one lowercase character (a to z).

Type: Boolean

Required: No

#### **RequireNumbers**

Specifies whether IAM user passwords must contain at least one numeric character (0 to 9).

Type: Boolean

Required: No

#### **RequireSymbols**

Specifies whether IAM user passwords must contain at least one of the following symbols:

! @ # \$ % ^ & \* ( ) \_ + - = [ ] { } | ^

Type: Boolean

Required: No

#### **RequireUppercaseCharacters**

Specifies whether IAM user passwords must contain at least one uppercase character (A to Z).

Type: Boolean

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# PermissionsBoundaryDecisionDetail

Contains information about the effect that a permissions boundary has on a policy simulation when the boundary is applied to an IAM entity.

## Contents

### AllowedByPermissionsBoundary

Specifies whether an action is allowed by a permissions boundary that is applied to an IAM entity (user or role). A value of `true` means that the permissions boundary does not deny the action. This means that the policy includes an `Allow` statement that matches the request. In this case, if an identity-based policy also allows the action, the request is allowed. A value of `false` means that either the requested action is not allowed (implicitly denied) or that the action is explicitly denied by the permissions boundary. In both of these cases, the action is not allowed, regardless of the identity-based policy.

Type: Boolean

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Policy

Contains information about a managed policy.

This data type is used as a response element in the [CreatePolicy \(p. 43\)](#), [GetPolicy \(p. 181\)](#), and [ListPolicies \(p. 270\)](#) operations.

For more information about managed policies, refer to [Managed policies and inline policies](#) in the *IAM User Guide*.

## Contents

### Arn

The Amazon Resource Name (ARN). ARNs are unique identifiers for AWS resources.

For more information about ARNs, go to [Amazon Resource Names \(ARNs\)](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: No

### AttachmentCount

The number of entities (users, groups, and roles) that the policy is attached to.

Type: Integer

Required: No

### CreateDate

The date and time, in [ISO 8601 date-time format](#), when the policy was created.

Type: Timestamp

Required: No

### DefaultVersionId

The identifier for the version of the policy that is set as the default version.

Type: String

Pattern: `v[1-9][0-9]*(\.[A-Za-z0-9-]*)?`

Required: No

### Description

A friendly description of the policy.

This element is included in the response to the [GetPolicy \(p. 181\)](#) operation. It is not included in the response to the [ListPolicies \(p. 270\)](#) operation.

Type: String

Length Constraints: Maximum length of 1000.

Required: No

**IsAttachable**

Specifies whether the policy can be attached to an IAM user, group, or role.

Type: Boolean

Required: No

**Path**

The path to the policy.

For more information about paths, see [IAM identifiers](#) in the *IAM User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: ((/[A-Za-z0-9\.,\+@=\_-]+)\*)/

Required: No

**PermissionsBoundaryUsageCount**

The number of entities (users and roles) for which the policy is used to set the permissions boundary.

For more information about permissions boundaries, see [Permissions boundaries for IAM identities](#) in the *IAM User Guide*.

Type: Integer

Required: No

**PolicyId**

The stable and unique string identifying the policy.

For more information about IDs, see [IAM identifiers](#) in the *IAM User Guide*.

Type: String

Length Constraints: Minimum length of 16. Maximum length of 128.

Pattern: [\w]+

Required: No

**PolicyName**

The friendly name (not ARN) identifying the policy.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [\w+=,.@-]+

Required: No

**Tags.member.N**

A list of tags that are attached to the instance profile. For more information about tagging, see [Tagging IAM resources](#) in the *IAM User Guide*.

Type: Array of [Tag \(p. 553\)](#) objects

Array Members: Maximum number of 50 items.

Required: No

#### **UpdateDate**

The date and time, in [ISO 8601 date-time format](#), when the policy was last updated.

When a policy has only one version, this field contains the date and time when the policy was created. When a policy has more than one version, this field contains the date and time when the most recent policy version was created.

Type: Timestamp

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# PolicyDetail

Contains information about an IAM policy, including the policy document.

This data type is used as a response element in the [GetAccountAuthorizationDetails \(p. 142\)](#) operation.

## Contents

### PolicyDocument

The policy document.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 131072.

Pattern: [\u0009\u000A\u000D\u0020-\u00FF]+

Required: No

### PolicyName

The name of the policy.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [\w+=, .@-]+

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# PolicyGrantingServiceAccess

Contains details about the permissions policies that are attached to the specified identity (user, group, or role).

This data type is an element of the [ListPoliciesGrantingServiceAccessEntry \(p. 502\)](#) object.

## Contents

### EntityName

The name of the entity (user or role) to which the inline policy is attached.

This field is null for managed policies. For more information about these policy types, see [Managed policies and inline policies](#) in the *IAM User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [\w+=, .@-]+

Required: No

### EntityType

The type of entity (user or role) that used the policy to access the service to which the inline policy is attached.

This field is null for managed policies. For more information about these policy types, see [Managed policies and inline policies](#) in the *IAM User Guide*.

Type: String

Valid Values: USER | ROLE | GROUP

Required: No

### PolicyArn

The Amazon Resource Name (ARN). ARNs are unique identifiers for AWS resources.

For more information about ARNs, go to [Amazon Resource Names \(ARNs\)](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: No

### PolicyName

The policy name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [\w+=, .@-]+

Required: Yes

### PolicyType

The policy type. For more information about these policy types, see [Managed policies and inline policies](#) in the *IAM User Guide*.

Type: String

Valid Values: INLINE | MANAGED

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# PolicyGroup

Contains information about a group that a managed policy is attached to.

This data type is used as a response element in the [ListEntitiesForPolicy \(p. 237\)](#) operation.

For more information about managed policies, refer to [Managed policies and inline policies](#) in the *IAM User Guide*.

## Contents

### GroupId

The stable and unique string identifying the group. For more information about IDs, see [IAM identifiers](#) in the *IAM User Guide*.

Type: String

Length Constraints: Minimum length of 16. Maximum length of 128.

Pattern: `[\w]+`

Required: No

### GroupName

The name (friendly name, not ARN) identifying the group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=, .@-]+`

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# PolicyRole

Contains information about a role that a managed policy is attached to.

This data type is used as a response element in the [ListEntitiesForPolicy \(p. 237\)](#) operation.

For more information about managed policies, refer to [Managed policies and inline policies](#) in the *IAM User Guide*.

## Contents

### **RoleId**

The stable and unique string identifying the role. For more information about IDs, see [IAM identifiers](#) in the *IAM User Guide*.

Type: String

Length Constraints: Minimum length of 16. Maximum length of 128.

Pattern: `[\w]+`

Required: No

### **RoleName**

The name (friendly name, not ARN) identifying the role.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w+=, .@-]+`

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# PolicyUser

Contains information about a user that a managed policy is attached to.

This data type is used as a response element in the [ListEntitiesForPolicy \(p. 237\)](#) operation.

For more information about managed policies, refer to [Managed policies and inline policies](#) in the *IAM User Guide*.

## Contents

### **UserId**

The stable and unique string identifying the user. For more information about IDs, see [IAM identifiers](#) in the *IAM User Guide*.

Type: String

Length Constraints: Minimum length of 16. Maximum length of 128.

Pattern: `[\w]+`

Required: No

### **UserName**

The name (friendly name, not ARN) identifying the user.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w+=, .@-]+`

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# PolicyVersion

Contains information about a version of a managed policy.

This data type is used as a response element in the [CreatePolicyVersion \(p. 47\)](#), [GetPolicyVersion \(p. 184\)](#), [ListPolicyVersions \(p. 281\)](#), and [GetAccountAuthorizationDetails \(p. 142\)](#) operations.

For more information about managed policies, refer to [Managed policies and inline policies](#) in the *IAM User Guide*.

## Contents

### **CreateDate**

The date and time, in [ISO 8601 date-time format](#), when the policy version was created.

Type: [Timestamp](#)

Required: No

### **Document**

The policy document.

The policy document is returned in the response to the [GetPolicyVersion \(p. 184\)](#) and [GetAccountAuthorizationDetails \(p. 142\)](#) operations. It is not returned in the response to the [CreatePolicyVersion \(p. 47\)](#) or [ListPolicyVersions \(p. 281\)](#) operations.

The policy document returned in this structure is URL-encoded compliant with [RFC 3986](#). You can use a URL decoding method to convert the policy back to plain JSON text. For example, if you use Java, you can use the decode method of the `java.net.URLDecoder` utility class in the Java SDK. Other languages and SDKs provide similar functionality.

Type: [String](#)

Length Constraints: Minimum length of 1. Maximum length of 131072.

Pattern: `[\u0009\u000A\u000D\u0020-\u00FF]+`

Required: No

### **IsDefaultVersion**

Specifies whether the policy version is set as the policy's default version.

Type: [Boolean](#)

Required: No

### **VersionId**

The identifier for the policy version.

Policy version identifiers always begin with v (always lowercase). When a policy is created, the first policy version is v1.

Type: [String](#)

Pattern: `v[1-9][0-9]*(\.[A-Za-z0-9-]*)?`

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Position

Contains the row and column of a location of a Statement element in a policy document.

This data type is used as a member of the [Statement \(p. 552\)](#) type.

## Contents

### Column

The column in the line containing the specified position in the document.

Type: Integer

Required: No

### Line

The line containing the specified position in the document.

Type: Integer

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ResourceSpecificResult

Contains the result of the simulation of a single API operation call on a single resource.

This data type is used by a member of the [EvaluationResult \(p. 493\)](#) data type.

## Contents

### **EvalDecisionDetails** , `EvalDecisionDetails.entry.N.key` (key) , `EvalDecisionDetails.entry.N.value` (value)

Additional details about the results of the evaluation decision on a single resource. This parameter is returned only for cross-account simulations. This parameter explains how each policy type contributes to the resource-specific evaluation decision.

Type: String to string map

Key Length Constraints: Minimum length of 3. Maximum length of 256.

Valid Values: allowed | explicitDeny | implicitDeny

Required: No

### **EvalResourceDecision**

The result of the simulation of the simulated API operation on the resource specified in `EvalResourceName`.

Type: String

Valid Values: allowed | explicitDeny | implicitDeny

Required: Yes

### **EvalResourceName**

The name of the simulated resource, in Amazon Resource Name (ARN) format.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: Yes

### **MatchedStatements.member.N**

A list of the statements in the input policies that determine the result for this part of the simulation. Remember that even if multiple statements allow the operation on the resource, if *any* statement denies that operation, then the explicit deny overrides any allow. In addition, the deny statement is the only entry included in the result.

Type: Array of [Statement \(p. 552\)](#) objects

Required: No

### **MissingContextValues.member.N**

A list of context keys that are required by the included input policies but that were not provided by one of the input parameters. This list is used when a list of ARNs is included in the `ResourceArns` parameter instead of `"*"`. If you do not specify individual resources, by setting `ResourceArns` to `"*"` or by not including the `ResourceArns` parameter, then any missing context values are instead included under the `EvaluationResults` section. To discover the

context keys used by a set of policies, you can call [GetContextKeysForCustomPolicy \(p. 155\)](#) or [GetContextKeysForPrincipalPolicy \(p. 158\)](#).

Type: Array of strings

Length Constraints: Minimum length of 5. Maximum length of 256.

Required: No

#### PermissionsBoundaryDecisionDetail

Contains information about the effect that a permissions boundary has on a policy simulation when that boundary is applied to an IAM entity.

Type: [PermissionsBoundaryDecisionDetail \(p. 512\)](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Role

Contains information about an IAM role. This structure is returned as a response element in several API operations that interact with roles.

## Contents

### Arn

The Amazon Resource Name (ARN) specifying the role. For more information about ARNs and how to use them in policies, see [IAM identifiers](#) in the *IAM User Guide* guide.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

### AssumeRolePolicyDocument

The policy that grants an entity permission to assume the role.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 131072.

Pattern: [\u0009\u000A\u000D\u0020-\u00FF]+

Required: No

### CreateDate

The date and time, in [ISO 8601 date-time format](#), when the role was created.

Type: Timestamp

Required: Yes

### Description

A description of the role that you provide.

Type: String

Length Constraints: Maximum length of 1000.

Pattern: [\p{L}\p{M}\p{Z}\p{S}\p{N}\p{P}]\*

Required: No

### MaxSessionDuration

The maximum session duration (in seconds) for the specified role. Anyone who uses the AWS CLI, or API to assume the role can specify the duration using the optional `DurationSeconds` API parameter or `duration-seconds` CLI parameter.

Type: Integer

Valid Range: Minimum value of 3600. Maximum value of 43200.

Required: No

### Path

The path to the role. For more information about paths, see [IAM identifiers](#) in the *IAM User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: (\u002F)|(\\u002F[\u0021-\u007F]+\u002F)

Required: Yes

### PermissionsBoundary

The ARN of the policy used to set the permissions boundary for the role.

For more information about permissions boundaries, see [Permissions boundaries for IAM identities](#) in the *IAM User Guide*.

Type: [AttachedPermissionsBoundary \(p. 485\)](#) object

Required: No

### RoleId

The stable and unique string identifying the role. For more information about IDs, see [IAM identifiers](#) in the *IAM User Guide*.

Type: String

Length Constraints: Minimum length of 16. Maximum length of 128.

Pattern: [\w]+

Required: Yes

### RoleLastUsed

Contains information about the last time that an IAM role was used. This includes the date and time and the Region in which the role was last used. Activity is only reported for the trailing 400 days. This period can be shorter if your Region began supporting these features within the last year. The role might have been used more than 400 days ago. For more information, see [Regions where data is tracked](#) in the *IAM User Guide*.

Type: [RoleLastUsed \(p. 533\)](#) object

Required: No

### RoleName

The friendly name that identifies the role.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [\w+=, .@-]+

Required: Yes

### Tags.member.N

A list of tags that are attached to the role. For more information about tagging, see [Tagging IAM resources](#) in the *IAM User Guide*.

Type: Array of [Tag \(p. 553\)](#) objects

Array Members: Maximum number of 50 items.

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# RoleDetail

Contains information about an IAM role, including all of the role's policies.

This data type is used as a response element in the [GetAccountAuthorizationDetails \(p. 142\)](#) operation.

## Contents

### Arn

The Amazon Resource Name (ARN). ARNs are unique identifiers for AWS resources.

For more information about ARNs, go to [Amazon Resource Names \(ARNs\)](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: No

### AssumeRolePolicyDocument

The trust policy that grants permission to assume the role.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 131072.

Pattern: [ \u0009 \u000A \u000D \u0020 - \u00FF ] +

Required: No

### AttachedManagedPolicies.member.N

A list of managed policies attached to the role. These policies are the role's access (permissions) policies.

Type: Array of [AttachedPolicy \(p. 486\)](#) objects

Required: No

### CreateDate

The date and time, in [ISO 8601 date-time format](#), when the role was created.

Type: Timestamp

Required: No

### InstanceProfileList.member.N

A list of instance profiles that contain this role.

Type: Array of [InstanceProfile \(p. 500\)](#) objects

Required: No

### Path

The path to the role. For more information about paths, see [IAM identifiers](#) in the *IAM User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: (\u002F)|(\\u002F[\u0021-\u007F]+\u002F)

Required: No

#### **PermissionsBoundary**

The ARN of the policy used to set the permissions boundary for the role.

For more information about permissions boundaries, see [Permissions boundaries for IAM identities](#) in the *IAM User Guide*.

Type: [AttachedPermissionsBoundary \(p. 485\)](#) object

Required: No

#### **RoleId**

The stable and unique string identifying the role. For more information about IDs, see [IAM identifiers](#) in the *IAM User Guide*.

Type: String

Length Constraints: Minimum length of 16. Maximum length of 128.

Pattern: [\w]+

Required: No

#### **RoleLastUsed**

Contains information about the last time that an IAM role was used. This includes the date and time and the Region in which the role was last used. Activity is only reported for the trailing 400 days. This period can be shorter if your Region began supporting these features within the last year. The role might have been used more than 400 days ago. For more information, see [Regions where data is tracked](#) in the *IAM User Guide*.

Type: [RoleLastUsed \(p. 533\)](#) object

Required: No

#### **RoleName**

The friendly name that identifies the role.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [\w+=, .@-]+

Required: No

#### **RolePolicyList.member.N**

A list of inline policies embedded in the role. These policies are the role's access (permissions) policies.

Type: Array of [PolicyDetail \(p. 516\)](#) objects

Required: No

#### **Tags.member.N**

A list of tags that are attached to the role. For more information about tagging, see [Tagging IAM resources](#) in the *IAM User Guide*.

Type: Array of [Tag \(p. 553\)](#) objects

Array Members: Maximum number of 50 items.

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

## RoleLastUsed

Contains information about the last time that an IAM role was used. This includes the date and time and the Region in which the role was last used. Activity is only reported for the trailing 400 days. This period can be shorter if your Region began supporting these features within the last year. The role might have been used more than 400 days ago. For more information, see [Regions where data is tracked](#) in the *IAM User Guide*.

This data type is returned as a response element in the [GetRole \(p. 187\)](#) and [GetAccountAuthorizationDetails \(p. 142\)](#) operations.

## Contents

### LastUsedDate

The date and time, in [ISO 8601 date-time format](#) that the role was last used.

This field is null if the role has not been used within the IAM tracking period. For more information about the tracking period, see [Regions where data is tracked](#) in the *IAM User Guide*.

Type: Timestamp

Required: No

### Region

The name of the AWS Region in which the role was last used.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# RoleUsageType

An object that contains details about how a service-linked role is used, if that information is returned by the service.

This data type is used as a response element in the [GetServiceLinkedRoleDeletionStatus \(p. 207\)](#) operation.

## Contents

### Region

The name of the Region where the service-linked role is being used.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

### Resources.member.N

The name of the resource that is using the service-linked role.

Type: Array of strings

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# SAMLProviderListEntry

Contains the list of SAML providers for this account.

## Contents

### Arn

The Amazon Resource Name (ARN) of the SAML provider.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: No

### CreateDate

The date and time when the SAML provider was created.

Type: Timestamp

Required: No

### ValidUntil

The expiration date and time for the SAML provider.

Type: Timestamp

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ServerCertificate

Contains information about a server certificate.

This data type is used as a response element in the [GetServerCertificate \(p. 195\)](#) operation.

## Contents

### **CertificateBody**

The contents of the public key certificate.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 16384.

Pattern: [\u0009\u000A\u000D\u0020-\u00FF]+

Required: Yes

### **CertificateChain**

The contents of the public key certificate chain.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2097152.

Pattern: [\u0009\u000A\u000D\u0020-\u00FF]+

Required: No

### **ServerCertificateMetadata**

The meta information of the server certificate, such as its name, path, ID, and ARN.

Type: [ServerCertificateMetadata \(p. 538\)](#) object

Required: Yes

### **Tags.member.N**

A list of tags that are attached to the server certificate. For more information about tagging, see [Tagging IAM resources](#) in the *IAM User Guide*.

Type: Array of [Tag \(p. 553\)](#) objects

Array Members: Maximum number of 50 items.

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)



# ServerCertificateMetadata

Contains information about a server certificate without its certificate body, certificate chain, and private key.

This data type is used as a response element in the [UploadServerCertificate \(p. 463\)](#) and [ListServerCertificates \(p. 299\)](#) operations.

## Contents

### Arn

The Amazon Resource Name (ARN) specifying the server certificate. For more information about ARNs and how to use them in policies, see [IAM identifiers](#) in the *IAM User Guide*.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

### Expiration

The date on which the certificate is set to expire.

Type: Timestamp

Required: No

### Path

The path to the server certificate. For more information about paths, see [IAM identifiers](#) in the *IAM User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `(\u002F)|(\\u002F[\u0021-\u007F]+\u002F)`

Required: Yes

### ServerCertificateId

The stable and unique string identifying the server certificate. For more information about IDs, see [IAM identifiers](#) in the *IAM User Guide*.

Type: String

Length Constraints: Minimum length of 16. Maximum length of 128.

Pattern: `[\w]+`

Required: Yes

### ServerCertificateName

The name that identifies the server certificate.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [\\w+=, .@-]+

Required: Yes

**UploadDate**

The date when the server certificate was uploaded.

Type: Timestamp

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ServiceLastAccessed

Contains details about the most recent attempt to access the service.

This data type is used as a response element in the [GetServiceLastAccessedDetails \(p. 198\)](#) operation.

## Contents

### LastAuthenticated

The date and time, in [ISO 8601 date-time format](#), when an authenticated entity most recently attempted to access the service. AWS does not report unauthenticated requests.

This field is null if no IAM entities attempted to access the service within the [tracking period](#).

Type: Timestamp

Required: No

### LastAuthenticatedEntity

The ARN of the authenticated entity (user or role) that last attempted to access the service. AWS does not report unauthenticated requests.

This field is null if no IAM entities attempted to access the service within the [tracking period](#).

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: No

### LastAuthenticatedRegion

The Region from which the authenticated entity (user or role) last attempted to access the service. AWS does not report unauthenticated requests.

This field is null if no IAM entities attempted to access the service within the [tracking period](#).

Type: String

Required: No

### ServiceName

The name of the service in which access was attempted.

Type: String

Required: Yes

### ServiceNamespace

The namespace of the service in which access was attempted.

To learn the service namespace of a service, see [Actions, resources, and condition keys for AWS services](#) in the *Service Authorization Reference*. Choose the name of the service to view details for that service. In the first paragraph, find the service prefix. For example, (service prefix: a4b). For more information about service namespaces, see [AWS Service Namespaces](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w-]*`

Required: Yes

#### **TotalAuthenticatedEntities**

The total number of authenticated principals (root user, IAM users, or IAM roles) that have attempted to access the service.

This field is null if no principals attempted to access the service within the [tracking period](#).

Type: Integer

Required: No

#### **TrackedActionsLastAccessed.member.N**

An object that contains details about the most recent attempt to access a tracked action within the service.

This field is null if there are no tracked actions or if the principal did not use the tracked actions within the [tracking period](#). This field is also null if the report was generated at the service level and not the action level. For more information, see the [Granularity](#) field in [GenerateServiceLastAccessedDetails \(p. 137\)](#).

Type: Array of [TrackedActionLastAccessed \(p. 554\)](#) objects

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ServiceSpecificCredential

Contains the details of a service-specific credential.

## Contents

### **CreateDate**

The date and time, in [ISO 8601 date-time format](#), when the service-specific credential were created.

Type: Timestamp

Required: Yes

### **ServiceName**

The name of the service associated with the service-specific credential.

Type: String

Required: Yes

### **ServicePassword**

The generated password for the service-specific credential.

Type: String

Required: Yes

### **ServiceSpecificCredentialId**

The unique identifier for the service-specific credential.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 128.

Pattern: `[\w]+`

Required: Yes

### **ServiceUserName**

The generated user name for the service-specific credential. This value is generated by combining the IAM user's name combined with the ID number of the AWS account, as in `jane-at-123456789012`, for example. This value cannot be configured by the user.

Type: String

Length Constraints: Minimum length of 17. Maximum length of 200.

Pattern: `[\w+=,.@-]+`

Required: Yes

### **Status**

The status of the service-specific credential. `Active` means that the key is valid for API calls, while `Inactive` means it is not.

Type: String

Valid Values: Active | Inactive

Required: Yes

#### **UserName**

The name of the IAM user associated with the service-specific credential.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [\w+=, .@-]+

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ServiceSpecificCredentialMetadata

Contains additional details about a service-specific credential.

## Contents

### **CreateDate**

The date and time, in [ISO 8601 date-time format](#), when the service-specific credential were created.

Type: Timestamp

Required: Yes

### **ServiceName**

The name of the service associated with the service-specific credential.

Type: String

Required: Yes

### **ServiceSpecificCredentialId**

The unique identifier for the service-specific credential.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 128.

Pattern: `[\w]+`

Required: Yes

### **ServiceUserName**

The generated user name for the service-specific credential.

Type: String

Length Constraints: Minimum length of 17. Maximum length of 200.

Pattern: `[\w+=,.@-]+`

Required: Yes

### **Status**

The status of the service-specific credential. Active means that the key is valid for API calls, while Inactive means it is not.

Type: String

Valid Values: Active | Inactive

Required: Yes

### **UserName**

The name of the IAM user associated with the service-specific credential.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w+=, .@-]+`

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# SigningCertificate

Contains information about an X.509 signing certificate.

This data type is used as a response element in the [UploadSigningCertificate \(p. 468\)](#) and [ListSigningCertificates \(p. 308\)](#) operations.

## Contents

### **CertificateBody**

The contents of the signing certificate.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 16384.

Pattern: [\u0009\u000A\u000D\u0020-\u00FF]+

Required: Yes

### **CertificateId**

The ID for the signing certificate.

Type: String

Length Constraints: Minimum length of 24. Maximum length of 128.

Pattern: [\w]+

Required: Yes

### **Status**

The status of the signing certificate. Active means that the key is valid for API calls, while Inactive means it is not.

Type: String

Valid Values: Active | Inactive

Required: Yes

### **UploadDate**

The date when the signing certificate was uploaded.

Type: Timestamp

Required: No

### **UserName**

The name of the user the signing certificate is associated with.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [\w+=, .@-]+

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# SSHPublicKey

Contains information about an SSH public key.

This data type is used as a response element in the [GetSSHPublicKey \(p. 210\)](#) and [UploadSSHPublicKey \(p. 472\)](#) operations.

## Contents

### Fingerprint

The MD5 message digest of the SSH public key.

Type: String

Length Constraints: Fixed length of 48.

Pattern: [:\w]+

Required: Yes

### SSHPublicKeyBody

The SSH public key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 16384.

Pattern: [\u0009\u000A\u000D\u0020-\u00FF]+

Required: Yes

### SSHPublicKeyId

The unique identifier for the SSH public key.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 128.

Pattern: [\w]+

Required: Yes

### Status

The status of the SSH public key. Active means that the key can be used for authentication with an CodeCommit repository. Inactive means that the key cannot be used.

Type: String

Valid Values: Active | Inactive

Required: Yes

### UploadDate

The date and time, in [ISO 8601 date-time format](#), when the SSH public key was uploaded.

Type: Timestamp

Required: No

### **UserName**

The name of the IAM user associated with the SSH public key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w+=, .@-]+`

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# SSHPublicKeyMetadata

Contains information about an SSH public key, without the key's body or fingerprint.

This data type is used as a response element in the [ListSSHPublicKeys \(p. 311\)](#) operation.

## Contents

### SSHPublicKeyId

The unique identifier for the SSH public key.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 128.

Pattern: `[\w]+`

Required: Yes

### Status

The status of the SSH public key. Active means that the key can be used for authentication with an CodeCommit repository. Inactive means that the key cannot be used.

Type: String

Valid Values: Active | Inactive

Required: Yes

### UploadDate

The date and time, in [ISO 8601 date-time format](#), when the SSH public key was uploaded.

Type: Timestamp

Required: Yes

### UserName

The name of the IAM user associated with the SSH public key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w+=, .@-]+`

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)



# Statement

Contains a reference to a Statement element in a policy document that determines the result of the simulation.

This data type is used by the `MatchedStatements` member of the [EvaluationResult \(p. 493\)](#) type.

## Contents

### **EndPosition**

The row and column of the end of a Statement in an IAM policy.

Type: [Position \(p. 524\)](#) object

Required: No

### **SourcePolicyId**

The identifier of the policy that was provided as an input.

Type: String

Required: No

### **SourcePolicyType**

The type of the policy.

Type: String

Valid Values: `user` | `group` | `role` | `aws-managed` | `user-managed` | `resource` | `none`

Required: No

### **StartPosition**

The row and column of the beginning of the Statement in an IAM policy.

Type: [Position \(p. 524\)](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Tag

A structure that represents user-provided metadata that can be associated with an IAM resource. For more information about tagging, see [Tagging IAM resources](#) in the *IAM User Guide*.

## Contents

### Key

The key name that can be used to look up or retrieve the associated value. For example, `Department` or `Cost Center` are common choices.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\p{L}\p{Z}\p{N}_.:/=+\-@]+`

Required: Yes

### Value

The value associated with this tag. For example, tags with a key name of `Department` could have values such as `Human Resources`, `Accounting`, and `Support`. Tags with a key name of `Cost Center` might have values that consist of the number associated with the different cost centers in your company. Typically, many resources have tags with the same key name but with different values.

#### Note

AWS always interprets the tag `Value` as a single string. If you need to store an array, you can store comma-separated values in the string. However, you must interpret the value in your code.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\p{L}\p{Z}\p{N}_.:/=+\-@]*`

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# TrackedActionLastAccessed

Contains details about the most recent attempt to access an action within the service.

This data type is used as a response element in the [GetServiceLastAccessedDetails \(p. 198\)](#) operation.

## Contents

### ActionName

The name of the tracked action to which access was attempted. Tracked actions are actions that report activity to IAM.

Type: String

Required: No

### LastAccessedEntity

The Amazon Resource Name (ARN). ARNs are unique identifiers for AWS resources.

For more information about ARNs, go to [Amazon Resource Names \(ARNs\)](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: No

### LastAccessedRegion

The Region from which the authenticated entity (user or role) last attempted to access the tracked action. AWS does not report unauthenticated requests.

This field is null if no IAM entities attempted to access the service within the [tracking period](#).

Type: String

Required: No

### LastAccessedTime

The date and time, in [ISO 8601 date-time format](#), when an authenticated entity most recently attempted to access the tracked service. AWS does not report unauthenticated requests.

This field is null if no IAM entities attempted to access the service within the [tracking period](#).

Type: Timestamp

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

# User

Contains information about an IAM user entity.

This data type is used as a response element in the following operations:

- [CreateUser \(p. 63\)](#)
- [GetUser \(p. 213\)](#)
- [ListUsers \(p. 317\)](#)

## Contents

### Arn

The Amazon Resource Name (ARN) that identifies the user. For more information about ARNs and how to use ARNs in policies, see [IAM Identifiers](#) in the *IAM User Guide*.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

### CreateDate

The date and time, in [ISO 8601 date-time format](#), when the user was created.

Type: Timestamp

Required: Yes

### PasswordLastUsed

The date and time, in [ISO 8601 date-time format](#), when the user's password was last used to sign in to an AWS website. For a list of AWS websites that capture a user's last sign-in time, see the [Credential reports](#) topic in the *IAM User Guide*. If a password is used more than once in a five-minute span, only the first use is returned in this field. If the field is null (no value), then it indicates that they never signed in with a password. This can be because:

- The user never had a password.
- A password exists but has not been used since IAM started tracking this information on October 20, 2014.

A null value does not mean that the user *never* had a password. Also, if the user does not currently have a password but had one in the past, then this field contains the date and time the most recent password was used.

This value is returned only in the  [GetUser \(p. 213\)](#) and [ListUsers \(p. 317\)](#) operations.

Type: Timestamp

Required: No

### Path

The path to the user. For more information about paths, see [IAM identifiers](#) in the *IAM User Guide*.

The ARN of the policy used to set the permissions boundary for the user.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `(\u002F)|(\\u002F[\u0021-\u007F]+\u002F)`

Required: Yes

#### **PermissionsBoundary**

For more information about permissions boundaries, see [Permissions boundaries for IAM identities](#) in the *IAM User Guide*.

Type: [AttachedPermissionsBoundary \(p. 485\)](#) object

Required: No

#### **Tags.member.N**

A list of tags that are associated with the user. For more information about tagging, see [Tagging IAM resources](#) in the *IAM User Guide*.

Type: Array of [Tag \(p. 553\)](#) objects

Array Members: Maximum number of 50 items.

Required: No

#### **UserId**

The stable and unique string identifying the user. For more information about IDs, see [IAM identifiers](#) in the *IAM User Guide*.

Type: String

Length Constraints: Minimum length of 16. Maximum length of 128.

Pattern: `[\w]+`

Required: Yes

#### **UserName**

The friendly name identifying the user.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w+=,.@-]+`

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# UserDetail

Contains information about an IAM user, including all the user's policies and all the IAM groups the user is in.

This data type is used as a response element in the [GetAccountAuthorizationDetails \(p. 142\)](#) operation.

## Contents

### Arn

The Amazon Resource Name (ARN). ARNs are unique identifiers for AWS resources.

For more information about ARNs, go to [Amazon Resource Names \(ARNs\)](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: No

### AttachedManagedPolicies.member.N

A list of the managed policies attached to the user.

Type: Array of [AttachedPolicy \(p. 486\)](#) objects

Required: No

### CreateDate

The date and time, in [ISO 8601 date-time format](#), when the user was created.

Type: Timestamp

Required: No

### GroupList.member.N

A list of IAM groups that the user is in.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+=, .@-]+`

Required: No

### Path

The path to the user. For more information about paths, see [IAM identifiers](#) in the *IAM User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `(\u002F)|(\\u002F[\u0021-\u007F]+\u002F)`

Required: No

### PermissionsBoundary

The ARN of the policy used to set the permissions boundary for the user.

For more information about permissions boundaries, see [Permissions boundaries for IAM identities](#) in the *IAM User Guide*.

Type: [AttachedPermissionsBoundary \(p. 485\)](#) object

Required: No

### Tags.member.N

A list of tags that are associated with the user. For more information about tagging, see [Tagging IAM resources](#) in the *IAM User Guide*.

Type: Array of [Tag \(p. 553\)](#) objects

Array Members: Maximum number of 50 items.

Required: No

### UserId

The stable and unique string identifying the user. For more information about IDs, see [IAM identifiers](#) in the *IAM User Guide*.

Type: String

Length Constraints: Minimum length of 16. Maximum length of 128.

Pattern: `[\w]+`

Required: No

### UserName

The friendly name identifying the user.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w+=,.@-]+`

Required: No

### UserPolicyList.member.N

A list of the inline policies embedded in the user.

Type: Array of [PolicyDetail \(p. 516\)](#) objects

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

# VirtualMFADevice

Contains information about a virtual MFA device.

## Contents

### Base32StringSeed

The base32 seed defined as specified in [RFC3548](#). The Base32StringSeed is base64-encoded.

Type: Base64-encoded binary data object

Required: No

### EnableDate

The date and time on which the virtual MFA device was enabled.

Type: Timestamp

Required: No

### QRCodePNG

A QR code PNG image that encodes otpauth://totp/\$virtualMFADeviceName@\$AccountName?secret=\$Base32String where \$virtualMFADeviceName is one of the create call arguments. AccountName is the user name if set (otherwise, the account ID otherwise), and Base32String is the seed in base32 format. The Base32String value is base64-encoded.

Type: Base64-encoded binary data object

Required: No

### SerialNumber

The serial number associated with VirtualMFADevice.

Type: String

Length Constraints: Minimum length of 9. Maximum length of 256.

Pattern: [\w+=/:,.@-]+

Required: Yes

### Tags.member.N

A list of tags that are attached to the virtual MFA device. For more information about tagging, see [Tagging IAM resources](#) in the *IAM User Guide*.

Type: Array of [Tag \(p. 553\)](#) objects

Array Members: Maximum number of 50 items.

Required: No

### User

The IAM user associated with this virtual MFA device.

Type: [User \(p. 556\)](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signature Version 4 Signing Process](#) in the *Amazon Web Services General Reference*.

## Action

The action to be performed.

Type: string

Required: Yes

## Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

## X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

## X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4\_request"). The value is expressed in the following format: *access\_key/YYYYMMDD/region/service/aws4\_request*.

For more information, see [Task 2: Create a String to Sign for Signature Version 4](#) in the *Amazon Web Services General Reference*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

## X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is

not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Handling Dates in Signature Version 4](#) in the *Amazon Web Services General Reference*.

Type: string

Required: Conditional

**X-Amz-Security-Token**

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS Security Token Service, go to [AWS Services That Work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from the AWS Security Token Service, you must include the security token.

Type: string

Required: Conditional

**X-Amz-Signature**

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

**X-Amz-SignedHeaders**

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Task 1: Create a Canonical Request For Signature Version 4](#) in the *Amazon Web Services General Reference*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

# Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

## **AccessDeniedException**

You do not have sufficient access to perform this action.

HTTP Status Code: 400

## **IncompleteSignature**

The request signature does not conform to AWS standards.

HTTP Status Code: 400

## **InternalFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## **InvalidAction**

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

## **InvalidClientId**

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

## **InvalidParameterCombination**

Parameters that must not be used together were used together.

HTTP Status Code: 400

## **InvalidParameterValue**

An invalid or out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

## **InvalidQueryParameter**

The AWS query string is malformed or does not adhere to AWS standards.

HTTP Status Code: 400

## **MalformedQueryString**

The query string contains a syntax error.

HTTP Status Code: 404

## **MissingAction**

The request is missing an action or a required parameter.

HTTP Status Code: 400

**MissingAuthenticationToken**

The request must contain either a valid (registered) AWS access key ID or X.509 certificate.

HTTP Status Code: 403

**MissingParameter**

A required parameter for the specified action is not supplied.

HTTP Status Code: 400

**NotAuthorized**

You do not have permission to perform this action.

HTTP Status Code: 400

**OptInRequired**

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

**RequestExpired**

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

**ServiceUnavailable**

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

**ThrottlingException**

The request was denied due to request throttling.

HTTP Status Code: 400

**ValidationException**

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400