




 Secrets


 ABAP


 Apex


 C


 C++


 CloudFormation


 COBOL


 C#


 CSS


 Flex


 Go


 HTML


 Java


 JavaScript


 Kotlin


 Objective C


 PHP


 PL/I


 PL/SQL


 Python


 RPG


 Ruby


 Scala


 Swift


 **Terraform**


 Text


 TypeScript

 T-SQL

 VB.NET

 VB6


 XML





Terraform static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your TERRAFORM code


All rules 50

 Vulnerability 5


 Security Hotspot 43

 Code Smell 2


Tags ▾

Search by name... 


Enabling Azure resource-specific admin accounts is security-sensitive

 Security Hotspot


Disabling Managed Identities for Azure resources is security-sensitive

 Security Hotspot


Assigning high privileges Azure Active Directory built-in roles is security-sensitive

 Security Hotspot


Defining a short backup retention duration is security-sensitive

 Security Hotspot


Using unencrypted EFS file systems is security-sensitive

 Security Hotspot


Using unencrypted SQS queues is security-sensitive

 Security Hotspot


Using unencrypted SNS topics is security-sensitive

 Security Hotspot


Using unencrypted SageMaker notebook instances is security-sensitive

 Security Hotspot


Using unencrypted Elasticsearch domains is security-sensitive

 Security Hotspot

Using unencrypted RDS databases is security-sensitive


 Security Hotspot


Using unencrypted EBS volumes is security-sensitive


 Security Hotspot

Creating App Engine handlers without requiring TLS is security-sensitive

Analyze your code

 Security Hotspot

 Major ?

 gcp

App Engine supports encryption in transit through TLS. As soon as the app is deployed, it can be requested using `appspot.com` domains or custom domains. By default, endpoints accept both clear-text and encrypted traffic. When communication isn't encrypted, there is a risk that an attacker could intercept it and read confidential information.

When creating an App Engine, request handlers can be set with different security level for encryption:

- `SECURE_NEVER`: only HTTP requests are allowed (HTTPS requests are redirected to HTTP).
- `SECURE_OPTIONAL` and `SECURE_DEFAULT`: both HTTP and HTTPS requests are allowed.
- `SECURE_ALWAYS`: only HTTPS requests are allowed (HTTP requests are redirected to HTTPS).

Ask Yourself Whether

- The handler serves confidential data in HTTP responses.

There is a risk if you answered yes to this question.

Recommended Secure Coding Practices

It's recommended for App Engine handlers to require TLS for all traffic. It can be achieved by setting the security level to `SECURE_ALWAYS`.

Sensitive Code Example

```
SECURE_DEFAULT, SECURE_NEVER and SECURE_OPTIONAL are sensitive TLS security level:
```





```
resource "google_app_engine_standard_app_version" "exam
  version_id = "v1"
  service    = "default"
  runtime    = "nodejs"

  handlers {
    url_regex          = ".*"
    redirect_http_response_code = "REDIRECT_HTTP_RESPON
    security_level      = "SECURE_OPTIONAL" # S
    script {
      script_path = "auto"
    }
  }
}
```

Compliant Solution

https://rules.sonarsource.com/terraform/RSPEC-6407

1/2

Disabling logging is security-sensitive
 Security Hotspot
Administration services access should be restricted to specific IP addresses
 Vulnerability
Unversioned Google Cloud Storage buckets are security-sensitive
 Security Hotspot
Disabling S3 bucket MFA delete is security-sensitive
 Security Hotspot
Disabling versioning of S3 buckets is

Force the use of TLS for the handler by setting the security level on SECURE_ALWAYS:

```
resource "google_app_engine_standard_app_version" "exam
  version_id = "v1"
  service    = "default"
  runtime    = "nodejs"

  handlers {
    url_regex          = ".*"
    redirect_http_response_code = "REDIRECT_HTTP_RESPON
    security_level     = "SECURE_ALWAYS"
    script {
      script_path = "auto"
    }
  }
}
```

- See
- [OWASP Top 10 2021 Category A2](#) - Cryptographic Failures
 - [OWASP Top 10 2017 Category A3](#) - Sensitive Data Exposure
 - [OWASP Top 10 2017 Category A6](#) - Security Misconfiguration
 - [MITRE, CWE-200](#) - Exposure of Sensitive Information to an Unauthorized Actor
 - [MITRE, CWE-319](#) - Cleartext Transmission of Sensitive Information
 - [GCP Documentation](#) - Overview of App Security

Available In:
 | 