




Secrets


ABAP


Apex


C


C++


CloudFormation


COBOL


C#


CSS


Flex


Go


HTML


Java


JavaScript


Kotlin


Objective C


PHP


PL/I


PL/SQL


Python


RPG


Ruby


Scala


Swift


Terraform


Text


TypeScript

T-SQL

VB.NET

VB6


XML





Terraform static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your TERRAFORM code


All rules 50


 Vulnerability 5

 Security Hotspot 43


 Code Smell 2


Tags ▾

Search by name... 


 Security Hotspot


Using unencrypted EFS file systems is security-sensitive

 Security Hotspot


 Security Hotspot


Using unencrypted SQS queues is security-sensitive

 Security Hotspot


 Security Hotspot


Using unencrypted SNS topics is security-sensitive

 Security Hotspot


 Security Hotspot


Using unencrypted SageMaker notebook instances is security-sensitive

 Security Hotspot


 Security Hotspot


Using unencrypted Elasticsearch domains is security-sensitive

 Security Hotspot


 Security Hotspot


Using unencrypted RDS databases is security-sensitive

 Security Hotspot


 Security Hotspot


Using unencrypted EBS volumes is security-sensitive

 Security Hotspot


 Security Hotspot

Disabling logging is security-sensitive


 Security Hotspot

 Vulnerability

Administration services access should be restricted to specific IP addresses





 Security Hotspot

Unversioned Google Cloud Storage buckets are security-sensitive

 Security Hotspot

Disabling S3 bucket MFA delete is security-sensitive

Creating DNS zones without DNSSEC enabled is security-sensitive

 Security Hotspot  Major   gcp

Domain Name Systems (DNS) are vulnerable by default to various types of attacks.

One of the biggest risks is DNS cache poisoning, which occurs when a DNS accepts spoofed DNS data, caches the malicious records, and potentially sends them later in response to legitimate DNS request lookups. This attack typically relies on the attacker's **MITM** ability on the network and can be used to redirect users from an intended website to a malicious website.

To prevent these vulnerabilities, Domain Name System Security Extensions (DNSSEC) ensure the integrity and authenticity of DNS data by digitally signing DNS zones.

The public key of a DNS zone used to validate signatures can be trusted as DNSSEC is based on the following chain of trust:

- The parent DNS zone adds a "fingerprint" of the public key of the child zone in a "DS record".
- The parent DNS zone signs it with its own private key.
- And this process continues until the root zone.

Ask Yourself Whether

The parent DNS zone (likely managed by the DNS registrar of the domain name) supports DNSSEC and

- The DNS zone is public (contains data such as public reachable IP addresses).

There is a risk if you answered yes to this question.

Recommended Secure Coding Practices

It's recommended to use DNSSEC when creating private and public DNS zones.

Private DNS zones cannot be queried on the Internet and provide DNS name resolution for private networks. The risk of MITM attacks might be considered low on these networks and therefore implementing DNSSEC is still recommended but not with a high priority.






Note: Choose a robust signing algorithm when setting up DNSSEC, such as **rsasha256**. The **insecure rsasha1** algorithm should no longer be used.

Sensitive Code Example

```
resource "google_dns_managed_zone" "example" { # Sensitive
  name      = "foobar"
  dns_name = "foo.bar."
}
```

https://rules.sonarsource.com/terraform/RSPEC-6402

1/2

 Security Hotspot
Disabling versioning of S3 buckets is security-sensitive  Security Hotspot
Disabling server-side encryption of S3 buckets is security-sensitive  Security Hotspot
AWS tag keys should comply with a naming convention  Code Smell
Terraform parsing failure  Code Smell

Compliant Solution

```
resource "google_dns_managed_zone" "example" {
  name      = "foobar"
  dns_name = "foo.bar."

  dnssec_config {
    default_key_specs {
      algorithm = "rsasha256"
    }
  }
}
```

See

- [OWASP Top 10 2021 Category A8](#) - Software and Data Integrity Failures
- [OWASP Top 10 2017 Category A6](#) - Security Misconfiguration
- [GCP Documentation](#) - Manage DNSSEC configuration
- [MITRE, CWE-345](#) - Insufficient Verification of Data Authenticity
- [MITRE, CWE-353](#) - Missing Support for Integrity Check

Available In:

