




 Secrets


 ABAP


 Apex


 C


 C++


 CloudFormation


 COBOL


 C#


 CSS


 Flex


 Go


 HTML


 Java


 JavaScript


 Kotlin


 Objective C


 PHP


 PL/I


 PL/SQL


 Python


 RPG


 Ruby


 Scala


 Swift


 **Terraform**


 Text


 TypeScript

 T-SQL

 VB.NET

 VB6

 XML



Terraform static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your TERRAFORM code


All rules 50

Vulnerability 5


Security Hotspot 43

Code Smell 2


Tags ▾

Search by name... 


sensitive

 Security Hotspot


Disabling certificate-based authentication is security-sensitive

 Security Hotspot


Assigning high privileges Azure Resource Manager built-in roles is security-sensitive

 Security Hotspot


Authorizing anonymous access to Azure resources is security-sensitive

 Security Hotspot


Enabling Azure resource-specific admin accounts is security-sensitive

 Security Hotspot


Disabling Managed Identities for Azure resources is security-sensitive

 Security Hotspot


Assigning high privileges Azure Active Directory built-in roles is security-sensitive

 Security Hotspot


Defining a short backup retention duration is security-sensitive

 Security Hotspot


Using unencrypted EFS file systems is security-sensitive

 Security Hotspot


Using unencrypted SQS queues is security-sensitive



 Security Hotspot




Using unencrypted SNS topics is security-sensitive

 Security Hotspot

Enabling Attribute-Based Access Control for Kubernetes is security-sensitive

 Security Hotspot

 Major 

 cwe  owasp  gcp

Enabling Legacy Authorization, Attribute-Based Access Control (ABAC), on Google Kubernetes Engine resources can reduce an organization's ability to protect itself against access controls being compromised.

For Kubernetes, Attribute-Based Access Control has been superseded by Role-Based Access Control. ABAC is not under active development anymore and thus should be avoided.

Ask Yourself Whether

- This resource is essential for the information system infrastructure.
- This resource is essential for mission-critical functions.
- Compliance policies require access to this resource to be enforced through the use of Role-Based Access Control.

There is a risk if you answered yes to any of those questions.

Recommended Secure Coding Practices

Unless you are relying on ABAC, leave it disabled.

Sensitive Code Example

For [Google Kubernetes Engine](#):

```
resource "google_container_cluster" "example" {
  enable_legacy_abac = true # Sensitive
}
```

Compliant Solution





For [Google Kubernetes Engine](#):

```
resource "google_container_cluster" "example" {
  enable_legacy_abac = false
}
```

See

- [OWASP Top 10 2021 Category A1](#) - Broken Access Control
- [OWASP Top 10 2017 Category A5](#) - Broken Access Control
- [MITRE, CWE-668](#) - Exposure of Resource to Wrong Sphere
- [Google Cloud Documentation](#) - Hardening your cluster's security

Available In:

Using unencrypted SageMaker notebook instances is security-sensitive
 Security Hotspot
Using unencrypted Elasticsearch domains is security-sensitive
 Security Hotspot
Using unencrypted RDS databases is security-sensitive
 Security Hotspot
Using unencrypted EBS volumes is security-sensitive
 Security Hotspot
Disabling logging is security-sensitive