

































-  Secrets
-  ABAP
-  Apex
-  C
-  C++
-  CloudFormation
-  COBOL
-  C#
-  CSS
-  Flex
-  Go
-  HTML
-  Java
-  JavaScript
-  Kotlin
-  Kubernetes
-  Objective C
-  PHP
-  PL/I
-  PL/SQL
-  Python
-  RPG
-  Ruby
-  Scala
-  Swift
-  Terraform
-  Text
-  TypeScript
-  T-SQL
-  VB.NET
-  VB6
-  XML

















CloudFormation static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your CLOUDFORMATION code

- All rules 27
-  Vulnerability 3
-  Security Hotspot 20
-  Code Smell 4

Tags ▼

Search by name... 

 Security Hotspot
Using unencrypted SNS topics is security-sensitive
 Security Hotspot
Using unencrypted SageMaker notebook instances is security-sensitive
 Security Hotspot
Using unencrypted Elasticsearch domains is security-sensitive
 Security Hotspot
Using unencrypted RDS databases is security-sensitive
 Security Hotspot
Using unencrypted EBS volumes is security-sensitive
 Security Hotspot
Disabling logging is security-sensitive
 Security Hotspot
"Log Groups" should be declared explicitly
 Code Smell
Administration services access should be restricted to specific IP addresses
 Vulnerability
Disabling versioning of S3 buckets is security-sensitive
 Security Hotspot
Disabling server-side encryption of S3 buckets is security-sensitive
 Security Hotspot
AWS tag keys should comply with a naming convention
 Code Smell
CloudFormation parsing failure
 Code Smell

AWS tag keys should comply with a naming convention

Analyze your code

-  Code Smell
-  Minor 
-  aws convention

Shared conventions allow teams to collaborate effectively. This rule allows to check that all tag keys match a provided regular expression.

Noncompliant Code Example

With default provided regular expression `^([A-Z]:)([A-Z][A-Za-z]*)$`:

```
AWSTemplateFormatVersion: 2010-09-09
Resources:
  S3Bucket:
    Type: 'AWS::S3::Bucket'
    Properties:
      BucketName: "mybucketname"
      Tags:
        - Key: "anycompany:cost-center" # Noncompliant
          Value: "Accounting"
        - Key: "anycompany:EnvironmentType" # Noncompliant
          Value: "PROD"
```

Compliant Solution

```
AWSTemplateFormatVersion: 2010-09-09
Resources:
  S3Bucket:
    Type: 'AWS::S3::Bucket'
    Properties:
      BucketName: "mybucketname"
      Tags:
        - Key: "Anycompany:CostCenter"
          Value: "Accounting"
        - Key: "Anycompany:EnvironmentType"
          Value: "PROD"
```

See

- [AWS Documentation](#): Adopt a Standardized Approach for Tag Names

Available In:

