




 Secrets


 ABAP


 Apex


 C


 C++


 CloudFormation


 COBOL


 C#


 CSS


 Flex


 Go


 HTML


 Java


 JavaScript


 Kotlin


 Objective C


 PHP


 PL/I


 PL/SQL


 Python


 RPG


 Ruby


 Scala


 Swift


 **Terraform**


 Text


 TypeScript

 T-SQL

 VB.NET

 VB6


 XML





## Terraform static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your TERRAFORM code


All rules 50


 Vulnerability 5

 Security Hotspot 43


 Code Smell 2


Tags ▾

Search by name... 


 Security Hotspot


Using unencrypted EFS file systems is security-sensitive




 Security Hotspot


Using unencrypted SQS queues is security-sensitive




 Security Hotspot


Using unencrypted SNS topics is security-sensitive




 Security Hotspot


Using unencrypted SageMaker notebook instances is security-sensitive




 Security Hotspot


Using unencrypted Elasticsearch domains is security-sensitive




 Security Hotspot


Using unencrypted RDS databases is security-sensitive



 Security Hotspot

Using unencrypted EBS volumes is security-sensitive



 Security Hotspot

Disabling logging is security-sensitive



 Vulnerability

Administration services access should be restricted to specific IP addresses




 Security Hotspot

Unversioned Google Cloud Storage buckets are security-sensitive

 Security Hotspot

Disabling S3 bucket MFA delete is security-sensitive

### Enabling Azure resource-specific admin accounts is security-sensitive

 Security Hotspot  Major  azure

Enabling Azure resource-specific admin accounts can reduce an organization's ability to protect itself against account or service account thefts.

Full Administrator permissions fail to correctly separate duties and create potentially critical attack vectors on the impacted resources.

In case of abuse of elevated permissions, both the data on which impacted resources operate and their access traceability are at risk.

#### Ask Yourself Whether

- This Azure resource is essential for the information system infrastructure.
- This Azure resource is essential for mission-critical functions.
- Compliance policies require this resource to disable its administrative accounts or permissions.

There is a risk if you answered yes to any of those questions.

#### Recommended Secure Coding Practices

Disable the administrative accounts or permissions in this Azure resource.

#### Sensitive Code Example






For [Azure Batch Pools](#):

```
resource "azurerm_batch_pool" "example" {
  name = "sensitive"

  start_task {
    command_line = "echo 'Hello World'"
    max_task_retry_count = 1
    wait_for_success = true

    user_identity {
      auto_user {
        elevation_level = "Admin" # Sensitive
        scope = "Task"
      }
    }
  }
}
```

For [Azure Container Registries](#):

 Security Hotspot
Disabling versioning of S3 buckets is security-sensitive  Security Hotspot
Disabling server-side encryption of S3 buckets is security-sensitive  Security Hotspot
AWS tag keys should comply with a naming convention  Code Smell
Terraform parsing failure  Code Smell

```
resource "azurerm_container_registry" "example" {
  name = "example"
  admin_enabled = true # Sensitive
}
```

Compliant Solution

For [Azure Batch Pools](#):

```
resource "azurerm_batch_pool" "example" {
  name = "example"

  start_task {
    command_line = "echo 'Hello World'"
    max_task_retry_count = 1
    wait_for_success = true

    user_identity {
      auto_user {
        elevation_level = "NonAdmin"
        scope = "Task"
      }
    }
  }
}
```

For [Azure Container Registries](#):

```
resource "azurerm_container_registry" "example" {
  name = "example"
  admin_enabled = false
}
```

See

- [OWASP Top 10 2021 Category A1](#) - Broken Access Control
- [OWASP Top 10 2017 Category A5](#) - Broken Access Control
- [MITRE, CWE-284](#) - Improper Access Control

Available In:

