
IAM Roles Anywhere

API Reference

API Version 2018-05-10



IAM Roles Anywhere: API Reference

Copyright © 2022 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
CreateProfile	3
Request Syntax	3
URI Request Parameters	3
Request Body	3
Response Syntax	4
Response Elements	5
Errors	5
See Also	5
CreateTrustAnchor	6
Request Syntax	6
URI Request Parameters	6
Request Body	6
Response Syntax	7
Response Elements	7
Errors	7
See Also	8
DeleteCrl	9
Request Syntax	9
URI Request Parameters	9
Request Body	9
Response Syntax	9
Response Elements	9
Errors	10
See Also	10
DeleteProfile	11
Request Syntax	11
URI Request Parameters	11
Request Body	11
Response Syntax	11
Response Elements	11
Errors	12
See Also	12
DeleteTrustAnchor	13
Request Syntax	13
URI Request Parameters	13
Request Body	13
Response Syntax	13
Response Elements	13
Errors	14
See Also	14
DisableCrl	15
Request Syntax	15
URI Request Parameters	15
Request Body	15
Response Syntax	15
Response Elements	15
Errors	16
See Also	16
DisableProfile	17
Request Syntax	17
URI Request Parameters	17
Request Body	17

Response Syntax	17
Response Elements	17
Errors	18
See Also	18
DisableTrustAnchor	19
Request Syntax	19
URI Request Parameters	19
Request Body	19
Response Syntax	19
Response Elements	19
Errors	20
See Also	20
EnableCrl	21
Request Syntax	21
URI Request Parameters	21
Request Body	21
Response Syntax	21
Response Elements	21
Errors	22
See Also	22
EnableProfile	23
Request Syntax	23
URI Request Parameters	23
Request Body	23
Response Syntax	23
Response Elements	23
Errors	24
See Also	24
EnableTrustAnchor	25
Request Syntax	25
URI Request Parameters	25
Request Body	25
Response Syntax	25
Response Elements	25
Errors	26
See Also	26
GetCrl	27
Request Syntax	27
URI Request Parameters	27
Request Body	27
Response Syntax	27
Response Elements	27
Errors	28
See Also	28
GetProfile	29
Request Syntax	29
URI Request Parameters	29
Request Body	29
Response Syntax	29
Response Elements	29
Errors	30
See Also	30
GetSubject	31
Request Syntax	31
URI Request Parameters	31
Request Body	31
Response Syntax	31

Response Elements	32
Errors	32
See Also	32
GetTrustAnchor	33
Request Syntax	33
URI Request Parameters	33
Request Body	33
Response Syntax	33
Response Elements	33
Errors	34
See Also	34
ImportCrl	35
Request Syntax	35
URI Request Parameters	35
Request Body	35
Response Syntax	36
Response Elements	36
Errors	36
See Also	37
ListCrls	38
Request Syntax	38
URI Request Parameters	38
Request Body	38
Response Syntax	38
Response Elements	38
Errors	39
See Also	39
ListProfiles	40
Request Syntax	40
URI Request Parameters	40
Request Body	40
Response Syntax	40
Response Elements	40
Errors	41
See Also	41
ListSubjects	42
Request Syntax	42
URI Request Parameters	42
Request Body	42
Response Syntax	42
Response Elements	42
Errors	43
See Also	43
ListTagsForResource	44
Request Syntax	44
URI Request Parameters	44
Request Body	44
Response Syntax	44
Response Elements	44
Errors	45
See Also	45
ListTrustAnchors	46
Request Syntax	46
URI Request Parameters	46
Request Body	46
Response Syntax	46
Response Elements	47

Errors	47
See Also	47
TagResource	48
Request Syntax	48
URI Request Parameters	48
Request Body	48
Response Syntax	48
Response Elements	48
Errors	49
See Also	49
UntagResource	50
Request Syntax	50
URI Request Parameters	50
Request Body	50
Response Syntax	50
Response Elements	50
Errors	51
See Also	51
UpdateCrl	52
Request Syntax	52
URI Request Parameters	52
Request Body	52
Response Syntax	53
Response Elements	53
Errors	53
See Also	53
UpdateProfile	55
Request Syntax	55
URI Request Parameters	55
Request Body	55
Response Syntax	56
Response Elements	56
Errors	57
See Also	57
UpdateTrustAnchor	58
Request Syntax	58
URI Request Parameters	58
Request Body	58
Response Syntax	59
Response Elements	59
Errors	59
See Also	60
Data Types	61
CredentialSummary	62
Contents	62
See Also	62
CrlDetail	64
Contents	64
See Also	65
InstanceProperty	66
Contents	66
See Also	66
ProfileDetail	67
Contents	67
See Also	68
Source	70
Contents	70

See Also	70
SourceData	71
Contents	71
See Also	71
SubjectDetail	72
Contents	72
See Also	73
SubjectSummary	74
Contents	74
See Also	75
Tag	76
Contents	76
See Also	76
TrustAnchorDetail	77
Contents	77
See Also	78
Common Parameters	79
Common Errors	81

Welcome

AWS Identity and Access Management Roles Anywhere provides a secure way for your workloads such as servers, containers, and applications that run outside of AWS to obtain temporary AWS credentials. Your workloads can use the same IAM policies and roles you have for native AWS applications to access AWS resources. Using IAM Roles Anywhere eliminates the need to manage long-term credentials for workloads running outside of AWS.

To use IAM Roles Anywhere, your workloads must use X.509 certificates issued by their certificate authority (CA) . You register the CA with IAM Roles Anywhere as a trust anchor to establish trust between your public key infrastructure (PKI) and IAM Roles Anywhere. If you don't manage your own PKI system, you can use AWS Private Certificate Authority to create a CA and then use that to establish trust with IAM Roles Anywhere.

This guide describes the IAM Roles Anywhere operations that you can call programmatically. For more information about IAM Roles Anywhere, see the [IAM Roles Anywhere User Guide](#).

This document was last published on November 23, 2022.

Actions

The following actions are supported:

- [CreateProfile](#) (p. 3)
- [CreateTrustAnchor](#) (p. 6)
- [DeleteCrl](#) (p. 9)
- [DeleteProfile](#) (p. 11)
- [DeleteTrustAnchor](#) (p. 13)
- [DisableCrl](#) (p. 15)
- [DisableProfile](#) (p. 17)
- [DisableTrustAnchor](#) (p. 19)
- [EnableCrl](#) (p. 21)
- [EnableProfile](#) (p. 23)
- [EnableTrustAnchor](#) (p. 25)
- [GetCrl](#) (p. 27)
- [GetProfile](#) (p. 29)
- [GetSubject](#) (p. 31)
- [GetTrustAnchor](#) (p. 33)
- [ImportCrl](#) (p. 35)
- [ListCrls](#) (p. 38)
- [ListProfiles](#) (p. 40)
- [ListSubjects](#) (p. 42)
- [ListTagsForResource](#) (p. 44)
- [ListTrustAnchors](#) (p. 46)
- [TagResource](#) (p. 48)
- [UntagResource](#) (p. 50)
- [UpdateCrl](#) (p. 52)
- [UpdateProfile](#) (p. 55)
- [UpdateTrustAnchor](#) (p. 58)

CreateProfile

Creates a *profile*, a list of the roles that Roles Anywhere service is trusted to assume. You use profiles to intersect permissions with IAM managed policies.

Required permissions: rolesanywhere:CreateProfile.

Request Syntax

```
POST /profiles HTTP/1.1
Content-type: application/json

{
  "durationSeconds": number,
  "enabled": boolean,
  "managedPolicyArns": [ "string" ],
  "name": "string",
  "roleArns": [ "string" ],
  "sessionPolicy": "string",
  "tags": [
    {
      "key": "string",
      "value": "string"
    }
  ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

durationSeconds (p. 3)

The number of seconds the vended session credentials are valid for.

Type: Integer

Valid Range: Minimum value of 900. Maximum value of 43200.

Required: No

enabled (p. 3)

Specifies whether the profile is enabled.

Type: Boolean

Required: No

managedPolicyArns (p. 3)

A list of managed policy ARNs that apply to the vended session credentials.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 200.

Required: No

name (p. 3)

The name of the profile.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9-_*]*$`

Required: Yes

roleArns (p. 3)

A list of IAM roles that this profile can assume in a temporary credential request.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `^arn:aws(-[:]+)?:iam(:.){2}(:role.)*$`

Required: Yes

sessionPolicy (p. 3)

A session policy that applies to the trust boundary of the vended session credentials.

Type: String

Required: No

tags (p. 3)

The tags to attach to the profile.

Type: Array of [Tag](#) (p. 76) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "profile": {
    "createdAt": number,
    "createdBy": "string",
    "durationSeconds": number,
    "enabled": boolean,
    "managedPolicyArns": [ "string" ],
    "name": "string",
```

```
"profileArn": "string",  
"profileId": "string",  
"requireInstanceProperties": boolean,  
"roleArns": [ "string" ],  
"sessionPolicy": "string",  
"updatedAt": number  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

profile (p. 4)

The state of the profile after a read or write operation.

Type: [ProfileDetail \(p. 67\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 81\)](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ValidationException

Validation exception error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateTrustAnchor

Creates a trust anchor to establish trust between IAM Roles Anywhere and your certificate authority (CA). You can define a trust anchor as a reference to an AWS Private Certificate Authority (AWS Private CA) or by uploading a CA certificate. Your AWS workloads can authenticate with the trust anchor using certificates issued by the CA in exchange for temporary AWS credentials.

Required permissions: `rolesanywhere:CreateTrustAnchor`.

Request Syntax

```
POST /trustanchors HTTP/1.1
Content-type: application/json

{
  "enabled": boolean,
  "name": "string",
  "source": {
    "sourceData": {
      "acmPcaArn": "string",
      "x509CertificateData": "string"
    },
    "sourceType": "string"
  },
  "tags": [
    {
      "key": "string",
      "value": "string"
    }
  ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

enabled (p. 6)

Specifies whether the trust anchor is enabled.

Type: Boolean

Required: No

name (p. 6)

The name of the trust anchor.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9-_*]$`

Required: Yes

source (p. 6)

The trust anchor type and its related certificate data.

Type: [Source \(p. 70\)](#) object

Required: Yes

tags (p. 6)

The tags to attach to the trust anchor.

Type: Array of [Tag \(p. 76\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "trustAnchor": {
    "createdAt": number,
    "enabled": boolean,
    "name": "string",
    "source": {
      "sourceData": {
        "acmPcaArn": "string",
        "x509CertificateData": "string"
      },
      "sourceType": "string"
    },
    "trustAnchorArn": "string",
    "trustAnchorId": "string",
    "updatedAt": number
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

trustAnchor (p. 7)

The state of the trust anchor after a read or write operation.

Type: [TrustAnchorDetail \(p. 77\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 81\)](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ValidationException

Validation exception error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteCrl

Deletes a certificate revocation list (CRL).

Required permissions: `rolesanywhere:DeleteCrl`.

Request Syntax

```
DELETE /crl/crlId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

`crlId` (p. 9)

The unique identifier of the certificate revocation list (CRL).

Length Constraints: Fixed length of 36.

Pattern: `[a-f0-9]{8}-([a-z0-9]{4}-){3}[a-z0-9]{12}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "crl": {
    "createdAt": number,
    "crlArn": "string",
    "crlData": blob,
    "crlId": "string",
    "enabled": boolean,
    "name": "string",
    "trustAnchorArn": "string",
    "updatedAt": number
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

`crl` (p. 9)

The state of the certificate revocation list (CRL) after a read or write operation.

Type: [CrlDetail](#) (p. 64) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 81).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteProfile

Deletes a profile.

Required permissions: `rolesanywhere:DeleteProfile`.

Request Syntax

```
DELETE /profile/profileId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

`profileId` (p. 11)

The unique identifier of the profile.

Length Constraints: Fixed length of 36.

Pattern: `[a-f0-9]{8}-([a-z0-9]{4}-){3}[a-z0-9]{12}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "profile": {
    "createdAt": number,
    "createdBy": "string",
    "durationSeconds": number,
    "enabled": boolean,
    "managedPolicyArns": [ "string" ],
    "name": "string",
    "profileArn": "string",
    "profileId": "string",
    "requireInstanceProperties": boolean,
    "roleArns": [ "string" ],
    "sessionPolicy": "string",
    "updatedAt": number
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

profile (p. 11)

The state of the profile after a read or write operation.

Type: [ProfileDetail \(p. 67\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 81\)](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteTrustAnchor

Deletes a trust anchor.

Required permissions: `rolesanywhere:DeleteTrustAnchor`.

Request Syntax

```
DELETE /trustanchor/trustAnchorId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

trustAnchorId (p. 13)

The unique identifier of the trust anchor.

Length Constraints: Fixed length of 36.

Pattern: `[a-f0-9]{8}-([a-z0-9]{4}-){3}[a-z0-9]{12}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "trustAnchor": {
    "createdAt": number,
    "enabled": boolean,
    "name": "string",
    "source": {
      "sourceData": {
        "acmPcaArn": "string",
        "x509CertificateData": "string"
      },
      "sourceType": "string"
    },
    "trustAnchorArn": "string",
    "trustAnchorId": "string",
    "updatedAt": number
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

trustAnchor (p. 13)

The state of the trust anchor after a read or write operation.

Type: [TrustAnchorDetail \(p. 77\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 81\)](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DisableCrl

Disables a certificate revocation list (CRL).

Required permissions: `rolesanywhere:DisableCrl`.

Request Syntax

```
POST /crl/crlId/disable HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

`crlId` (p. 15)

The unique identifier of the certificate revocation list (CRL).

Length Constraints: Fixed length of 36.

Pattern: `[a-f0-9]{8}-([a-z0-9]{4}-){3}[a-z0-9]{12}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "crl": {
    "createdAt": number,
    "crlArn": "string",
    "crlData": blob,
    "crlId": "string",
    "enabled": boolean,
    "name": "string",
    "trustAnchorArn": "string",
    "updatedAt": number
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

`crl` (p. 15)

The state of the certificate revocation list (CRL) after a read or write operation.

Type: [CrlDetail \(p. 64\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 81\)](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DisableProfile

Disables a profile. When disabled, temporary credential requests with this profile fail.

Required permissions: `rolesanywhere:DisableProfile`.

Request Syntax

```
POST /profile/profileId/disable HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

profileId (p. 17)

The unique identifier of the profile.

Length Constraints: Fixed length of 36.

Pattern: `[a-f0-9]{8}-([a-z0-9]{4}-){3}[a-z0-9]{12}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "profile": {
    "createdAt": number,
    "createdBy": "string",
    "durationSeconds": number,
    "enabled": boolean,
    "managedPolicyArns": [ "string" ],
    "name": "string",
    "profileArn": "string",
    "profileId": "string",
    "requireInstanceProperties": boolean,
    "roleArns": [ "string" ],
    "sessionPolicy": "string",
    "updatedAt": number
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

profile (p. 17)

The state of the profile after a read or write operation.

Type: [ProfileDetail \(p. 67\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 81\)](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DisableTrustAnchor

Disables a trust anchor. When disabled, temporary credential requests specifying this trust anchor are unauthorized.

Required permissions: `rolesanywhere:DisableTrustAnchor`.

Request Syntax

```
POST /trustanchor/trustAnchorId/disable HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

`trustAnchorId` (p. 19)

The unique identifier of the trust anchor.

Length Constraints: Fixed length of 36.

Pattern: `[a-f0-9]{8}-([a-z0-9]{4}-){3}[a-z0-9]{12}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "trustAnchor": {
    "createdAt": number,
    "enabled": boolean,
    "name": "string",
    "source": {
      "sourceData": {
        "acmPcaArn": "string",
        "x509CertificateData": "string"
      },
      "sourceType": "string"
    },
    "trustAnchorArn": "string",
    "trustAnchorId": "string",
    "updatedAt": number
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[trustAnchor](#) (p. 19)

The state of the trust anchor after a read or write operation.

Type: [TrustAnchorDetail](#) (p. 77) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 81).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

EnableCrl

Enables a certificate revocation list (CRL). When enabled, certificates stored in the CRL are unauthorized to receive session credentials.

Required permissions: `rolesanywhere:EnableCrl`.

Request Syntax

```
POST /crl/crlId/enable HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

`crlId` (p. 21)

The unique identifier of the certificate revocation list (CRL).

Length Constraints: Fixed length of 36.

Pattern: `[a-f0-9]{8}-([a-z0-9]{4}-){3}[a-z0-9]{12}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "crl": {
    "createdAt": number,
    "crlArn": "string",
    "crlData": blob,
    "crlId": "string",
    "enabled": boolean,
    "name": "string",
    "trustAnchorArn": "string",
    "updatedAt": number
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[crl \(p. 21\)](#)

The state of the certificate revocation list (CRL) after a read or write operation.

Type: [CrlDetail \(p. 64\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 81\)](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

EnableProfile

Enables temporary credential requests for a profile.

Required permissions: `rolesanywhere:EnableProfile`.

Request Syntax

```
POST /profile/profileId/enable HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

`profileId` (p. 23)

The unique identifier of the profile.

Length Constraints: Fixed length of 36.

Pattern: `[a-f0-9]{8}-([a-z0-9]{4}-){3}[a-z0-9]{12}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "profile": {
    "createdAt": number,
    "createdBy": "string",
    "durationSeconds": number,
    "enabled": boolean,
    "managedPolicyArns": [ "string" ],
    "name": "string",
    "profileArn": "string",
    "profileId": "string",
    "requireInstanceProperties": boolean,
    "roleArns": [ "string" ],
    "sessionPolicy": "string",
    "updatedAt": number
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

profile (p. 23)

The state of the profile after a read or write operation.

Type: [ProfileDetail \(p. 67\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 81\)](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

EnableTrustAnchor

Enables a trust anchor. When enabled, certificates in the trust anchor chain are authorized for trust validation.

Required permissions: `rolesanywhere:EnableTrustAnchor`.

Request Syntax

```
POST /trustanchor/trustAnchorId/enable HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

trustAnchorId (p. 25)

The unique identifier of the trust anchor.

Length Constraints: Fixed length of 36.

Pattern: `[a-f0-9]{8}-([a-z0-9]{4}-){3}[a-z0-9]{12}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "trustAnchor": {
    "createdAt": number,
    "enabled": boolean,
    "name": "string",
    "source": {
      "sourceData": {
        "acmPcaArn": "string",
        "x509CertificateData": "string"
      },
      "sourceType": "string"
    },
    "trustAnchorArn": "string",
    "trustAnchorId": "string",
    "updatedAt": number
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

trustAnchor (p. 25)

The state of the trust anchor after a read or write operation.

Type: [TrustAnchorDetail \(p. 77\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 81\)](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetCrl

Gets a certificate revocation list (CRL).

Required permissions: `rolesanywhere:GetCrl`.

Request Syntax

```
GET /crl/crlId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

`crlId` (p. 27)

The unique identifier of the certificate revocation list (CRL).

Length Constraints: Fixed length of 36.

Pattern: `[a-f0-9]{8}-([a-z0-9]{4}-){3}[a-z0-9]{12}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "crl": {
    "createdAt": number,
    "crlArn": "string",
    "crlData": blob,
    "crlId": "string",
    "enabled": boolean,
    "name": "string",
    "trustAnchorArn": "string",
    "updatedAt": number
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

`crl` (p. 27)

The state of the certificate revocation list (CRL) after a read or write operation.

Type: [CrlDetail \(p. 64\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 81\)](#).

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetProfile

Gets a profile.

Required permissions: rolesanywhere:GetProfile.

Request Syntax

```
GET /profile/profileId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[profileId \(p. 29\)](#)

The unique identifier of the profile.

Length Constraints: Fixed length of 36.

Pattern: [a-f0-9]{8}-([a-z0-9]{4}-){3}[a-z0-9]{12}

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "profile": {
    "createdAt": number,
    "createdBy": "string",
    "durationSeconds": number,
    "enabled": boolean,
    "managedPolicyArns": [ "string" ],
    "name": "string",
    "profileArn": "string",
    "profileId": "string",
    "requireInstanceProperties": boolean,
    "roleArns": [ "string" ],
    "sessionPolicy": "string",
    "updatedAt": number
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

profile (p. 29)

The state of the profile after a read or write operation.

Type: [ProfileDetail \(p. 67\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 81\)](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetSubject

Gets a *subject*, which associates a certificate identity with authentication attempts. The subject stores auditing information such as the status of the last authentication attempt, the certificate data used in the attempt, and the last time the associated identity attempted authentication.

Required permissions: `rolesanywhere:GetSubject`.

Request Syntax

```
GET /subject/subjectId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[subjectId \(p. 31\)](#)

The unique identifier of the subject.

Length Constraints: Fixed length of 36.

Pattern: `[a-f0-9]{8}-([a-z0-9]{4}-){3}[a-z0-9]{12}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "subject": {
    "createdAt": number,
    "credentials": [
      {
        "enabled": boolean,
        "failed": boolean,
        "issuer": "string",
        "seenAt": number,
        "serialNumber": "string",
        "x509CertificateData": "string"
      }
    ],
    "enabled": boolean,
    "instanceProperties": [
      {
        "failed": boolean,
        "properties": {
          "string" : "string"
        },
        "seenAt": number
      }
    ]
  }
}
```

```
    },  
    "lastSeenAt": number,  
    "subjectArn": "string",  
    "subjectId": "string",  
    "updatedAt": number,  
    "x509Subject": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[subject \(p. 31\)](#)

The state of the subject after a read or write operation.

Type: [SubjectDetail \(p. 72\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 81\)](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetTrustAnchor

Gets a trust anchor.

Required permissions: `rolesanywhere:GetTrustAnchor`.

Request Syntax

```
GET /trustanchor/trustAnchorId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

trustAnchorId (p. 33)

The unique identifier of the trust anchor.

Length Constraints: Fixed length of 36.

Pattern: `[a-f0-9]{8}-([a-z0-9]{4}-){3}[a-z0-9]{12}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "trustAnchor": {
    "createdAt": number,
    "enabled": boolean,
    "name": "string",
    "source": {
      "sourceData": {
        "acmPcaArn": "string",
        "x509CertificateData": "string"
      },
      "sourceType": "string"
    },
    "trustAnchorArn": "string",
    "trustAnchorId": "string",
    "updatedAt": number
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

trustAnchor (p. 33)

The state of the trust anchor after a read or write operation.

Type: [TrustAnchorDetail \(p. 77\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 81\)](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 404

ValidationException

Validation exception error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ImportCrl

Imports the certificate revocation list (CRL). A CRL is a list of certificates that have been revoked by the issuing certificate Authority (CA). IAM Roles Anywhere validates against the CRL before issuing credentials.

Required permissions: `rolesanywhere:ImportCrl`.

Request Syntax

```
POST /crls HTTP/1.1
Content-type: application/json

{
  "crlData": blob,
  "enabled": boolean,
  "name": "string",
  "tags": [
    {
      "key": "string",
      "value": "string"
    }
  ],
  "trustAnchorArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

crlData (p. 35)

The x509 v3 specified certificate revocation list (CRL).

Type: Base64-encoded binary data object

Length Constraints: Minimum length of 1. Maximum length of 300000.

Required: Yes

enabled (p. 35)

Specifies whether the certificate revocation list (CRL) is enabled.

Type: Boolean

Required: No

name (p. 35)

The name of the certificate revocation list (CRL).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9-]*$`

Required: Yes

[tags \(p. 35\)](#)

A list of tags to attach to the certificate revocation list (CRL).

Type: Array of [Tag \(p. 76\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

[trustAnchorArn \(p. 35\)](#)

The ARN of the TrustAnchor the certificate revocation list (CRL) will provide revocation for.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `^arn:aws(-[^\:]+)?:rolesanywhere(:.*){2}(:trust-anchor.*)$`

Required: Yes

Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "crl": {
    "createdAt": number,
    "crlArn": "string",
    "crlData": blob,
    "crlId": "string",
    "enabled": boolean,
    "name": "string",
    "trustAnchorArn": "string",
    "updatedAt": number
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

[crl \(p. 36\)](#)

The state of the certificate revocation list (CRL) after a read or write operation.

Type: [CrlDetail \(p. 64\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 81\)](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ValidationException

Validation exception error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListCrls

Lists all certificate revocation lists (CRL) in the authenticated account and AWS Region.

Required permissions: `rolesanywhere:ListCrls`.

Request Syntax

```
GET /crls?nextToken=nextToken&pageSize=pageSize HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

`nextToken` (p. 38)

A token that indicates where the output should continue from, if a previous request did not show all results. To get the next results, make the request again with this value.

Length Constraints: Minimum length of 1. Maximum length of 10000.

`pageSize` (p. 38)

The number of resources in the paginated list.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "crls": [
    {
      "createdAt": number,
      "crlArn": "string",
      "crlData": blob,
      "crlId": "string",
      "enabled": boolean,
      "name": "string",
      "trustAnchorArn": "string",
      "updatedAt": number
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[crls \(p. 38\)](#)

A list of certificate revocation lists (CRL).

Type: Array of [CrlDetail \(p. 64\)](#) objects

[nextToken \(p. 38\)](#)

A token that indicates where the output should continue from, if a previous request did not show all results. To get the next results, make the request again with this value.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 81\)](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ValidationException

Validation exception error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListProfiles

Lists all profiles in the authenticated account and AWS Region.

Required permissions: `rolesanywhere:ListProfiles`.

Request Syntax

```
GET /profiles?nextToken=nextToken&pageSize=pageSize HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

`nextToken` (p. 40)

A token that indicates where the output should continue from, if a previous request did not show all results. To get the next results, make the request again with this value.

Length Constraints: Minimum length of 1. Maximum length of 10000.

`pageSize` (p. 40)

The number of resources in the paginated list.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextToken": "string",
  "profiles": [
    {
      "createdAt": number,
      "createdBy": "string",
      "durationSeconds": number,
      "enabled": boolean,
      "managedPolicyArns": [ "string" ],
      "name": "string",
      "profileArn": "string",
      "profileId": "string",
      "requireInstanceProperties": boolean,
      "roleArns": [ "string" ],
      "sessionPolicy": "string",
      "updatedAt": number
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken (p. 40)

A token that indicates where the output should continue from, if a previous request did not show all results. To get the next results, make the request again with this value.

Type: String

profiles (p. 40)

A list of profiles.

Type: Array of [ProfileDetail \(p. 67\)](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 81\)](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ValidationException

Validation exception error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListSubjects

Lists the subjects in the authenticated account and AWS Region.

Required permissions: `rolesanywhere:ListSubjects`.

Request Syntax

```
GET /subjects?nextToken=nextToken&pageSize=pageSize HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

`nextToken` (p. 42)

A token that indicates where the output should continue from, if a previous request did not show all results. To get the next results, make the request again with this value.

Length Constraints: Minimum length of 1. Maximum length of 10000.

`pageSize` (p. 42)

The number of resources in the paginated list.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextToken": "string",
  "subjects": [
    {
      "createdAt": number,
      "enabled": boolean,
      "lastSeenAt": number,
      "subjectArn": "string",
      "subjectId": "string",
      "updatedAt": number,
      "x509Subject": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken (p. 42)

A token that indicates where the output should continue from, if a previous request did not show all results. To get the next results, make the request again with this value.

Type: String

subjects (p. 42)

A list of subjects.

Type: Array of [SubjectSummary \(p. 74\)](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 81\)](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ValidationException

Validation exception error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

Lists the tags attached to the resource.

Required permissions: `rolesanywhere:ListTagsForResource`.

Request Syntax

```
GET /ListTagsForResource?resourceArn=resourceArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

`resourceArn` (p. 44)

The ARN of the resource.

Length Constraints: Minimum length of 1. Maximum length of 1011.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "tags": [
    {
      "key": "string",
      "value": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

`tags` (p. 44)

A list of tags attached to the resource.

Type: Array of [Tag](#) (p. 76) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 81\)](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 404

ValidationException

Validation exception error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTrustAnchors

Lists the trust anchors in the authenticated account and AWS Region.

Required permissions: `rolesanywhere:ListTrustAnchors`.

Request Syntax

```
GET /trustanchors?nextToken=nextToken&pageSize=pageSize HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

`nextToken` (p. 46)

A token that indicates where the output should continue from, if a previous request did not show all results. To get the next results, make the request again with this value.

Length Constraints: Minimum length of 1. Maximum length of 10000.

`pageSize` (p. 46)

The number of resources in the paginated list.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextToken": "string",
  "trustAnchors": [
    {
      "createdAt": number,
      "enabled": boolean,
      "name": "string",
      "source": {
        "sourceData": {
          "acmPcaArn": "string",
          "x509CertificateData": "string"
        },
        "sourceType": "string"
      },
      "trustAnchorArn": "string",
      "trustAnchorId": "string",
      "updatedAt": number
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken (p. 46)

A token that indicates where the output should continue from, if a previous request did not show all results. To get the next results, make the request again with this value.

Type: String

trustAnchors (p. 46)

A list of trust anchors.

Type: Array of [TrustAnchorDetail](#) (p. 77) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 81).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ValidationException

Validation exception error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

TagResource

Attaches tags to a resource.

Required permissions: `rolesanywhere:TagResource`.

Request Syntax

```
POST /TagResource HTTP/1.1
Content-type: application/json
```

```
{
  "resourceArn": "string",
  "tags": [
    {
      "key": "string",
      "value": "string"
    }
  ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

resourceArn (p. 48)

The ARN of the resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Required: Yes

tags (p. 48)

The tags to attach to the resource.

Type: Array of [Tag](#) (p. 76) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: Yes

Response Syntax

```
HTTP/1.1 201
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 81\)](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 404

TooManyTagsException

Too many tags.

HTTP Status Code: 400

ValidationException

Validation exception error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UntagResource

Removes tags from the resource.

Required permissions: `rolesanywhere:UntagResource`.

Request Syntax

```
POST /UntagResource HTTP/1.1
Content-type: application/json

{
  "resourceArn": "string",
  "tagKeys": [ "string" ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

resourceArn (p. 50)

The ARN of the resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Required: Yes

tagKeys (p. 50)

A list of keys. Tag keys are the unique identifiers of tags.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_ . : / = + @ -] * $`

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 81\)](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 404

ValidationException

Validation exception error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateCrl

Updates the certificate revocation list (CRL). A CRL is a list of certificates that have been revoked by the issuing certificate authority (CA). IAM Roles Anywhere validates against the CRL before issuing credentials.

Required permissions: `rolesanywhere:UpdateCrl`.

Request Syntax

```
PATCH /crl/crlId HTTP/1.1
Content-type: application/json

{
  "crlData": blob,
  "name": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

crlId (p. 52)

The unique identifier of the certificate revocation list (CRL).

Length Constraints: Fixed length of 36.

Pattern: `[a-f0-9]{8}-([a-z0-9]{4}-){3}[a-z0-9]{12}`

Required: Yes

Request Body

The request accepts the following data in JSON format.

crlData (p. 52)

The x509 v3 specified certificate revocation list (CRL).

Type: Base64-encoded binary data object

Length Constraints: Minimum length of 1. Maximum length of 300000.

Required: No

name (p. 52)

The name of the Crl.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9-_*]$`

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "crl": {
    "createdAt": number,
    "crlArn": "string",
    "crlData": blob,
    "crlId": "string",
    "enabled": boolean,
    "name": "string",
    "trustAnchorArn": "string",
    "updatedAt": number
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

crl (p. 53)

The state of the certificate revocation list (CRL) after a read or write operation.

Type: [CrlDetail](#) (p. 64) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 81).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 404

ValidationException

Validation exception error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateProfile

Updates a *profile*, a list of the roles that IAM Roles Anywhere service is trusted to assume. You use profiles to intersect permissions with IAM managed policies.

Required permissions: `rolesanywhere:UpdateProfile`.

Request Syntax

```
PATCH /profile/profileId HTTP/1.1
Content-type: application/json

{
  "durationSeconds": number,
  "managedPolicyArns": [ "string" ],
  "name": "string",
  "roleArns": [ "string" ],
  "sessionPolicy": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

profileId (p. 55)

The unique identifier of the profile.

Length Constraints: Fixed length of 36.

Pattern: `[a-f0-9]{8}-([a-z0-9]{4}-){3}[a-z0-9]{12}`

Required: Yes

Request Body

The request accepts the following data in JSON format.

durationSeconds (p. 55)

The number of seconds the vended session credentials are valid for.

Type: Integer

Valid Range: Minimum value of 900. Maximum value of 43200.

Required: No

managedPolicyArns (p. 55)

A list of managed policy ARNs that apply to the vended session credentials.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 200.

Required: No

name (p. 55)

The name of the profile.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9-]*$`

Required: No

roleArns (p. 55)

A list of IAM roles that this profile can assume in a temporary credential request.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `^arn:aws(-[^\:]+)?:iam(:.*){2}(:role.*)$`

Required: No

sessionPolicy (p. 55)

A session policy that applies to the trust boundary of the vended session credentials.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100000.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "profile": {
    "createdAt": number,
    "createdBy": "string",
    "durationSeconds": number,
    "enabled": boolean,
    "managedPolicyArns": [ "string" ],
    "name": "string",
    "profileArn": "string",
    "profileId": "string",
    "requireInstanceProperties": boolean,
    "roleArns": [ "string" ],
    "sessionPolicy": "string",
    "updatedAt": number
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

profile (p. 56)

The state of the profile after a read or write operation.

Type: [ProfileDetail \(p. 67\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 81\)](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 404

ValidationException

Validation exception error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateTrustAnchor

Updates a trust anchor. You establish trust between IAM Roles Anywhere and your certificate authority (CA) by configuring a trust anchor. You can define a trust anchor as a reference to an AWS Private Certificate Authority (AWS Private CA) or by uploading a CA certificate. Your AWS workloads can authenticate with the trust anchor using certificates issued by the CA in exchange for temporary AWS credentials.

Required permissions: `rolesanywhere:UpdateTrustAnchor`.

Request Syntax

```
PATCH /trustanchor/trustAnchorId HTTP/1.1
Content-type: application/json

{
  "name": "string",
  "source": {
    "sourceData": {
      "acmPcaArn": "string",
      "x509CertificateData": "string"
    },
    "sourceType": "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

trustAnchorId (p. 58)

The unique identifier of the trust anchor.

Length Constraints: Fixed length of 36.

Pattern: `[a-f0-9]{8}-([a-z0-9]{4}-){3}[a-z0-9]{12}`

Required: Yes

Request Body

The request accepts the following data in JSON format.

name (p. 58)

The name of the trust anchor.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9-_*]$`

Required: No

source (p. 58)

The trust anchor type and its related certificate data.

Type: [Source \(p. 70\)](#) object

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "trustAnchor": {
    "createdAt": number,
    "enabled": boolean,
    "name": "string",
    "source": {
      "sourceData": {
        "acmPcaArn": "string",
        "x509CertificateData": "string"
      },
      "sourceType": "string"
    },
    "trustAnchorArn": "string",
    "trustAnchorId": "string",
    "updatedAt": number
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

trustAnchor (p. 59)

The state of the trust anchor after a read or write operation.

Type: [TrustAnchorDetail \(p. 77\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 81\)](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 404

ValidationException

Validation exception error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The IAM Roles Anywhere API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [CredentialSummary](#) (p. 62)
- [CrlDetail](#) (p. 64)
- [InstanceProperty](#) (p. 66)
- [ProfileDetail](#) (p. 67)
- [Source](#) (p. 70)
- [SourceData](#) (p. 71)
- [SubjectDetail](#) (p. 72)
- [SubjectSummary](#) (p. 74)
- [Tag](#) (p. 76)
- [TrustAnchorDetail](#) (p. 77)

CredentialSummary

A record of a presented X509 credential from a temporary credential request.

Contents

enabled

Indicates whether the credential is enabled.

Type: Boolean

Required: No

failed

Indicates whether the temporary credential request was successful.

Type: Boolean

Required: No

issuer

The fully qualified domain name of the issuing certificate for the presented end-entity certificate.

Type: String

Required: No

seenAt

The ISO-8601 time stamp of when the certificate was last used in a temporary credential request.

Type: Timestamp

Required: No

serialNumber

The serial number of the certificate.

Type: String

Required: No

x509CertificateData

The PEM-encoded data of the certificate.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

CrlDetail

The state of the certificate revocation list (CRL) after a read or write operation.

Contents

createdAt

The ISO-8601 timestamp when the certificate revocation list (CRL) was created.

Type: Timestamp

Required: No

crlArn

The ARN of the certificate revocation list (CRL).

Type: String

Required: No

crlData

The state of the certificate revocation list (CRL) after a read or write operation.

Type: Base64-encoded binary data object

Required: No

crlId

The unique identifier of the certificate revocation list (CRL).

Type: String

Length Constraints: Fixed length of 36.

Pattern: [a-f0-9]{8}-([a-z0-9]{4}-){3}[a-z0-9]{12}

Required: No

enabled

Indicates whether the certificate revocation list (CRL) is enabled.

Type: Boolean

Required: No

name

The name of the certificate revocation list (CRL).

Type: String

Required: No

trustAnchorArn

The ARN of the TrustAnchor the certificate revocation list (CRL) will provide revocation for.

Type: String

Required: No

updatedAt

The ISO-8601 timestamp when the certificate revocation list (CRL) was last updated.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InstanceProperty

A key-value pair you set that identifies a property of the authenticating instance.

Contents

failed

Indicates whether the temporary credential request was successful.

Type: Boolean

Required: No

properties

A list of instanceProperty objects.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 200.

Value Length Constraints: Minimum length of 1. Maximum length of 200.

Required: No

seenAt

The ISO-8601 time stamp of when the certificate was last used in a temporary credential request.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ProfileDetail

The state of the profile after a read or write operation.

Contents

createdAt

The ISO-8601 timestamp when the profile was created.

Type: Timestamp

Required: No

createdBy

The AWS account that created the profile.

Type: String

Required: No

durationSeconds

The number of seconds the vended session credentials are valid for.

Type: Integer

Required: No

enabled

Indicates whether the profile is enabled.

Type: Boolean

Required: No

managedPolicyArns

A list of managed policy ARNs that apply to the vended session credentials.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 200.

Required: No

name

The name of the profile.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9-_*]$`

Required: No

profileArn

The ARN of the profile.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `^arn:aws(-[^\:]+)?:rolesanywhere(:.){2}(:profile.)*$`

Required: No

profileId

The unique identifier of the profile.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[a-f0-9]{8}-([a-z0-9]{4}-){3}[a-z0-9]{12}`

Required: No

requireInstanceProperties

Specifies whether instance properties are required in temporary credential requests with this profile.

Type: Boolean

Required: No

roleArns

A list of IAM roles that this profile can assume in a temporary credential request.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `^arn:aws(-[^\:]+)?:iam(:.){2}(:role.)*$`

Required: No

sessionPolicy

A session policy that applies to the trust boundary of the vended session credentials.

Type: String

Required: No

updatedAt

The ISO-8601 timestamp when the profile was last updated.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Source

The trust anchor type and its related certificate data.

Contents

sourceData

The data field of the trust anchor depending on its type.

Type: [SourceData](#) (p. 71) object

Required: No

sourceType

The type of the trust anchor.

Type: String

Valid Values: `AWS_ACM_PCA` | `CERTIFICATE_BUNDLE`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SourceData

The data field of the trust anchor depending on its type.

Contents

acmPcaArn

The root certificate of the AWS Private Certificate Authority specified by this ARN is used in trust validation for temporary credential requests. Included for trust anchors of type `AWS_ACM_PCA`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Required: No

x509CertificateData

The PEM-encoded data for the certificate anchor. Included for trust anchors of type `CERTIFICATE_BUNDLE`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 8000.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SubjectDetail

The state of the subject after a read or write operation.

Contents

createdAt

The ISO-8601 timestamp when the subject was created.

Type: Timestamp

Required: No

credentials

The temporary session credentials vended at the last authenticating call with this subject.

Type: Array of [CredentialSummary](#) (p. 62) objects

Required: No

enabled

The enabled status of the subject.

Type: Boolean

Required: No

instanceProperties

The specified instance properties associated with the request.

Type: Array of [InstanceProperty](#) (p. 66) objects

Required: No

lastSeenAt

The ISO-8601 timestamp of the last time this subject requested temporary session credentials.

Type: Timestamp

Required: No

subjectArn

The ARN of the resource.

Type: String

Required: No

subjectId

The id of the resource

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[a-f0-9]{8}-([a-z0-9]{4}-){3}[a-z0-9]{12}`

Required: No

updatedAt

The ISO-8601 timestamp when the subject was last updated.

Type: Timestamp

Required: No

x509Subject

The x509 principal identifier of the authenticating certificate.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SubjectSummary

A summary representation of subjects.

Contents

createdAt

The ISO-8601 time stamp of when the certificate was first used in a temporary credential request.

Type: Timestamp

Required: No

enabled

The enabled status of the subject.

Type: Boolean

Required: No

lastSeenAt

The ISO-8601 time stamp of when the certificate was last used in a temporary credential request.

Type: Timestamp

Required: No

subjectArn

The ARN of the resource.

Type: String

Required: No

subjectId

The id of the resource.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[a-f0-9]{8}-([a-z0-9]{4}-){3}[a-z0-9]{12}`

Required: No

updatedAt

The ISO-8601 timestamp when the subject was last updated.

Type: Timestamp

Required: No

x509Subject

The x509 principal identifier of the authenticating certificate.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Tag

A label that consists of a key and value you define.

Contents

key

The tag key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_.:/=+@-]*$`

Required: Yes

value

The tag value.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `^[a-zA-Z0-9_.:/=+@-]*$`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TrustAnchorDetail

The state of the trust anchor after a read or write operation.

Contents

createdAt

The ISO-8601 timestamp when the trust anchor was created.

Type: Timestamp

Required: No

enabled

Indicates whether the trust anchor is enabled.

Type: Boolean

Required: No

name

The name of the trust anchor.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9-_*]$`

Required: No

source

The trust anchor type and its related certificate data.

Type: [Source \(p. 70\)](#) object

Required: No

trustAnchorArn

The ARN of the trust anchor.

Type: String

Required: No

trustAnchorId

The unique identifier of the trust anchor.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[a-f0-9]{8}-([a-z0-9]{4}-){3}[a-z0-9]{12}`

Required: No

updatedAt

The ISO-8601 timestamp when the trust anchor was last updated.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signature Version 4 Signing Process](#) in the *Amazon Web Services General Reference*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Task 2: Create a String to Sign for Signature Version 4](#) in the *Amazon Web Services General Reference*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'THHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is

not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Handling Dates in Signature Version 4](#) in the *Amazon Web Services General Reference*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS Security Token Service, go to [AWS Services That Work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from the AWS Security Token Service, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Task 1: Create a Canonical Request For Signature Version 4](#) in the *Amazon Web Services General Reference*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 400

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

InvalidAction

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

InvalidClientTokenId

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

InvalidParameterCombination

Parameters that must not be used together were used together.

HTTP Status Code: 400

InvalidParameterValue

An invalid or out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

InvalidQueryParameter

The AWS query string is malformed or does not adhere to AWS standards.

HTTP Status Code: 400

MalformedQueryString

The query string contains a syntax error.

HTTP Status Code: 404

MissingAction

The request is missing an action or a required parameter.

HTTP Status Code: 400

MissingAuthenticationToken

The request must contain either a valid (registered) AWS access key ID or X.509 certificate.

HTTP Status Code: 403

MissingParameter

A required parameter for the specified action is not supplied.

HTTP Status Code: 400

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 400

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationError

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400