

































-  Secrets
-  ABAP
-  Apex
-  C
-  C++
-  CloudFormation
-  COBOL
-  C#
-  CSS
-  Flex
-  Go
-  HTML
-  Java
-  JavaScript
-  **Kotlin**
-  Kubernetes
-  Objective C
-  PHP
-  PL/I
-  PL/SQL
-  Python
-  RPG
-  Ruby
-  Scala
-  Swift
-  Terraform
-  Text
-  TypeScript
-  T-SQL
-  VB.NET
-  VB6
-  XML



Kotlin static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your KOTLIN code

All rules 98  Vulnerability 10  Bug 17  Security Hotspot 15  Code Smell 56


Tags

Search by name...


Hard-coded credentials are security-sensitive

 Security Hotspot


Cipher algorithms should be robust

 Vulnerability


Encryption algorithms should be used with secure mode and padding scheme

 Vulnerability


Server hostnames should be verified during SSL/TLS connections

 Vulnerability


Server certificates should be verified during SSL/TLS connections

 Vulnerability


Cryptographic keys should be robust

 Vulnerability


Weak SSL/TLS protocols should not be used

 Vulnerability


"SecureRandom" seeds should not be predictable

 Vulnerability

Cipher Block Chaining IVs should be unpredictable

 Vulnerability

Hashes should include an unpredictable salt











 Vulnerability

Regular expressions should be syntactically valid

 Bug

"runFinalizersOnExit" should not be called


 Bug


"ScheduledThreadPoolExecutor" should not have 0 core threads
 Bug
Jump statements should not occur in "finally" blocks
 Bug
Using clear-text protocols is security-sensitive
 Security Hotspot
Accessing Android external storage is security-sensitive
 Security Hotspot
Receiving intents is security-sensitive
 Security Hotspot
Broadcasting intents is security-sensitive
 Security Hotspot
Using weak hashing algorithms is security-sensitive
 Security Hotspot
Using pseudorandom number generators (PRNGs) is security-sensitive
 Security Hotspot
Empty lines should not be tested with regex MULTILINE flag
 Code Smell
Cognitive Complexity of functions should not be too high
 Code Smell


Using unencrypted files in mobile applications is security-sensitive

Analyze your code

 Security Hotspot

 Major



 cwe

owasp

android

Storing files locally is a common task for mobile applications. Files that are stored unencrypted can be read out and modified by an attacker with physical access to the device. Access to sensitive data can be harmful for the user of the application, for example when the device gets stolen.

Ask Yourself Whether

- The file contains sensitive data that could cause harm when leaked.

There is a risk if you answered yes to any of those questions.

Recommended Secure Coding Practices

It's recommended to password-encrypt local files that contain sensitive information. The class [EncryptedFile](#) can be used to easily encrypt files.

Sensitive Code Example

```
val targetFile = File(activity.filesDir, "data.txt")
targetFile.writeText(fileContent) // Sensitive
```

Compliant Solution

```
val mainKey = MasterKeys.getOrCreate(MasterKeys.AES256_GCM_SPECIFIC)

val encryptedFile = EncryptedFile.Builder(
    File(activity.filesDir, "data.txt"),
    activity,
    mainKey,
    EncryptedFile.FileEncryptionScheme.AES256_GCM_HKDF_4K
).build()

encryptedFile.openFileOutput().apply {
    write(fileContent)
    flush()
    close()
}
```

See

- [OWASP Top 10 2021 Category A4](#) - Insecure Design
- [Mobile AppSec Verification Standard](#) - Data Storage and Privacy Requirements
- [OWASP Mobile Top 10 2016 Category M2](#) - Insecure Data Storage
- [OWASP Top 10 2017 Category A3](#) - Sensitive Data Exposure
- [OWASP Top 10 2017 Category A6](#) - Security Misconfiguration
- [MITRE, CWE-311](#) - Missing Encryption of Sensitive Data

Available In:

sonarcloud  | sonarqube 