

































-  Secrets
-  ABAP
-  Apex
-  C
-  C++
-  CloudFormation
-  COBOL
-  C#
-  CSS
-  Flex
-  Go
-  HTML
-  Java
-  JavaScript
-  **Kotlin**
-  Kubernetes
-  Objective C
-  PHP
-  PL/I
-  PL/SQL
-  Python
-  RPG
-  Ruby
-  Scala
-  Swift
-  Terraform
-  Text
-  TypeScript
-  T-SQL
-  VB.NET
-  VB6
-  XML















Kotlin static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your KOTLIN code

- All rules 98
-  Vulnerability 10
-  Bug 17
-  Security Hotspot 15
-  Code Smell 56




Tags

Search by name...

Hard-coded credentials are security-sensitive		Security Hotspot
Cipher algorithms should be robust		Vulnerability
Encryption algorithms should be used with secure mode and padding scheme		Vulnerability
Server hostnames should be verified during SSL/TLS connections		Vulnerability
Server certificates should be verified during SSL/TLS connections		Vulnerability
Cryptographic keys should be robust		Vulnerability
Weak SSL/TLS protocols should not be used		Vulnerability
"SecureRandom" seeds should not be predictable		Vulnerability
Cipher Block Chaining IVs should be unpredictable		Vulnerability
Hashes should include an unpredictable salt		Vulnerability
Regular expressions should be syntactically valid		Bug
"runFinalizersOnExit" should not be called		Bug

Suspending functions should be main-safe

Analyze your code

-  Code Smell
-  Major
-  coroutines performance bad-practice pitfall

Generally speaking, main threads should be available to allow user-facing parts of an application to remain responsive. Long-running blocking operations can significantly reduce threads' availability and are best executed on a designated thread pool.

As a consequence, suspending functions should not block main threads and instead move any long-running blocking tasks off the main thread. This can be done conveniently by using `withContext` with an appropriate dispatcher. Alternatively, coroutine builders such as `launch` and `async` accept an optional `CoroutineContext`. An appropriate dispatcher could be `Dispatchers.IO` for long-running blocking IO operations, which can create and shutdown threads on demand.

For some blocking tasks and APIs there may already be suspending alternatives available. When available, these alternatives should be used instead of their blocking counterparts.

This rule raises an issue when the call of a long-running blocking function is detected within a suspending function without the use of an appropriate dispatcher. If non-blocking alternatives to the called function are known, they may be suggested (e.g. use `delay(...)` instead of `Thread.sleep(...)`).

Noncompliant Code Example

Executing long-running blocking IO operations on the main thread pool:

```
class workerClass {
    suspend fun worker(): String {
        val client = HttpClient.newHttpClient()
        val request = HttpRequest.newBuilder(URI("https://..."))
        return coroutineScope {
            client.send(request, HttpResponse.BodyHandlers.ofMain())
        }
    }
}
```











Using inappropriate blocking APIs:

```
suspend fun example() {
    ...
    Thread.sleep(1000) // Noncompliant
    ...
}
```

Compliant Solution

Executing long-running blocking IO operations in an appropriate thread pool using `Dispatcher.IO`:

```
class workerClass(
    private val ioDispatcher: CoroutineDispatcher = Dispatchers.IO
) {
    suspend fun worker(): String {
        val client = HttpClient.newHttpClient()
        val request = HttpRequest.newBuilder(URI("https://..."))
```

"ScheduledThreadPoolExecutor" should not have 0 core threads	 Bug
Jump statements should not occur in "finally" blocks	 Bug
Using clear-text protocols is security-sensitive	 Security Hotspot
Accessing Android external storage is security-sensitive	 Security Hotspot
Receiving intents is security-sensitive	 Security Hotspot
Broadcasting intents is security-sensitive	 Security Hotspot
Using weak hashing algorithms is security-sensitive	 Security Hotspot
Using pseudorandom number generators (PRNGs) is security-sensitive	 Security Hotspot
Empty lines should not be tested with regex MULTILINE flag	 Code Smell
Cognitive Complexity of functions should not be too high	 Code Smell

```
        return withContext(ioDispatcher) {
            client.send(request, HttpResponse.BodyHandler
        }
    }
}
```

Using appropriate non-blocking APIs:

```
suspend fun example() {
    ...
    delay(1000) // Compliant
    ...
}
```

See

- [Coroutine context and dispatchers](#)
- [Suspend functions should be safe to call from the main thread](#) (Android coroutines best practices)
- [IO CoroutineDispatcher](#)
- [Default CoroutineDispatcher](#)

Available In:

sonarlint

sonarcloud

sonarqube