

-  Secrets
-  ABAP
-  Apex
-  C
-  C++
-  CloudFormation
-  COBOL
-  C#
-  CSS
-  Flex
-  Go
-  HTML
-  Java
-  JavaScript
-  **Kotlin**
-  Kubernetes
-  Objective C
-  PHP
-  PL/I
-  PL/SQL
-  Python
-  RPG
-  Ruby
-  Scala
-  Swift
-  Terraform
-  Text
-  TypeScript
-  T-SQL
-  VB.NET
-  VB6
-  XML



Kotlin static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your KOTLIN code

All rules 98 Vulnerability 10 Bug 17 Security Hotspot 15 Code Smell 56

Tags

Search by name...



Hard-coded credentials are security-sensitive

Security Hotspot

Cipher algorithms should be robust

Vulnerability

Encryption algorithms should be used with secure mode and padding scheme

Vulnerability

Server hostnames should be verified during SSL/TLS connections

Vulnerability

Server certificates should be verified during SSL/TLS connections

Vulnerability

Cryptographic keys should be robust

Vulnerability

Weak SSL/TLS protocols should not be used

Vulnerability

"SecureRandom" seeds should not be predictable

Vulnerability

Cipher Block Chaining IVs should be unpredictable

Vulnerability

Hashes should include an unpredictable salt

Vulnerability

Regular expressions should be syntactically valid

Bug

"runFinalizersOnExit" should not be called

Bug

"=+" should not be used instead of "+="

Analyze your code

Bug Major ?

The use of operators pairs (=+, == or =!) where the reversed, single operator was meant (+=, -= or !=) will compile and run, but not produce the expected results.

This rule raises an issue when =+, ==, or =! is used without any spacing between the two operators and when there is at least one whitespace character after.

Noncompliant Code Example

```
var target = -5
val num = 3

target -= num // Noncompliant; target = -3. Is that real
target += num // Noncompliant; target = 3
```

Compliant Solution

```
var target = -5
val num = 3

target = -num // Compliant; intent to assign inverse val
target += num
```

Available In:

sonarlint | sonarcloud | sonarqube

© 2008-2022 SonarSource S.A., Switzerland. All content is copyright protected. SONAR, SONARSOURCE, SONARLINT, SONARQUBE and SONARCLOUD are trademarks of SonarSource S.A. All other trademarks and copyrights are the property of their respective owners. All rights are expressly reserved. [Privacy Policy](#)

<div>"ScheduledThreadPoolExecutor" should not have 0 core threads</div> <div> Bug</div>
<div>Jump statements should not occur in "finally" blocks</div> <div> Bug</div>
<div>Using clear-text protocols is security-sensitive</div> <div> Security Hotspot</div>
<div>Accessing Android external storage is security-sensitive</div> <div> Security Hotspot</div>
<div>Receiving intents is security-sensitive</div> <div> Security Hotspot</div>
<div>Broadcasting intents is security-sensitive</div> <div> Security Hotspot</div>
<div>Using weak hashing algorithms is security-sensitive</div> <div> Security Hotspot</div>
<div>Using pseudorandom number generators (PRNGs) is security-sensitive</div> <div> Security Hotspot</div>
<div>Empty lines should not be tested with regex MULTILINE flag</div> <div> Code Smell</div>
<div>Cognitive Complexity of functions should not be too high</div> <div> Code Smell</div>