

-  Secrets
-  ABAP
-  Apex
-  C
-  C++
-  CloudFormation
-  COBOL
-  C#
-  CSS
-  Flex
-  Go
-  HTML
-  Java
-  JavaScript
-  **Kotlin**
-  Kubernetes
-  Objective C
-  PHP
-  PL/I
-  PL/SQL
-  Python
-  RPG
-  Ruby
-  Scala
-  Swift
-  Terraform
-  Text
-  TypeScript
-  T-SQL
-  VB.NET
-  VB6
-  XML



Kotlin static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your KOTLIN code

All rules 98  Vulnerability 10  Bug 17  Security Hotspot 15  Code Smell 56

Tags ▾


Search by name...




Hard-coded credentials are security-sensitive

 Security Hotspot


Cipher algorithms should be robust

 Vulnerability


Encryption algorithms should be used with secure mode and padding scheme

 Vulnerability


Server hostnames should be verified during SSL/TLS connections

 Vulnerability


Server certificates should be verified during SSL/TLS connections

 Vulnerability

Cryptographic keys should be robust

 Vulnerability


Weak SSL/TLS protocols should not be used

 Vulnerability

"SecureRandom" seeds should not be predictable

 Vulnerability

Cipher Block Chaining IVs should be unpredictable

 Vulnerability

Hashes should include an unpredictable salt

 Vulnerability

Regular expressions should be syntactically valid

 Bug

"runFinalizersOnExit" should not be called

 Bug

Lambdas should not have too many lines

Analyze your code

 Code Smell  Major 

Lambdas are a very convenient and compact way to inject a behavior without having to create a dedicated class or method. But those lambdas should be used only if the behavior to be injected can be defined in a few lines of code, otherwise the source code can quickly become unreadable.

Available In:

sonarlint  | **sonarcloud**  | **sonarqube** 

© 2008-2022 SonarSource S.A., Switzerland. All content is copyright protected. SONAR, SONARSOURCE, SONARLINT, SONARQUBE and SONARCLOUD are trademarks of SonarSource S.A. All other trademarks and copyrights are the property of their respective owners. All rights are expressly reserved. [Privacy Policy](#)

| |
|---|
| <div>"ScheduledThreadPoolExecutor" should not have 0 core threads</div> <div> Bug</div> |
| <div>Jump statements should not occur in "finally" blocks</div> <div> Bug</div> |
| <div>Using clear-text protocols is security-sensitive</div> <div> Security Hotspot</div> |
| <div>Accessing Android external storage is security-sensitive</div> <div> Security Hotspot</div> |
| <div>Receiving intents is security-sensitive</div> <div> Security Hotspot</div> |
| <div>Broadcasting intents is security-sensitive</div> <div> Security Hotspot</div> |
| <div>Using weak hashing algorithms is security-sensitive</div> <div> Security Hotspot</div> |
| <div>Using pseudorandom number generators (PRNGs) is security-sensitive</div> <div> Security Hotspot</div> |
| <div>Empty lines should not be tested with regex MULTILINE flag</div> <div> Code Smell</div> |
| <div>Cognitive Complexity of functions should not be too high</div> <div> Code Smell</div> |
| |