

- Secrets
- ABAP
- Apex
- C
- C++
- CloudFormation
- COBOL
- COBOL
- C#
- CSS
- Flex
- Go
- HTML
- Java
- JavaScript
- Kotlin
- Kubernetes
- Objective C
- PHP
- PL/I
- PL/SQL
- Python
- RPG
- Ruby
- Scala
- Swift
- Terraform
- Text
- TypeScript
- T-SQL
- VB.NET
- VB6
- XML



Kotlin static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your KOTLIN code

All rules 98 Vulnerability 10 Bug 17 Security Hotspot 15 Code Smell 56

Tags

Search by name...

Hard-coded credentials are security-sensitive

Security Hotspot

Cipher algorithms should be robust

Vulnerability

Encryption algorithms should be used with secure mode and padding scheme

Vulnerability

Server hostnames should be verified during SSL/TLS connections

Vulnerability

Server certificates should be verified during SSL/TLS connections

Vulnerability

Cryptographic keys should be robust

Vulnerability

Weak SSL/TLS protocols should not be used

Vulnerability

"SecureRandom" seeds should not be predictable

Vulnerability

Cipher Block Chaining IVs should be unpredictable

Vulnerability

Hashes should include an unpredictable salt

Vulnerability

Regular expressions should be syntactically valid

Bug

"runFinalizersOnExit" should not be called

Bug

Using pseudorandom number generators (PRNGs) is security-sensitive

Analyze your code

Security Hotspot Critical cwe owasp

Using pseudorandom number generators (PRNGs) is security-sensitive. For example, it has led in the past to the following vulnerabilities:

- CVE-2013-6386
- CVE-2006-3419
- CVE-2008-4102

When software generates predictable values in a context requiring unpredictability, it may be possible for an attacker to guess the next value that will be generated, and use this guess to impersonate another user or access sensitive information.

Ask Yourself Whether

- the code using the generated value requires it to be unpredictable. It is the case for all encryption mechanisms or when a secret value, such as a password, is hashed.
- the function you use generates a value which can be predicted (pseudo-random).
- the generated value is used multiple times.
- an attacker can access the generated value.

There is a risk if you answered yes to any of those questions.

Recommended Secure Coding Practices

- Only use random number generators which are recommended by OWASP or any other trusted organization.
- Use the generated random values only once.
- You should not expose the generated random value. If you have to store it, make sure that the database or file is secure.

Sensitive Code Example











```
val random = Random() // Noncompliant: Random() is not a
val bytes = ByteArray(20)
random.nextBytes(bytes)
```

Compliant Solution

```
val random = SecureRandom() // Compliant
val bytes = ByteArray(20)
random.nextBytes(bytes)
```

See

- OWASP Top 10 2021 Category A2 - Cryptographic Failures
- OWASP Top 10 2017 Category A3 - Sensitive Data Exposure
- Mobile AppSec Verification Standard - Cryptography Requirements
- OWASP Mobile Top 10 2016 Category M5 - Insufficient Cryptography
- MITRE, CWE-338 - Use of Cryptographically Weak Pseudo-Random Number Generator (PRNG)
- MITRE, CWE-330 - Use of Insufficiently Random Values
- MITRE, CWE-326 - Inadequate Encryption Strength

<div>"ScheduledThreadPoolExecutor" should not have 0 core threads</div> <div> Bug</div>
<div>Jump statements should not occur in "finally" blocks</div> <div> Bug</div>
<div>Using clear-text protocols is security-sensitive</div> <div> Security Hotspot</div>
<div>Accessing Android external storage is security-sensitive</div> <div> Security Hotspot</div>
<div>Receiving intents is security-sensitive</div> <div> Security Hotspot</div>
<div>Broadcasting intents is security-sensitive</div> <div> Security Hotspot</div>
<div>Using weak hashing algorithms is security-sensitive</div> <div> Security Hotspot</div>
<div>Using pseudorandom number generators (PRNGs) is security-sensitive</div> <div> Security Hotspot</div>
<div>Empty lines should not be tested with regex MULTILINE flag</div> <div> Code Smell</div>
<div>Cognitive Complexity of functions should not be too high</div> <div> Code Smell</div>

- [MITRE, CWE-1241](#) - Use of Predictable Algorithm in Random Number Generator
- Derived from FindSecBugs rule [Predictable Pseudo Random Number Generator](#)

Available In:

© 2008-2022 SonarSource S.A., Switzerland. All content is copyright protected. SONAR, SONARSOURCE, SONARLINT, SONARQUBE and SONARCLOUD are trademarks of SonarSource S.A. All other trademarks and copyrights are the property of their respective owners. All rights are expressly reserved. [Privacy Policy](#)