

-  Secrets
-  ABAP
-  Apex
-  C
-  C++
-  CloudFormation
-  COBOL
-  C#
-  CSS
-  Flex
-  Go
-  HTML
-  Java
-  JavaScript
-  **Kotlin**
-  Kubernetes
-  Objective C
-  PHP
-  PL/I
-  PL/SQL
-  Python
-  RPG
-  Ruby
-  Scala
-  Swift
-  Terraform
-  Text
-  TypeScript
-  T-SQL
-  VB.NET
-  VB6
-  XML
















# Kotlin static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your KOTLIN code

**All rules** 98    Vulnerability 10    Bug 17    Security Hotspot 15    Code Smell 56



Tags ▾

Search by name... 

Hard-coded credentials are security-sensitive		Security Hotspot
Cipher algorithms should be robust		Vulnerability
Encryption algorithms should be used with secure mode and padding scheme		Vulnerability
Server hostnames should be verified during SSL/TLS connections		Vulnerability
Server certificates should be verified during SSL/TLS connections		Vulnerability
Cryptographic keys should be robust		Vulnerability
Weak SSL/TLS protocols should not be used		Vulnerability
"SecureRandom" seeds should not be predictable		Vulnerability
Cipher Block Chaining IVs should be unpredictable		Vulnerability
Hashes should include an unpredictable salt		Vulnerability
Regular expressions should be syntactically valid		Bug
"runFinalizersOnExit" should not be called		Bug

## "when" clauses should not have too many lines of code

Analyze your code

 Code Smell    Major ?    brain-overload

The `when` statement should be used only to clearly define some new branches in the control flow. As soon as a case clause contains too many statements this highly decreases the readability of the overall control flow statement. In such case, the content of the case clause should be extracted into a dedicated function.

### Noncompliant Code Example

With the threshold set at 5:

```
when (myVariable) {
    0 -> { // Noncompliant: 6 lines till next case
        methodCall1("");
        methodCall2("");
        methodCall3("");
        methodCall4("");
    }
    1 -> {
        ...
    }
}
```

### Compliant Solution

```
when (myVariable) {
    0 -> doSomething()
    1 -> {
        ...
    }
}
...
fun doSomething() {
    methodCall1("");
    methodCall2("");
    methodCall3("");
    methodCall4("");
}
```

Available In:

sonarlint  | sonarcloud  | sonarqube 

<div>"ScheduledThreadPoolExecutor" should not have 0 core threads</div> <div> Bug</div>
<div>Jump statements should not occur in "finally" blocks</div> <div> Bug</div>
<div>Using clear-text protocols is security-sensitive</div> <div> Security Hotspot</div>
<div>Accessing Android external storage is security-sensitive</div> <div> Security Hotspot</div>
<div>Receiving intents is security-sensitive</div> <div> Security Hotspot</div>
<div>Broadcasting intents is security-sensitive</div> <div> Security Hotspot</div>
<div>Using weak hashing algorithms is security-sensitive</div> <div> Security Hotspot</div>
<div>Using pseudorandom number generators (PRNGs) is security-sensitive</div> <div> Security Hotspot</div>
<div>Empty lines should not be tested with regex MULTILINE flag</div> <div> Code Smell</div>
<div>Cognitive Complexity of functions should not be too high</div> <div> Code Smell</div>