

-  Secrets
-  ABAP
-  Apex
-  C
-  C++
-  CloudFormation
-  COBOL
-  C#
-  CSS
-  Flex
-  Go
-  HTML
-  Java
-  JavaScript
-  **Kotlin**
-  Kubernetes
-  Objective C
-  PHP
-  PL/I
-  PL/SQL
-  Python
-  RPG
-  Ruby
-  Scala
-  Swift
-  Terraform
-  Text
-  TypeScript
-  T-SQL
-  VB.NET
-  VB6
-  XML



## Kotlin static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your KOTLIN code

**All rules** 98    Vulnerability 10    Bug 17    Security Hotspot 15    Code Smell 56


Tags

Search by name...


Hard-coded credentials are security-sensitive

 Security Hotspot

Cipher algorithms should be robust

 Vulnerability


Encryption algorithms should be used with secure mode and padding scheme

 Vulnerability


Server hostnames should be verified during SSL/TLS connections

 Vulnerability


Server certificates should be verified during SSL/TLS connections

 Vulnerability

Cryptographic keys should be robust

 Vulnerability


Weak SSL/TLS protocols should not be used

 Vulnerability

"SecureRandom" seeds should not be predictable

 Vulnerability

Cipher Block Chaining IVs should be unpredictable

 Vulnerability

Hashes should include an unpredictable salt

 Vulnerability

Regular expressions should be syntactically valid

 Bug

"runFinalizersOnExit" should not be called

 Bug

### Track uses of "FIXME" tags

Analyze your code

 Code Smell    Major ?    cwe

FIXME tags are commonly used to mark places where a bug is suspected, but which the developer wants to deal with later.

Sometimes the developer will not have the time or will simply forget to get back to that tag.

This rule is meant to track those tags and to ensure that they do not go unnoticed.

#### Noncompliant Code Example

```
// FIXME denominator value might be 0
fun divide(numerator: Int, denominator: Int): Int = nume
```

#### See

- [MITRE, CWE-546](#) - Suspicious Comment

Available In:

sonarlint  | sonarcloud  | sonarqube 

<div>"ScheduledThreadPoolExecutor" should not have 0 core threads</div> <div> Bug</div>
<div>Jump statements should not occur in "finally" blocks</div> <div> Bug</div>
<div>Using clear-text protocols is security-sensitive</div> <div> Security Hotspot</div>
<div>Accessing Android external storage is security-sensitive</div> <div> Security Hotspot</div>
<div>Receiving intents is security-sensitive</div> <div> Security Hotspot</div>
<div>Broadcasting intents is security-sensitive</div> <div> Security Hotspot</div>
<div>Using weak hashing algorithms is security-sensitive</div> <div> Security Hotspot</div>
<div>Using pseudorandom number generators (PRNGs) is security-sensitive</div> <div> Security Hotspot</div>
<div>Empty lines should not be tested with regex MULTILINE flag</div> <div> Code Smell</div>
<div>Cognitive Complexity of functions should not be too high</div> <div> Code Smell</div>