

- Secrets
- ABAP
- Apex
- C
- C++
- CloudFormation
- COBOL
- C#**
- CSS
- Flex
- Go
- HTML
- Java
- JavaScript
- Kotlin
- Objective C
- PHP
- PL/I
- PL/SQL
- Python
- RPG
- Ruby
- Scala
- Swift
- Terraform
- Text
- TypeScript
- T-SQL
- VB.NET
- VB6
- XML



## C# static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your C# code

All rules **409**

Vulnerability **34**

Bug **76**

Security Hotspot **28**

Code Smell **271**

Quick Fix **52**

Tags ▾

Search by name... 🔍

"protected" members

Code Smell

Underscores should be used to make large numbers readable

Code Smell

"ToString()" calls should not be redundant

Code Smell

"==" should not be used when "Equals" is overridden

Code Smell

An abstract class should have both abstract and concrete methods

Code Smell

Multiple variables should not be declared on the same line

Code Smell

Culture should be specified for "string" operations

Code Smell

"switch" statements should have at least 3 "case" clauses

Code Smell

break statements should not be used except for switch cases

Code Smell

String literals should not be duplicated

Code Smell

Files should contain an empty newline at the end

Code Smell

Unused "using" should be removed

Code Smell

### Generic event handlers should be used

Analyze your code

Code Smell Major ?

Since .Net Framework version 2.0 it is not necessary to declare a delegate that specifies a class derived from `System.EventArgs`. The `System.EventHandler<TEventArgs>` delegate mechanism should be used instead as it allows any class derived from `EventArgs` to be used with that handler.

This rule raises an issue when an old style delegate is used as an event handler.

#### Noncompliant Code Example

```
public class MyEventArgs : EventArgs
{
}

public delegate void MyEventHandler(object sender, MyEventArgs e)

public class EventProducer
{
    public event MyEventHandler MyEvent;

    protected virtual void OnMyEvent(MyEventArgs e)
    {
        if (MyEvent != null)
        {
            MyEvent(e);
        }
    }
}

public class EventConsumer
{
    public EventConsumer(EventProducer producer)
    {
        producer.MyEvent += HandleEvent;
    }

    private void HandleEvent(object sender, MyEventArgs e)
    {
        // Do something...
    }
}
```

#### Compliant Solution

```
public class MyEventArgs : EventArgs
{
}

public class EventProducer
```

A close curly brace should be located at the beginning of a line

 Code Smell

Tabulation characters should not be used

 Code Smell

Methods and properties should be named in PascalCase

 Code Smell

Track uses of in-source issue suppressions

 Code Smell

```
{
    public event EventHandler<MyEventArgs> MyEvent;

    protected virtual void OnMyEvent(MyEventArgs e)
    {
        if (MyEvent != null)
        {
            MyEvent(e);
        }
    }
}

public class EventConsumer
{
    public EventConsumer(EventProducer producer)
    {
        producer.MyEvent += HandleEvent;
    }

    private void HandleEvent(object sender, MyEventArgs e)
    {
        // Do something...
    }
}
```

Available In:

**sonarlint**  | **sonarcloud**  | **sonarqube** 