

- Secrets
- ABAP
- Apex
- C
- C++
- CloudFormation
- COBOL
- C#**
- CSS
- Flex
- Go
- HTML
- Java
- JavaScript
- Kotlin
- Objective C
- PHP
- PL/I
- PL/SQL
- Python
- RPG
- Ruby
- Scala
- Swift
- Terraform
- Text
- TypeScript
- T-SQL
- VB.NET
- VB6
- XML



## C# static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your C# code

All rules 409

Vulnerability 34

Bug 76

Security Hotspot 28

Code Smell 271

Quick Fix 52

Tags ▾

Search by name... 🔍

"protected" members

Code Smell

Underscores should be used to make large numbers readable

Code Smell

"ToString()" calls should not be redundant

Code Smell

"==" should not be used when "Equals" is overridden

Code Smell

An abstract class should have both abstract and concrete methods

Code Smell

Multiple variables should not be declared on the same line

Code Smell

Culture should be specified for "string" operations

Code Smell

"switch" statements should have at least 3 "case" clauses

Code Smell

break statements should not be used except for switch cases

Code Smell

String literals should not be duplicated

Code Smell

Files should contain an empty newline at the end

Code Smell

Unused "using" should be removed

Code Smell

### Pointers to unmanaged memory should not be visible

Analyze your code

Code Smell Critical ?

Pointer and unmanaged function pointer types such as IntPtr, UIntPtr, int\* etc. are used to access unmanaged memory, usually in order to use C or C++ libraries. If such a pointer is not secured by making it private, internal or readonly, it can lead to a vulnerability allowing access to arbitrary locations.

#### Noncompliant Code Example

```
using System;

namespace MyLibrary
{
    public class MyClass
    {
        public IntPtr myPointer; // Noncompliant
        protected UIntPtr myOtherPointer; // Noncompliant
    }
}
```

#### Compliant Solution

```
using System;

namespace MyLibrary
{
    public class MyClass
    {
        private IntPtr myPointer;
        protected readonly UIntPtr myOtherPointer;
    }
}
```

Available In:

sonarlint | sonarcloud | sonarqube

**A close curly brace should be located at the beginning of a line**

 Code Smell

**Tabulation characters should not be used**

 Code Smell

**Methods and properties should be named in PascalCase**

 Code Smell

**Track uses of in-source issue suppressions**

 Code Smell