Sql server, .net and c# video tutorial

Free C#, .Net and Sql server video tutorial for beginners and intermediate programmers.

Abstract Factory Design Pattern
ASP.NET Core Tutorial for Beginners
RoutePrefix attribute in Web API
Web API versioning using querystring parameter
ASP.NET Web API and SQL Server
ASP.NET Core Tutorial
Angular password and confirm password validation
SQL Serve Questions

How to get authenticated user identity name in asp.net web api

Suggested Videos
Part 24 - ASP.NET Web API login page
Part 25 - Web api bearer token example
Part 26 - ASP.NET Web API logout

In this video we will discuss **how to get authenticated user identity name in asp.net web api and display it on the web page**. This is continuation to Part 26. Please watch Part 26 from ASP.NET Web API tutorial before proceeding.

We want to display the logged in username on the web page as shown below.

ID	First Name	Last Name	Gender	Salary
1	Mark	Hastings	Male	60000
2	Steve	Pound	Male	45000
3	Ben	Hoskins	Male	70000
4	Philip	Hastings	Male	45000
5	Mary	Lambeth	Female	30000
6	Valarie	Vikings	Female	35000
7	John	Stanmore	Male	80000

Step 1 : On the Login.html page, store the username in the browser local storage. The **success()** function is called when the user is successfully logged in. The response that we get from the server includes userName property which has the userName that is

Ads by Google
Employee Portal
C# Tutorial
Ads by Google
Employee Portal
ASP Tutorial

Pragim Technologies - Best software training and placements in marathahalli, bangalore. For further details please call 09945699393.

ReactJS Tutorial
Part 1 - Video | Text | Slides
Part 2 - Video | Text | Slides

Complete Tutorials
JavaScript tutorial
Bootstrap tutorial
Angular tutorial for beginners
Angular 5 Tutorial for beginners

Important Videos
The Gift of Education
Web application for your business

used to login. We are storing the logged in username in the broswer localstorage using the key userName.

```
success: function (response) {
    localStorage.setItem("accessToken", response.access_token);
    localStorage.setItem("userName", response.userName);
    window.location.href = "Data.html";
}
```

Step 2 : On the Data.html page include the following span element just below the **"Load Employees"** button. We will use this span element to display the logged in username.

```
<span id="spanUsername" class="text-muted"></span>
```

Step 3 : On the Data.html page, in $(document).ready() function include the following line of jQuery code to retrieve and display the logged in username.

```
$('#spanUsername').text('Hello ' + localStorage.getItem('userName'));
```

How to get logged in user identity details in ASP.NET Web API controller

From the ASP.NET Web API controller use the User.Identity object to retrieve user details

User.Identity.IsAuthenticated - Returns true or false depending on whether the user is authenticated
User.Identity.AuthenticationType - Authentication Type used
User.Identity.Name - Logged in username

RequestContext.Principal.Identity.IsAuthenticated - Returns true or false depending on whether the user is authenticated
RequestContext.Principal.Identity.AuthenticationType - Authentication Type used
RequestContext.Principal.Identity.Name - Logged in username

Instead of using User.Identity, we can also use RequestContext.Principal.Identity

To see what the respective properties return, set a break point in the Get() method of Employees controller and run the application in debug mode. Navigate to Login page and login. On the Data.html page click "Load Employees" button. When the execution pauses at the breakpoint, open Immediate Window and type the above properties one by one and press enter. To open immediate window, in Visual Studio select Debug - Windows - Immediate.

```
[Authorize]
public class EmployeesController : Api
{
    public IEnumerable<Employee> Get()
    { ≤12,603ms elapsed
        using (EmployeeDBEntities enti
        {
            return entities.Employees.
        }
```

```
Immediate Window
User.Identity.IsAuthenticated
true
User.Identity.AuthenticationType
"Bearer"
User.Identity.Name
"test1@test.com"

RequestContext.Principal.Identity.IsAuthenticated
true
RequestContext.Principal.Identity.AuthenticationType
"Bearer"
RequestContext.Principal.Identity.Name
"test1@test.com"
```

Now let us see what these properties return if we are not logged in.
1. Add a new **Empty Web API 2 Controller** to the **EmployeeService** project. Name it TestController.

2. Copy and paste the following code in TestController.

```
using System.Web.Http;
namespace EmployeeService.Controllers
```


How to become .NET developer

Resources available to help you

Dot Net Video Tutorials

ASP.NET Core Tutorial

ASP.NET Core Razor Pages Tutorial

Angular 6 Tutorial

Angular CRUD Tutorial

Angular CLI Tutorial

Angular 2 Tutorial

Design Patterns

SOLID Principles

ASP.NET Web API

Bootstrap

AngularJS Tutorial

jQuery Tutorial

JavaScript with ASP.NET Tutorial

JavaScript Tutorial

Charts Tutorial

LINQ

LINQ to SQL

LINQ to XML

Entity Framework

WCF

ASP.NET Web Services

Dot Net Basics

C#

SQL Server

ADO.NET

ASP.NET

GridView

ASP.NET MVC

Visual Studio Tips and Tricks

Dot Net Interview Questions

Slides

Entity Framework

WCF

ASP.NET Web Services

Dot Net Basics

C#

SQL Server

ADO.NET

ASP.NET

GridView

```
{
    public class TestController : ApiController
    {
        public string Get()
        {
            return "Hello from TestController";
        }
    }
}
```

3. Set a breakpoint on the Get() method in TestController. Run the application in Debug mode and navigate to /api/Test. When the execution pauses at the break point, open Immediate Window and type the above properties one by one and press enter.

```
public class TestController : ApiController
{
    public string Get()
    {
        return "Hello from TestController";
    }
```

```
Immediate Window
User.Identity.IsAuthenticated
false
User.Identity.AuthenticationType
null
User.Identity.Name
null
```

Since we are not logged in, notice IsAuthenticated property returns false. Since we are not authenticated AuthenticationType and Name properties return NULL.

3 comments:

raj December 15, 2016 at 7:28 AM

hi my guru venkat after this series please explain some SharePoint concepts thank you....

Reply

Dinesh Kudale August 27, 2019 at 5:07 AM

☆☆Nice information.☆☆

I have observed that if we use 'response.username' in following line using intelligence window, then it will not work. It needs to provide 'response.userName'. I think that it is case-sensitive.

localStorage.setItem("userName", response.userName);

Reply

saleh September 12, 2019 at 11:11 PM

Hello, I have problem that i need trouble shooting. i made the same exact api and it works. Now the problem i am facing is i made another project in the solution and copied the login, register and data pages to it and added the right path to the url in the ajax call. now i can register successfully from the client application but when i try to login i get error of same cross origin policy even tho i have enabled cors in WEBAPI.CONFIG. Please can someone troubleshoot this error for me or tell me what i am doing wrong?

Reply

ASP.NET MVC

Visual Studio Tips and Tricks

Java Video Tutorials

Part 1 : Video | Text | Slides

Part 2 : Video | Text | Slides

Part 3 : Video | Text | Slides

Interview Questions

C#

SQL Server

Written Test

Enter your comment...

Comment as: Google Accou ▼

Publish Preview

If you like this website, please share with your friends on facebook and Google+ and recommend us on google using the g+1 button on the top right hand corner.

Links to this post

Create a Link

Newer Post Home Older Post

Subscribe to: Post Comments (Atom)

Powered by Blogger.