

# Django

Documentation

## Writing your first Django app, part 3

This tutorial begins where [Tutorial 2](#) left off. We're continuing the Web-poll application and will focus on creating the public interface – “views.”

### Overview

A view is a “type” of Web page in your Django application that generally serves a specific function and has a specific template. For example, in a blog application, you might have the following views:

- Blog homepage – displays the latest few entries.
- Entry “detail” page – permalink page for a single entry.
- Year-based archive page – displays all months with entries in the given year.
- Month-based archive page – displays all days with entries in the given month.
- Day-based archive page – displays all entries in the given day.
- Comment action – handles posting comments to a given entry.

In our poll application, we'll have the following four views:

- Question “index” page – displays the latest few questions.
- Question “detail” page – displays a question text, with no results but with a form to vote.
- Question “results” page – displays results for a particular question.
- Vote action – handles voting for a particular choice in a particular question.

In Django, web pages and other content are delivered by views. Each view is represented by a simple Python function (or method, in the case of class-based views). Django will choose a view by examining the URL that's requested (to be precise, the part of the URL after the domain name).

Now in your time on the web you may have come across such beauties as “ME2/Sites/dirmod.asp?sid=&type=gen&mod=Core+Pages&gid=A6CD4967199A42D9B65B1B”. You will be pleased to know that Django allows us much more elegant *URL patterns* than that.

A URL pattern is simply the general form of a URL - for example: `/newsarchive/<year>/<month>/`.

To get from a URL to a view, Django uses what are known as ‘URLconfs’. A URLconf maps URL patterns (described as regular expressions) to views.

This tutorial provides basic instruction in the use of URLconfs, and you can refer to [django.core.urlresolvers](#) for more information.

### Writing more views

Now let's add a few more views to `polls/views.py`. These views are slightly different, because they take an argument:

`polls/views.py`

```
def detail(request, question_id):
    return HttpResponse("You're looking at question %s." % question_id)

def results(request, question_id):
    response = "You're looking at the results of question %s."
    return HttpResponse(response % question_id)

def vote(request, question_id):
    return HttpResponse("You're voting on question %s." % question_id)
```

Wire these new views into the `polls.urls` module by adding the following `url()` calls:

`polls/urls.py`

Language: en

```
from django.conf.urls import url

from . import views

urlpatterns = [
    # ex: /polls/
    url(r'^$', views.index, name='index'),
    # ex: /polls/5/
    url(r'^(?P<question_id>[0-9]+)/$', views.detail, name='detail'),
    # ex: /polls/5/results/
    url(r'^(?P<question_id>[0-9]+)/results/$', views.results, name='results'),
    # ex: /polls/5/vote/
    url(r'^(?P<question_id>[0-9]+)/vote/$', views.vote, name='vote'),
]
```

Take a look in your browser, at `/polls/34/`. It'll run the `detail()` method and display whatever ID you provide in the URL. Try `/polls/34/results/` and `/polls/34/vote/` too – these will display the placeholder results and voting pages.

When somebody requests a page from your website – say, `/polls/34/`, Django will load the `mysite.urls` Python module because it's pointed to by the `ROOT_URLCONF` setting. It finds the variable named `urlpatterns` and traverses the regular expressions in order. After finding the match at `^polls/`, it strips off the matching text (`"polls/"`) and sends the remaining text – `"34/"` – to the `polls.urls` URLconf for further processing. There it matches `^(?P<question_id>[0-9]+)/$`, resulting in a call to the `detail()` view like so:

```
detail(request=<HttpRequest object>, question_id='34')
```

The `question_id='34'` part comes from `(?P<question_id>[0-9]+)`. Using parentheses around a pattern “captures” the text matched by that pattern and sends it as an argument to the view function; `?P<question_id>` defines the name that will be used to identify the matched pattern; and `[0-9]+` is a regular expression to match a sequence of digits (i.e., a number).

Because the URL patterns are regular expressions, there really is no limit on what you can do with them. And there's no need to add URL cruft such as `.html` – unless you want to, in which case you can do something like this:

```
url(r'^polls/latest\.html$', views.index),
```

But, don't do that. It's silly.

## Write views that actually do something

Each view is responsible for doing one of two things: returning an `HttpResponse` object containing the content for the requested page, or raising an exception such as `Http404`. The rest is up to you.

Your view can read records from a database, or not. It can use a template system such as Django's – or a third-party Python template system – or not. It can generate a PDF file, output XML, create a ZIP file on the fly, anything you want, using whatever Python libraries you want.

All Django wants is that `HttpResponse`. Or an exception.

Because it's convenient, let's use Django's own database API, which we covered in [Tutorial 2](#). Here's one stab at a new `index()` view, which displays the latest 5 poll questions in the system, separated by commas, according to publication date:

polls/views.py

```
from django.http import HttpResponse

from .models import Question

def index(request):
    latest_question_list = Question.objects.order_by('-pub_date')[:5]
    output = ', '.join([q.question_text for q in latest_question_list])
    return HttpResponse(output)

# Leave the rest of the views (detail, results, vote) unchanged
```

Language: en

First, create a directory called `templates` in your `polls` directory. Django will look for templates in there.

## Writing your first Django app, part 3 | Django d...

<https://docs.djangoproject.com/en/1.9/intro/tutor...>

Your project's `TEMPLATES` setting describes how Django will load and render templates. The default settings file configures a `DjangoTemplates` backend whose `APP_DIRS` option is set to `True`. By convention `DjangoTemplates` looks for a "templates" subdirectory in each of the `INSTALLED_APPS`.

Within the `templates` directory you have just created, create another directory called `polls`, and within that create a file called `index.html`. In other words, your template should be at `polls/templates/polls/index.html`. Because of how the `app_directories` template loader works as described above, you can refer to this template within Django simply as `polls/index.html`.



### Template namespacing

Now we *might* be able to get away with putting our templates directly in `polls/templates` (rather than creating another `polls` subdirectory), but it would actually be a bad idea. Django will choose the first template it finds whose name matches, and if you had a template with the same name in a *different* application, Django would be unable to distinguish between them. We need to be able to point Django at the right one, and the easiest way to ensure this is by *namespacing* them. That is, by putting those templates inside *another* directory named for the application itself.

Put the following code in that template:

`polls/templates/polls/index.html`

```
{% if latest_question_list %}
<ul>
  {% for question in latest_question_list %}
    <li><a href="/polls/{{ question.id }}">{{ question.question_text }}</a></li>
  {% endfor %}
</ul>
{% else %}
  <p>No polls are available.</p>
{% endif %}
```

Now let's update our `index` view in `polls/views.py` to use the template:

`polls/views.py`

```
from django.http import HttpResponseRedirect
from django.template import loader

from .models import Question

def index(request):
    latest_question_list = Question.objects.order_by('-pub_date')[:5]
    template = loader.get_template('polls/index.html')
    context = {
        'latest_question_list': latest_question_list,
    }
    return HttpResponseRedirect(template.render(context, request))
```

That code loads the template called `polls/index.html` and passes it a context. The context is a dictionary mapping template variable names to Python objects.

Load the page by pointing your browser at `/polls/`, and you should see a bulleted-list containing the "What's up" question from Tutorial 2. The link points to the question's detail page.

## A shortcut: `render()`

It's a very common idiom to load a template, fill a context and return an `HttpResponse` object with the result of the rendered template. Django provides a shortcut. Here's the full `index()` view, rewritten:

`polls/views.py`

```
from django.shortcuts import render

from .models import Question

def index(request):
    latest_question_list = Question.objects.order_by('-pub_date')[:5]
    context = {'latest_question_list': latest_question_list}
    return render(request, 'polls/index.html', context)
```

Language: en

The `render()` function takes the request object as its first argument, a template name as its second argument and a dictionary as its optional third argument. It returns an `HttpResponse` object of the given template rendered with the given context.

## Raising a 404 error

Now, let's tackle the question detail view – the page that displays the question text for a given poll. Here's the view:

polls/views.py

```
from django.http import Http404
from django.shortcuts import render

from .models import Question
# ...
def detail(request, question_id):
    try:
        question = Question.objects.get(pk=question_id)
    except Question.DoesNotExist:
        raise Http404("Question does not exist")
    return render(request, 'polls/detail.html', {'question': question})
```

The new concept here: The view raises the `Http404` exception if a question with the requested ID doesn't exist.

We'll discuss what you could put in that `polls/detail.html` template a bit later, but if you'd like to quickly get the above example working, a file containing just:

polls/templates/polls/detail.html

```
{{ question }}
```

will get you started for now.

## A shortcut: `get_object_or_404()`

It's a very common idiom to use `get()` and raise `Http404` if the object doesn't exist. Django provides a shortcut. Here's the `detail()` view, rewritten:

polls/views.py

```
from django.shortcuts import get_object_or_404, render

from .models import Question
# ...
def detail(request, question_id):
    question = get_object_or_404(Question, pk=question_id)
    return render(request, 'polls/detail.html', {'question': question})
```

The `get_object_or_404()` function takes a Django model as its first argument and an arbitrary number of keyword arguments, which it passes to the `get()` function of the model's manager. It raises `Http404` if the object doesn't exist.



### Philosophy

Why do we use a helper function `get_object_or_404()` instead of automatically catching the `ObjectDoesNotExist` exceptions at a higher level, or having the model API raise `Http404` instead of `ObjectDoesNotExist`?

Because that would couple the model layer to the view layer. One of the foremost design goals of Django is to maintain loose coupling. Some controlled coupling is introduced in the `django.shortcuts` module.

There's also a `get_list_or_404()` function, which works just as `get_object_or_404()` – except using `filter()` instead of `get()`. It raises `Http404` if the list is empty.

Language: en

Back to the **detail()** view for our poll application. Given the context variable **question**, here's what the **polls/detail.html** template might look like:

polls/templates/polls/detail.html

```
<h1>{{ question.question_text }}</h1>
<ul>
{% for choice in question.choice_set.all %}
  <li>{{ choice.choice_text }}</li>
{% endfor %}
</ul>
```

The template system uses dot-lookup syntax to access variable attributes. In the example of **{{ question.question\_text }}**, first Django does a dictionary lookup on the object **question**. Failing that, it tries an attribute lookup – which works, in this case. If attribute lookup had failed, it would've tried a list-index lookup.

Method-calling happens in the **{% for %}** loop: **question.choice\_set.all** is interpreted as the Python code **question.choice\_set.all()**, which returns an iterable of **Choice** objects and is suitable for use in the **{% for %}** tag.

See the [template guide](#) for more about templates.

## Removing hardcoded URLs in templates

Remember, when we wrote the link to a question in the **polls/index.html** template, the link was partially hardcoded like this:

```
<li><a href="/polls/{{ question.id }}/">{{ question.question_text }}</a></li>
```

The problem with this hardcoded, tightly-coupled approach is that it becomes challenging to change URLs on projects with a lot of templates. However, since you defined the **name** argument in the **url()** functions in the **polls.urls** module, you can remove a reliance on specific URL paths defined in your url configurations by using the **{% url %}** template tag:

```
<li><a href="{% url 'detail' question.id %}">{{ question.question_text }}</a></li>
```

The way this works is by looking up the URL definition as specified in the **polls.urls** module. You can see exactly where the URL name of 'detail' is defined below:

```
...
# the 'name' value as called by the {% url %} template tag
url(r'^(?P<question_id>[0-9]+)/$', views.detail, name='detail'),
...
```

If you want to change the URL of the polls detail view to something else, perhaps to something like **polls/specifics/12/** instead of doing it in the template (or templates) you would change it in **polls/urls.py**:

```
...
# added the word 'specifics'
url(r'^specifics/(?P<question_id>[0-9]+)/$', views.detail, name='detail'),
...
```

## Namespacing URL names

polls/urls.py

```
from django.conf.urls import url

from . import views

app_name = 'polls'
urlpatterns = [
    url(r'^$', views.index, name='index'),
    url(r'^(?P<question_id>[0-9]+)/$', views.detail, name='detail'),
    url(r'^(?P<question_id>[0-9]+)/results/$', views.results, name='results'),
    url(r'^(?P<question_id>[0-9]+)/vote/$', views.vote, name='vote'),
]
```

Now change your `polls/index.html` template from:

polls/templates/polls/index.html

```
<li><a href="{% url 'detail' question.id %}">{{ question.question_text }}</a></li>
```

to point at the namespaced detail view:

polls/templates/polls/index.html

```
<li><a href="{% url 'polls:detail' question.id %}">{{ question.question_text }}</a></li>
```

When you're comfortable with writing views, read [part 4 of this tutorial](#) to learn about simple form processing and generic views.

## Learn More

- About Django
- Getting Started with Django
- Team Organization
- Django Software Foundation
- Code of Conduct
- Diversity statement

## Get Involved

- Join a Group
- 6 of 7  
Contribute to Django
- Submit a Bug

---

## Follow Us

[GitHub](#)

[Twitter](#)

[News RSS](#)

[Django Users Mailing List](#)

© 2005-2016 [Django Software Foundation](#) and individual contributors. Django is a [registered trademark](#) of the Django Software Foundation.

Language: **en**