

# CLOSE ENCOUNTERS

with  
PHP



Level 5

# Validation With Respect

---

Object-oriented Validation



# A Closer Look at the Validator Class

validation.php

```
<?php
use Respect\Validation\Validator;

$v = new Validator;
var_dump($v);

function validate_date($date_string)
{
    if ($time = strtotime($date_string)) {
        return date('F jS Y', $date_string);
    } else {
        return $date_string . ' does not look valid.';
    }
}
```




# A Closer Look at the Validator Class

validation.php

*new is how we make an object*

*\$v is now an object of the Validator  
type*

*Validator is the  
name of a class*




```
$v = new Validator;  
var_dump($v);
```



# What Is a Class?

A class is a way to group our code and provide a blueprint for a single-purpose object.




*Methods are functions inside of a class*



# Creating an Object

With the new keyword, we create an object that is a single instance of the Validator class.





# How Can We Use Validator Here?


validation.php

```
<?php
use Respect\Validation\Validator;

$v = new Validator;
var_dump($v);

function validate_date($date_string)
{
    if ($time = strtotime($date_string)) {
        return date('F jS Y', $date_string);
    } else {
        return $date_string . ' does not look valid.';
    }
}
```

*We need to replace all of the code inside the  
validate\_date function with something  
from the Validator class*






# Using Respect/Validation for the Date

validation.php

```
<?php
use Respect\Validation\Validator;

function validate_date($date_string)
{
    if(Validator::notEmpty()->validate($date_string)) {
        return date('F jS Y', $date_string);
    }
}
```

*This validate call will return true or false, so it is okay to use it as a conditional*



*There is a lot going on here! Let's take a closer look.*



# Inspecting the Validator Class

---

This line of code means, “If the \$date\_string is not empty, return true; otherwise, return false.”

*validate is a method that tests our data against the rules — in this case, notEmpty*



```
Validator::notEmpty()->validate($date_string);
```

The diagram consists of two white arrows. One arrow originates from the word 'notEmpty' in the code line below and points diagonally upwards and to the right towards the word 'validate' in the explanatory text above. The second arrow originates from the word 'validate' in the code line and points diagonally upwards and to the left towards the word 'validate' in the explanatory text above.

*notEmpty is a method (function) in the Validator class, which validator calls a rule*



# Validation of a Date

---

We have validated that our date string is not empty, but how do we know it is a date?

*First, we are evaluating that \$date\_string is not empty!*



```
Validator::notEmpty()->validate($date_string);
```

```
Validator::date()->validate($date_string);
```



*date() verifies that the string entered is in a valid date format*



# Chaining Validation Methods


---

With Respect/Validation, we can chain rules together for simplicity and clarity.

*Now we're validating that we have some data and that it looks like a date in one line*

```
Validator::date()->notEmpty()->validate($date_string);
```

*We can chain the validation rules together  
by using an object operator ->*



*This is great, but can we do more?*



# Creating Custom Validators

---

Clarifying our code is easy when we create a custom validator variable.


*We can assign a Validator class with rules to a variable*



```
$date_validator = Validator::date()->notEmpty();
```

```
$date_validator->validate($date_string);
```

*Now we only have to run the validate method on the \$date\_validator variable we created!*





# Validation With Our Custom Validator

validation.php

```
<?php  
use Respect\Validation\Validator;
```

*Create our validator for the date*

```
function validate_date($date_string)  
{  
    $date_validator = Validator::date()->notEmpty();
```

```
    if ($date_validator->validate($date_string)) {  
        $date_time = strtotime($date_string);  
        return date('F jS Y', $date_time);
```

*Use a conditional to test our validator*

```
    }  
}
```



# Requiring a Date Format

We can set a format inside our date validator call, using any format from the PHP date function.


validation.php

```
<?php
use Respect\Validation\Validator;

function validate_date($date_string)
{
    $date_validator = Validator::date('d-m-Y')->notEmpty();

    if ($date_validator->validate($date_string)) {
        $date_time = strtotime($date_string);
        return date('F jS Y', $date_time);
    }
}
```

*The format d-m-Y requires that the date be entered like this: 30-12-2017*





# Returning a Message on Error


validation.php

```
<?php
use Respect\Validation\Validator;

function validate_date($date_string)
{
    $date_validator = Validator::date('d-m-Y')->notEmpty();

    if ($date_validator->validate($date_string)) {
        $date_time = strtotime($date_string);
        return date('F jS Y', $date_time);
    } else {
        return 'The date must be in a DD-MM-YYYY format.';
    }
}
```

*If the validator fails, return a message about the format!*





# Validator Class Review

---

What we have gone over in this section

- How to create an object
- Using our **Validator** class and methods
- The **validate** method with the **notEmpty** rule
- Chaining rules with the object operator
- Storing custom validators in a variable
- Using custom validators in a conditional



# CLOSE ENCOUNTERS

with  
PHP