





































-  Secrets
-  ABAP
-  Apex
-  AzureResourceManager
-  C
-  C#
-  C++
-  CloudFormation
-  COBOL
-  CSS
-  Dart
-  Docker
-  Flex
-  Go
-  HTML
-  Java
-  JavaScript
-  JCL
-  Kotlin
-  Kubernetes
-  Objective C
-  PHP
-  PL/I
-  PL/SQL
-  Python
-  RPG
-  Ruby
-  Scala
-  Swift
-  Terraform
-  Text
-  TypeScript
-  T-SQL
-  VB.NET
-  VB6
-  XML



Docker static code analysis


Unique rules to find Vulnerabilities, Security Hotspots, and Code Smells in your DOCKER code

- All rules 44
-  Vulnerability 4
-  Bug 4
-  Security Hotspot 15
-  Code Smell 21

Tags ▼

Impact ▼

Clean code attribute ▼

Search by name... 

 Code Smell

Instructions should be upper case

 Code Smell

Allowing non-root users to modify resources copied to an image is security-sensitive

 Security Hotspot

Automatically installing recommended packages is security-sensitive

 Security Hotspot

Running containers as a privileged user is security-sensitive

 Security Hotspot

Delivering code in production with debug features activated is security-sensitive

 Security Hotspot

Use ADD instruction to retrieve remote resources

 Code Smell

Arguments in long RUN instructions should be sorted

 Code Smell

Track uses of "TODO" tags

 Code Smell


Descriptive labels are mandatory

 Code Smell

Use digest to pin versions of base images

 Code Smell

Dockerfile parsing failure

 Code Smell

Allowing non-root users to modify resources copied to an image is security-sensitive

Analyze your code

Responsibility - Trustworthy

Security ▼

 Security Hotspot  Minor   dockerfile cwe

Ownership or write permissions for a file or directory copied to the Docker image have been assigned to a user other than root.

Write permissions enable malicious actors, who have a foothold on the container, to tamper with the resource and thus potentially manipulate the container's expected behavior. Manipulating files could disrupt services or aid in escalating privileges inside the container.

This also breaches the container immutability principle as it facilitates container changes during its life. Immutability, a container best practice, allows for a more reliable and reproducible behavior of Docker containers.

If a user is given ownership on a file but no write permissions, the user can still modify it by using his ownership to change the file permissions first. This is why both ownership and write permissions should be avoided.

Ask Yourself Whether

- A non-root user owns the resource.
- A non-root user has been granted write permissions for the resource.

There is a risk if you answered yes to any of these questions.

Recommended Secure Coding Practices

- Use `--chmod` to change the permissions so that only root users can write to files.
- Use `--chown` to change the file/directory owner to a root user.
- Be mindful of the container immutability principle.

Sensitive Code Example

```
FROM example

RUN useradd exampleuser
# Sensitive
COPY --chown=exampleuser:exampleuser src.py dst.py
```

Compliant Solution

```
FROM example

COPY --chown=root:root --chmod=755 src.py dst.py
```

See

- [Dockerfile reference](#) - ADD instruction
- [Dockerfile reference](#) - COPY instruction
- CWE - CWE-732 - [Incorrect Permission Assignment for Critical Resource](#)
- [Google Cloud, Immutability](#) - Best practices for operating containers

Available In:

sonarlint  | **sonarcloud**  | **sonarqube** 

