

- Secrets
- ABAP
- Apex
- C**
- C++
- CloudFormation
- COBOL
- C#
- CSS
- Flex
- Go
- HTML
- Java
- JavaScript
- Kotlin
- Kubernetes
- Objective C
- PHP
- PL/I
- PL/SQL
- Python
- RPG
- Ruby
- Scala
- Swift
- Terraform
- Text
- TypeScript
- T-SQL
- VB.NET
- VB6
- XML



C static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your C code

All rules **311**

Vulnerability **13**

Bug **74**

Security Hotspot **18**

Code Smell **206**

Quick Fix **14**

Tags

Search by name...



"memset" should not be used to delete sensitive data

Vulnerability

POSIX functions should not be called with arguments that trigger buffer overflows

Vulnerability

XML parsers should not be vulnerable to XXE attacks

Vulnerability

Function-like macros should not be invoked without all of their arguments

Bug

The address of an automatic object should not be assigned to another object that may persist after the first object has ceased to exist

Bug

"pthread_mutex_t" should be unlocked in the reverse order they were locked

Bug

"pthread_mutex_t" should be properly initialized and destroyed

Bug

"pthread_mutex_t" should not be consecutively locked or unlocked twice

Bug

Functions with "noreturn" attribute should not return

Bug

"memcpy" should only be called with pointers to trivially copyable types with no padding

Bug

Lines starting with "#" should contain valid preprocessing directives

Analyze your code

Bug Major based-on-misra preprocessor

Preprocessing directives (lines that start with #) can be used to conditionally include or exclude code from compilation. Malformed preprocessing directives could lead to the exclusion or inclusion of more code than was intended. Therefore all preprocessing directives should be syntactically meaningful.

Noncompliant Code Example

```
#define AAA 2
...
int foo(void)
{
    int x = 0;
    ...

    #ifndef AAA
        x = 1;
    #else /* Noncompliant */
        x = AAA;
    #endif

    ...
    return x;
}
```

Compliant Solution

```
#define AAA 2
...
int foo(void)
{
    int x = 0;
    ...

    #ifndef AAA
        x = 1;
    #else
        x = AAA;
    #endif

    ...
    return x;
}
```

See

- MISRA C:2004, 19.16 - Preprocessing directives shall be syntactically meaningful even when excluded by preprocessor.
- MISRA C++:2008, 16-0-8 - If the # token appears as the first token on a line, then it shall be immediately followed by a preprocessing token.

Stack allocated memory and non-owned memory should not be freed

 Bug

Closed resources should not be accessed

 Bug

Dynamically allocated memory should be released

 Bug

Freed memory should not be used

- MISRA C:2012, 20.13 - A line whose first token is # shall be a valid preprocessing directive

Available In:

sonarlint  | sonarcloud  | sonarqube  Developer Edition

© 2008-2022 SonarSource S.A., Switzerland. All content is copyright protected. SONAR, SONARSOURCE, SONARLINT, SONARQUBE and SONARCLOUD are trademarks of SonarSource S.A. All other trademarks and copyrights are the property of their respective owners. All rights are expressly reserved.
[Privacy Policy](#)