

- Secrets
- ABAP
- Apex
- C**
- C++
- CloudFormation
- COBOL
- C#
- CSS
- Flex
- Go
- HTML
- Java
- JavaScript
- Kotlin
- Kubernetes
- Objective C
- PHP
- PL/I
- PL/SQL
- Python
- RPG
- Ruby
- Scala
- Swift
- Terraform
- Text
- TypeScript
- T-SQL
- VB.NET
- VB6
- XML



C static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your C code

All rules **311**

Vulnerability **13**

Bug **74**

Security Hotspot **18**

Code Smell **206**

Quick Fix **14**

Tags

Search by name...



"memset" should not be used to delete sensitive data

Vulnerability

POSIX functions should not be called with arguments that trigger buffer overflows

Vulnerability

XML parsers should not be vulnerable to XXE attacks

Vulnerability

Function-like macros should not be invoked without all of their arguments

Bug

The address of an automatic object should not be assigned to another object that may persist after the first object has ceased to exist

Bug

"pthread_mutex_t" should be unlocked in the reverse order they were locked

Bug

"pthread_mutex_t" should be properly initialized and destroyed

Bug

"pthread_mutex_t" should not be consecutively locked or unlocked twice

Bug

Functions with "noreturn" attribute should not return

Bug

"memcpy" should only be called with pointers to trivially copyable types with no padding

Bug

Signed and unsigned types should not be mixed in expressions

Analyze your code

Code Smell Minor based-on-misra cert

Some signed to unsigned conversions may lead to implementation-defined behavior. This behavior may not be consistent with developer expectations.

If you need to mix signed and unsigned types, you should make your intent explicit by using explicit casts and avoiding implicit casts.

This rule will detect implicit conversions that change the signedness.

Noncompliant Code Example

```
void f(int a) {
    unsigned int b = a; // Noncompliant
    int c = (a > 0) ? a : b; // Noncompliant

    if (a > b) { // Noncompliant
        // ...
    }
}
```

Compliant Solution

```
void f(int a) {
    unsigned int b = static_cast<unsigned int>(a); // Compliant
}
```

See

- MISRA C++ 2008, 5-0-4
- CERT, INT31-C.** - Ensure that integer conversions do not result in lost or misinterpreted data

Available In:

sonarlint

sonarcloud

sonarqube

Developer Edition

Stack allocated memory and non-owned memory should not be freed

 Bug

Closed resources should not be accessed

 Bug

Dynamically allocated memory should be released

 Bug

Freed memory should not be used