

- Secrets
- ABAP
- Apex
- C
- C++
- CloudFormation
- COBOL
- C#
- CSS
- Flex
- Go
- HTML
- Java
- JavaScript
- Kotlin
- Kubernetes
- Objective C
- PHP
- PL/I
- PL/SQL
- Python
- RPG
- Ruby
- Scala
- Swift
- Terraform
- Text
- TypeScript
- T-SQL
- VB.NET
- VB6
- XML



C++ static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your C++ code

All rules 578

Vulnerability 13

Bug 111

Security Hotspot 18

Code Smell 436

Quick Fix 68

Tags

Search by name...

"memset" should not be used to delete sensitive data

Vulnerability

POSIX functions should not be called with arguments that trigger buffer overflows

Vulnerability

XML parsers should not be vulnerable to XXE attacks

Vulnerability

Function-like macros should not be invoked without all of their arguments

Bug

The address of an automatic object should not be assigned to another object that may persist after the first object has ceased to exist

Bug

Assigning to an optional should directly target the optional

Bug

Result of the standard remove algorithms should not be ignored

Bug

"std::scoped_lock" should be created with constructor arguments

Bug

Objects should not be sliced

Bug

Immediately dangling references should not be created

Bug

"pthread_mutex_t" should be unlocked in the reverse order they were locked

Bug

"pthread_mutex_t" should be properly initialized and destroyed

Bug

"pthread_mutex_t" should not be consecutively locked or unlocked twice

Methods should not have identical implementations

Analyze your code

Code Smell Major ? confusing duplicate suspicious

When two methods have the same implementation, either it was a mistake - something else was intended - or the duplication was intentional, but may be confusing to maintainers. In the latter case, one implementation should invoke the other.

This rule raises an exception when two methods implemented inside the class definition share the same implementation.

Noncompliant Code Example

```
class Point {
    int x;
    int y;

    // .....

public:
    void setX(int v) {
        if (v >= 0 && v < MAX_X) {
            x = v;
            return;
        }
        error();
    }

    void setY(int v) { // Noncompliant
        if (v >= 0 && v < MAX_X) {
            x = v;
            return;
        }
        error();
    }
};
```

Compliant Solution

```
class Point {
    int x;
    int y;

    // .....

public:
    void setX(int v) {
        if (v >= 0 && v < MAX_X) {
            x = v;
            return;
        }
        error();
    }

    void setY(int v) {
        if (v >= 0 && v < MAX_X) {
            y = v;
            return;
        }
        error();
    }
};
```

 Bug
"std::move" and "std::forward" should not be confused  Bug
A call to "wait()" on a "std::condition_variable" should have a condition  Bug
A pointer to a virtual base class shall only be cast to a pointer to a derived class by means of dynamic_cast  Bug
Functions with "noreturn" attribute should not return  Bug
RAII objects should not be temporary  Bug
"memcmp" should only be called with pointers to trivially copyable types with no padding  Bug
"memcpy", "memmove", and "memset" should only be called with pointers to trivially copyable types  Bug
"std::auto_ptr" should not be used  Bug
Destructors should be "noexcept"  Bug

```
};
```

Exceptions

Empty methods, methods with the same name (overload) and methods with only one statement are ignored.

Available In:

sonarlint

sonarcloud

sonarqube Developer Edition