

































-  Secrets
-  ABAP
-  Apex
-  C
-  **C++**
-  CloudFormation
-  COBOL
-  C#
-  CSS
-  Flex
-  Go
-  HTML
-  Java
-  JavaScript
-  Kotlin
-  Kubernetes
-  Objective C
-  PHP
-  PL/I
-  PL/SQL
-  Python
-  RPG
-  Ruby
-  Scala
-  Swift
-  Terraform
-  Text
-  TypeScript
-  T-SQL
-  VB.NET
-  VB6
-  XML



# C++ static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your C++ code

All rules 578

 Vulnerability 13

 Bug 111

 Security Hotspot 18

 Code Smell 436

 Quick Fix 68

Tags

Search by name...



"memset" should not be used to delete sensitive data

 Vulnerability

POSIX functions should not be called with arguments that trigger buffer overflows

 Vulnerability

XML parsers should not be vulnerable to XXE attacks

 Vulnerability

Function-like macros should not be invoked without all of their arguments

 Bug

The address of an automatic object should not be assigned to another object that may persist after the first object has ceased to exist

 Bug

Assigning to an optional should directly target the optional

 Bug

Result of the standard remove algorithms should not be ignored

 Bug

"std::scoped\_lock" should be created with constructor arguments

 Bug

Objects should not be sliced

 Bug

Immediately dangling references should not be created

 Bug

"pthread\_mutex\_t" should be unlocked in the reverse order they were locked

 Bug

"pthread\_mutex\_t" should be properly initialized and destroyed

 Bug

"pthread\_mutex\_t" should not be consecutively locked or unlocked twice

## Function exit paths should have appropriate return values

Analyze your code

 Bug  Critical  cwe based-on-misra cert

Every call to a function with a non-void return type is expected to return some value. Including a return path in a non-void function that does not explicitly return a value results in undefined behavior.

Conversely, every call to a function with a void return type is expected to not return any value. Returning a value from a void function probably indicates a programming error.

### Noncompliant Code Example

```
int my_func (int a)
{
    if (a > 100)
    {
        return; // Noncompliant
    }

    if (a > 80)
    {
        throw new Exception(); // Compliant
    }

    // Noncompliant
}
```

### Compliant Solution

```
int my_func (int a)
{
    if (a > 100)
    {
        return 12;
    }

    if (a > 80)
    {
        throw new Exception();
    }

    return a;
}
```

### Exceptions

This rule doesn't raise an exception when the `return` statement for a void function, is itself a void expression.

```
void foo() {
    // Do stuff ...
}

void bar() {
    return foo();
}
```

Furthermore, the issue is not raised for the coroutines, introduced in `{{cpp20}}`, that

 Bug
<b>"std::move" and "std::forward" should not be confused</b>  Bug
<b>A call to "wait()" on a "std::condition_variable" should have a condition</b>  Bug
<b>A pointer to a virtual base class shall only be cast to a pointer to a derived class by means of dynamic_cast</b>  Bug
<b>Functions with "noreturn" attribute should not return</b>  Bug
<b>RAII objects should not be temporary</b>  Bug
<b>"memcpy" should only be called with pointers to trivially copyable types with no padding</b>  Bug
<b>"memcpy", "memmove", and "memset" should only be called with pointers to trivially copyable types</b>  Bug
<b>"std::auto_ptr" should not be used</b>  Bug
<b>Destructors should be "noexcept"</b>  Bug

always declare coroutine object as a return type, but returned object is implicitly created by compiler. The coroutine body itself may never contains return statement (the use of it is disallowed), and `co_return` is used for coroutine that returns a value (define `return_value` in promise-type).

See

- [{rule:cpp:S6369}](#) - Coroutine should have `co_return` on each execution path or provide `return_void`
- MISRA C:2004, 16.8 - All exit paths from a function with non-void return type shall have an explicit return statement with an expression
- MISRA C++:2008, 8-4-3 - All exit paths from a function with non-void return type shall have an explicit return statement with an expression
- MISRA C:2012, 17.4 - All exit paths from a function with non-void return type shall have an explicit return statement with an expression
- [MITRE, CWE-394](#) - Unexpected Status Code or Return Value
- [CERT, MSC37-C](#) - Ensure that control never reaches the end of a non-void function
- [CERT, MSC52-CPP](#) - Value-returning functions must return a value from all exit paths
- [CERT, MSC53-CPP](#) - Do not return from a function declared `[[noreturn]]`

Available In:

 |  |  