

- Secrets
- ABAP
- Apex
- C
- C++
- CloudFormation
- COBOL
- C#
- CSS
- Flex
- Go
- HTML
- Java
- JavaScript
- Kotlin
- Kubernetes
- Objective C
- PHP
- PL/I
- PL/SQL
- Python
- RPG
- Ruby
- Scala
- Swift
- Terraform
- Text
- TypeScript
- T-SQL
- VB.NET
- VB6
- XML



C++ static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your C++ code

All rules 578

Vulnerability 13

Bug 111

Security Hotspot 18

Code Smell 436

Quick Fix 68

Tags

Search by name...

"memset" should not be used to delete sensitive data

Vulnerability

POSIX functions should not be called with arguments that trigger buffer overflows

Vulnerability

XML parsers should not be vulnerable to XXE attacks

Vulnerability

Function-like macros should not be invoked without all of their arguments

Bug

The address of an automatic object should not be assigned to another object that may persist after the first object has ceased to exist

Bug

Assigning to an optional should directly target the optional

Bug

Result of the standard remove algorithms should not be ignored

Bug

"std::scoped_lock" should be created with constructor arguments

Bug

Objects should not be sliced

Bug

Immediately dangling references should not be created

Bug

"pthread_mutex_t" should be unlocked in the reverse order they were locked

Bug

"pthread_mutex_t" should be properly initialized and destroyed

Bug

"pthread_mutex_t" should not be consecutively locked or unlocked twice

"std::move" should only be added when necessary

Analyze your code

Code Smell

Major

cppcoreguidelines performance bad-practice since-c++11 clumsy

Usually, when copying an object, the source object is unchanged, which means that all resources owned by the source objects have to be duplicated during the copy operation. In the case that the source object will no longer be used, this duplication is not efficient. Since C++11, a mechanism named move semantic has been added to detect such cases and replace the expensive copy by a much cheaper move operation that will steal resources.

The cornerstone of move semantic is the ability to detect during a "copy" if the source object will be reused or not. There are three situations:

- The object is a temporary object, with no name, and if it can't be named, it can't be used
- The object is used in some specific places, such as a return statement
- The user explicitly promises to the compiler that he won't care for the current value of the object any longer. He does so by using the specific cast operation named `std::move`.

If the user write `std::move` in one situation that is already handled by the first two cases, it has two drawbacks:

- It is clumsy, useless code, which make understanding the code more complex
- In some cases, it can decrease performances, because this can deactivate another optimization of the compiler, named copy elision.

When copy elision occurs, the object is neither copied nor moved (even if the copy/move constructors have side effects), in fact, the two objects are collapsed into only one memory location. When copy elision occurs is compiler-dependent, but is mandatory in the following cases:

- in a return statement if the returned object is a prvalue of the same class type as the function return type
- in the initialization of a variable if the initializer expression is a prvalue of the same class type as the variable type

This rule reports an issue when the use of `std::move` prevents the copy elision from happening.

Noncompliant Code Example

```
class A {};  
A getA();  
  
A f() {  
    A a = std::move(getA()); // Noncompliant, prevents copy eli  
    vector<A> v;  
    v.push_back(std::move(getA())); // Noncompliant  
    return std::move(a); // Noncompliant, prevents copy elision  
}
```

Compliant Solution

```
class A {};  
void test(A a);  
  
A f() {  
    A a = getA(); // Compliant  
    vector<A> v;  
    v.push_back(getA()); // Compliant  
}
```

 Bug
"std::move" and "std::forward" should not be confused  Bug
A call to "wait()" on a "std::condition_variable" should have a condition  Bug
A pointer to a virtual base class shall only be cast to a pointer to a derived class by means of dynamic_cast  Bug
Functions with "noreturn" attribute should not return  Bug
RAII objects should not be temporary  Bug
"memcmp" should only be called with pointers to trivially copyable types with no padding  Bug
"memcpy", "memmove", and "memset" should only be called with pointers to trivially copyable types  Bug
"std::auto_ptr" should not be used  Bug
Destructors should be "noexcept"  Bug

```
    return a; // Compliant
}
```

See

- [C++ Core Guidelines I.4](#): Don't return std::move(local)

Available In:

sonarlint

sonarcloud

sonarqube Developer Edition