

- Secrets
- ABAP
- Apex
- C**
- C++
- CloudFormation
- COBOL
- C#
- CSS
- Flex
- Go
- HTML
- Java
- JavaScript
- Kotlin
- Kubernetes
- Objective C
- PHP
- PL/I
- PL/SQL
- Python
- RPG
- Ruby
- Scala
- Swift
- Terraform
- Text
- TypeScript
- T-SQL
- VB.NET
- VB6
- XML



## C static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your C code

All rules 311

Vulnerability 13

Bug 74

Security Hotspot 18

Code Smell 206

Quick Fix 14

Tags

Search by name...



"memset" should not be used to delete sensitive data

Vulnerability

POSIX functions should not be called with arguments that trigger buffer overflows

Vulnerability

XML parsers should not be vulnerable to XXE attacks

Vulnerability

Function-like macros should not be invoked without all of their arguments

Bug

The address of an automatic object should not be assigned to another object that may persist after the first object has ceased to exist

Bug

"pthread\_mutex\_t" should be unlocked in the reverse order they were locked

Bug

"pthread\_mutex\_t" should be properly initialized and destroyed

Bug

"pthread\_mutex\_t" should not be consecutively locked or unlocked twice

Bug

Functions with "noreturn" attribute should not return

Bug

"memcpy" should only be called with pointers to trivially copyable types with no padding

Bug

### Using "strcpy" or "wcscpy" is security-sensitive

Analyze your code

Security Hotspot Major cwe owasp cert

In C, a string is just a buffer of characters, normally using the `null` character as a sentinel for the end of the string. This means that the developer has to be aware of low-level details such as buffer sizes or having an extra character to store the final `null` character. Doing that correctly and consistently is notoriously difficult and any error can lead to a security vulnerability, for instance, giving access to sensitive data or allowing arbitrary code execution.

The function `char *strcpy(char * restrict dest, const char * restrict src);` copies characters from `src` to `dest`. The `wcscpy` does the same for wide characters and should be used with the same guidelines.

Note: the functions `strncpy` and `wcscncpy` might look like attractive safe replacements for `strcpy` and `wcscpy`, but they have their own set of issues (see [rule:cpp:S5816](#)), and you should probably prefer another more adapted alternative.

#### Ask Yourself Whether

- There is a possibility that either the source or the destination pointer is `null`
- There is a possibility that the source string is not correctly `null`-terminated, or that its length (including the final `null` character) can be larger than the size of the destination buffer.
- There is an overlap between source and destination

There is a risk if you answered yes to any of those questions.

#### Recommended Secure Coding Practices

- C11 provides, in its annex K, the `strncpy_s` and the `wcscpy_s` that were designed as safer alternatives to `strcpy` and `wcscpy`. It's not recommended to use them in all circumstances, because they introduce a runtime overhead and require to write more code for error handling, but they perform checks that will limit the consequences of calling the function with bad arguments.
- Even if your compiler does not exactly support annex K, you probably have access to similar functions, for example, `strncpy` in FreeBSD
- If you are writing C++ code, using `std::string` to manipulate strings is much simpler and less error-prone

#### Sensitive Code Example

```
int f(char *src) {
    char dest[256];
    strcpy(dest, src); // Sensitive: might overflow
    return doSomethingWith(dest);
}
```

#### Compliant Solution

```
int f(char *src) {
    char *dest = malloc(strlen(src) + 1); // For the final 0
    strcpy(dest, src); // Compliant: we made sure the buffer is
```

Stack allocated memory and non-owned memory should not be freed



Closed resources should not be accessed



Dynamically allocated memory should be released



Freed memory should not be used

```
int r= doSomethingWith(dest);
free(dest);
return r;
}
```

#### See

- [OWASP Top 10 2021 Category A6](#) - Vulnerable and Outdated Components
- [OWASP Top 10 2017 Category A9](#) - Using Components with Known Vulnerabilities
- [MITRE, CWE-120](#) - Buffer Copy without Checking Size of Input ('Classic Buffer Overflow')
- [CERT, STR07-C](#) - Use the bounds-checking interfaces for string manipulation

Available In:

sonardcloud  | sonarqube  Developer Edition