


































-  Secrets
-  ABAP
-  Apex
-  C
-  C++
-  CloudFormation
-  COBOL
-  C#
-  CSS
-  Flex
-  Go
-  HTML
-  Java
-  JavaScript
-  Kotlin
-  Kubernetes
-  Objective C
-  PHP
-  PL/I
-  PL/SQL
-  Python
-  RPG
-  Ruby
-  Scala
-  Swift
-  Terraform
-  Text
-  TypeScript
-  T-SQL
-  VB.NET
-  VB6
-  XML





## C++ static code analysis


Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your C++ code


All rules 578

 Vulnerability 13

 Bug 111

 Security Hotspot 18

 Code Smell 436

 Quick Fix 68

Tags

Search by name...



"memset" should not be used to delete sensitive data

 Vulnerability

POSIX functions should not be called with arguments that trigger buffer overflows

 Vulnerability

XML parsers should not be vulnerable to XXE attacks

 Vulnerability

Function-like macros should not be invoked without all of their arguments

 Bug

The address of an automatic object should not be assigned to another object that may persist after the first object has ceased to exist

 Bug

Assigning to an optional should directly target the optional

 Bug

Result of the standard remove algorithms should not be ignored

 Bug

"std::scoped\_lock" should be created with constructor arguments

 Bug

Objects should not be sliced

 Bug

Immediately dangling references should not be created

 Bug

"pthread\_mutex\_t" should be unlocked in the reverse order they were locked

 Bug

"pthread\_mutex\_t" should be properly initialized and destroyed

 Bug

"pthread\_mutex\_t" should not be consecutively locked or unlocked twice

"operator=" should check for assignment to self

Analyze your code

 Bug  Minor 

In some cases, we might end up with some code that assigns an object to itself. Therefore, when writing an `operator=`, we must ensure that this use case works correctly, which may require special care. One technique to achieve this is to explicitly check at the start of `operator=` if we are assigning to ourselves, and in that case, just do nothing.

It is usually a bad idea to perform this check for optimization purposes only, because it optimizes for a very rare case while adding an extra check for the more common case. But when it is necessary for correctness, it should be added.

This rule raises an issue when an `operator=` does not check for assignment to self before proceeding with the assignment.

### Noncompliant Code Example

```
class MyClass
{
    private:
        int someVal;
        char* pData;

    MyClass& operator=(const MyClass& rhs)
    {
        this->someVal = rhs.someVal;           // useless oper
        delete [] pData;                       // data is lost
        pData = new char[strlen(rhs.pData) +1]; // null pointer
        strcpy(pData, rhs.pData);

        return (*this);
    }
};
```











### Compliant Solution

```
class MyClass
{
    private:
        int someVal;
        char* pData;

    MyClass& operator=(const MyClass& rhs)
    {
        if (this != &rhs)
        {
            this->someVal = rhs.someVal;
            delete [] pData;
            pData = new char[strlen(rhs.pData) +1];
            strcpy(pData, rhs.pData);
        }
        return (*this);
    }
};
```

Or much better:

```
class MyClass
{
```

 Bug
<b>"std::move" and "std::forward" should not be confused</b>  Bug
<b>A call to "wait()" on a "std::condition_variable" should have a condition</b>  Bug
<b>A pointer to a virtual base class shall only be cast to a pointer to a derived class by means of dynamic_cast</b>  Bug
<b>Functions with "noreturn" attribute should not return</b>  Bug
<b>RAII objects should not be temporary</b>  Bug
<b>"memcmp" should only be called with pointers to trivially copyable types with no padding</b>  Bug
<b>"memcpy", "memmove", and "memset" should only be called with pointers to trivially copyable types</b>  Bug
<b>"std::auto_ptr" should not be used</b>  Bug
<b>Destructors should be "noexcept"</b>  Bug

```
private:
    int someVal;
    std::string data; // No need for manual operator=
};
```

**Deprecated**

This rule is deprecated, and will eventually be removed.

Available In:

sonarlint

sonarcloud

sonarqube Developer Edition