

- Secrets
- ABAP
- Apex
- C
- C++
- CloudFormation
- COBOL
- C#
- CSS
- Flex
- Go
- HTML
- Java
- JavaScript
- Kotlin
- Kubernetes
- Objective C
- PHP
- PL/I
- PL/SQL
- Python
- RPG
- Ruby
- Scala
- Swift
- Terraform
- Text
- TypeScript
- T-SQL
- VB.NET
- VB6
- XML



C++ static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your C++ code

All rules 578

Vulnerability 13

Bug 111

Security Hotspot 18

Code Smell 436

Quick Fix 68

Tags

Search by name...

"memset" should not be used to delete sensitive data

Vulnerability

POSIX functions should not be called with arguments that trigger buffer overflows

Vulnerability

XML parsers should not be vulnerable to XXE attacks

Vulnerability

Function-like macros should not be invoked without all of their arguments

Bug

The address of an automatic object should not be assigned to another object that may persist after the first object has ceased to exist

Bug

Assigning to an optional should directly target the optional

Bug

Result of the standard remove algorithms should not be ignored

Bug

"std::scoped_lock" should be created with constructor arguments

Bug

Objects should not be sliced

Bug

Immediately dangling references should not be created

Bug

"pthread_mutex_t" should be unlocked in the reverse order they were locked

Bug

"pthread_mutex_t" should be properly initialized and destroyed

Bug

"pthread_mutex_t" should not be consecutively locked or unlocked twice

The return value of "std::move" should be used in a function

Analyze your code

Code Smell Critical suspicious

std::move is not really moving anything, but tells the compiler that a value can be considered as no longer useful. It is technically a cast to a RValue, and allows overload resolution to select the version of a function that will perform destructive operations on that value (therefore actually moving from it).

```
void f(A const &a); // Just reading from a
void f(A&& a); // I can perform destructive operations on a,

void g() {
    A a;
    f(a); // First overload is selected
    f(std::move(a)); // Second overload is selected
}
```

As a consequence, calling std::move on an object and then not directly using the returned value as a function argument is not the typical pattern, and may be indicative of a bug. Note that calling a member function on the result of std::move is considered as passing it to a function (as the hidden this parameter), as well as using it as an operand (the called function is the overloaded operator) or initializing an object with it (the called function is the constructor).

Noncompliant Code Example

```
void sink(A &&a) {
    std::move(a); // Noncompliant, and not doing anything
}

void f(A &&a) {
    // May or may not move the member name, depending on its ty
    // for instance, is `a` supposed to be in a moved-from stat
    g(std::move(a).name); // Noncompliant
}
```

Compliant Solution

```
void f(A &&a) {
    g(std::move(a.name)); // Compliant, `a.name` is in moved-fr
```

Exceptions

Even if calling a built-in operator or initializing data of built-in type are not function calls, for consistency with cases that involve user-defined types, this rule will not report in those cases:

```
struct Data {A a; int b; };

Data add(Data &&d1, Data &&d2) {
    return Data{
        std::move(d1.a) + std::move(d2.a), // Compliant, operator
        std::move(d1.b) + std::move(d2.b) // Compliant by except
    };
}
```

Available In:

| |
|---|
|  Bug |
| "std::move" and "std::forward" should not be confused  Bug |
| A call to "wait()" on a "std::condition_variable" should have a condition  Bug |
| A pointer to a virtual base class shall only be cast to a pointer to a derived class by means of dynamic_cast  Bug |
| Functions with "noreturn" attribute should not return  Bug |
| RAII objects should not be temporary  Bug |
| "memcmp" should only be called with pointers to trivially copyable types with no padding  Bug |
| "memcpy", "memmove", and "memset" should only be called with pointers to trivially copyable types  Bug |
| "std::auto_ptr" should not be used  Bug |
| Destructors should be "noexcept"  Bug |