

# C static code analysis: "memset" should not be used to delete sensitive data

2-3 minutes

---

The compiler is generally allowed to remove code that does not have any effect, according to the abstract machine of the C language. This means that if you have a buffer that contains sensitive data (for instance passwords), calling `memset` on the buffer before releasing the memory will probably be optimized away.

The function [memset\\_s](#) behaves similarly to `memset`, but the main difference is that it cannot be optimized away, the memory will be overwritten in all cases. You should always use this function to scrub security-sensitive data.

This rule raises an issue when a call to `memset` is followed by the destruction of the buffer.

Note that `memset_s` is defined in annex K of C11, so to have access to it, you need a standard library that supports it (this can be tested with the macro `__STDC_LIB_EXT1__`), and you need to enable it by defining the macro

`__STDC_WANT_LIB_EXT1__` before including `<string.h>`.

Other platform specific functions can perform the same operation, for instance [SecureZeroMemory](#) (Windows) or [explicit\\_bzero](#) (FreeBSD)

## Noncompliant Code Example

```
void f(char *password, size_t bufferSize) {  
    char localToken[256];  
    init(localToken, password);  
    memset(password, ' ', strlen(password)); // Noncompliant,  
password is about to be freed  
    memset(localToken, ' ', strlen(localToken)); // Noncompliant,  
localToken is about to go out of scope  
    free(password);  
}
```

## Compliant Solution

```
void f(char *password, size_t bufferSize) {  
    char localToken[256];  
    init(localToken, password);  
    memset_s(password, bufferSize, ' ', strlen(password));  
    memset_s(localToken, sizeof(localToken), ' ',  
strlen(localToken));  
    free(password);  
}
```

## See

- [OWASP Top 10 2017 Category A3](#) - Sensitive Data Exposure
- [MITRE, CWE-14](#) - Compiler Removal of Code to Clear Buffers