

- Secrets
- ABAP
- Apex
- C**
- C++
- CloudFormation
- COBOL
- C#
- CSS
- Flex
- Go
- HTML
- Java
- JavaScript
- Kotlin
- Kubernetes
- Objective C
- PHP
- PL/I
- PL/SQL
- Python
- RPG
- Ruby
- Scala
- Swift
- Terraform
- Text
- TypeScript
- T-SQL
- VB.NET
- VB6
- XML



C static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your C code

All rules **311**

Vulnerability **13**

Bug **74**

Security Hotspot **18**

Code Smell **206**

Quick Fix **14**

Tags

Search by name...



"memset" should not be used to delete sensitive data

Vulnerability

POSIX functions should not be called with arguments that trigger buffer overflows

Vulnerability

XML parsers should not be vulnerable to XXE attacks

Vulnerability

Function-like macros should not be invoked without all of their arguments

Bug

The address of an automatic object should not be assigned to another object that may persist after the first object has ceased to exist

Bug

"pthread_mutex_t" should be unlocked in the reverse order they were locked

Bug

"pthread_mutex_t" should be properly initialized and destroyed

Bug

"pthread_mutex_t" should not be consecutively locked or unlocked twice

Bug

Functions with "noreturn" attribute should not return

Bug

"memcpy" should only be called with pointers to trivially copyable types with no padding

Bug

"enum" values should not be used as operands to built-in operators other than [], =, ==, !=, unary &, and the relational operators <, <=, >, >=

Analyze your code

Code Smell Major based-on-misra suspicious

Enumerations are used to represent symbolic values, or sometimes bit fields. They are not supposed to be used in arithmetic contexts.

Additionally, even though comparing them with integer numbers can make sense (for instance, to test if an enum lies with a certain range), comparing them with floating point numbers does not (and is deprecated since C++20).

There are other restrictions related to the use of enums, see for instance {rule:cpp:S2753}.

Noncompliant Code Example

```
enum { COLOUR_0, COLOUR_1, COLOUR_2, COLOUR_COUNT } colour;
if ( COLOUR_0 == colour ) { ... }
if ( ( COLOUR_0 + COLOUR_1 ) == colour ) { ... } // Noncompliant
if ( colour < COLOUR_COUNT ) { ... }
if ( colour > 3.14 ) { ... } // Noncompliant, comparison with
```

See

- MISRA C++:2008, 4-5-2 - Expressions with type enum shall not be used as operands to builtin operators other than the subscript operator [], the assignment operator =, the equality operators == and !=, the unary & operator, and the relational operators <, <=, >, >=

Available in:

sonarlint sonarcloud sonarqube Developer Edition

© 2008-2022 SonarSource S.A., Switzerland. All content is copyright protected. SONAR, SONARSOURCE, SONARLINT, SONARQUBE and SONARCLOUD are trademarks of SonarSource S.A. All other trademarks and copyrights are the property of their respective owners. All rights are expressly reserved.

[Privacy Policy](#)

Stack allocated memory and non-owned memory should not be freed

 Bug

Closed resources should not be accessed

 Bug

Dynamically allocated memory should be released

 Bug

Freed memory should not be used