


-  Secrets
-  ABAP
-  Apex
-  C
-  **C++**
-  CloudFormation
-  COBOL
-  C#
-  CSS
-  Flex
-  Go
-  HTML
-  Java
-  JavaScript
-  Kotlin
-  Kubernetes
-  Objective C
-  PHP
-  PL/I
-  PL/SQL
-  Python
-  RPG
-  Ruby
-  Scala
-  Swift
-  Terraform
-  Text
-  TypeScript
-  T-SQL
-  VB.NET
-  VB6
-  XML



## C++ static code analysis


Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your C++ code


All rules 578

 Vulnerability 13

 Bug 111

 Security Hotspot 18

 Code Smell 436


 Quick Fix 68

Tags


Search by name...




"memset" should not be used to delete sensitive data

 Vulnerability

POSIX functions should not be called with arguments that trigger buffer overflows

 Vulnerability

XML parsers should not be vulnerable to XXE attacks

 Vulnerability

Function-like macros should not be invoked without all of their arguments

 Bug

The address of an automatic object should not be assigned to another object that may persist after the first object has ceased to exist

 Bug

Assigning to an optional should directly target the optional

 Bug

Result of the standard remove algorithms should not be ignored

 Bug

"std::scoped\_lock" should be created with constructor arguments

 Bug

Objects should not be sliced

 Bug

Immediately dangling references should not be created

 Bug

"pthread\_mutex\_t" should be unlocked in the reverse order they were locked

 Bug




"pthread\_mutex\_t" should be properly initialized and destroyed

 Bug

"pthread\_mutex\_t" should not be consecutively locked or unlocked twice

All "if ... else if" constructs shall be terminated with an "else" clause

Analyze your code

 Code Smell  Minor  misra-c++2008

This rule is a strict implementation of a MISRA (Motor Industry Software Reliability Association) rule. MISRA defines best practices for developing safety-critical software. You can learn more about this rule in the MISRA documents referenced below.

If you are not concerned with MISRA compliance or with safety-critical software, you might consider using rule ElselfWithoutElse instead ; it targets the same kind of issue for general-purpose software.

### See

- MISRA C++2008, 6-4-2

Available In:

 |  |  Developer Edition

© 2008-2022 SonarSource S.A., Switzerland. All content is copyright protected. SONAR, SONARSOURCE, SONARLINT, SONARQUBE and SONARCLOUD are trademarks of SonarSource S.A. All other trademarks and copyrights are the property of their respective owners. All rights are expressly reserved.  
[Privacy Policy](#)

 Bug
<b>"std::move" and "std::forward" should not be confused</b>  Bug
<b>A call to "wait()" on a "std::condition_variable" should have a condition</b>  Bug
<b>A pointer to a virtual base class shall only be cast to a pointer to a derived class by means of dynamic_cast</b>  Bug
<b>Functions with "noreturn" attribute should not return</b>  Bug
<b>RAII objects should not be temporary</b>  Bug
<b>"memcmp" should only be called with pointers to trivially copyable types with no padding</b>  Bug
<b>"memcpy", "memmove", and "memset" should only be called with pointers to trivially copyable types</b>  Bug
<b>"std::auto_ptr" should not be used</b>  Bug
<b>Destructors should be "noexcept"</b>  Bug