






-  Secrets
-  ABAP
-  Apex
-  C
-  **C++**
-  CloudFormation
-  COBOL
-  C#
-  CSS
-  Flex
-  Go
-  HTML
-  Java
-  JavaScript
-  Kotlin
-  Kubernetes
-  Objective C
-  PHP
-  PL/I
-  PL/SQL
-  Python
-  RPG
-  Ruby
-  Scala
-  Swift
-  Terraform
-  Text
-  TypeScript
-  T-SQL
-  VB.NET
-  VB6
-  XML















C++ static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your C++ code

- All rules 578
-  Vulnerability 13
-  Bug 111
-  Security Hotspot 18
-  Code Smell 436
-  Quick Fix 68




Tags ▾

Search by name... 

"memset" should not be used to delete sensitive data		Vulnerability
POSIX functions should not be called with arguments that trigger buffer overflows		Vulnerability
XML parsers should not be vulnerable to XXE attacks		Vulnerability
Function-like macros should not be invoked without all of their arguments		Bug
The address of an automatic object should not be assigned to another object that may persist after the first object has ceased to exist		Bug
Assigning to an optional should directly target the optional		Bug
Result of the standard remove algorithms should not be ignored		Bug
"std::scoped_lock" should be created with constructor arguments		Bug
Objects should not be sliced		Bug
Immediately dangling references should not be created		Bug
"pthread_mutex_t" should be unlocked in the reverse order they were locked		Bug
"pthread_mutex_t" should be properly initialized and destroyed		Bug
"pthread_mutex_t" should not be consecutively locked or unlocked twice		

Nested blocks of code should not be left empty

Analyze your code

 Code Smell  Major  suspicious

Most of the time a block of code is empty when a piece of code is really missing. So such empty block must be either filled or removed.

Noncompliant Code Example

```
void foo()
{
    int x;
    if (x == 42)
        /* Noncompliant - the following nested block is empty */
        {
        }
    else
    {
        printf("x != 42");
    }
}

void bar()
/* Compliant - functions are not nested blocks */
{
}
```

Compliant Solution

```
void foo()
{
    int x;
    if (x != 42)
        /* Compliant */
        {
            printf("x != 42");
        }
}

/* ... */
```

Exceptions

When a block contains a comment, this block is not considered to be empty.

Available In:

   Developer Edition

 Bug
"std::move" and "std::forward" should not be confused  Bug
A call to "wait()" on a "std::condition_variable" should have a condition  Bug
A pointer to a virtual base class shall only be cast to a pointer to a derived class by means of dynamic_cast  Bug
Functions with "noreturn" attribute should not return  Bug
RAII objects should not be temporary  Bug
"memcmp" should only be called with pointers to trivially copyable types with no padding  Bug
"memcpy", "memmove", and "memset" should only be called with pointers to trivially copyable types  Bug
"std::auto_ptr" should not be used  Bug
Destructors should be "noexcept"  Bug