

- Secrets
- ABAP
- Apex
- C
- C++
- CloudFormation
- COBOL
- C#
- CSS
- Flex
- Go
- HTML
- Java
- JavaScript
- Kotlin
- Kubernetes
- Objective C
- PHP
- PL/I
- PL/SQL
- Python
- RPG
- Ruby
- Scala
- Swift
- Terraform
- Text
- TypeScript
- T-SQL
- VB.NET
- VB6
- XML



C++ static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your C++ code

All rules578

Vulnerability13

Bug111

Security Hotspot18

Code Smell436

Quick Fix68

Tags

Search by name...

"memset" should not be used to delete sensitive data

Vulnerability

POSIX functions should not be called with arguments that trigger buffer overflows

Vulnerability

XML parsers should not be vulnerable to XXE attacks

Vulnerability

Function-like macros should not be invoked without all of their arguments

Bug

The address of an automatic object should not be assigned to another object that may persist after the first object has ceased to exist

Bug

Assigning to an optional should directly target the optional

Bug

Result of the standard remove algorithms should not be ignored

Bug

"std::scoped_lock" should be created with constructor arguments

Bug

Objects should not be sliced

Bug

Immediately dangling references should not be created

Bug

"pthread_mutex_t" should be unlocked in the reverse order they were locked

Bug

"pthread_mutex_t" should be properly initialized and destroyed

Bug

"pthread_mutex_t" should not be consecutively locked or unlocked twice

Limited dependence should be placed on operator precedence

Analyze your code

Code SmellMajorcwe cert

The rules of operator precedence are complicated and can lead to errors. For this reason, parentheses should be used for clarification in complex statements. However, this does not mean that parentheses should be gratuitously added around every operation.

Parentheses are not needed:

- with a unary operator, except when ! is used as left operand in comparison expressions
- when all the operators in an expression are the same
- when only a single operator is involved
- around the right-hand side of an assignment operator unless the right-hand side itself contains an assignment

Parentheses are needed:

- in the condition of a ternary operator if it uses operators
- when overloaded shift operator << or >> is used in an expression with comparison operators

Noncompliant Code Example

```
x = a + b;
x = a * -1;
x = a + b + c;
x = f ( a + b, c );

x = a == b ? a : a - b; // Noncompliant
x = a + b - c + d; // Noncompliant
x = a * 3 + c + d; // Noncompliant

if (a = f(b,c) == true) { ... } // Noncompliant; == evaluated
x - b ? a : c; // Noncompliant; "-" evaluated first
s << 5 == 1; // Noncompliant; "<<" evaluated first
```

Compliant Solution

```
x = a + b;
x = a * -1;
x = a + b + c;
x = f ( a + b, c );

x = ( a == b ) ? a : ( a - b );
x = ( a + b ) - ( c + d );
x = ( a * 3 ) + c + d;

if ( (a = f(b,c)) == true) { ... }
(x - b) ? a : c; // Compliant
(s << 5) == 1; // Compliant
```

See

- MISRA C:2004, 12.1 - Limited dependence should be placed on C's operator precedence rules in expressions
- MISRA C:2004, 12.2 - The value of an expression shall be the same under any order of evaluation that the standard permits.
- MISRA C:2004, 12.5 - The operands of a logical && or || shall be primary-expressions.

 Bug
"std::move" and "std::forward" should not be confused  Bug
A call to "wait()" on a "std::condition_variable" should have a condition  Bug
A pointer to a virtual base class shall only be cast to a pointer to a derived class by means of dynamic_cast  Bug
Functions with "noreturn" attribute should not return  Bug
RAII objects should not be temporary  Bug
"memcmp" should only be called with pointers to trivially copyable types with no padding  Bug
"memcpy", "memmove", and "memset" should only be called with pointers to trivially copyable types  Bug
"std::auto_ptr" should not be used  Bug
Destructors should be "noexcept"  Bug

- MISRA C++:2008, 5-0-1 - The value of an expression shall be the same under any order of evaluation that the standard permits.
- MISRA C++:2008, 5-0-2 - Limited dependence should be placed on C++ operator precedence rules in expressions
- MISRA C++:2008, 5-2-1 - Each operand of a logical && or || shall be a postfix-expression.
- MISRA C:2012, 12.1 - The precedence of operators within expressions should be made explicit
- [CERT, EXP00-C](#) - Use parentheses for precedence of operation
- [CERT, EXP53-J](#) - Use parentheses for precedence of operation
- [MITRE, CWE-783](#) - Operator Precedence Logic Error

Available In:

sonarlint

sonarcloud

sonarqube Developer Edition