

- Secrets
- ABAP
- Apex
- C**
- C++
- CloudFormation
- COBOL
- C#
- CSS
- Flex
- Go
- HTML
- Java
- JavaScript
- Kotlin
- Kubernetes
- Objective C
- PHP
- PL/I
- PL/SQL
- Python
- RPG
- Ruby
- Scala
- Swift
- Terraform
- Text
- TypeScript
- T-SQL
- VB.NET
- VB6
- XML



## C static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your C code

All rules 311

Vulnerability 13

Bug 74

Security Hotspot 18

Code Smell 206

Quick Fix 14

Tags

Search by name...

"memset" should not be used to delete sensitive data

Vulnerability

POSIX functions should not be called with arguments that trigger buffer overflows

Vulnerability

XML parsers should not be vulnerable to XXE attacks

Vulnerability

Function-like macros should not be invoked without all of their arguments

Bug

The address of an automatic object should not be assigned to another object that may persist after the first object has ceased to exist

Bug

"pthread\_mutex\_t" should be unlocked in the reverse order they were locked

Bug

"pthread\_mutex\_t" should be properly initialized and destroyed

Bug

"pthread\_mutex\_t" should not be consecutively locked or unlocked twice

Bug

Functions with "noreturn" attribute should not return

Bug

"memcpy" should only be called with pointers to trivially copyable types with no padding

Bug

"#pragma warning (default: ...)" should not be used

Analyze your code

Code Smell Minor ? cert

Using "#pragma warning (default: ...)" resets the warning in question to its default settings, which may not be what the compiler was initially invoked with. Typically, this usage is seen after a warning is turned off, in preparation for code that is known to cause warnings. Instead, the warning's current state should be saved, and then restored after the code in question.

### Noncompliant Code Example

```
#pragma warning (disable: TheWarning)
#include problem_code.h
#pragma warning (default: TheWarning)
```

### Compliant Solution

```
#pragma warning (push)
#include problem_code.h
#pragma warning (pop)
```

### See

- [CERT, MSC00-C.](#) - Compile cleanly at high warning levels

Available In:

sonarlint sonarcloud sonarqube Developer Edition

© 2008-2022 SonarSource S.A., Switzerland. All content is copyright protected. SONAR, SONARSOURCE, SONARLINT, SONARQUBE and SONARCLOUD are trademarks of SonarSource S.A. All other trademarks and copyrights are the property of their respective owners. All rights are expressly reserved.  
[Privacy Policy](#)

Stack allocated memory and non-owned memory should not be freed

 Bug

Closed resources should not be accessed

 Bug

Dynamically allocated memory should be released

 Bug

Freed memory should not be used