

- Secrets
- ABAP
- Apex
- C
- C++
- CloudFormation
- COBOL
- COBOL
- C#
- CSS
- Flex
- Go
- HTML
- Java
- JavaScript
- Kotlin
- Kubernetes
- Objective C
- PHP
- PL/I
- PL/SQL
- Python
- RPG
- Ruby
- Scala
- Swift
- Terraform
- Text
- TypeScript
- T-SQL
- VB.NET
- VB6
- XML



Flex static code analysis

Unique rules to find Bugs, Security Hotspots, and Code Smells in your FLEX code

All rules 76 Vulnerability 5 Bug 9 Security Hotspot 1 Code Smell 61

Tags

Search by name...

Security.allowDomain(...) should only be used in a tightly focused manner

Vulnerability

The flash.system.Security.exactSettings property should never be set to false

Vulnerability

Dynamic classes should not be used

Code Smell

"LocalConnection" should be configured to narrowly specify the domains with which local connections to other Flex application are allowed

Vulnerability

"default" clauses should be first or last

Code Smell

Event types should be defined in metadata tags

Code Smell

Event names should not be hardcoded in event listeners

Code Smell

The special "star" type should not be used

Code Smell

Variables of the "Object" type should not be used

Code Smell

Methods should not be empty

Code Smell

Constant names should comply with a naming convention

Code Smell

All branches in a conditional structure should not have exactly the same implementation

Bug

Classes that extend "Event" should

Objects should not be instantiated inside a loop

Analyze your code

Code Smell Major performance

It can be expensive to instantiate a new object, and doing so inside a loop is typically an error. Instead, create the object once, before the loop.

Noncompliant Code Example

```
for (var i:int = 0; i < 10; i++) {
    var temp:MyObj = new MyObject(); // Noncompliant
    //...
}
```











Compliant Solution

```
var temp:MyObj = new MyObject();
for (var i:int = 0; i < 10; i++) {
    //...
}
```

Available In:

sonarcloud | sonarqube

© 2008-2022 SonarSource S.A., Switzerland. All content is copyright protected. SONAR, SONARSOURCE, SONARLINT, SONARQUBE and SONARCLOUD are trademarks of SonarSource S.A. All other trademarks and copyrights are the property of their respective owners. All rights are expressly reserved. [Privacy Policy](#)

<div>override "Event.clone()"</div> <div> Bug</div>
<div>Constructors should not dispatch events</div> <div> Bug</div>
<div>"ManagedEvents" tags should have companion "Event" tags</div> <div> Bug</div>
<div>Objects should not be instantiated inside a loop</div> <div> Code Smell</div>
<div>Two branches in a conditional structure should not have exactly the same implementation</div> <div> Code Smell</div>
<div>Constructor bodies should be as lightweight as possible</div> <div> Code Smell</div>
<div>Only "while", "do" and "for" statements should be labelled</div> <div> Code Smell</div>
<div>Statements, operators and keywords specific to ActionScript 2 should not be used</div> <div> Code Smell</div>
<div>"for" loop stop conditions should be invariant</div> <div> Code Smell</div>
<div>Unused function parameters should be removed</div> <div> Code Smell</div>