

-  Secrets
-  ABAP
-  Apex
-  C
-  C++
-  CloudFormation
-  COBOL
-  C#
-  CSS
-  **Flex**
-  Go
-  HTML
-  Java
-  JavaScript
-  Kotlin
-  Kubernetes
-  Objective C
-  PHP
-  PL/I
-  PL/SQL
-  Python
-  RPG
-  Ruby
-  Scala
-  Swift
-  Terraform
-  Text
-  TypeScript
-  T-SQL
-  VB.NET
-  VB6
-  XML



Flex static code analysis

Unique rules to find Bugs, Security Hotspots, and Code Smells in your FLEX code

- All rules 76
-  Vulnerability 5
-  Bug 9
-  Security Hotspot 1
-  Code Smell 61




Tags ▾

Search by name... 

Security.allowDomain(...) should only be used in a tightly focused manner		Vulnerability
The flash.system.Security.exactSettings property should never be set to false		Vulnerability
Dynamic classes should not be used		Code Smell
"LocalConnection" should be configured to narrowly specify the domains with which local connections to other Flex application are allowed		Vulnerability
"default" clauses should be first or last		Code Smell
Event types should be defined in metadata tags		Code Smell
Event names should not be hardcoded in event listeners		Code Smell
The special "star" type should not be used		Code Smell
Variables of the "Object" type should not be used		Code Smell
Methods should not be empty		Code Smell
Constant names should comply with a naming convention		Code Smell
All branches in a conditional structure should not have exactly the same implementation		Bug
Classes that extend "Event" should		

Classes should not have too many fields

Analyze your code

-  Code Smell
-  Major 
-  brain-overload

A class that grows too much tends to aggregate too many responsibilities and inevitably becomes harder to understand and therefore to maintain, and having a lot of fields is an indication that a class has grown too large.

Above a specific threshold, it is strongly advised to refactor the class into smaller ones which focus on well defined topics.

Available In:

sonarcloud  | sonarqube 

© 2008-2022 SonarSource S.A., Switzerland. All content is copyright protected. SONAR, SONARSOURCE, SONARLINT, SONARQUBE and SONARCLOUD are trademarks of SonarSource S.A. All other trademarks and copyrights are the property of their respective owners. All rights are expressly reserved. [Privacy Policy](#)

<div>override "Event.clone()"</div> <div> Bug</div>
<div>Constructors should not dispatch events</div> <div> Bug</div>
<div>"ManagedEvents" tags should have companion "Event" tags</div> <div> Bug</div>
<div>Objects should not be instantiated inside a loop</div> <div> Code Smell</div>
<div>Two branches in a conditional structure should not have exactly the same implementation</div> <div> Code Smell</div>
<div>Constructor bodies should be as lightweight as possible</div> <div> Code Smell</div>
<div>Only "while", "do" and "for" statements should be labelled</div> <div> Code Smell</div>
<div>Statements, operators and keywords specific to ActionScript 2 should not be used</div> <div> Code Smell</div>
<div>"for" loop stop conditions should be invariant</div> <div> Code Smell</div>
<div>Unused function parameters should be removed</div> <div> Code Smell</div>