

-  Secrets
-  ABAP
-  Ansible
-  Apex
-  AzureResourceManager
-  C
-  C#
-  C++
-  CloudFormation
-  COBOL
-  CSS
-  **Dart**
-  Docker
-  Flex
-  Go
-  HTML
-  Java
-  JavaScript
-  JCL
-  Kotlin
-  Kubernetes
-  Objective C
-  PHP
-  PL/I
-  PL/SQL
-  Python
-  RPG
-  Ruby
-  Scala
-  Swift
-  Terraform
-  Text
-  TypeScript
-  T-SQL
-  VB.NET
-  VB6
-  XML



Dart static code analysis

Unique rules to write Clean DART Code

All rules **115**

 Bug **15**

 Code Smell **100**

Conditional assignment should be preferred		Code Smell
"this" should only be used when required		Code Smell
Exceptions should not be ignored		Code Smell
Code annotated as deprecated should not be used		Code Smell
File names should comply with a naming convention		Code Smell
Unused local variables should be removed		Code Smell
Package names should comply with a naming convention		Code Smell
Overriding methods should do more than simply call the same method in the super class		Code Smell
"isEmpty" or "isEmpty" should be used to test for emptiness		Code Smell
Unnecessary imports should be removed		Code Smell
Empty statements should be removed		Code Smell
Class names should comply with a naming convention		Code Smell

Tags ▾

Impact ▾

Clean code attribute ▾

Search by name... 🔍

Conditional assignment should be preferred

Analyze your code

Intentionality - Clear

Maintainability ▾

 Code Smell

 Minor ⓘ

 clumsy

Why is this an issue?

More Info

In the interests of keeping code clean, the simplest possible conditional syntax should be used. That means using the `??=` (conditional assignment) operator for a self-assign-if-not-null operation.

Noncompliant code example

```
if (a == null) { // Noncompliant
  a = Object();
}
```

Compliant solution

```
a ??= Object();
```

Available In:

sonarcloud 

