 **sonar** RULES

Secrets

ABAP

Apex

C

C++

CloudFormation

COBOL

C#

CSS

Flex

Go

HTML

Java

JavaScript

Kotlin

Objective C

PHP

PL/I

PL/SQL

Python

RPG

Ruby

Scala

Swift

Terraform

Text

TypeScript

T-SQL

VB.NET

VB6

XML



Java static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your JAVA code

All rules 632

Vulnerability 53


Bug 154

Security Hotspot 36

Code Smell 389

Quick Fix 42

Tags ▾

Search by name... 

Abstract class names should comply with a naming convention
Code Smell
Strings literals should be placed on the left side when checking for equality
Code Smell
Files should contain an empty newline at the end
Code Smell
Source code should be indented consistently
Code Smell
A close curly brace should be located at the beginning of a line
Code Smell
Close curly brace and the next "else", "catch" and "finally" keywords should be on two different lines
Code Smell
Close curly brace and the next "else", "catch" and "finally" keywords should be located on the same line
Code Smell
An open curly brace should be located at the beginning of a line
Code Smell
An open curly brace should be located at the end of a line
Code Smell
Tabulation characters should not be used
Code Smell
Functions should not be defined with a variable number of arguments
Code Smell

The non-serializable super class of a "Serializable" class should have a no-argument constructor

Analyze your code

Bug

Minor

?

serialization

When a `Serializable` object has a non-serializable ancestor in its inheritance chain, object deserialization (re-instantiating the object from file) starts at the first non-serializable class, and proceeds down the chain, adding the properties of each subsequent child class, until the final object has been instantiated.

In order to create the non-serializable ancestor, its no-argument constructor is called. Therefore the non-serializable ancestor of a `Serializable` class must have a no-arg constructor. Otherwise the class is `Serializable` but not deserializable.

Noncompliant Code Example

```
public class Fruit {
    private Season ripe;

    public Fruit (Season ripe) {...}
    public void setRipe(Season ripe) {...}
    public Season getRipe() {...}
}

public class Raspberry extends Fruit
    implements Serializable { // Noncompliant; nonserializable
    private static final long serialVersionUID = 1;

    private String variety;

    public Raspberry(Season ripe, String variety) { ...}
    public void setVariety(String variety) {...}
    public String getVariety() {...}
}
```

Compliant Solution





```
public class Fruit {
    private Season ripe;

    public Fruit () {...}; // Compliant; no-arg constructor added
    public Fruit (Season ripe) {...}
    public void setRipe(Season ripe) {...}
    public Season getRipe() {...}
}

public class Raspberry extends Fruit
    implements Serializable {
    private static final long serialVersionUID = 1;

    private String variety;

    public Raspberry(Season ripe, String variety) {...}
```

<div>Local-Variable Type Inference should be used</div> <div> Code Smell</div>
<div>Migrate your tests from JUnit4 to the new JUnit5 annotations</div> <div> Code Smell</div>
<div>Track uses of disallowed classes</div> <div> Code Smell</div>
<div>Track uses of "@SuppressWarnings" annotations</div> <div> Code Smell</div>

```
public void setVariety(String variety) {...}
public String getVariety() {...}
}
```

Available In:

sonarlint  | **sonarcloud**  | **sonarqube** 

© 2008-2022 SonarSource S.A., Switzerland. All content is copyright protected. SONAR, SONARSOURCE, SONARLINT, SONARQUBE and SONARCLOUD are trademarks of SonarSource S.A. All other trademarks and copyrights are the property of their respective owners. All rights are expressly reserved.
[Privacy Policy](#)