








-  **sonar** RULES
-  Secrets


 ABAP


 Apex


 C


 C++


 CloudFormation


 COBOL


 C#


 CSS


 Flex


 Go


 HTML


 **Java**


 JavaScript


 Kotlin


 Objective C


 PHP


 PL/I


 PL/SQL


 Python


 RPG


 Ruby


 Scala


 Swift


 Terraform


 Text

 TypeScript

 T-SQL

 VB.NET

 VB6

 XML



Java static code analysis


Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your JAVA code


- All rules 632
-  Vulnerability 53
-  Bug 154
-  Security Hotspot 36
-  Code Smell 389
-  Quick Fix 42


Tags ▾


Search by name... 


- BigDecimal and primitive wrapper classes


 Code Smell
- "URL.hashCode" and "URL.equals" should be avoided


 Code Smell
- Two branches in a conditional structure should not have exactly the same implementation


 Code Smell
- Unused assignments should be removed


 Code Smell
- "Object.wait(...)" should never be called on objects that implement "java.util.concurrent.locks.Condition"


 Code Smell
- A field should not duplicate the name of its containing class


 Code Smell
- JUnit4 @Ignored and JUnit5 @Disabled annotations should be used to disable tests and should provide a rationale

 Code Smell
- Anonymous inner classes containing only one method should become lambdas

 Code Smell
- "switch" statements should not have too many "case" clauses

 Code Smell
- "for" loop stop conditions should be invariant

 Code Smell
- Sections of code should not be commented out

 Code Smell

Optional value should only be accessed after calling isPresent()

Analyze your code

 Bug

 Major 

 cwe

Optional value can hold either a value or not. The value held in the Optional can be accessed using the `get()` method, but it will throw a `NoSuchElementException` if there is no value present. To avoid the exception, calling the `isPresent()` or `! isEmpty()` method should always be done before any call to `get()`.

Alternatively, note that other methods such as `orElse(...)`, `orElseGet(...)` or `orElseThrow(...)` can be used to specify what to do with an empty Optional.

Noncompliant Code Example

```
Optional<String> value = this.getOptionalValue();

// ...

String stringValue = value.get(); // Noncompliant
```

```
if (methodThatReturnsOptional().isEmpty()) {
    throw new NotFoundException();
}
String value = methodThatReturnsOptional().get(); // Noncompliant
```

Compliant Solution

```
this.getOptionalValue().ifPresent(stringValue ->
    // Do something with stringValue
);
```

or

```
Optional<String> value = this.getOptionalValue();

// ...

if (value.isPresent()) {
    String stringValue = value.get();
}
```

or

```
Optional<String> value = this.getOptionalValue();

// ...

String stringValue = value.orElse("default");
```

Non-constructor methods should not have the same name as the enclosing class

 Code Smell

Exception types should not be tested using "instanceof" in catch blocks

 Code Smell

Classes from "sun.*" packages should not be used

 Code Smell

Throwable and Error should not be caught

```
Optional<String> optional = methodThatReturnsOptional();
if (optional.isEmpty()) {
    throw new NotFoundException();
}
String value = optional.get();
```

See

- [MITRE, CWE-476](#) - NULL Pointer Dereference

Available In:

 |  | 