




 Secrets


 ABAP


 Apex


 C


 C++


 CloudFormation


 COBOL


 C#


 CSS


 Flex


 Go


 HTML


 **Java**


 JavaScript


 Kotlin


 Objective C


 PHP


 PL/I


 PL/SQL


 Python


 RPG


 Ruby


 Scala


 Swift


 Terraform


 Text


 TypeScript

 T-SQL

 VB.NET

 VB6

 XML



Java static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your JAVA code

All rules632

Vulnerability53

Bug154


Security Hotspot36

Code Smell389


Quick Fix42


Tags ▾

Search by name... 🔍


 Bug


"runFinalizersOnExit" should not be called







"ScheduledThreadPoolExecutor" should not have 0 core threads







"Random" objects should be reused







The signature of "finalize()" should match that of "Object.finalize()"







Jump statements should not occur in "finally" blocks





"super.finalize()" should be called at the end of "Object.finalize()" implementations





Using slow regular expressions is security-sensitive

Using publicly writable directories is security-sensitive

Using clear-text protocols is security-sensitive

Accessing Android external storage is security-sensitive

Receiving intents is security-sensitive

Broadcasting intents is security-sensitive

Encryption algorithms should be used with secure mode and padding scheme

Analyze your code

VulnerabilityCritical🔍cwe privacy owasp sans-top25

Encryption operation mode and the padding scheme should be chosen appropriately to guarantee data confidentiality, integrity and authenticity:

- For block cipher encryption algorithms (like AES):
 - The GCM (Galois Counter Mode) mode which **works internally** with zero/no padding scheme, is recommended, as it is designed to provide both data authenticity (integrity) and confidentiality. Other similar modes are CCM, CWC, EAX, IAPM and OCB.
 - The CBC (Cipher Block Chaining) mode by itself provides only data confidentiality, it's recommended to use it along with Message Authentication Code or similar to achieve data authenticity (integrity) too and thus to **prevent padding oracle attacks**.
 - The ECB (Electronic Codebook) mode doesn't provide serious message confidentiality: under a given key any given plaintext block always gets encrypted to the same ciphertext block. This mode should not be used.
- For RSA encryption algorithm, the recommended padding scheme is OAEP.

Noncompliant Code Example

```
Cipher c1 = Cipher.getInstance("AES"); // Noncompliant: by d
Cipher c2 = Cipher.getInstance("AES/ECB/NoPadding"); // Nonc

Cipher c3 = Cipher.getInstance("RSA/None/NoPadding"); // Non
```

Compliant Solution

```
// Recommended for block ciphers
Cipher c1 = Cipher.getInstance("AES/GCM/NoPadding"); // Comp





// Recommended for RSA
Cipher c3 = Cipher.getInstance("RSA/None/OAEPWITHSHA-256ANDM
// or the ECB mode can be used for RSA when "None" is not av
Cipher c3 = Cipher.getInstance("RSA/ECB/OAEPWITHSHA-256ANDMG
```

See

- [OWASP Top 10 2021 Category A2](#) - Cryptographic Failures
- [OWASP Top 10 2017 Category A6](#) - Security Misconfiguration
- [Mobile AppSec Verification Standard](#) - Cryptography Requirements
- [OWASP Mobile Top 10 2016 Category M5](#) - Insufficient Cryptography
- [MITRE, CWE-327](#) - Use of a Broken or Risky Cryptographic Algorithm
- [CERT, MSC61-J](#) - Do not use insecure or weak cryptographic algorithms
- [SANS Top 25](#) - Porous Defenses

Available In:

sonarlint🔗sonarcloud🔗sonarqube🔗

Broadcasting intents is security-sensitive  Security Hotspot
Expanding archive files without controlling resource consumption is security-sensitive  Security Hotspot
Configuring loggers is security-sensitive  Security Hotspot
Using weak hashing algorithms is security-sensitive  Security Hotspot

© 2008-2022 SonarSource S.A., Switzerland. All content is copyright protected. SONAR, SONARSOURCE, SONARLINT, SONARQUBE and SONARCLOUD are trademarks of SonarSource S.A. All other trademarks and copyrights are the property of their respective owners. All rights are expressly reserved.
[Privacy Policy](#)