




 Secrets


 ABAP


 Apex


 C


 C++


 CloudFormation


 COBOL


 C#


 CSS


 Flex


 Go


 HTML


 **Java**


 JavaScript


 Kotlin


 Objective C


 PHP


 PL/I


 PL/SQL


 Python


 RPG


 Ruby


 Scala


 Swift


 Terraform


 Text

 TypeScript

 T-SQL

 VB.NET

 VB6

 XML



Java static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your JAVA code

All rules 632

Vulnerability 53

Bug 154

Security Hotspot 36

Code Smell 389

Quick Fix 42

Tags ▾

Search by name... 🔍

Test assertions should include messages	Code Smell
Mutable members should not be stored or returned directly	Code Smell
Redundant modifiers should not be used	Code Smell
"private" and "final" methods that don't access instance data should be "static"	Code Smell
Files should not be empty	Code Smell
Collection methods with O(n) performance should be used carefully	Code Smell
"Exception" should not be caught when not required by called methods	Code Smell
"collect" should be used with "Streams" instead of "list::add"	Code Smell
Switches should be used for sequences of simple "String" tests	Code Smell
"final" classes should not have "protected" members	Code Smell
Underscores should be used to make large numbers readable	Code Smell
"Serializable" inner classes of	

"for" loop stop conditions should be invariant

Analyze your code

Code Smell Major ? pitfall

A `for` loop stop condition should test the loop counter against an invariant value (i.e. one that is true at both the beginning and ending of every loop iteration). Ideally, this means that the stop condition is set to a local variable just before the loop begins.

Stop conditions that are not invariant are slightly less efficient, as well as being difficult to understand and maintain, and likely lead to the introduction of errors in the future.

This rule tracks three types of non-invariant stop conditions:

- When the loop counters are updated in the body of the `for` loop
- When the stop condition depend upon a method call
- When the stop condition depends on an object property, since such properties could change during the execution of the loop.

Noncompliant Code Example





```
for (int i = 0; i < 10; i++) {  
    ...  
    i = i - 1; // Noncompliant; counter updated in the body of  
    ...  
}
```

Compliant Solution

```
for (int i = 0; i < 10; i++) {...}
```

Available In:

sonarlint | sonarcloud | sonarqube

<div>Serialize inner classes or "Serializable" classes should be static</div> <div> Code Smell</div>
<div>Member variable visibility should be specified</div> <div> Code Smell</div>
<div>Classes and methods that rely on the default system encoding should not be used</div> <div> Code Smell</div>
<div>Simple class names should be used</div> <div> Code Smell</div>
<div>Variables should not be declared</div>