




 Secrets


 ABAP


 Apex


 C


 C++


 CloudFormation


 COBOL


 C#


 CSS


 Flex


 Go


 HTML


 **Java**


 JavaScript


 Kotlin


 Objective C


 PHP


 PL/I


 PL/SQL


 Python


 RPG


 Ruby


 Scala


 Swift


 Terraform


 Text


 TypeScript

 T-SQL

 VB.NET

 VB6

 XML



## Java static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your JAVA code

All rules632

Vulnerability53

Bug154

Security Hotspot36

Code Smell389

Quick Fix42

Tags ▾

Search by name... 🔍

Security Hotspot

Enabling JavaScript support for WebViews is security-sensitive

Security Hotspot

Constructing arguments of system commands from user input is security-sensitive

Security Hotspot

Using unencrypted files in mobile applications is security-sensitive

Security Hotspot

Using biometric authentication without a cryptographic solution is security-sensitive

Security Hotspot

Using unencrypted databases in mobile applications is security-sensitive

Security Hotspot

Authorizing non-authenticated users to use keys in the Android KeyStore is security-sensitive

Security Hotspot

Allowing user enumeration is security-sensitive

Security Hotspot

Allowing requests with excessive content length is security-sensitive

Security Hotspot

Disabling auto-escaping in template engines is security-sensitive

Security Hotspot

Allowing deserialization of LDAP objects is security-sensitive

Security Hotspot

Setting loose POSIX file permissions

### Constants should not be defined in interfaces

Analyze your code

Code Smell

Critical

bad-practice

According to Joshua Bloch, author of "Effective Java":

The constant interface pattern is a poor use of interfaces. That a class uses some constants internally is an implementation detail. Implementing a constant interface causes this implementation detail to leak into the class's exported API. It is of no consequence to the users of a class that the class implements a constant interface. In fact, it may even confuse them. Worse, it represents a commitment: if in a future release the class is modified so that it no longer needs to use the constants, it still must implement the interface to ensure binary compatibility. If a nonfinal class implements a constant interface, all of its subclasses will have their namespaces polluted by the constants in the interface.

This rule raises an issue when an interface consists solely of fields, without any other members.

#### Noncompliant Code Example

```
interface Status {
    int OPEN = 1;
    int CLOSED = 2;
}
```

#### Compliant Solution

```
public enum Status {
    OPEN,
    CLOSED;
}
```

or

```
public final class Status {
    public static final int OPEN = 1;
    public static final int CLOSED = 2;
}
```

Available In:

sonarlint





sonarcloud

sonarqube

https://rules.sonarsource.com/java/RSPEC-1214

© 2008-2022 SonarSource S.A., Switzerland. All content is copyright protected. SONAR,

1/2

<b>is security-sensitive</b>  Security Hotspot
<b>Formatting SQL queries is security-sensitive</b>  Security Hotspot
<b>Deprecated annotations should include explanations</b>  Code Smell
<b>Restricted Identifiers should not be used as Identifiers</b>  Code Smell
<b>Redundant constructors/methods</b>

SONARSOURCE, SONARLINT, SONARQUBE and SONARCLOUD are trademarks of SonarSource S.A. All other trademarks and copyrights are the property of their respective owners. All rights are expressly reserved.  
[Privacy Policy](#)