




 Secrets


 ABAP


 Apex


 C


 C++


 CloudFormation


 COBOL


 C#


 CSS


 Flex


 Go


 HTML


 **Java**


 JavaScript


 Kotlin


 Objective C


 PHP


 PL/I


 PL/SQL


 Python


 RPG


 Ruby


 Scala


 Swift


 Terraform


 Text


 TypeScript

 T-SQL

 VB.NET

 VB6

 XML



Java static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your JAVA code

All rules 632

Vulnerability 53

Bug 154

Security Hotspot 36

Code Smell 389

Quick Fix 42

Tags ▾

Search by name... 🔍

Abstract class names should comply with a naming convention

Code Smell

Strings literals should be placed on the left side when checking for equality

Code Smell

Files should contain an empty newline at the end

Code Smell

Source code should be indented consistently

Code Smell

A close curly brace should be located at the beginning of a line

Code Smell

Close curly brace and the next "else", "catch" and "finally" keywords should be on two different lines

Code Smell

Close curly brace and the next "else", "catch" and "finally" keywords should be located on the same line

Code Smell

An open curly brace should be located at the beginning of a line

Code Smell

An open curly brace should be located at the end of a line

Code Smell

Tabulation characters should not be used

Code Smell

Functions should not be defined with a variable number of arguments

Code Smell

Functional Interfaces should be as specialised as possible

Analyze your code

Code Smell Minor ? performance

The `java.util.function` package provides a large array of functional interface definitions for use in lambda expressions and method references. In general it is recommended to use the more specialised form to avoid auto-boxing. For instance `IntFunction<Foo>` should be preferred over `Function<Integer, Foo>`.

This rule raises an issue when any of the following substitution is possible:





Current Interface	Preferred Interface
<code>Function<Integer, R></code>	<code>IntFunction<R></code>
<code>Function<Long, R></code>	<code>LongFunction<R></code>
<code>Function<Double, R></code>	<code>DoubleFunction<R></code>
<code>Function<Double, Integer></code>	<code>DoubleToIntFunction</code>
<code>Function<Double, Long></code>	<code>DoubleToLongFunction</code>
<code>Function<Long, Double></code>	<code>LongToDoubleFunction</code>
<code>Function<Long, Integer></code>	<code>LongToIntFunction</code>
<code>Function<R, Integer></code>	<code>ToIntFunction<R></code>
<code>Function<R, Long></code>	<code>ToLongFunction<R></code>
<code>Function<R, Double></code>	<code>ToDoubleFunction<R></code>
<code>Function<T, T></code>	<code>UnaryOperator<T></code>
<code>BiFunction<T, T, T></code>	<code>BinaryOperator<T></code>
<code>Consumer<Integer></code>	<code>IntConsumer</code>
<code>Consumer<Double></code>	<code>DoubleConsumer</code>
<code>Consumer<Long></code>	<code>LongConsumer</code>
<code>BiConsumer<T, Integer></code>	<code>ObjIntConsumer<T></code>
<code>BiConsumer<T, Long></code>	<code>ObjLongConsumer<T></code>
<code>BiConsumer<T, Double></code>	<code>ObjDoubleConsumer<T></code>
<code>Predicate<Integer></code>	<code>IntPredicate</code>
<code>Predicate<Double></code>	<code>DoublePredicate</code>
<code>Predicate<Long></code>	<code>LongPredicate</code>
<code>Supplier<Integer></code>	<code>IntSupplier</code>
<code>Supplier<Double></code>	<code>DoubleSupplier</code>
<code>Supplier<Long></code>	<code>LongSupplier</code>
<code>Supplier<Boolean></code>	<code>BooleanSupplier</code>
<code>UnaryOperator<Integer></code>	<code>IntUnaryOperator</code>
<code>UnaryOperator<Double></code>	<code>DoubleUnaryOperator</code>
<code>UnaryOperator<Long></code>	<code>LongUnaryOperator</code>
<code>BinaryOperator<Integer></code>	<code>IntBinaryOperator</code>
<code>BinaryOperator<Long></code>	<code>LongBinaryOperator</code>
<code>BinaryOperator<Double></code>	<code>DoubleBinaryOperator</code>
<code>Function<T, Boolean></code>	<code>Predicate<T></code>
<code>BiFunction<T, U, Boolean></code>	<code>BiPredicate<T, U></code>

Noncompliant Code Example

```
public class Foo implements Supplier<Integer> { // Noncompliant
    @Override
    public Integer get() {
```

https://rules.sonarsource.com/java/RSPEC-4276

1/2

Local-Variable Type Inference should be used
 Code Smell
Migrate your tests from JUnit4 to the new JUnit5 annotations
 Code Smell
Track uses of disallowed classes
 Code Smell
Track uses of "@SuppressWarnings" annotations
 Code Smell

```
// ...  
}  
}
```

Compliant Solution

```
public class Foo implements IntSupplier {  
  
    @Override  
    public int getAsInt() {  
        // ...  
    }  
}
```

Available In:
sonarlint  | **sonarcloud**  | **sonarqube** 