




 Secrets


 ABAP


 Apex


 C


 C++


 CloudFormation


 COBOL


 C#


 CSS


 Flex


 Go


 HTML


 **Java**


 JavaScript


 Kotlin


 Objective C


 PHP


 PL/I


 PL/SQL


 Python


 RPG


 Ruby


 Scala


 Swift


 Terraform


 Text


 TypeScript

 T-SQL

 VB.NET

 VB6

 XML



## Java static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your JAVA code

All rules632

Vulnerability53

Bug154

Security Hotspot36

Code Smell389

Quick Fix42

Tags ▾

Search by name... 🔍

Test classes should comply with a naming convention

Code Smell

Loggers should be named for their enclosing classes

Code Smell

Methods should not return constants

Code Smell

"private" methods called only by inner classes should be moved to those classes

Code Smell

"enum" fields should not be publicly mutable

Code Smell

Abstract methods should not be redundant

Code Smell

Arrays should not be copied using loops

Code Smell

Static non-final field names should comply with a naming convention

Code Smell

JUnit rules should be used

Code Smell

Nested "enum"s should not be declared static

Code Smell

"catch" clauses should do more than rethrow

Code Smell

Mutable fields should not be "public static"

"StringBuilder" and "StringBuffer" should not be instantiated with a character

Analyze your code

BugMajor?pitfall

Instantiating a `StringBuilder` or a `StringBuffer` with a character is misleading because most Java developers would expect the character to be the initial value of the `StringBuffer`.

What actually happens is that the int representation of the character is used to determine the initial size of the `StringBuffer`.

Noncompliant Code Example

```
StringBuffer foo = new StringBuffer('x'); //equivalent to
```

Compliant Solution

```
StringBuffer foo = new StringBuffer("x");
```

Available In:

sonarlint






sonarcloud

sonarqube

© 2008-2022 SonarSource S.A., Switzerland. All content is copyright protected. SONAR, SONARSOURCE, SONARLINT, SONARQUBE and SONARCLOUD are trademarks of SonarSource S.A. All other trademarks and copyrights are the property of their respective owners. All rights are expressly reserved.  
[Privacy Policy](#)

https://rules.sonarsource.com/java/RSPEC-1317

1/2

 Code Smell
<b>The diamond operator ("&lt;&gt;") should be used</b>  Code Smell
<b>"finalize" should not set fields to "null"</b>  Code Smell
<b>Subclasses that add fields should override "equals"</b>  Code Smell
<b>Catches should be combined</b>  Code Smell